
xgboost

Release 2.0.3

xgboost developers

Dec 19, 2023

CONTENTS

1	Contents	3
1.1	Installation Guide	3
1.2	Building From Source	9
1.3	Get Started with XGBoost	18
1.4	XGBoost Tutorials	20
1.5	Frequently Asked Questions	101
1.6	XGBoost GPU Support	103
1.7	XGBoost Parameters	105
1.8	Prediction	118
1.9	Tree Methods	120
1.10	XGBoost Python Package	122
1.11	XGBoost R Package	388
1.12	XGBoost JVM Package	405
1.13	XGBoost.jl	426
1.14	XGBoost C Package	426
1.15	XGBoost C++ API	458
1.16	XGBoost Command Line version	458
1.17	Contribute to XGBoost	458
	Python Module Index	477
	Index	479

XGBoost is an optimized distributed gradient boosting library designed to be highly **efficient**, **flexible** and **portable**. It implements machine learning algorithms under the **Gradient Boosting** framework. XGBoost provides a parallel tree boosting (also known as GBDT, GBM) that solve many data science problems in a fast and accurate way. The same code runs on major distributed environment (Hadoop, SGE, MPI) and can solve problems beyond billions of examples.

CONTENTS

1.1 Installation Guide

XGBoost provides binary packages for some language bindings. The binary packages support the GPU algorithm (`device=cuda:0`) on machines with NVIDIA GPUs. Please note that **training with multiple GPUs is only supported for Linux platform**. See *XGBoost GPU Support*. Also we have both stable releases and nightly builds, see below for how to install them. For building from source, visit *this page*.

Contents

- *Installation Guide*
 - *Stable Release*
 - * *Python*
 - *Conda*
 - * *R*
 - * *JVM*
 - *Nightly Build*
 - * *Python*
 - * *R*
 - * *JVM*

1.1.1 Stable Release

Python

Pre-built binary wheels are uploaded to PyPI (Python Package Index) for each release. Supported platforms are Linux (x86_64, aarch64), Windows (x86_64) and MacOS (x86_64, Apple Silicon).

```
# Pip 21.3+ is required
pip install xgboost
```

You might need to run the command with `--user` flag or use `virtualenv` if you run into permission errors.

Note: Windows users need to install Visual C++ Redistributable

XGBoost requires DLLs from [Visual C++ Redistributable](#) in order to function, so make sure to install it. Exception: If you have Visual Studio installed, you already have access to necessary libraries and thus don't need to install Visual C++ Redistributable.

Capabilities of binary wheels for each platform:

Platform	GPU	Multi-Node-Multi-GPU
Linux x86_64	✓	✓
Linux aarch64		
MacOS x86_64		
MacOS Apple Silicon		
Windows	✓	

Conda

You may use the Conda packaging manager to install XGBoost:

```
conda install -c conda-forge py-xgboost
```

Conda should be able to detect the existence of a GPU on your machine and install the correct variant of XGBoost. If you run into issues, try indicating the variant explicitly:

```
# CPU only
conda install -c conda-forge py-xgboost-cpu
# Use NVIDIA GPU
conda install -c conda-forge py-xgboost-gpu
```

Visit the [Miniconda website](#) to obtain Conda.

Note: `py-xgboost-gpu` not available on Windows.

The `py-xgboost-gpu` is currently not available on Windows. If you are using Windows, please use `pip` to install XGBoost with GPU support.

R

- From CRAN:

```
install.packages("xgboost")
```

Note: Using all CPU cores (threads) on Mac OSX

If you are using Mac OSX, you should first install OpenMP library (`libomp`) by running

```
brew install libomp
```

and then run `install.packages("xgboost")`. Without OpenMP, XGBoost will only use a single CPU core, leading to suboptimal training speed.

- We also provide **experimental** pre-built binary with GPU support. With this binary, you will be able to use the GPU algorithm without building XGBoost from the source. Download the binary package from the Releases page. The file name will be of the form `xgboost_r_gpu_[os]_[version].tar.gz`, where `[os]` is either `linux` or `win64`. (We build the binaries for 64-bit Linux and Windows.) Then install XGBoost by running:

```
# Install dependencies
R -q -e "install.packages(c('data.table', 'jsonlite'))"
# Install XGBoost
R CMD INSTALL ./xgboost_r_gpu_linux.tar.gz
```

JVM

- XGBoost4j/XGBoost4j-Spark

Listing 1: Maven

```
<properties>
...
<!-- Specify Scala version in package name -->
<scala.binary.version>2.12</scala.binary.version>
</properties>

<dependencies>
...
<dependency>
  <groupId>ml.dmlc</groupId>
  <artifactId>xgboost4j_${scala.binary.version}</artifactId>
  <version>latest_version_num</version>
</dependency>
<dependency>
  <groupId>ml.dmlc</groupId>
  <artifactId>xgboost4j-spark_${scala.binary.version}</artifactId>
  <version>latest_version_num</version>
</dependency>
</dependencies>
```

Listing 2: sbt

```
libraryDependencies += Seq(
  "ml.dmlc" %% "xgboost4j" % "latest_version_num",
  "ml.dmlc" %% "xgboost4j-spark" % "latest_version_num"
)
```

- XGBoost4j-GPU/XGBoost4j-Spark-GPU

Listing 3: Maven

```
<properties>
...
<!-- Specify Scala version in package name -->
<scala.binary.version>2.12</scala.binary.version>
</properties>
```

(continues on next page)

(continued from previous page)

```
<dependencies>
...
<dependency>
  <groupId>ml.dmlc</groupId>
  <artifactId>xgboost4j-gpu_${scala.binary.version}</artifactId>
  <version>latest_version_num</version>
</dependency>
<dependency>
  <groupId>ml.dmlc</groupId>
  <artifactId>xgboost4j-spark-gpu_${scala.binary.version}</artifactId>
  <version>latest_version_num</version>
</dependency>
</dependencies>
```

Listing 4: sbt

```
libraryDependencies += Seq(
  "ml.dmlc" %% "xgboost4j-gpu" % "latest_version_num",
  "ml.dmlc" %% "xgboost4j-spark-gpu" % "latest_version_num"
)
```

This will check out the latest stable version from the Maven Central.

For the latest release version number, please check [release page](#).

To enable the GPU algorithm (`device='cuda'`), use artifacts `xgboost4j-gpu_2.12` and `xgboost4j-spark-gpu_2.12` instead (note the `gpu` suffix).

Note: Windows not supported in the JVM package

Currently, XGBoost4J-Spark does not support Windows platform, as the distributed training algorithm is inoperational for Windows. Please use Linux or MacOS.

1.1.2 Nightly Build

Python

Nightly builds are available. You can go to [this page](#), find the wheel with the commit ID you want and install it with `pip`:

```
pip install <url to the wheel>
```

The capability of Python pre-built wheel is the same as stable release.

R

Other than standard CRAN installation, we also provide *experimental* pre-built binary on with GPU support. You can go to [this page](#), Find the commit ID you want to install and then locate the file `xgboost_r_gpu_[os]_[commit].tar.gz`, where `[os]` is either `linux` or `win64`. (We build the binaries for 64-bit Linux and Windows.) Download it and run the following commands:

```
# Install dependencies
R -q -e "install.packages(c('data.table', 'jsonlite', 'remotes'))"
# Install XGBoost
R CMD INSTALL ./xgboost_r_gpu_linux.tar.gz
```

JVM

- XGBoost4j/XGBoost4j-Spark

Listing 5: Maven

```
<repository>
  <id>XGBoost4J Snapshot Repo</id>
  <name>XGBoost4J Snapshot Repo</name>
  <url>https://s3-us-west-2.amazonaws.com/xgboost-maven-repo/snapshot/</url>
</repository>
```

Listing 6: sbt

```
resolvers += "XGBoost4J Snapshot Repo" at "https://s3-us-west-2.amazonaws.com/xgboost-
↳maven-repo/snapshot/"
```

Then add XGBoost4J as a dependency:

Listing 7: maven

```
<properties>
  ...
  <!-- Specify Scala version in package name -->
  <scala.binary.version>2.12</scala.binary.version>
</properties>

<dependencies>
  ...
  <dependency>
    <groupId>ml.dmlc</groupId>
    <artifactId>xgboost4j_${scala.binary.version}</artifactId>
    <version>latest_version_num-SNAPSHOT</version>
  </dependency>
  <dependency>
    <groupId>ml.dmlc</groupId>
    <artifactId>xgboost4j-spark_${scala.binary.version}</artifactId>
    <version>latest_version_num-SNAPSHOT</version>
  </dependency>
</dependencies>
```

Listing 8: sbt

```
libraryDependencies += Seq(  
  "ml.dmlc" %% "xgboost4j" % "latest_version_num-SNAPSHOT",  
  "ml.dmlc" %% "xgboost4j-spark" % "latest_version_num-SNAPSHOT"  
)
```

- XGBoost4j-GPU/XGBoost4j-Spark-GPU

Listing 9: maven

```
<properties>  
  ...  
  <!-- Specify Scala version in package name -->  
  <scala.binary.version>2.12</scala.binary.version>  
</properties>  
  
<dependencies>  
  ...  
  <dependency>  
    <groupId>ml.dmlc</groupId>  
    <artifactId>xgboost4j-gpu_${scala.binary.version}</artifactId>  
    <version>latest_version_num-SNAPSHOT</version>  
  </dependency>  
  <dependency>  
    <groupId>ml.dmlc</groupId>  
    <artifactId>xgboost4j-spark-gpu_${scala.binary.version}</artifactId>  
    <version>latest_version_num-SNAPSHOT</version>  
  </dependency>  
</dependencies>
```

Listing 10: sbt

```
libraryDependencies += Seq(  
  "ml.dmlc" %% "xgboost4j-gpu" % "latest_version_num-SNAPSHOT",  
  "ml.dmlc" %% "xgboost4j-spark-gpu" % "latest_version_num-SNAPSHOT"  
)
```

Look up the version field in [pom.xml](#) to get the correct version number.

The SNAPSHOT JARs are hosted by the XGBoost project. Every commit in the master branch will automatically trigger generation of a new SNAPSHOT JAR. You can control how often Maven should upgrade your SNAPSHOT installation by specifying `updatePolicy`. See [here](#) for details.

You can browse the file listing of the Maven repository at <https://s3-us-west-2.amazonaws.com/xgboost-maven-repo/list.html>.

To enable the GPU algorithm (`device='cuda'`), use artifacts `xgboost4j-gpu_2.12` and `xgboost4j-spark-gpu_2.12` instead (note the `gpu` suffix).

1.2 Building From Source

This page gives instructions on how to build and install XGBoost from the source code on various systems. If the instructions do not work for you, please feel free to ask questions at [the user forum](#).

Note: Pre-built binary is available: now with GPU support

Consider installing XGBoost from a pre-built binary, to avoid the trouble of building XGBoost from the source. Check-out *Installation Guide*.

Contents

- *Obtaining the Source Code*
- *Building the Shared Library*
 - *Building on Linux and other UNIX-like systems*
 - *Building on MacOS*
 - *Building on Windows*
 - *Building with GPU support*
- *Building Python Package from Source*
 - *Building Python Package with Default Toolchains*
 - *Building Python Package for Windows with MinGW-w64 (Advanced)*
- *Building R Package From Source*
 - *Installing the development version (Linux / Mac OSX)*
 - *Installing the development version with Visual Studio (Windows)*
 - *Building R package with GPU support*
- *Building JVM Packages*
 - *Enabling OpenMP for Mac OS*
 - *Building with GPU support*
- *Building the Documentation*

1.2.1 Obtaining the Source Code

To obtain the development repository of XGBoost, one needs to use `git`.

Note: Use of Git submodules

XGBoost uses Git submodules to manage dependencies. So when you clone the repo, remember to specify `--recursive` option:

```
git clone --recursive https://github.com/dmlc/xgboost
```

For windows users who use github tools, you can open the git shell and type the following command:

```
git submodule init
git submodule update
```

1.2.2 Building the Shared Library

This section describes the procedure to build the shared library and CLI interface independently. For building language specific package, see corresponding sections in this document.

- On Linux and other UNIX-like systems, the target library is `libxgboost.so`
- On MacOS, the target library is `libxgboost.dylib`
- On Windows the target library is `xgboost.dll`

This shared library is used by different language bindings (with some additions depending on the binding you choose). The minimal building requirement is

- A recent C++ compiler supporting C++11 (g++-5.0 or higher)
- CMake 3.14 or higher.

For a list of CMake options like GPU support, see `#-- Options` in `CMakeLists.txt` on top level of source tree.

Building on Linux and other UNIX-like systems

After obtaining the source code, one builds XGBoost by running CMake:

```
cd xgboost
mkdir build
cd build
cmake ..
make -j$(nproc)
```

Building on MacOS

Obtain `libomp` from [Homebrew](#):

```
brew install libomp
```

Rest is the same as building on Linux.

Building on Windows

XGBoost support compilation with Microsoft Visual Studio and MinGW. To build with Visual Studio, we will need CMake. Make sure to install a recent version of CMake. Then run the following from the root of the XGBoost directory:

```
mkdir build
cd build
cmake .. -G"Visual Studio 14 2015 Win64"
# for VS15: cmake .. -G"Visual Studio 15 2017" -A x64
# for VS16: cmake .. -G"Visual Studio 16 2019" -A x64
cmake --build . --config Release
```

This specifies an out of source build using the Visual Studio 64 bit generator. (Change the `-G` option appropriately if you have a different version of Visual Studio installed.)

After the build process successfully ends, you will find a `xgboost.dll` library file inside `./lib/` folder. Some notes on using MinGW is added in *[Building Python Package for Windows with MinGW-w64 \(Advanced\)](#)*.

Building with GPU support

XGBoost can be built with GPU support for both Linux and Windows using CMake. See *[Building R package with GPU support](#)* for special instructions for R.

An up-to-date version of the CUDA toolkit is required.

Note: Checking your compiler version

CUDA is really picky about supported compilers, a table for the compatible compilers for the latest CUDA version on Linux can be seen [here](#).

Some distros package a compatible gcc version with CUDA. If you run into compiler errors with `nvcc`, try specifying the correct compiler with `-DCMAKE_CXX_COMPILER=/path/to/correct/g++ -DCMAKE_C_COMPILER=/path/to/correct/gcc`. On Arch Linux, for example, both binaries can be found under `/opt/cuda/bin/`.

From the command line on Linux starting from the XGBoost directory:

```
mkdir build
cd build
cmake .. -DUSE_CUDA=ON
make -j4
```

Note: Specifying compute capability

To speed up compilation, the compute version specific to your GPU could be passed to `cmake` as, e.g., `-DGPU_COMPUTE_VER=50`. A quick explanation and numbers for some architectures can be found [in this page](#).

Note: Faster distributed GPU training with NCCL

By default, distributed GPU training is enabled and uses Rabbit for communication. For faster training, set the option `USE_NCCL=ON`. Faster distributed GPU training depends on NCCL2, available at [this link](#). Since NCCL2 is only available for Linux machines, **faster distributed GPU training is available only for Linux**.

```
mkdir build
cd build
cmake .. -DUSE_CUDA=ON -DUSE_NCCL=ON -DNCCL_ROOT=/path/to/nccl2
make -j4
```

On Windows, run CMake as follows:

```
mkdir build
cd build
cmake .. -G"Visual Studio 17 2022" -A x64 -DUSE_CUDA=ON
```

(Change the `-G` option appropriately if you have a different version of Visual Studio installed.)

The above cmake configuration run will create an `xgboost.sln` solution file in the build directory. Build this solution in Release mode, either from Visual studio or from command line:

```
cmake --build . --target xgboost --config Release
```

To speed up compilation, run multiple jobs in parallel by appending option `-- /MP`.

1.2.3 Building Python Package from Source

The Python package is located at `python-package/`.

Building Python Package with Default Toolchains

There are several ways to build and install the package from source:

1. Build C++ core with CMake first

You can first build C++ library using CMake as described in *Building the Shared Library*. After compilation, a shared library will appear in `lib/` directory. On Linux distributions, the shared library is `lib/libxgboost.so`. The install script `pip install .` will reuse the shared library instead of compiling it from scratch, making it quite fast to run.

```
$ cd python-package/
$ pip install . # Will re-use lib/libxgboost.so
```

2. Install the Python package directly

You can navigate to `python-package/` directory and install the Python package directly by running

```
$ cd python-package/
$ pip install -v .
```

which will compile XGBoost's native (C++) code using default CMake flags. To enable additional compilation options, pass corresponding `--config-settings`:

```
$ pip install -v . --config-settings use_cuda=True --config-settings use_
↪nccl=True
```

Use Pip 22.1 or later to use `--config-settings` option.

Here are the available options for `--config-settings`:

```
@dataclasses.dataclass
class BuildConfiguration: # pylint: disable=R0902
    """Configurations use when building libxgboost"""

    # Whether to hide C++ symbols in libxgboost.so
    hide_cxx_symbols: bool = True
    # Whether to enable OpenMP
    use_openmp: bool = True
    # Whether to enable CUDA
    use_cuda: bool = False
    # Whether to enable NCCL
```

(continues on next page)

(continued from previous page)

```

use_nccl: bool = False
# Whether to enable HDFS
use_hdfs: bool = False
# Whether to enable Azure Storage
use_azure: bool = False
# Whether to enable AWS S3
use_s3: bool = False
# Whether to enable the dense parser plugin
plugin_dense_parser: bool = False
# Special option: See explanation below
use_system_libxgboost: bool = False

```

`use_system_libxgboost` is a special option. See Item 4 below for detailed description.

Note: Verbose flag recommended

As `pip install .` will build C++ code, it will take a while to complete. To ensure that the build is progressing successfully, we suggest that you add the verbose flag (`-v`) when invoking `pip install`.

3. Editable installation

To further enable rapid development and iteration, we provide an **editable installation**. In an editable installation, the installed package is simply a symbolic link to your working copy of the XGBoost source code. So every changes you make to your source directory will be immediately visible to the Python interpreter. Here is how to install XGBoost as editable installation:

```

# Under xgboost source directory
mkdir build
cd build
# Build shared library libxgboost.so
cmake .. -GNinja
ninja
# Install as editable installation
cd ../python-package
pip install -e .

```

4. Use `libxgboost.so` on system path.

This option is useful for package managers that wish to separately package `libxgboost.so` and the XGBoost Python package. For example, Conda publishes `libxgboost` (for the shared library) and `py-xgboost` (for the Python package).

To use this option, first make sure that `libxgboost.so` exists in the system library path:

```

import sys
import pathlib
libpath = pathlib.Path(sys.base_prefix).joinpath("lib", "libxgboost.so")
assert libpath.exists()

```

Then pass `use_system_libxgboost=True` option to `pip install`:

```

cd python-package
pip install . --config-settings use_system_libxgboost=True

```

Note: See [Notes on packaging XGBoost's Python package](#) for instructions on packaging and distributing XGBoost as Python distributions.

Building Python Package for Windows with MinGW-w64 (Advanced)

Windows versions of Python are built with Microsoft Visual Studio. Usually Python binary modules are built with the same compiler the interpreter is built with. However, you may not be able to use Visual Studio, for following reasons:

1. VS is proprietary and commercial software. Microsoft provides a freeware “Community” edition, but its licensing terms impose restrictions as to where and how it can be used.
2. Visual Studio contains telemetry, as documented in [Microsoft Visual Studio Licensing Terms](#). Running software with telemetry may be against the policy of your organization.

So you may want to build XGBoost with GCC own your own risk. This presents some difficulties because MSVC uses Microsoft runtime and MinGW-w64 uses own runtime, and the runtimes have different incompatible memory allocators. But in fact this setup is usable if you know how to deal with it. Here is some experience.

1. The Python interpreter will crash on exit if XGBoost was used. This is usually not a big issue.
2. `-O3` is OK.
3. `-mtune=native` is also OK.
4. Don't use `-march=native` gcc flag. Using it causes the Python interpreter to crash if the DLL was actually used.
5. You may need to provide the lib with the runtime libs. If `mingw32/bin` is not in `PATH`, build a wheel (pip wheel), open it with an archiver and put the needed dlls to the directory where `xgboost.dll` is situated. Then you can install the wheel with `pip`.

1.2.4 Building R Package From Source

By default, the package installed by running `install.packages` is built from source. Here we list some other options for installing development version.

Installing the development version (Linux / Mac OSX)

Make sure you have installed git and a recent C++ compiler supporting C++11 (See above sections for requirements of building C++ core).

Due to the use of git-submodules, `remotes::install_github()` cannot be used to install the latest version of R package. Thus, one has to run git to check out the code first, see [Obtaining the Source Code](#) on how to initialize the git repository for XGBoost. The simplest way to install the R package after obtaining the source code is:

```
cd R-package
R CMD INSTALL .
```

But if you want to use CMake build for better performance (which has the logic for detecting available CPU instructions) or greater flexibility around compile flags, the above snippet can be replaced by:

```
mkdir build
cd build
cmake .. -DR_LIB=ON
```

(continues on next page)

(continued from previous page)

```
make -j$(nproc)
make install
```

Installing the development version with Visual Studio (Windows)

On Windows, CMake with Visual C++ Build Tools (or Visual Studio) can be used to build the R package.

While not required, this build can be faster if you install the R package `processx` with `install.packages("processx")`.

Note: Setting correct PATH environment variable on Windows

If you are using Windows, make sure to include the right directories in the PATH environment variable.

- If you are using R 4.x with RTools 4.0: - C:\rtools40\usr\bin - C:\rtools40\mingw64\bin
- If you are using R 3.x with RTools 3.x:
 - C:\Rtools\bin
 - C:\Rtools\mingw_64\bin

Open the Command Prompt and navigate to the XGBoost directory, and then run the following commands. Make sure to specify the correct R version.

```
cd C:\path\to\xgboost
mkdir build
cd build
cmake .. -G"Visual Studio 16 2019" -A x64 -DR_LIB=ON -DR_VERSION=4.0.0
cmake --build . --target install --config Release
```

Building R package with GPU support

The procedure and requirements are similar as in *Building with GPU support*, so make sure to read it first.

On Linux, starting from the XGBoost directory type:

```
mkdir build
cd build
cmake .. -DUSE_CUDA=ON -DR_LIB=ON
make install -j$(nproc)
```

When default target is used, an R package shared library would be built in the build area. The `install` target, in addition, assembles the package files with this shared library under `build/R-package` and runs `R CMD INSTALL`.

On Windows, CMake with Visual Studio has to be used to build an R package with GPU support. Rtools must also be installed.

Note: Setting correct PATH environment variable on Windows

If you are using Windows, make sure to include the right directories in the PATH environment variable.

- If you are using R 4.x with RTools 4.0:
 - C:\rtools40\usr\bin

- C:\rtools40\mingw64\bin
 - If you are using R 3.x with RTools 3.x:
 - C:\Rtools\bin
 - C:\Rtools\mingw_64\bin
-

Open the Command Prompt and navigate to the XGBoost directory, and then run the following commands. Make sure to specify the correct R version.

```
cd C:\path\to\xgboost
mkdir build
cd build
cmake .. -G"Visual Studio 16 2019" -A x64 -DUSE_CUDA=ON -DRLIB=ON -DR_VERSION=4.0.0
cmake --build . --target install --config Release
```

If CMake can't find your R during the configuration step, you might provide the location of R to CMake like this: `-DLIBR_HOME="C:\Program Files\R\R-4.0.0"`.

If on Windows you get a “permission denied” error when trying to write to `...Program Files/R/...` during the package installation, create a `.Rprofile` file in your personal home directory (if you don't already have one in there), and add a line to it which specifies the location of your R packages user library, like the following:

```
.libPaths( unique(c("C:/Users/USERNAME/Documents/R/win-library/3.4", .libPaths())) )
```

You might find the exact location by running `.libPaths()` in R GUI or RStudio.

1.2.5 Building JVM Packages

Building XGBoost4J using Maven requires Maven 3 or newer, Java 7+ and CMake 3.13+ for compiling Java code as well as the Java Native Interface (JNI) bindings.

Before you install XGBoost4J, you need to define environment variable `JAVA_HOME` as your JDK directory to ensure that your compiler can find `jni.h` correctly, since XGBoost4J relies on JNI to implement the interaction between the JVM and native libraries.

After your `JAVA_HOME` is defined correctly, it is as simple as run `mvn package` under `jvm-packages` directory to install XGBoost4J. You can also skip the tests by running `mvn -DskipTests=true package`, if you are sure about the correctness of your local setup.

To publish the artifacts to your local maven repository, run

```
mvn install
```

Or, if you would like to skip tests, run

```
mvn -DskipTests install
```

This command will publish the xgboost binaries, the compiled java classes as well as the java sources to your local repository. Then you can use XGBoost4J in your Java projects by including the following dependency in `pom.xml`:

```
<dependency>
  <groupId>m1.dmlc</groupId>
  <artifactId>xgboost4j</artifactId>
  <version>latest_source_version_num</version>
</dependency>
```

For sbt, please add the repository and dependency in build.sbt as following:

```
resolvers += "Local Maven Repository" at "file://" + Path.userHome.absolutePath + "/.m2/
↳ repository"

"ml.dmlc" % "xgboost4j" % "latest_source_version_num"
```

If you want to use XGBoost4J-Spark, replace xgboost4j with xgboost4j-spark.

Note: XGBoost4J-Spark requires Apache Spark 2.3+

XGBoost4J-Spark now requires **Apache Spark 2.3+**. Latest versions of XGBoost4J-Spark uses facilities of *org.apache.spark.ml.param.shared* extensively to provide for a tight integration with Spark MLLIB framework, and these facilities are not fully available on earlier versions of Spark.

Also, make sure to install Spark directly from [Apache website](#). **Upstream XGBoost is not guaranteed to work with third-party distributions of Spark, such as Cloudera Spark.** Consult appropriate third parties to obtain their distribution of XGBoost.

Enabling OpenMP for Mac OS

If you are on Mac OS and using a compiler that supports OpenMP, you need to go to the file `xgboost/jvm-packages/create_jni.py` and comment out the line

```
CONFIG["USE_OPENMP"] = "OFF"
```

in order to get the benefit of multi-threading.

Building with GPU support

If you want to build XGBoost4J that supports distributed GPU training, run

```
mvn -Duse.cuda=ON install
```

1.2.6 Building the Documentation

XGBoost uses [Sphinx](#) for documentation. To build it locally, you need a installed XGBoost with all its dependencies along with:

- System dependencies
 - git
 - graphviz
- Python dependencies

Checkout the `requirements.txt` file under `doc/`

Under `xgboost/doc` directory, run `make <format>` with `<format>` replaced by the format you want. For a list of supported formats, run `make help` under the same directory.

1.3 Get Started with XGBoost

This is a quick start tutorial showing snippets for you to quickly try out XGBoost on the demo dataset on a binary classification task.

1.3.1 Links to Other Helpful Resources

- See *Installation Guide* on how to install XGBoost.
- See *Text Input Format* on using text format for specifying training/testing data.
- See *Tutorials* for tips and tutorials.
- See *Learning to use XGBoost by Examples* for more code examples.

1.3.2 Python

```
from xgboost import XGBClassifier
# read data
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split
data = load_iris()
X_train, X_test, y_train, y_test = train_test_split(data['data'], data['target'], test_
↪size=.2)
# create model instance
bst = XGBClassifier(n_estimators=2, max_depth=2, learning_rate=1, objective=
↪'binary:logistic')
# fit model
bst.fit(X_train, y_train)
# make predictions
preds = bst.predict(X_test)
```

1.3.3 R

```
# load data
data(agaricus.train, package='xgboost')
data(agaricus.test, package='xgboost')
train <- agaricus.train
test <- agaricus.test
# fit model
bst <- xgboost(data = train$data, label = train$label, max.depth = 2, eta = 1, nrounds =
↪2,
               nthread = 2, objective = "binary:logistic")
# predict
pred <- predict(bst, test$data)
```

1.3.4 Julia

```
using XGBoost
# read data
train_X, train_Y = readlibsvm("demo/data/agaricus.txt.train", (6513, 126))
test_X, test_Y = readlibsvm("demo/data/agaricus.txt.test", (1611, 126))
# fit model
num_round = 2
bst = xgboost(train_X, num_round, label=train_Y, eta=1, max_depth=2)
# predict
pred = predict(bst, test_X)
```

1.3.5 Scala

```
import ml.dmlc.xgboost4j.scala.DMatrix
import ml.dmlc.xgboost4j.scala.XGBoost

object XGBoostScalaExample {
  def main(args: Array[String]) {
    // read training data, available at xgboost/demo/data
    val trainData =
      new DMatrix("/path/to/agaricus.txt.train")
    // define parameters
    val paramMap = List(
      "eta" -> 0.1,
      "max_depth" -> 2,
      "objective" -> "binary:logistic").toMap
    // number of iterations
    val round = 2
    // train the model
    val model = XGBoost.train(trainData, paramMap, round)
    // run prediction
    val predTrain = model.predict(trainData)
    // save model to the file.
    model.saveModel("/local/path/to/model")
  }
}
```

1.4 XGBoost Tutorials

This section contains official tutorials inside XGBoost package. See [Awesome XGBoost](#) for more resources. Also, don't miss the feature introductions in each package.

1.4.1 Introduction to Boosted Trees

XGBoost stands for “Extreme Gradient Boosting”, where the term “Gradient Boosting” originates from the paper *Greedy Function Approximation: A Gradient Boosting Machine*, by Friedman.

The **gradient boosted trees** has been around for a while, and there are a lot of materials on the topic. This tutorial will explain boosted trees in a self-contained and principled way using the elements of supervised learning. We think this explanation is cleaner, more formal, and motivates the model formulation used in XGBoost.

Elements of Supervised Learning

XGBoost is used for supervised learning problems, where we use the training data (with multiple features) x_i to predict a target variable y_i . Before we learn about trees specifically, let us start by reviewing the basic elements in supervised learning.

Model and Parameters

The **model** in supervised learning usually refers to the mathematical structure of by which the prediction y_i is made from the input x_i . A common example is a *linear model*, where the prediction is given as $\hat{y}_i = \sum_j \theta_j x_{ij}$, a linear combination of weighted input features. The prediction value can have different interpretations, depending on the task, i.e., regression or classification. For example, it can be logistic transformed to get the probability of positive class in logistic regression, and it can also be used as a ranking score when we want to rank the outputs.

The **parameters** are the undetermined part that we need to learn from data. In linear regression problems, the parameters are the coefficients θ . Usually we will use θ to denote the parameters (there are many parameters in a model, our definition here is sloppy).

Objective Function: Training Loss + Regularization

With judicious choices for y_i , we may express a variety of tasks, such as regression, classification, and ranking. The task of **training** the model amounts to finding the best parameters θ that best fit the training data x_i and labels y_i . In order to train the model, we need to define the **objective function** to measure how well the model fit the training data.

A salient characteristic of objective functions is that they consist of two parts: **training loss** and **regularization term**:

$$\text{obj}(\theta) = L(\theta) + \Omega(\theta)$$





where L is the training loss function, and Ω is the regularization term. The training loss measures how *predictive* our model is with respect to the training data. A common choice of L is the *mean squared error*, which is given by

$$L(\theta) = \sum_i (y_i - \hat{y}_i)^2$$

Another commonly used loss function is logistic loss, to be used for logistic regression:

$$L(\theta) = \sum_i [y_i \ln(1 + e^{-\hat{y}_i}) + (1 - y_i) \ln(1 + e^{\hat{y}_i})]$$

The **regularization term** is what people usually forget to add. The regularization term controls the complexity of the model, which helps us to avoid overfitting. This sounds a bit abstract, so let us consider the following problem in the following picture. You are asked to *fit* visually a step function given the input data points on the upper left corner of the image. Which solution among the three do you think is the best fit?



The correct answer is marked in red. Please consider if this visually seems a reasonable fit to you. The general principle is we want both a *simple* and *predictive* model. The tradeoff between the two is also referred as **bias-variance tradeoff** in machine learning.

Why introduce the general principle?


The elements introduced above form the basic elements of supervised learning, and they are natural building blocks of machine learning toolkits. For example, you should be able to describe the differences and commonalities between gradient boosted trees and random forests. Understanding the process in a formalized way also helps us to understand the objective that we are learning and the reason behind the heuristics such as pruning and smoothing.

Decision Tree Ensembles

Now that we have introduced the elements of supervised learning, let us get started with real trees. To begin with, let us first learn about the model choice of XGBoost: **decision tree ensembles**. The tree ensemble model consists of a set of classification and regression trees (CART). Here's a simple example of a CART that classifies whether someone will like a hypothetical computer game X.


Input: age, gender, occupation, ...

Like the computer game X



We classify the members of a family into different leaves, and assign them the score on the corresponding leaf. A CART is a bit different from decision trees, in which the leaf only contains decision values. In CART, a real score is associated with each of the leaves, which gives us richer interpretations that go beyond classification. This also allows for a principled, unified approach to optimization, as we will see in a later part of this tutorial.

Usually, a single tree is not strong enough to be used in practice. What is actually used is the ensemble model, which sums the prediction of multiple trees together.



Here is an example of a tree ensemble of two trees. The prediction scores of each individual tree are summed up to

get the final score. If you look at the example, an important fact is that the two trees try to *complement* each other. Mathematically, we can write our model in the form

$$\hat{y}_i = \sum_{k=1}^K f_k(x_i), f_k \in \mathcal{F}$$

where K is the number of trees, f_k is a function in the functional space \mathcal{F} , and \mathcal{F} is the set of all possible CARTs. The objective function to be optimized is given by

$$\text{obj}(\theta) = \sum_i^n l(y_i, \hat{y}_i) + \sum_{k=1}^K \omega(f_k)$$

where $\omega(f_k)$ is the complexity of the tree f_k , defined in detail later.

Now here comes a trick question: what is the *model* used in random forests? Tree ensembles! So random forests and boosted trees are really the same models; the difference arises from how we train them. This means that, if you write a predictive service for tree ensembles, you only need to write one and it should work for both random forests and gradient boosted trees. (See [Treelite](#) for an actual example.) One example of why elements of supervised learning rock.

Tree Boosting

Now that we introduced the model, let us turn to training: How should we learn the trees? The answer is, as is always for all supervised learning models: *define an objective function and optimize it!*

Let the following be the objective function (remember it always needs to contain training loss and regularization):

$$\text{obj} = \sum_{i=1}^n l(y_i, \hat{y}_i^{(t)}) + \sum_{i=1}^t \omega(f_i)$$

Additive Training

The first question we want to ask: what are the **parameters** of trees? You can find that what we need to learn are those functions f_i , each containing the structure of the tree and the leaf scores. Learning tree structure is much harder than traditional optimization problem where you can simply take the gradient. It is intractable to learn all the trees at once. Instead, we use an additive strategy: fix what we have learned, and add one new tree at a time. We write the prediction value at step t as $\hat{y}_i^{(t)}$. Then we have

$$\begin{aligned} \hat{y}_i^{(0)} &= 0 \\ \hat{y}_i^{(1)} &= f_1(x_i) = \hat{y}_i^{(0)} + f_1(x_i) \\ \hat{y}_i^{(2)} &= f_1(x_i) + f_2(x_i) = \hat{y}_i^{(1)} + f_2(x_i) \\ &\dots \\ \hat{y}_i^{(t)} &= \sum_{k=1}^t f_k(x_i) = \hat{y}_i^{(t-1)} + f_t(x_i) \end{aligned}$$

It remains to ask: which tree do we want at each step? A natural thing is to add the one that optimizes our objective.

$$\begin{aligned} \text{obj}^{(t)} &= \sum_{i=1}^n l(y_i, \hat{y}_i^{(t)}) + \sum_{i=1}^t \omega(f_i) \\ &= \sum_{i=1}^n l(y_i, \hat{y}_i^{(t-1)} + f_t(x_i)) + \omega(f_t) + \text{constant} \end{aligned}$$

If we consider using mean squared error (MSE) as our loss function, the objective becomes

$$\begin{aligned}\text{obj}^{(t)} &= \sum_{i=1}^n (y_i - (\hat{y}_i^{(t-1)} + f_t(x_i)))^2 + \sum_{i=1}^t \omega(f_i) \\ &= \sum_{i=1}^n [2(\hat{y}_i^{(t-1)} - y_i)f_t(x_i) + f_t(x_i)^2] + \omega(f_t) + \text{constant}\end{aligned}$$

The form of MSE is friendly, with a first order term (usually called the residual) and a quadratic term. For other losses of interest (for example, logistic loss), it is not so easy to get such a nice form. So in the general case, we take the *Taylor expansion of the loss function up to the second order*:

$$\text{obj}^{(t)} = \sum_{i=1}^n [l(y_i, \hat{y}_i^{(t-1)}) + g_i f_t(x_i) + \frac{1}{2} h_i f_t^2(x_i)] + \omega(f_t) + \text{constant}$$

where the g_i and h_i are defined as

$$\begin{aligned}g_i &= \partial_{\hat{y}_i^{(t-1)}} l(y_i, \hat{y}_i^{(t-1)}) \\ h_i &= \partial_{\hat{y}_i^{(t-1)}}^2 l(y_i, \hat{y}_i^{(t-1)})\end{aligned}$$

After we remove all the constants, the specific objective at step t becomes

$$\sum_{i=1}^n [g_i f_t(x_i) + \frac{1}{2} h_i f_t^2(x_i)] + \omega(f_t)$$

This becomes our optimization goal for the new tree. One important advantage of this definition is that the value of the objective function only depends on g_i and h_i . This is how XGBoost supports custom loss functions. We can optimize every loss function, including logistic regression and pairwise ranking, using exactly the same solver that takes g_i and h_i as input!

Model Complexity

We have introduced the training step, but wait, there is one important thing, the **regularization term**! We need to define the complexity of the tree $\omega(f)$. In order to do so, let us first refine the definition of the tree $f(x)$ as

$$f_t(x) = w_{q(x)}, w \in R^T, q : R^d \rightarrow \{1, 2, \dots, T\}.$$

Here w is the vector of scores on leaves, q is a function assigning each data point to the corresponding leaf, and T is the number of leaves. In XGBoost, we define the complexity as

$$\omega(f) = \gamma T + \frac{1}{2} \lambda \sum_{j=1}^T w_j^2$$

Of course, there is more than one way to define the complexity, but this one works well in practice. The regularization is one part most tree packages treat less carefully, or simply ignore. This was because the traditional treatment of tree learning only emphasized improving impurity, while the complexity control was left to heuristics. By defining it formally, we can get a better idea of what we are learning and obtain models that perform well in the wild.

The Structure Score

Here is the magical part of the derivation. After re-formulating the tree model, we can write the objective value with the t -th tree as:

$$\begin{aligned}\text{obj}^{(t)} &\approx \sum_{i=1}^n [g_i w_{q(x_i)} + \frac{1}{2} h_i w_{q(x_i)}^2] + \gamma T + \frac{1}{2} \lambda \sum_{j=1}^T w_j^2 \\ &= \sum_{j=1}^T [(\sum_{i \in I_j} g_i) w_j + \frac{1}{2} (\sum_{i \in I_j} h_i + \lambda) w_j^2] + \gamma T\end{aligned}$$

where $I_j = \{i | q(x_i) = j\}$ is the set of indices of data points assigned to the j -th leaf. Notice that in the second line we have changed the index of the summation because all the data points on the same leaf get the same score. We could further compress the expression by defining $G_j = \sum_{i \in I_j} g_i$ and $H_j = \sum_{i \in I_j} h_i$:






$$\text{obj}^{(t)} = \sum_{j=1}^T [G_j w_j + \frac{1}{2} (H_j + \lambda) w_j^2] + \gamma T$$


In this equation, w_j are independent with respect to each other, the form $G_j w_j + \frac{1}{2} (H_j + \lambda) w_j^2$ is quadratic and the best w_j for a given structure $q(x)$ and the best objective reduction we can get is:

$$\begin{aligned}w_j^* &= -\frac{G_j}{H_j + \lambda} \\ \text{obj}^* &= -\frac{1}{2} \sum_{j=1}^T \frac{G_j^2}{H_j + \lambda} + \gamma T\end{aligned}$$

The last equation measures *how good* a tree structure $q(x)$ is.

Instance index gradient statistics

1		g_1, h_1
2		g_2, h_2
3		g_3, h_3
4		g_4, h_4
5		g_5, h_5



$$Obj = -\sum_j \frac{G_j^2}{H_j + \lambda} + 3\gamma$$

The smaller the score is, the better the structure is

If all this sounds a bit complicated, let's take a look at the picture, and see how the scores can be calculated. Basically, for a given tree structure, we push the statistics g_i and h_i to the leaves they belong to, sum the statistics together, and use the formula to calculate how good the tree is. This score is like the impurity measure in a decision tree, except that it also takes the model complexity into account.


Learn the tree structure

Now that we have a way to measure how good a tree is, ideally we would enumerate all possible trees and pick the best one. In practice this is intractable, so we will try to optimize one level of the tree at a time. Specifically we try to split a leaf into two leaves, and the score it gains is

$$Gain = \frac{1}{2} \left[\frac{G_L^2}{H_L + \lambda} + \frac{G_R^2}{H_R + \lambda} - \frac{(G_L + G_R)^2}{H_L + H_R + \lambda} \right] - \gamma$$

This formula can be decomposed as 1) the score on the new left leaf 2) the score on the new right leaf 3) The score on the original leaf 4) regularization on the additional leaf. We can see an important fact here: if the gain is smaller than γ , we would do better not to add that branch. This is exactly the **pruning** techniques in tree based models! By using the principles of supervised learning, we can naturally come up with the reason these techniques work :)

For real valued data, we usually want to search for an optimal split. To efficiently do so, we place all the instances in sorted order, like the following picture.



A left to right scan is sufficient to calculate the structure score of all possible split solutions, and we can find the best split efficiently.

Note: Limitation of additive tree learning

Since it is intractable to enumerate all possible tree structures, we add one split at a time. This approach works well most of the time, but there are some edge cases that fail due to this approach. For those edge cases, training results in a degenerate model because we consider only one feature dimension at a time. See [Can Gradient Boosting Learn Simple Arithmetic?](#) for an example.

Final words on XGBoost

Now that you understand what boosted trees are, you may ask, where is the introduction for XGBoost? XGBoost is exactly a tool motivated by the formal principle introduced in this tutorial! More importantly, it is developed with both deep consideration in terms of **systems optimization** and **principles in machine learning**. The goal of this library is to push the extreme of the computation limits of machines to provide a **scalable**, **portable** and **accurate** library. Make sure you try it out, and most importantly, contribute your piece of wisdom (code, examples, tutorials) to the community!

1.4.2 Introduction to Model IO

In XGBoost 1.0.0, we introduced support of using [JSON](#) for saving/loading XGBoost models and related hyper-parameters for training, aiming to replace the old binary internal format with an open format that can be easily reused. Later in XGBoost 1.6.0, additional support for [Universal Binary JSON](#) is added as an optimization for more efficient model IO. They have the same document structure with different representations, and we will refer them collectively as the JSON format. This tutorial aims to share some basic insights into the JSON serialisation method used in XGBoost. Without explicitly mentioned, the following sections assume you are using the one of the 2 outputs formats, which can be enabled by providing the file name with `.json` (or `.ubj` for binary JSON) as file extension when saving/loading model: `booster.save_model('model.json')`. More details below.

Before we get started, XGBoost is a gradient boosting library with focus on tree model, which means inside XGBoost, there are 2 distinct parts:

1. The model consisting of trees and
2. Hyperparameters and configurations used for building the model.

If you come from Deep Learning community, then it should be clear to you that there are differences between the neural network structures composed of weights with fixed tensor operations, and the optimizers (like RMSprop) used to train them.

So when one calls `booster.save_model(xgb.save in R)`, XGBoost saves the trees, some model parameters like number of input columns in trained trees, and the objective function, which combined to represent the concept of “model” in XGBoost. As for why are we saving the objective as part of model, that’s because objective controls transformation of global bias (called `base_score` in XGBoost). Users can share this model with others for prediction, evaluation or continue the training with a different set of hyper-parameters etc.

However, this is not the end of story. There are cases where we need to save something more than just the model itself. For example, in distributed training, XGBoost performs checkpointing operation. Or for some reasons, your favorite distributed computing framework decide to copy the model from one worker to another and continue the training in there. In such cases, the serialisation output is required to contain enough information to continue previous training without user providing any parameters again. We consider such scenario as **memory snapshot** (or memory based serialisation method) and distinguish it with normal model IO operation. Currently, memory snapshot is used in the following places:

- Python package: when the `Booster` object is pickled with the built-in `pickle` module.
- R package: when the `xgb.Booster` object is persisted with the built-in functions `saveRDS` or `save`.
- JVM packages: when the `Booster` object is serialized with the built-in functions `saveModel`.

Other language bindings are still working in progress.

Note: The old binary format doesn’t distinguish difference between model and raw memory serialisation format, it’s a mix of everything, which is part of the reason why we want to replace it with a more robust serialisation method. JVM Package has its own memory based serialisation methods.

To enable JSON format support for model IO (saving only the trees and objective), provide a filename with `.json` or `.ubj` as file extension, the latter is the extension for [Universal Binary JSON](#)

Listing 11: Python

```
bst.save_model('model_file_name.json')
```

Listing 12: R

```
xgb.save(bst, 'model_file_name.json')
```

Listing 13: Scala

```
val format = "json" // or val format = "ubj"  
model.write.option("format", format).save("model_directory_path")
```

Note: Only load models from JSON files that were produced by XGBoost. Attempting to load JSON files that were produced by an external source may lead to undefined behaviors and crashes.

While for memory snapshot, UBJSON is the default starting with xgboost 1.6.

A note on backward compatibility of models and memory snapshots

We guarantee backward compatibility for models but not for memory snapshots.

Models (trees and objective) use a stable representation, so that models produced in earlier versions of XGBoost are accessible in later versions of XGBoost. **If you'd like to store or archive your model for long-term storage, use `save_model` (Python) and `xgb.save` (R).**

On the other hand, memory snapshot (serialisation) captures many stuff internal to XGBoost, and its format is not stable and is subject to frequent changes. Therefore, memory snapshot is suitable for checkpointing only, where you persist the complete snapshot of the training configurations so that you can recover robustly from possible failures and resume the training process. Loading memory snapshot generated by an earlier version of XGBoost may result in errors or undefined behaviors. **If a model is persisted with `pickle.dump` (Python) or `saveRDS` (R), then the model may not be accessible in later versions of XGBoost.**

Custom objective and metric

XGBoost accepts user provided objective and metric functions as an extension. These functions are not saved in model file as they are language dependent features. With Python, user can pickle the model to include these functions in saved binary. One drawback is, the output from pickle is not a stable serialization format and doesn't work on different Python version nor XGBoost version, not to mention different language environments. Another way to workaround this limitation is to provide these functions again after the model is loaded. If the customized function is useful, please consider making a PR for implementing it inside XGBoost, this way we can have your functions working with different language bindings.

Loading pickled file from different version of XGBoost

As noted, pickled model is neither portable nor stable, but in some cases the pickled models are valuable. One way to restore it in the future is to load it back with that specific version of Python and XGBoost, export the model by calling `save_model`.

A similar procedure may be used to recover the model persisted in an old RDS file. In R, you are able to install an older version of XGBoost using the `remotes` package:

```
library(remotes)  
remotes::install_version("xgboost", "0.90.0.1") # Install version 0.90.0.1
```


Once the desired version is installed, you can load the RDS file with `readRDS` and recover the `xgb.Booster` object. Then call `xgb.save` to export the model using the stable representation. Now you should be able to use the model in the latest version of XGBoost.

Saving and Loading the internal parameters configuration

XGBoost's C API, Python API and R API support saving and loading the internal configuration directly as a JSON string. In Python package:

```
bst = xgboost.train(...)
config = bst.save_config()
print(config)
```

or in R:

```
config <- xgb.config(bst)
print(config)
```

Will print out something similar to (not actual output as it's too long for demonstration):

```
{
  "Learner": {
    "generic_parameter": {
      "device": "cuda:0",
      "gpu_page_size": "0",
      "n_jobs": "0",
      "random_state": "0",
      "seed": "0",
      "seed_per_iteration": "0"
    },
    "gradient_booster": {
      "gbtree_train_param": {
        "num_parallel_tree": "1",
        "process_type": "default",
        "tree_method": "hist",
        "updater": "grow_gpu_hist",
        "updater_seq": "grow_gpu_hist"
      },
      "name": "gbtree",
      "updater": {
        "grow_gpu_hist": {
          "gpu_hist_train_param": {
            "debug_synchronize": "0",
          },
        },
        "train_param": {
          "alpha": "0",
          "cache_opt": "1",
          "colsample_bylevel": "1",
          "colsample_bynode": "1",
          "colsample_bytree": "1",
          "default_direction": "learn",
          ...
        }
      }
    }
  }
}
```

(continues on next page)

(continued from previous page)

```

        "subsample": "1"
      }
    }
  },
  "learner_train_param": {
    "booster": "gbtree",
    "disable_default_eval_metric": "0",
    "objective": "reg:squarederror"
  },
  "metrics": [],
  "objective": {
    "name": "reg:squarederror",
    "reg_loss_param": {
      "scale_pos_weight": "1"
    }
  }
},
"version": [1, 0, 0]
}

```

You can load it back to the model generated by same version of XGBoost by:

```
bst.load_config(config)
```

This way users can study the internal representation more closely. Please note that some JSON generators make use of locale dependent floating point serialization methods, which is not supported by XGBoost.

Difference between saving model and dumping model

XGBoost has a function called `dump_model` in `Booster` object, which lets you to export the model in a readable format like `text`, `json` or `dot` (graphviz). The primary use case for it is for model interpretation or visualization, and is not supposed to be loaded back to XGBoost. The JSON version has a [schema](#). See next section for more info.

JSON Schema

Another important feature of JSON format is a documented [schema](#), based on which one can easily reuse the output model from XGBoost. Here is the JSON schema for the output model (not serialization, which will not be stable as noted above). For an example of parsing XGBoost tree model, see `/demo/json-model`. Please notice the “`weight_drop`” field used in “`dart`” booster. XGBoost does not scale tree leaf directly, instead it saves the weights as a separated array.

```

{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "definitions": {
    "gbtree": {
      "type": "object",
      "properties": {
        "name": {
          "const": "gbtree"
        }
      },
    },
  },
}

```

(continues on next page)

(continued from previous page)

```

"model": {
  "type": "object",
  "properties": {
    "gbtree_model_param": {
      "$ref": "#/definitions/gbtree_model_param"
    },
    "trees": {
      "type": "array",
      "items": {
        "type": "object",
        "properties": {
          "tree_param": {
            "$ref": "#/definitions/tree_param"
          },
          "id": {
            "type": "integer"
          },
          "loss_changes": {
            "type": "array",
            "items": {
              "type": "number"
            }
          },
          "sum_hessian": {
            "type": "array",
            "items": {
              "type": "number"
            }
          },
          "base_weights": {
            "type": "array",
            "items": {
              "type": "number"
            }
          },
          "left_children": {
            "type": "array",
            "items": {
              "type": "integer"
            }
          },
          "right_children": {
            "type": "array",
            "items": {
              "type": "integer"
            }
          },
          "parents": {
            "type": "array",
            "items": {
              "type": "integer"
            }
          }
        }
      }
    }
  }
}

```

(continues on next page)

(continued from previous page)

```
    },
    "split_indices": {
      "type": "array",
      "items": {
        "type": "integer"
      }
    },
    },
    "split_conditions": {
      "type": "array",
      "items": {
        "type": "number"
      }
    },
    },
    "split_type": {
      "type": "array",
      "items": {
        "type": "integer"
      }
    },
    },
    "default_left": {
      "type": "array",
      "items": {
        "type": "integer"
      }
    },
    },
    "categories": {
      "type": "array",
      "items": {
        "type": "integer"
      }
    },
    },
    "categories_nodes": {
      "type": "array",
      "items": {
        "type": "integer"
      }
    },
    },
    "categories_segments": {
      "type": "array",
      "items": {
        "type": "integer"
      }
    },
    },
    "categories_sizes": {
      "type": "array",
      "items": {
        "type": "integer"
      }
    },
    },
    "required": [
      "tree_param",
```

(continues on next page)

(continued from previous page)

```

        "loss_changes",
        "sum_hessian",
        "base_weights",
        "left_children",
        "right_children",
        "parents",
        "split_indices",
        "split_conditions",
        "default_left",
        "categories",
        "categories_nodes",
        "categories_segments",
        "categories_sizes"
    ]
}
},
"tree_info": {
    "type": "array",
    "items": {
        "type": "integer"
    }
}
},
"required": [
    "gbtree_model_param",
    "trees",
    "tree_info"
]
}
},
"required": [
    "name",
    "model"
]
},
"gbtree_model_param": {
    "type": "object",
    "properties": {
        "num_trees": {
            "type": "string"
        },
        "num_parallel_tree": {
            "type": "string"
        }
    },
    "required": [
        "num_trees",
        "num_parallel_tree"
    ]
},
"tree_param": {
    "type": "object",

```

(continues on next page)

(continued from previous page)

```
"properties": {
  "num_nodes": {
    "type": "string"
  },
  "size_leaf_vector": {
    "type": "string"
  },
  "num_feature": {
    "type": "string"
  }
},
"required": [
  "num_nodes",
  "num_feature",
  "size_leaf_vector"
],
"reg_loss_param": {
  "type": "object",
  "properties": {
    "scale_pos_weight": {
      "type": "string"
    }
  }
},
"pseudo_huber_param": {
  "type": "object",
  "properties": {
    "huber_slope": {
      "type": "string"
    }
  }
},
"aft_loss_param": {
  "type": "object",
  "properties": {
    "aft_loss_distribution": {
      "type": "string"
    },
    "aft_loss_distribution_scale": {
      "type": "string"
    }
  }
},
"softmax_multiclass_param": {
  "type": "object",
  "properties": {
    "num_class": { "type": "string" }
  }
},
"lambda_rank_param": {
  "type": "object",
```

(continues on next page)

(continued from previous page)

```

    "properties": {
      "num_pairsample": { "type": "string" },
      "fix_list_weight": { "type": "string" }
    }
  },
  "lambdarank_param": {
    "type": "object",
    "properties": {
      "lambdarank_num_pair_per_sample": { "type": "string" },
      "lambdarank_pair_method": { "type": "string" },
      "lambdarank_unbiased": { "type": "string" },
      "lambdarank_bias_norm": { "type": "string" },
      "ndcg_exp_gain": { "type": "string" }
    }
  }
},
"type": "object",
"properties": {
  "version": {
    "type": "array",
    "items": [
      {
        "type": "number",
        "minimum": 1
      },
      {
        "type": "number",
        "minimum": 0
      },
      {
        "type": "number",
        "minimum": 0
      }
    ]
  },
  "minItems": 3,
  "maxItems": 3
},
"learner": {
  "type": "object",
  "properties": {
    "feature_names": {
      "type": "array",
      "items": {
        "type": "string"
      }
    }
  },
  "feature_types": {
    "type": "array",
    "items": {
      "type": "string"
    }
  }
},

```

(continues on next page)

(continued from previous page)

```

"gradient_booster": {
  "oneOf": [
    {
      "$ref": "#/definitions/gbtree"
    },
    {
      "type": "object",
      "properties": {
        "name": { "const": "gblinear" },
        "model": {
          "type": "object",
          "properties": {
            "weights": {
              "type": "array",
              "items": {
                "type": "number"
              }
            }
          }
        }
      }
    },
    {
      "type": "object",
      "properties": {
        "name": { "const": "dart" },
        "gbtree": {
          "$ref": "#/definitions/gbtree"
        },
        "weight_drop": {
          "type": "array",
          "items": {
            "type": "number"
          }
        }
      },
      "required": [
        "name",
        "gbtree",
        "weight_drop"
      ]
    }
  ]
},

"objective": {
  "oneOf": [
    {
      "type": "object",
      "properties": {
        "name": { "const": "reg:squarederror" },
        "reg_loss_param": { "$ref": "#/definitions/reg_loss_param" }
      }
    }
  ]
}

```

(continues on next page)

(continued from previous page)

```

    },
    "required": [
      "name",
      "reg_loss_param"
    ]
  },
  {
    "type": "object",
    "properties": {
      "name": { "const": "reg:pseudohubererror" },
      "reg_loss_param": { "$ref": "#/definitions/reg_loss_param" }
    },
    "required": [
      "name",
      "reg_loss_param"
    ]
  },
  {
    "type": "object",
    "properties": {
      "name": { "const": "reg:squaredlogerror" },
      "reg_loss_param": { "$ref": "#/definitions/reg_loss_param" }
    },
    "required": [
      "name",
      "reg_loss_param"
    ]
  },
  {
    "type": "object",
    "properties": {
      "name": { "const": "reg:linear" },
      "reg_loss_param": { "$ref": "#/definitions/reg_loss_param" }
    },
    "required": [
      "name",
      "reg_loss_param"
    ]
  },
  {
    "type": "object",
    "properties": {
      "name": { "const": "reg:logistic" },
      "reg_loss_param": { "$ref": "#/definitions/reg_loss_param" }
    },
    "required": [
      "name",
      "reg_loss_param"
    ]
  },
  {
    "type": "object",

```

(continues on next page)

(continued from previous page)

```

    "properties": {
      "name": { "const": "binary:logistic" },
      "reg_loss_param": { "$ref": "#/definitions/reg_loss_param" }
    },
    "required": [
      "name",
      "reg_loss_param"
    ]
  },
  {
    "type": "object",
    "properties": {
      "name": { "const": "binary:logitraw" },
      "reg_loss_param": { "$ref": "#/definitions/reg_loss_param" }
    },
    "required": [
      "name",
      "reg_loss_param"
    ]
  },
  {
    "type": "object",
    "properties": {
      "name": { "const": "count:poisson" },
      "poisson_regression_param": {
        "type": "object",
        "properties": {
          "max_delta_step": { "type": "string" }
        }
      }
    },
    "required": [
      "name",
      "poisson_regression_param"
    ]
  },
  {
    "type": "object",
    "properties": {
      "name": { "const": "reg:tweedie" },
      "tweedie_regression_param": {
        "type": "object",
        "properties": {
          "tweedie_variance_power": { "type": "string" }
        }
      }
    },
    "required": [
      "name",
      "tweedie_regression_param"
    ]
  },

```

(continues on next page)

(continued from previous page)

```

    {
      "properties": {
        "name": {
          "const": "reg:absoluteerror"
        }
      },
      "type": "object"
    },
    {
      "properties": {
        "name": {
          "const": "reg:quantileerror"
        },
        "quantile_loss_param": {
          "type": "object",
          "properties": {
            "quantile_alpha": {"type": "array"}
          }
        }
      },
      "type": "object"
    },
    {
      "type": "object",
      "properties": {
        "name": { "const": "survival:cox" }
      },
      "required": [ "name" ]
    },
    {
      "type": "object",
      "properties": {
        "name": { "const": "reg:gamma" }
      },
      "required": [ "name" ]
    },
    {
      "type": "object",
      "properties": {
        "name": { "const": "multi:softprob" },
        "softmax_multiclass_param": { "$ref": "#/definitions/softmax_multiclass_
↪param" }
      },
      "required": [
        "name",
        "softmax_multiclass_param"
      ]
    },
    {
      "type": "object",
      "properties": {

```

(continues on next page)

(continued from previous page)

```

        "name": { "const": "multi:softmax" },
        "softmax_multiclass_param": { "$ref": "#/definitions/softmax_multiclass_
↪param" }
    },
    "required": [
        "name",
        "softmax_multiclass_param"
    ]
},
{
    "type": "object",
    "properties": {
        "name": { "const": "rank:pairwise" },
        "lambda_rank_param": { "$ref": "#/definitions/lambdarank_param" }
    },
    "required": [
        "name",
        "lambdarank_param"
    ]
},
{
    "type": "object",
    "properties": {
        "name": { "const": "rank:ndcg" },
        "lambda_rank_param": { "$ref": "#/definitions/lambdarank_param" }
    },
    "required": [
        "name",
        "lambdarank_param"
    ]
},
{
    "type": "object",
    "properties": {
        "name": { "const": "rank:map" },
        "lambda_rank_param": { "$ref": "#/definitions/lambda_rank_param" }
    },
    "required": [
        "name",
        "lambda_rank_param"
    ]
},
{
    "type": "object",
    "properties": {
        "name": { "const": "survival:aft" },
        "aft_loss_param": { "$ref": "#/definitions/aft_loss_param" }
    }
},
{
    "type": "object",

```

(continues on next page)

(continued from previous page)

```

        "properties": {
            "name": {"const": "binary:hinge"}
        }
    ],
},
"learner_model_param": {
    "type": "object",
    "properties": {
        "base_score": { "type": "string" },
        "num_class": { "type": "string" },
        "num_feature": { "type": "string" },
        "num_target": { "type": "string" }
    }
},
},
"required": [
    "gradient_booster",
    "objective"
]
}
},
"required": [
    "version",
    "learner"
]
}

```

1.4.3 Learning to Rank

Contents

- *Overview*
- *Training with the Pairwise Objective*
- *Position Bias*
- *Loss*
- *Constructing Pairs*
- *Obtaining Good Result*
- *Distributed Training*
- *Reproducible Result*
- *References*

Overview

Often in the context of information retrieval, learning-to-rank aims to train a model that arranges a set of query results into an ordered list [1]. For supervised learning-to-rank, the predictors are sample documents encoded as feature matrix, and the labels are relevance degree for each sample. Relevance degree can be multi-level (graded) or binary (relevant or not). The training samples are often grouped by their query index with each query group containing multiple query results.

XGBoost implements learning to rank through a set of objective functions and performance metrics. The default objective is `rank:ndcg` based on the LambdaMART [2] algorithm, which in turn is an adaptation of the LambdaRank [3] framework to gradient boosting trees. For a history and a summary of the algorithm, see [5]. The implementation in XGBoost features deterministic GPU computation, distributed training, position debiasing and two different pair construction strategies.

Training with the Pairwise Objective

LambdaMART is a pairwise ranking model, meaning that it compares the relevance degree for every pair of samples in a query group and calculate a proxy gradient for each pair. The default objective `rank:ndcg` is using the surrogate gradient derived from the `ndcg` metric. To train a XGBoost model, we need an additional sorted array called `qid` for specifying the query group of input samples. An example input would look like this:

QID	Label	Features
1	0	x_1
1	1	x_2
1	0	x_3
2	0	x_4
2	1	x_5
2	1	x_6
2	1	x_7

Notice that the samples are sorted based on their query index in a non-decreasing order. In the above example, the first three samples belong to the first query and the next four samples belong to the second. For the sake of simplicity, we will use a synthetic binary learning-to-rank dataset in the following code snippets, with binary labels representing whether the result is relevant or not, and randomly assign the query group index to each sample. For an example that uses a real world dataset, please see *Getting started with learning to rank*.

```
from sklearn.datasets import make_classification
import numpy as np

import xgboost as xgb

# Make a synthetic ranking dataset for demonstration
seed = 1994
X, y = make_classification(random_state=seed)
rng = np.random.default_rng(seed)
n_query_groups = 3
qid = rng.integers(0, 3, size=X.shape[0])

# Sort the inputs based on query index
sorted_idx = np.argsort(qid)
X = X[sorted_idx, :]
y = y[sorted_idx]
```

The simplest way to train a ranking model is by using the scikit-learn estimator interface. Continuing the previous snippet, we can train a simple ranking model without tuning:

```
ranker = xgb.XGBRanker(tree_method="hist", lambdarank_num_pair_per_sample=8, objective=
    ↪ "rank:ndcg", lambdarank_pair_method="topk")
ranker.fit(X, y, qid=qid)
```

Please note that, as of writing, there's no learning-to-rank interface in scikit-learn. As a result, the `xgboost.XGBRanker` class does not fully conform the scikit-learn estimator guideline and can not be directly used with some of its utility functions. For instances, the `auc_score` and `ndcg_score` in scikit-learn don't consider query group information nor the pairwise loss. Most of the metrics are implemented as part of XGBoost, but to use scikit-learn utilities like `sklearn.model_selection.cross_validation()`, we need to make some adjustments in order to pass the `qid` as an additional parameter for `xgboost.XGBRanker.score()`. Given a data frame `X` (either pandas or cuDF), add the column `qid` as follows:

```
df = pd.DataFrame(X, columns=[str(i) for i in range(X.shape[1])])
df["qid"] = qid
ranker.fit(df, y) # No need to pass qid as a separate argument

from sklearn.model_selection import StratifiedGroupKFold, cross_val_score
# Works with cv in scikit-learn, along with HPO utilities like GridSearchCV
kfold = StratifiedGroupKFold(shuffle=False)
cross_val_score(ranker, df, y, cv=kfold, groups=df.qid)
```

The above snippets build a model using LambdaMART with the NDCG@8 metric. The outputs of a ranker are relevance scores:

```
scores = ranker.predict(X)
sorted_idx = np.argsort(scores)[::-1]
# Sort the relevance scores from most relevant to least relevant
scores = scores[sorted_idx]
```

Position Bias

New in version 2.0.0.

Note: The feature is considered experimental. This is a heated research area, and your input is much appreciated!

Obtaining real relevance degrees for query results is an expensive and strenuous, requiring human labelers to label all results one by one. When such labeling task is infeasible, we might want to train the learning-to-rank model on user click data instead, as it is relatively easy to collect. Another advantage of using click data directly is that it can reflect the most up-to-date user preferences [1]. However, user clicks are often biased, as users tend to choose results that are displayed in higher positions. User clicks are also noisy, where users might accidentally click on irrelevant documents. To ameliorate these issues, XGBoost implements the Unbiased LambdaMART [4] algorithm to debias the position-dependent click data. The feature can be enabled by the `lambdarank_unbiased` parameter; see *Parameters for learning to rank* (`rank:ndcg`, `rank:map`, `rank:pairwise`) for related options and *Getting started with learning to rank* for a worked example with simulated user clicks.

Loss

XGBoost implements different LambdaMART objectives based on different metrics. We list them here as a reference. Other than those used as objective function, XGBoost also implements metrics like `pre` (for precision) for evaluation. See [parameters](#) for available options and the following sections for how to choose these objectives based of the amount of effective pairs.

- NDCG

Normalized Discounted Cumulative Gain NDCG can be used with both binary relevance and multi-level relevance. If you are not sure about your data, this metric can be used as the default. The name for the objective is `rank:ndcg`.

- MAP

Mean average precision MAP is a binary measure. It can be used when the relevance label is 0 or 1. The name for the objective is `rank:map`.

- Pairwise

The *LambdaMART* algorithm scales the logistic loss with learning to rank metrics like NDCG in the hope of including ranking information into the loss function. The `rank:pairwise` loss is the original version of the pairwise loss, also known as the *RankNet loss* [7] or the *pairwise logistic loss*. Unlike the `rank:map` and the `rank:ndcg`, no scaling is applied ($|\Delta Z_{ij}| = 1$).

Whether scaling with a LTR metric is actually more effective is still up for debate; [8] provides a theoretical foundation for general lambda loss functions and some insights into the framework.

Constructing Pairs

There are two implemented strategies for constructing document pairs for λ -gradient calculation. The first one is the mean method, another one is the `topk` method. The preferred strategy can be specified by the `lambdarank_pair_method` parameter.

For the mean strategy, XGBoost samples `lambdarank_num_pair_per_sample` pairs for each document in a query list. For example, given a list of 3 documents and `lambdarank_num_pair_per_sample` is set to 2, XGBoost will randomly sample 6 pairs, assuming the labels for these documents are different. On the other hand, if the pair method is set to `topk`, XGBoost constructs about $k \times |query|$ number of pairs with $|query|$ pairs for each sample at the top $k = \text{lambdarank_num_pair}$ position. The number of pairs counted here is an approximation since we skip pairs that have the same label.

Obtaining Good Result

Learning to rank is a sophisticated task and an active research area. It's not trivial to train a model that generalizes well. There are multiple loss functions available in XGBoost along with a set of hyperparameters. This section contains some hints for how to choose hyperparameters as a starting point. One can further optimize the model by tuning these hyperparameters.

The first question would be how to choose an objective that matches the task at hand. If your input data has multi-level relevance degrees, then either `rank:ndcg` or `rank:pairwise` should be used. However, when the input has binary labels, we have multiple options based on the target metric. [6] provides some guidelines on this topic and users are encouraged to see the analysis done in their work. The choice should be based on the number of *effective pairs*, which refers to the number of pairs that can generate non-zero gradient and contribute to training. *LambdaMART* with MRR has the least amount of effective pairs as the λ -gradient is only non-zero when the pair contains a non-relevant document ranked higher than the top relevant document. As a result, it's not implemented in XGBoost. Since NDCG is a multi-level metric, it usually generate more effective pairs than MAP.

However, when there are sufficiently many effective pairs, it's shown in [6] that matching the target metric with the objective is of significance. When the target metric is MAP and you are using a large dataset that can provide a sufficient amount of effective pairs, `rank:map` can in theory yield higher MAP value than `rank:ndcg`.

The consideration of effective pairs also applies to the choice of pair method (`lambdarank_pair_method`) and the number of pairs for each sample (`lambdarank_num_pair_per_sample`). For example, the mean-NDCG considers more pairs than NDCG@10, so the former generates more effective pairs and provides more granularity than the latter. Also, using the mean strategy can help the model generalize with random sampling. However, one might want to focus the training on the top k documents instead of using all pairs, to better fit their real-world application.

When using the mean strategy for generating pairs, where the target metric (like NDCG) is computed over the whole query list, users can specify how many pairs should be generated per each document, by setting the `lambdarank_num_pair_per_sample`. XGBoost will randomly sample `lambdarank_num_pair_per_sample` pairs for each element in the query group ($|pairs| = |query| \times num_pairsample$). Often, setting it to 1 can produce reasonable results. In cases where performance is inadequate due to insufficient number of effective pairs being generated, set `lambdarank_num_pair_per_sample` to a higher value. As more document pairs are generated, more effective pairs will be generated as well.

On the other hand, if you are prioritizing the top k documents, the `lambdarank_num_pair_per_sample` should be set slightly higher than k (with a few more documents) to obtain a good training result.

Summary If you have large amount of training data:

- Use the target-matching objective.
- Choose the `topk` strategy for generating document pairs (if it's appropriate for your application).

On the other hand, if you have comparatively small amount of training data:

- Select NDCG or the RankNet loss (`rank:pairwise`).
- Choose the mean strategy for generating document pairs, to obtain more effective pairs.

For any method chosen, you can modify `lambdarank_num_pair_per_sample` to control the amount of pairs generated.

Distributed Training

XGBoost implements distributed learning-to-rank with integration of multiple frameworks including Dask, Spark, and PySpark. The interface is similar to the single-node counterpart. Please refer to document of the respective XGBoost interface for details. Scattering a query group onto multiple workers is theoretically sound but can affect the model accuracy. For most of the use cases, the small discrepancy is not an issue, as the amount of training data is usually large when distributed training is used. As a result, users don't need to partition the data based on query groups. As long as each data partition is correctly sorted by query IDs, XGBoost can aggregate sample gradients accordingly.

Reproducible Result

Like any other tasks, XGBoost should generate reproducible results given the same hardware and software environments (and data partitions, if distributed interface is used). Even when the underlying environment has changed, the result should still be consistent. However, when the `lambdarank_pair_method` is set to `mean`, XGBoost uses random sampling, and results may differ depending on the platform used. The random number generator used on Windows (Microsoft Visual C++) is different from the ones used on other platforms like Linux (GCC, Clang)¹, so the output varies significantly between these platforms.

¹ `minstd_rand` implementation is different on MSVC. The implementations from GCC and Thrust produce the same output.

References

- [1] Tie-Yan Liu. 2009. “[Learning to Rank for Information Retrieval](#)”. *Found. Trends Inf. Retr.* 3, 3 (March 2009), 225–331.
- [2] Christopher J. C. Burges, Robert Ragno, and Quoc Viet Le. 2006. “[Learning to rank with nonsmooth cost functions](#)”. In *Proceedings of the 19th International Conference on Neural Information Processing Systems (NIPS’06)*. MIT Press, Cambridge, MA, USA, 193–200.
- [3] Wu, Q., Burges, C.J.C., Svore, K.M. et al. “[Adapting boosting for information retrieval measures](#)”. *Inf Retrieval* 13, 254–270 (2010).
- [4] Ziniu Hu, Yang Wang, Qu Peng, Hang Li. “[Unbiased LambdaMART: An Unbiased Pairwise Learning-to-Rank Algorithm](#)”. *Proceedings of the 2019 World Wide Web Conference*.
- [5] Burges, Chris J.C. “[From RankNet to LambdaRank to LambdaMART: An Overview](#)”. MSR-TR-2010-82
- [6] Pinar Donmez, Krysta M. Svore, and Christopher J.C. Burges. 2009. “[On the local optimality of LambdaRank](#)”. In *Proceedings of the 32nd international ACM SIGIR conference on Research and development in information retrieval (SIGIR ‘09)*. Association for Computing Machinery, New York, NY, USA, 460–467.
- [7] Chris Burges, Tal Shaked, Erin Renshaw, Ari Lazier, Matt Deeds, Nicole Hamilton, and Greg Hullender. 2005. “[Learning to rank using gradient descent](#)”. In *Proceedings of the 22nd international conference on Machine learning (ICML ‘05)*. Association for Computing Machinery, New York, NY, USA, 89–96.
- [8] Xuanhui Wang and Cheng Li and Nadav Golbandi and Mike Bendersky and Marc Najork. 2018. “[The LambdaLoss Framework for Ranking Metric Optimization](#)”. *Proceedings of The 27th ACM International Conference on Information and Knowledge Management (CIKM ‘18)*.

1.4.4 DART booster

XGBoost mostly combines a huge number of regression trees with a small learning rate. In this situation, trees added early are significant and trees added late are unimportant.

Vinayak and Gilad-Bachrach proposed a new method to add dropout techniques from the deep neural net community to boosted trees, and reported better results in some situations.

This is a instruction of new tree booster `dart`.

Original paper

Rashmi Korlakai Vinayak, Ran Gilad-Bachrach. “DART: Dropouts meet Multiple Additive Regression Trees.” [[PMLR](#), [arXiv](#)].

Features

- Drop trees in order to solve the over-fitting.
 - Trivial trees (to correct trivial errors) may be prevented.

Because of the randomness introduced in the training, expect the following few differences:

- Training can be slower than `gbtree` because the random dropout prevents usage of the prediction buffer.
- The early stop might not be stable, due to the randomness.

How it works

- In m -th training round, suppose k trees are selected to be dropped.
- Let $D = \sum_{i \in \mathbf{K}} F_i$ be the leaf scores of dropped trees and $F_m = \eta \tilde{F}_m$ be the leaf scores of a new tree.
- The objective function is as follows:

$$\text{Obj} = \sum_{j=1}^n L(y_j, \hat{y}_j^{m-1} - D_j + \tilde{F}_m) + \Omega(\tilde{F}_m).$$

- D and F_m are overshooting, so using scale factor

$$\hat{y}_j^m = \sum_{i \notin \mathbf{K}} F_i + a \left(\sum_{i \in \mathbf{K}} F_i + b F_m \right).$$

Parameters

The booster `dart` inherits `gbtree` booster, so it supports all parameters that `gbtree` does, such as `eta`, `gamma`, `max_depth` etc.

Additional parameters are noted below:

- `sample_type`: type of sampling algorithm.
 - `uniform`: (default) dropped trees are selected uniformly.
 - `weighted`: dropped trees are selected in proportion to weight.
- `normalize_type`: type of normalization algorithm.
 - `tree`: (default) New trees have the same weight of each of dropped trees.

$$\begin{aligned} a \left(\sum_{i \in \mathbf{K}} F_i + \frac{1}{k} F_m \right) &= a \left(\sum_{i \in \mathbf{K}} F_i + \frac{\eta}{k} \tilde{F}_m \right) \\ &\sim a \left(1 + \frac{\eta}{k} \right) D \\ &= a \frac{k + \eta}{k} D = D, \\ a &= \frac{k}{k + \eta} \end{aligned}$$

- `forest`: New trees have the same weight of sum of dropped trees (forest).

$$\begin{aligned} a \left(\sum_{i \in \mathbf{K}} F_i + F_m \right) &= a \left(\sum_{i \in \mathbf{K}} F_i + \eta \tilde{F}_m \right) \\ &\sim a (1 + \eta) D \\ &= a (1 + \eta) D = D, \\ a &= \frac{1}{1 + \eta}. \end{aligned}$$

- `rate_drop`: dropout rate.
 - range: [0.0, 1.0]
- `skip_drop`: probability of skipping dropout.
 - If a dropout is skipped, new trees are added in the same manner as `gbtree`.
 - range: [0.0, 1.0]

Sample Script

```
import xgboost as xgb
# read in data
dtrain = xgb.DMatrix('demo/data/agaricus.txt.train')
dtest = xgb.DMatrix('demo/data/agaricus.txt.test')
# specify parameters via map
param = {'booster': 'dart',
         'max_depth': 5, 'learning_rate': 0.1,
         'objective': 'binary:logistic',
         'sample_type': 'uniform',
         'normalize_type': 'tree',
         'rate_drop': 0.1,
         'skip_drop': 0.5}
num_round = 50
bst = xgb.train(param, dtrain, num_round)
preds = bst.predict(dtest)
```

1.4.5 Monotonic Constraints

It is often the case in a modeling problem or project that the functional form of an acceptable model is constrained in some way. This may happen due to business considerations, or because of the type of scientific question being investigated. In some cases, where there is a very strong prior belief that the true relationship has some quality, constraints can be used to improve the predictive performance of the model.

A common type of constraint in this situation is that certain features bear a **monotonic** relationship to the predicted response:

$$f(x_1, x_2, \dots, x, \dots, x_{n-1}, x_n) \leq f(x_1, x_2, \dots, x', \dots, x_{n-1}, x_n)$$

whenever $x \leq x'$ is an **increasing constraint**; or

$$f(x_1, x_2, \dots, x, \dots, x_{n-1}, x_n) \geq f(x_1, x_2, \dots, x', \dots, x_{n-1}, x_n)$$

whenever $x \leq x'$ is a **decreasing constraint**.


XGBoost has the ability to enforce monotonicity constraints on any features used in a boosted model.

A Simple Example


To illustrate, let's create some simulated data with two features and a response according to the following scheme

$$y = 5x_1 + \sin(10\pi x_1) - 5x_2 - \cos(10\pi x_2) + N(0, 0.01)x_1, x_2 \in [0, 1]$$

The response generally increases with respect to the x_1 feature, but a sinusoidal variation has been superimposed, resulting in the true effect being non-monotonic. For the x_2 feature the variation is decreasing with a sinusoidal variation.




Let's fit a boosted tree model to this data without imposing any monotonic constraints:



The black curve shows the trend inferred from the model for each feature. To make these plots the distinguished feature x_i is fed to the model over a one-dimensional grid of values, while all the other features (in this case only one other feature) are set to their average values. We see that the model does a good job of capturing the general trend with the oscillatory wave superimposed.

Here is the same model, but fit with monotonicity constraints:



We see the effect of the constraint. For each variable the general direction of the trend is still evident, but the oscillatory behaviour no longer remains as it would violate our imposed constraints.

Enforcing Monotonic Constraints in XGBoost

It is very simple to enforce monotonicity constraints in XGBoost. Here we will give an example using Python, but the same general idea generalizes to other platforms.

Suppose the following code fits your model without monotonicity constraints

```
model_no_constraints = xgb.train(params, dtrain,
                                num_boost_round = 1000, evals = evallist,
                                early_stopping_rounds = 10)
```

Then fitting with monotonicity constraints only requires adding a single parameter

```
params_constrained = params.copy()
params_constrained['monotone_constraints'] = (1,-1)

model_with_constraints = xgb.train(params_constrained, dtrain,
                                   num_boost_round = 1000, evals = evallist,
                                   early_stopping_rounds = 10)
```

In this example the training data X has two columns, and by using the parameter values $(1, -1)$ we are telling XGBoost to impose an increasing constraint on the first predictor and a decreasing constraint on the second.

Some other examples:

- $(1, 0)$: An increasing constraint on the first predictor and no constraint on the second.
- $(0, -1)$: No constraint on the first predictor and a decreasing constraint on the second.

Note: Note for the ‘hist’ tree construction algorithm. If `tree_method` is set to either `hist` or `approx`, enabling monotonic constraints may produce unnecessarily shallow trees. This is because the `hist` method reduces the number of candidate splits to be considered at each split. Monotonic constraints may wipe out all available split candidates, in which case no split is made. To reduce the effect, you may want to increase the `max_bin` parameter to consider more split candidates.

Using feature names

XGBoost's Python package supports using feature names instead of feature index for specifying the constraints. Given a data frame with columns ["f0", "f1", "f2"], the monotonic constraint can be specified as {"f0": 1, "f2": -1}, and "f1" will default to 0 (no constraint).

1.4.6 Feature Interaction Constraints

The decision tree is a powerful tool to discover interaction among independent variables (features). Variables that appear together in a traversal path are interacting with one another, since the condition of a child node is predicated on the condition of the parent node. For example, the highlighted red path in the diagram below contains three variables: x_1 , x_7 , and x_{10} , so the highlighted prediction (at the highlighted leaf node) is the product of interaction between x_1 , x_7 , and x_{10} .

When the tree depth is larger than one, many variables interact on the sole basis of minimizing training loss, and the resulting decision tree may capture a spurious relationship (noise) rather than a legitimate relationship that generalizes across different datasets. **Feature interaction constraints** allow users to decide which variables are allowed to interact and which are not.

Potential benefits include:

- Better predictive performance from focusing on interactions that work – whether through domain specific knowledge or algorithms that rank interactions
- Less noise in predictions; better generalization
- More control to the user on what the model can fit. For example, the user may want to exclude some interactions even if they perform well due to regulatory constraints.

A Simple Example

Feature interaction constraints are expressed in terms of groups of variables that are allowed to interact. For example, the constraint [0, 1] indicates that variables x_0 and x_1 are allowed to interact with each other but with no other variable. Similarly, [2, 3, 4] indicates that x_2 , x_3 , and x_4 are allowed to interact with one another but with no other variable. A set of feature interaction constraints is expressed as a nested list, e.g. [[0, 1], [2, 3, 4]], where each inner list is a group of indices of features that are allowed to interact with each other.

In the following diagram, the left decision tree is in violation of the first constraint ([0, 1]), whereas the right decision tree complies with both the first and second constraints ([0, 1], [2, 3, 4]).

forbidden	allowed

Enforcing Feature Interaction Constraints in XGBoost

It is very simple to enforce feature interaction constraints in XGBoost. Here we will give an example using Python, but the same general idea generalizes to other platforms.

Suppose the following code fits your model without feature interaction constraints:

```
model_no_constraints = xgb.train(params, dtrain,
                                num_boost_round = 1000, evals = evallist,
                                early_stopping_rounds = 10)
```

Then fitting with feature interaction constraints only requires adding a single parameter:

```
params_constrained = params.copy()
# Use nested list to define feature interaction constraints
params_constrained['interaction_constraints'] = '[[0, 2], [1, 3, 4], [5, 6]]'
# Features 0 and 2 are allowed to interact with each other but with no other feature
# Features 1, 3, 4 are allowed to interact with one another but with no other feature
# Features 5 and 6 are allowed to interact with each other but with no other feature

model_with_constraints = xgb.train(params_constrained, dtrain,
                                   num_boost_round = 1000, evals = evallist,
                                   early_stopping_rounds = 10)
```

Using feature name instead

XGBoost's Python package supports using feature names instead of feature index for specifying the constraints. Given a data frame with columns ["f0", "f1", "f2"], the feature interaction constraint can be specified as ["f0", "f2"].

Advanced topic

The intuition behind interaction constraints is simple. Users may have prior knowledge about relations between different features, and encode it as constraints during model construction. But there are also some subtleties around specifying constraints. Take the constraint [[1, 2], [2, 3, 4]] as an example. The second feature appears in two different interaction sets, [1, 2] and [2, 3, 4]. So the union set of features allowed to interact with 2 is {1, 3, 4}. In the following diagram, the root splits at feature 2. Because all its descendants should be able to interact with it, all 4 features are legitimate split candidates at the second layer. At first sight, this might look like disregarding the specified constraint sets, but it is not.

This has lead to some interesting implications of feature interaction constraints. Take [[0, 1], [0, 1, 2], [1, 2]] as another example. Assuming we have only 3 available features in our training datasets for presentation purpose, careful readers might have found out that the above constraint is the same as simply [[0, 1, 2]]. Since no matter which feature is chosen for split in the root node, all its descendants are allowed to include every feature as legitimate split candidates without violating interaction constraints.

For one last example, we use [[0, 1], [1, 3, 4]] and choose feature 0 as split for the root node. At the second layer of the built tree, 1 is the only legitimate split candidate except for 0 itself, since they belong to the same constraint set. Following the grow path of our example tree below, the node at the second layer splits at feature 1. But due to the fact that 1 also belongs to second constraint set [1, 3, 4], at the third layer, we are allowed to include all features as split candidates and still comply with the interaction constraints of its ascendants.




Fig. 1: $\{1, 2, 3, 4\}$ represents the sets of legitimate split features.




Fig. 2: $\{0, 1, 3, 4\}$ represents the sets of legitimate split features.

1.4.7 Survival Analysis with Accelerated Failure Time

- *What is survival analysis?*
- *Accelerated Failure Time model*
- *How to use*

What is survival analysis?

Survival analysis (regression) models **time to an event of interest**. Survival analysis is a special kind of regression and differs from the conventional regression task as follows:

- The label is always positive, since you cannot wait a negative amount of time until the event occurs.
- The label may not be fully known, or **censored**, because “it takes time to measure time.”

The second bullet point is crucial and we should dwell on it more. As you may have guessed from the name, one of the earliest applications of survival analysis is to model mortality of a given population. Let’s take [NCCTG Lung Cancer Dataset](#) as an example. The first 8 columns represent features and the last column, Time to death, represents the label.

Inst	Age	Sex	ph.ecog	ph.karno	pat.karno	meal.cal	wt.loss	Time to death (days)
3	74	1	1	90	100	1175	N/A	306
3	68	1	0	90	90	1225	15	455
3	56	1	0	90	90	N/A	15	[1010, +∞)
5	57	1	1	90	60	1150	11	210
1	60	1	0	100	90	N/A	0	883
12	74	1	1	50	80	513	0	[1022, +∞)
7	68	2	2	70	60	384	10	310

Take a close look at the label for the third patient. **His label is a range, not a single number.** The third patient’s label is said to be **censored**, because for some reason the experimenters could not get a complete measurement for that label. One possible scenario: the patient survived the first 1010 days and walked out of the clinic on the 1011th day, so his death was not directly observed. Another possibility: The experiment was cut short (since you cannot run it forever) before his death could be observed. In any case, his label is $[1010, +\infty)$, meaning his time to death can be any number that’s higher than 1010, e.g. 2000, 3000, or 10000.

There are four kinds of censoring:

- **Uncensored:** the label is not censored and given as a single number.
- **Right-censored:** the label is of form $[a, +\infty)$, where a is the lower bound.
- **Left-censored:** the label is of form $[0, b]$, where b is the upper bound.
- **Interval-censored:** the label is of form $[a, b]$, where a and b are the lower and upper bounds, respectively.

Right-censoring is the most commonly used.

Accelerated Failure Time model

Accelerated Failure Time (AFT) model is one of the most commonly used models in survival analysis. The model is of the following form:

$$\ln Y = \langle \mathbf{w}, \mathbf{x} \rangle + \sigma Z$$

where

- \mathbf{x} is a vector in \mathbb{R}^d representing the features.
- \mathbf{w} is a vector consisting of d coefficients, each corresponding to a feature.
- $\langle \cdot, \cdot \rangle$ is the usual dot product in \mathbb{R}^d .
- $\ln(\cdot)$ is the natural logarithm.
- Y and Z are random variables.
 - Y is the output label.
 - Z is a random variable of a known probability distribution. Common choices are the normal distribution, the logistic distribution, and the extreme distribution. Intuitively, Z represents the “noise” that pulls the prediction $\langle \mathbf{w}, \mathbf{x} \rangle$ away from the true log label $\ln Y$.
- σ is a parameter that scales the size of Z .

Note that this model is a generalized form of a linear regression model $Y = \langle \mathbf{w}, \mathbf{x} \rangle$. In order to make AFT work with gradient boosting, we revise the model as follows:

$$\ln Y = \mathcal{T}(\mathbf{x}) + \sigma Z$$

where $\mathcal{T}(\mathbf{x})$ represents the output from a decision tree ensemble, given input \mathbf{x} . Since Z is a random variable, we have a likelihood defined for the expression $\ln Y = \mathcal{T}(\mathbf{x}) + \sigma Z$. So the goal for XGBoost is to maximize the (log) likelihood by fitting a good tree ensemble $\mathcal{T}(\mathbf{x})$.

How to use

The first step is to express the labels in the form of a range, so that **every data point has two numbers associated with it, namely the lower and upper bounds for the label**. For uncensored labels, use a degenerate interval of form $[a, a]$.

Censoring type	Interval form	Lower bound finite?	Upper bound finite?
Uncensored	$[a, a]$	✓	✓
Right-censored	$[a, +\infty)$	✓	
Left-censored	$[0, b]$	✓	✓
Interval-censored	$[a, b]$	✓	✓

Collect the lower bound numbers in one array (let’s call it `y_lower_bound`) and the upper bound number in another array (call it `y_upper_bound`). The ranged labels are associated with a data matrix object via calls to `xgboost.DMatrix.set_float_info()`:

Listing 14: Python

```
import numpy as np
import xgboost as xgb
```

(continues on next page)

(continued from previous page)

```
# 4-by-2 Data matrix
X = np.array([[1, -1], [-1, 1], [0, 1], [1, 0]])
dtrain = xgb.DMatrix(X)

# Associate ranged labels with the data matrix.
# This example shows each kind of censored labels.
#
#           uncensored    right    left    interval
y_lower_bound = np.array([ 2.0, 3.0, 0.0, 4.0])
y_upper_bound = np.array([ 2.0, +np.inf, 4.0, 5.0])
dtrain.set_float_info('label_lower_bound', y_lower_bound)
dtrain.set_float_info('label_upper_bound', y_upper_bound)
```

Listing 15: R

```
library(xgboost)

# 4-by-2 Data matrix
X <- matrix(c(1., -1., -1., 1., 0., 1., 1., 0.),
            nrow=4, ncol=2, byrow=TRUE)
dtrain <- xgb.DMatrix(X)

# Associate ranged labels with the data matrix.
# This example shows each kind of censored labels.
#
#           uncensored    right    left    interval
y_lower_bound <- c( 2., 3., 0., 4.)
y_upper_bound <- c( 2., +Inf, 4., 5.)
setinfo(dtrain, 'label_lower_bound', y_lower_bound)
setinfo(dtrain, 'label_upper_bound', y_upper_bound)
```

Now we are ready to invoke the training API:

Listing 16: Python

```
params = {'objective': 'survival:aft',
          'eval_metric': 'aft-nloglik',
          'aft_loss_distribution': 'normal',
          'aft_loss_distribution_scale': 1.20,
          'tree_method': 'hist', 'learning_rate': 0.05, 'max_depth': 2}
bst = xgb.train(params, dtrain, num_boost_round=5,
               evals=[(dtrain, 'train')])
```

Listing 17: R

```
params <- list(objective='survival:aft',
               eval_metric='aft-nloglik',
               aft_loss_distribution='normal',
               aft_loss_distribution_scale=1.20,
               tree_method='hist',
               learning_rate=0.05,
               max_depth=2)
watchlist <- list(train = dtrain)
bst <- xgb.train(params, dtrain, nrounds=5, watchlist)
```

We set objective parameter to `survival:aft` and `eval_metric` to `aft-nloglik`, so that the log likelihood for the AFT model would be maximized. (XGBoost will actually minimize the negative log likelihood, hence the name `aft-nloglik`.)

The parameter `aft_loss_distribution` corresponds to the distribution of the Z term in the AFT model, and `aft_loss_distribution_scale` corresponds to the scaling factor σ .

Currently, you can choose from three probability distributions for `aft_loss_distribution`:

aft_loss_distribution	Probability Density Function (PDF)
normal	$\frac{\exp(-z^2/2)}{\sqrt{2\pi}}$
logistic	$\frac{(1+e^z)^2}{e^z}$
extreme	$e^z e^{-\exp z}$

Note that it is not yet possible to set the ranged label using the scikit-learn interface (e.g. `xgboost.XGBRegressor`). For now, you should use `xgboost.train` with `xgboost.DMatrix`. For a collection of Python examples, see [Survival Analysis Walkthrough](#)

1.4.8 Categorical Data

Note: As of XGBoost 1.6, the feature is experimental and has limited features. Only the Python package is fully supported.

Starting from version 1.5, the XGBoost Python package has experimental support for categorical data available for public testing. For numerical data, the split condition is defined as $value < threshold$, while for categorical data the split is defined depending on whether partitioning or onehot encoding is used. For partition-based splits, the splits are specified as $value \in categories$, where `categories` is the set of categories in one feature. If onehot encoding is used instead, then the split is defined as $value == category$. More advanced categorical split strategy is planned for future releases and this tutorial details how to inform XGBoost about the data type.

Training with scikit-learn Interface

The easiest way to pass categorical data into XGBoost is using dataframe and the `scikit-learn` interface like `XGBClassifier`. For preparing the data, users need to specify the data type of input predictor as `category`. For `pandas/cudf Dataframe`, this can be achieved by

```
X["cat_feature"].astype("category")
```

for all columns that represent categorical features. After which, users can tell XGBoost to enable training with categorical data. Assuming that you are using the `XGBClassifier` for classification problem, specify the parameter `enable_categorical`:

```
# Supported tree methods are `approx` and `hist`.
clf = xgb.XGBClassifier(tree_method="hist", enable_categorical=True, device="cuda")
# X is the dataframe we created in previous snippet
clf.fit(X, y)
# Must use JSON/UBJSON for serialization, otherwise the information is lost.
clf.save_model("categorical-model.json")
```

Once training is finished, most of other features can utilize the model. For instance one can plot the model and calculate the global feature importance:

```
# Get a graph
graph = xgb.to_graphviz(clf, num_trees=1)
# Or get a matplotlib axis
ax = xgb.plot_tree(clf, num_trees=1)
# Get feature importances
clf.feature_importances_
```

The `scikit-learn` interface from `dask` is similar to single node version. The basic idea is create dataframe with category feature type, and tell XGBoost to use it by setting the `enable_categorical` parameter. See [Getting started with categorical data](#) for a worked example of using categorical data with `scikit-learn` interface with one-hot encoding. A comparison between using one-hot encoded data and XGBoost's categorical data support can be found [Train XGBoost with cat_in_the_dat dataset](#).

Optimal Partitioning

New in version 1.6.

Optimal partitioning is a technique for partitioning the categorical predictors for each node split, the proof of optimality for numerical output was first introduced by [1]. The algorithm is used in decision trees [2], later LightGBM [3] brought it to the context of gradient boosting trees and now is also adopted in XGBoost as an optional feature for handling categorical splits. More specifically, the proof by Fisher [1] states that, when trying to partition a set of discrete values into groups based on the distances between a measure of these values, one only needs to look at sorted partitions instead of enumerating all possible permutations. In the context of decision trees, the discrete values are categories, and the measure is the output leaf value. Intuitively, we want to group the categories that output similar leaf values. During split finding, we first sort the gradient histogram to prepare the contiguous partitions then enumerate the splits according to these sorted values. One of the related parameters for XGBoost is `max_cat_to_onehot`, which controls whether one-hot encoding or partitioning should be used for each feature, see [Parameters for Categorical Feature](#) for details.

Using native interface

The `scikit-learn` interface is user friendly, but lacks some features that are only available in native interface. For instance users cannot compute SHAP value directly or use quantized `DMatrix`. Also native interface supports data types other than dataframe, like `numpy/cupy` array. To use the native interface with categorical data, we need to pass the `similar` parameter to `DMatrix` and the `train` function. For dataframe input:

```
# X is a dataframe we created in previous snippet
Xy = xgb.DMatrix(X, y, enable_categorical=True)
booster = xgb.train({"tree_method": "hist", "max_cat_to_onehot": 5}, Xy)
# Must use JSON for serialization, otherwise the information is lost
booster.save_model("categorical-model.json")
```

SHAP value computation:

```
SHAP = booster.predict(Xy, pred_interactions=True)

# categorical features are listed as "c"
print(booster.feature_types)
```

For other types of input, like `numpy` array, we can tell XGBoost about the feature types by using the `feature_types` parameter in `DMatrix`:

```
# "q" is numerical feature, while "c" is categorical feature
ft = ["q", "c", "c"]
X: np.ndarray = load_my_data()
assert X.shape[1] == 3
Xy = xgb.DMatrix(X, y, feature_types=ft, enable_categorical=True)
```

For numerical data, the feature type can be "q" or "float", while for categorical feature it's specified as "c". The `Dask` module in XGBoost has the same interface so `dask.Array` can also be used for categorical data.

Miscellaneous

By default, XGBoost assumes input categories are integers starting from 0 till the number of categories $[0, n_categories)$. However, user might provide inputs with invalid values due to mistakes or missing values in training dataset. It can be negative value, integer values that can not be accurately represented by 32-bit floating point, or values that are larger than actual number of unique categories. During training this is validated but for prediction it's treated as the same as not-chosen category for performance reasons.

References

- [1] Walter D. Fisher. "On Grouping for Maximum Homogeneity". Journal of the American Statistical Association. Vol. 53, No. 284 (Dec., 1958), pp. 789-798.
- [2] Trevor Hastie, Robert Tibshirani, Jerome Friedman. "The Elements of Statistical Learning". Springer Series in Statistics Springer New York Inc. (2001).
- [3] Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, Tie-Yan Liu. "LightGBM: A Highly Efficient Gradient Boosting Decision Tree." Advances in Neural Information Processing Systems 30 (NIPS 2017), pp. 3149-3157.

1.4.9 Multiple Outputs

New in version 1.6.

Starting from version 1.6, XGBoost has experimental support for multi-output regression and multi-label classification with Python package. Multi-label classification usually refers to targets that have multiple non-exclusive class labels. For instance, a movie can be simultaneously classified as both sci-fi and comedy. For detailed explanation of terminologies related to different multi-output models please refer to the [scikit-learn user guide](#).

Note: As of XGBoost 2.0, the feature is experimental and has limited features. Only the Python package is tested.

Training with One-Model-Per-Target

By default, XGBoost builds one model for each target similar to sklearn meta estimators, with the added benefit of reusing data and other integrated features like SHAP. For a worked example of regression, see [A demo for multi-output regression](#). For multi-label classification, the binary relevance strategy is used. Input `y` should be of shape `(n_samples, n_classes)` with each column having a value of 0 or 1 to specify whether the sample is labeled as positive for respective class. Given a sample with 3 output classes and 2 labels, the corresponding `y` should be encoded as `[1, 0, 1]` with the second class labeled as negative and the rest labeled as positive. At the moment XGBoost supports only dense matrix for labels.

```
from sklearn.datasets import make_multilabel_classification
import numpy as np

X, y = make_multilabel_classification(
    n_samples=32, n_classes=5, n_labels=3, random_state=0
)
clf = xgb.XGBClassifier(tree_method="hist")
clf.fit(X, y)
np.testing.assert_allclose(clf.predict(X), y)
```

The feature is still under development with limited support from objectives and metrics.

Training with Vector Leaf

New in version 2.0.

Note: This is still working-in-progress, and most features are missing.

XGBoost can optionally build multi-output trees with the size of leaf equals to the number of targets when the tree method `hist` is used. The behavior can be controlled by the `multi_strategy` training parameter, which can take the value `one_output_per_tree` (the default) for building one model per-target or `multi_output_tree` for building multi-output trees.

```
clf = xgb.XGBClassifier(tree_method="hist", multi_strategy="multi_output_tree")
```

See [A demo for multi-output regression](#) for a worked example with regression.

1.4.10 Random Forests(TM) in XGBoost

XGBoost is normally used to train gradient-boosted decision trees and other gradient boosted models. Random Forests use the same model representation and inference, as gradient-boosted decision trees, but a different training algorithm. One can use XGBoost to train a standalone random forest or use random forest as a base model for gradient boosting. Here we focus on training standalone random forest.

We have native APIs for training random forests since the early days, and a new Scikit-Learn wrapper after 0.82 (not included in 0.82). Please note that the new Scikit-Learn wrapper is still **experimental**, which means we might change the interface whenever needed.

Standalone Random Forest With XGBoost API

The following parameters must be set to enable random forest training.

- `booster` should be set to `gbtree`, as we are training forests. Note that as this is the default, this parameter needn't be set explicitly.
- `subsample` must be set to a value less than 1 to enable random selection of training cases (rows).
- One of `colsample_by*` parameters must be set to a value less than 1 to enable random selection of columns. Normally, `colsample_bynode` would be set to a value less than 1 to randomly sample columns at each tree split.
- `num_parallel_tree` should be set to the size of the forest being trained.
- `num_boost_round` should be set to 1 to prevent XGBoost from boosting multiple random forests. Note that this is a keyword argument to `train()`, and is not part of the parameter dictionary.
- `eta` (alias: `learning_rate`) must be set to 1 when training random forest regression.
- `random_state` can be used to seed the random number generator.

Other parameters should be set in a similar way they are set for gradient boosting. For instance, `objective` will typically be `reg:squarederror` for regression and `binary:logistic` for classification, `lambda` should be set according to a desired regularization weight, etc.

If both `num_parallel_tree` and `num_boost_round` are greater than 1, training will use a combination of random forest and gradient boosting strategy. It will perform `num_boost_round` rounds, boosting a random forest of `num_parallel_tree` trees at each round. If early stopping is not enabled, the final model will consist of `num_parallel_tree * num_boost_round` trees.

Here is a sample parameter dictionary for training a random forest on a GPU using xgboost:

```
params = {
    "colsample_bynode": 0.8,
    "learning_rate": 1,
    "max_depth": 5,
    "num_parallel_tree": 100,
    "objective": "binary:logistic",
    "subsample": 0.8,
    "tree_method": "hist",
    "device": "cuda",
}
```

A random forest model can then be trained as follows:

```
bst = train(params, dmatrix, num_boost_round=1)
```

Standalone Random Forest With Scikit-Learn-Like API

`XGBRFClassifier` and `XGBRFRegressor` are SKL-like classes that provide random forest functionality. They are basically versions of `XGBClassifier` and `XGBRegressor` that train random forest instead of gradient boosting, and have default values and meaning of some of the parameters adjusted accordingly. In particular:

- `n_estimators` specifies the size of the forest to be trained; it is converted to `num_parallel_tree`, instead of the number of boosting rounds
- `learning_rate` is set to 1 by default
- `colsample_bynode` and `subsample` are set to 0.8 by default
- `booster` is always `gbtree`

For a simple example, you can train a random forest regressor with:

```
from sklearn.model_selection import KFold

# Your code ...

kf = KFold(n_splits=2)
for train_index, test_index in kf.split(X, y):
    xgb_model = xgb.XGBRFRegressor(random_state=42).fit(
        X[train_index], y[train_index])
```

Note that these classes have a smaller selection of parameters compared to using `train()`. In particular, it is impossible to combine random forests with gradient boosting using this API.

Caveats

- XGBoost uses 2nd order approximation to the objective function. This can lead to results that differ from a random forest implementation that uses the exact value of the objective function.
- XGBoost does not perform replacement when subsampling training cases. Each training case can occur in a subsampled set either 0 or 1 time.

1.4.11 Distributed XGBoost on Kubernetes

Distributed XGBoost training and batch prediction on [Kubernetes](#) are supported via [Kubeflow XGBoost Training Operator](#).

Instructions

In order to run a XGBoost job in a Kubernetes cluster, perform the following steps:

1. Install XGBoost Operator on the Kubernetes cluster.
 - a. XGBoost Operator is designed to manage the scheduling and monitoring of XGBoost jobs. Follow [this installation guide](#) to install XGBoost Operator.
2. Write application code that will be executed by the XGBoost Operator.
 - a. To use XGBoost Operator, you'll have to write a couple of Python scripts that implement the distributed training logic for XGBoost. Please refer to the [Iris classification example](#).

- b. Data reader/writer: you need to implement the data reader and writer based on the specific requirements of your chosen data source. For example, if your dataset is stored in a Hive table, you have to write the code to read from or write to the Hive table based on the index of the worker.
 - c. Model persistence: in the [Iris classification example](#), the model is stored in [Alibaba OSS](#). If you want to store your model in other storages such as Amazon S3 or Google NFS, you'll need to implement the model persistence logic based on the requirements of the chosen storage system.
3. Configure the XGBoost job using a YAML file.
 - a. YAML file is used to configure the computational resources and environment for your XGBoost job to run, e.g. the number of workers/masters and the number of CPU/GPUs. Please refer to this [YAML template](#) for an example.
4. Submit XGBoost job to a Kubernetes cluster.
 - a. Use [kubectl](#) to submit a distributed XGBoost job as illustrated [here](#).

Support

Please submit an issue on [XGBoost Operator repo](#) for any feature requests or problems.

1.4.12 Distributed XGBoost with Dask

[Dask](#) is a parallel computing library built on Python. Dask allows easy management of distributed workers and excels at handling large distributed data science workflows. The implementation in XGBoost originates from [dask-xgboost](#) with some extended functionalities and a different interface. The tutorial here focuses on basic usage of dask with CPU tree algorithms. For an overview of GPU based training and internal workings, see [A New, Official Dask API for XGBoost](#).

Contents

- [Requirements](#)
- [Overview](#)
- [Running prediction](#)
- [Scikit-Learn Estimator Interface](#)
- [GPU acceleration](#)
- [Working with other clusters](#)
- [Threads](#)
- [Working with asyncio](#)
- [Evaluation and Early Stopping](#)
- [Other customization](#)
- [Hyper-parameter tuning](#)
- [Troubleshooting](#)
- [IPv6 Support](#)
- [Why is the initialization of DaskDMatrix so slow and throws weird errors](#)
- [Reproducible Result](#)

- *Memory Usage*

Requirements

Dask can be installed using either pip or conda (see the [dask installation documentation](#) for more information). For accelerating XGBoost with GPUs, [dask-cuda](#) is recommended for creating GPU clusters.

Overview

A dask cluster consists of three different components: a centralized scheduler, one or more workers, and one or more clients which act as the user-facing entry point for submitting tasks to the cluster. When using XGBoost with dask, one needs to call the XGBoost dask interface from the client side. Below is a small example which illustrates basic usage of running XGBoost on a dask cluster:

```
import xgboost as xgb
import dask.array as da
import dask.distributed

if __name__ == "__main__":
    cluster = dask.distributed.LocalCluster()
    client = dask.distributed.Client(cluster)

    # X and y must be Dask dataframes or arrays
    num_obs = 1e5
    num_features = 20
    X = da.random.random(size=(num_obs, num_features), chunks=(1000, num_features))
    y = da.random.random(size=(num_obs, 1), chunks=(1000, 1))

    dtrain = xgb.dask.DaskDMatrix(client, X, y)
    # or
    # dtrain = xgb.dask.DaskQuantileDMatrix(client, X, y)

    output = xgb.dask.train(
        client,
        {"verbosity": 2, "tree_method": "hist", "objective": "reg:squarederror"},
        dtrain,
        num_boost_round=4,
        evals=[(dtrain, "train")],
    )
```

Here we first create a cluster in single-node mode with `distributed.LocalCluster`, then connect a `distributed.Client` to this cluster, setting up an environment for later computation. Notice that the cluster construction is guarded by `__name__ == "__main__"`, which is necessary otherwise there might be obscure errors.

We then create a `xgboost.dask.DaskDMatrix` object and pass it to `xgboost.dask.train()`, along with some other parameters, much like XGBoost's normal, non-dask interface. Unlike that interface, data and label must be either `Dask DataFrame` or `Dask Array` instances.

The primary difference with XGBoost's dask interface is we pass our dask client as an additional argument for carrying out the computation. Note that if client is set to `None`, XGBoost will use the default client returned by dask.

There are two sets of APIs implemented in XGBoost. The first set is functional API illustrated in above example. Given the data and a set of parameters, the `train` function returns a model and the computation history as a Python

dictionary:

```
{'booster': Booster,
  'history': dict}
```

For prediction, pass the output returned by `train` into `xgboost.dask.predict()`:

```
prediction = xgb.dask.predict(client, output, dtrain)
# Or equivalently, pass `output['booster']`:
prediction = xgb.dask.predict(client, output['booster'], dtrain)
```

Eliminating the construction of `DaskDMatrix` is also possible, this can make the computation a bit faster when meta information like `base_margin` is not needed:

```
prediction = xgb.dask.predict(client, output, X)
# Use inplace version.
prediction = xgb.dask.inplace_predict(client, output, X)
```

Here `prediction` is a `dask Array` object containing predictions from model if input is a `DaskDMatrix` or `da.Array`. When putting `dask collection` directly into the `predict` function or using `xgboost.dask.inplace_predict()`, the output type depends on input data. See next section for details.

Alternatively, XGBoost also implements the Scikit-Learn interface with [DaskXGBClassifier](#), [DaskXGBRegressor](#), [DaskXGBRanker](#) and 2 random forest variances. This wrapper is similar to the single node Scikit-Learn interface in `xgboost`, with `dask collection` as inputs and has an additional `client` attribute. See following sections and [XGBoost Dask Feature Walkthrough](#) for more examples.

Running prediction

In previous example we used `DaskDMatrix` as input to `predict` function. In practice, it's also possible to call `predict` function directly on `dask collections` like `Array` and `DataFrame` and might have better prediction performance. When `DataFrame` is used as prediction input, the result is a `dask Series` instead of `array`. Also, there's in-place `predict` support on `dask interface`, which can help reducing both memory usage and prediction time.

```
# dtrain is the DaskDMatrix defined above.
prediction = xgb.dask.predict(client, booster, dtrain)
```

or equivalently:

```
# where X is a dask DataFrame or dask Array.
prediction = xgb.dask.predict(client, booster, X)
```

Also for inplace prediction:

```
# where X is a dask DataFrame or dask Array backed by cupy or cuDF.
booster.set_param({"device": "cuda"})
prediction = xgb.dask.inplace_predict(client, booster, X)
```

When input is `da.Array` object, output is always `da.Array`. However, if the input type is `dd.DataFrame`, output can be `dd.Series`, `dd.DataFrame` or `da.Array`, depending on output shape. For example, when SHAP-based prediction is used, the return value can have 3 or 4 dimensions, in such cases an `Array` is always returned.

The performance of running prediction, either using `predict` or `inplace_predict`, is sensitive to number of blocks. Internally, it's implemented using `da.map_blocks` and `dd.map_partitions`. When number of partitions is large and each of them have only small amount of data, the overhead of calling `predict` becomes visible. On the other hand, if not

using GPU, the number of threads used for prediction on each block matters. Right now, xgboost uses single thread for each partition. If the number of blocks on each workers is smaller than number of cores, then the CPU workers might not be fully utilized.

One simple optimization for running consecutive predictions is using `distributed.Future`:

```
dataset = [X_0, X_1, X_2]
booster_f = client.scatter(booster, broadcast=True)
futures = []
for X in dataset:
    # Here we pass in a future instead of concrete booster
    shap_f = xgb.dask.predict(client, booster_f, X, pred_contribs=True)
    futures.append(shap_f)

results = client.gather(futures)
```

This is only available on functional interface, as the Scikit-Learn wrapper doesn't know how to maintain a valid future for booster. To obtain the booster object from Scikit-Learn wrapper object:

```
cls = xgb.dask.DaskXGBClassifier()
cls.fit(X, y)

booster = cls.get_booster()
```

Scikit-Learn Estimator Interface

As mentioned previously, there's another interface that mimics the scikit-learn estimators with higher level of abstraction. The interface is easier to use compared to the functional interface but with more constraints. It's worth mentioning that, although the interface mimics scikit-learn estimators, it doesn't work with normal scikit-learn utilities like `GridSearchCV` as scikit-learn doesn't understand distributed dask data collection.

```
from distributed import LocalCluster, Client
import xgboost as xgb

def main(client: Client) -> None:
    X, y = load_data()
    clf = xgb.dask.DaskXGBClassifier(n_estimators=100, tree_method="hist")
    clf.client = client # assign the client
    clf.fit(X, y, eval_set=[(X, y)])
    proba = clf.predict_proba(X)

if __name__ == "__main__":
    with LocalCluster() as cluster:
        with Client(cluster) as client:
            main(client)
```

GPU acceleration

For most of the use cases with GPUs, the [Dask-CUDA](#) project should be used to create the cluster, which automatically configures the correct device ordinal for worker processes. As a result, users should NOT specify the ordinal (good: `device=cuda`, bad: `device=cuda:1`). See *Example of training with Dask on GPU* and *Use scikit-learn regressor interface with GPU histogram tree method* for worked examples.

Working with other clusters

Using Dask's `LocalCluster` is convenient for getting started quickly on a single-machine. Once you're ready to scale your work, though, there are a number of ways to deploy Dask on a distributed cluster. You can use [Dask-CUDA](#), for example, for GPUs and you can use [Dask Cloud Provider](#) to deploy Dask clusters in the cloud. See the [Dask documentation](#) for a more comprehensive list.

In the example below, a `KubeCluster` is used for deploying Dask on Kubernetes:

```
from dask_kubernetes import KubeCluster # Need to install the ``dask-kubernetes`` package
from dask.distributed import Client
import xgboost as xgb
import dask
import dask.array as da

dask.config.set({"kubernetes.scheduler-service-type": "LoadBalancer",
                 "kubernetes.scheduler-service-wait-timeout": 360,
                 "distributed.comm.timeouts.connect": 360})

def main():
    """Connect to a remote kube cluster with GPU nodes and run training on it."""
    m = 1000
    n = 10
    kWorkers = 2 # assuming you have 2 GPU nodes on that cluster.
    # You need to work out the worker-spec yourself. See document in dask_kubernetes for
    # its usage. Here we just want to show that XGBoost works on various clusters.
    cluster = KubeCluster.from_yaml('worker-spec.yaml', deploy_mode='remote')
    cluster.scale(kWorkers) # scale to use all GPUs

    with Client(cluster) as client:
        X = da.random.random(size=(m, n), chunks=100)
        y = da.random.random(size=(m, ), chunks=100)

        regressor = xgb.dask.DaskXGBRegressor(n_estimators=10, missing=0.0)
        regressor.client = client
        regressor.set_params(tree_method='hist', device="cuda")
        regressor.fit(X, y, eval_set=[(X, y)])

if __name__ == '__main__':
    # Launch the kube cluster on somewhere like GKE, then run this as client process.
    # main function will connect to that cluster and start training xgboost model.
    main()
```

Different cluster classes might have subtle differences like network configuration, or specific cluster implementation might contains bugs that we are not aware of. Open an issue if such case is found and there's no documentation on how

to resolve it in that cluster implementation.

Threads

XGBoost has built in support for parallel computation through threads by the setting `nthread` parameter (`n_jobs` for scikit-learn). If these parameters are set, they will override the configuration in Dask. For example:

```
with dask.distributed.LocalCluster(n_workers=7, threads_per_worker=4) as cluster:
```

There are 4 threads allocated for each dask worker. Then by default XGBoost will use 4 threads in each process for training. But if `nthread` parameter is set:

```
output = xgb.dask.train(
    client,
    {"verbosity": 1, "nthread": 8, "tree_method": "hist"},
    dtrain,
    num_boost_round=4,
    evals=[(dtrain, "train")],
)
```

XGBoost will use 8 threads in each training process.

Working with asyncio

New in version 1.2.0.

XGBoost's dask interface supports the new `asyncio` in Python and can be integrated into asynchronous workflows. For using dask with asynchronous operations, please refer to [this dask example](#) and document in [distributed](#). To use XGBoost's dask interface asynchronously, the `client` which is passed as an argument for training and prediction must be operating in asynchronous mode by specifying `asynchronous=True` when the `client` is created (example below). All functions (including `DaskDMatrix`) provided by the functional interface will then return coroutines which can then be awaited to retrieve their result.

Functional interface:

```
async with dask.distributed.Client(scheduler_address, asynchronous=True) as client:
    X, y = generate_array()
    m = await xgb.dask.DaskDMatrix(client, X, y)
    output = await xgb.dask.train(client, {}, dtrain=m)

    with_m = await xgb.dask.predict(client, output, m)
    with_X = await xgb.dask.predict(client, output, X)
    inplace = await xgb.dask.inplace_predict(client, output, X)

    # Use ``client.compute`` instead of the ``compute`` method from dask collection
    print(await client.compute(with_m))
```

While for the Scikit-Learn interface, trivial methods like `set_params` and accessing class attributes like `evals_result()` do not require `await`. Other methods involving actual computation will return a coroutine and hence require awaiting:

```
async with dask.distributed.Client(scheduler_address, asynchronous=True) as client:
    X, y = generate_array()
    regressor = await xgb.dask.DaskXGBRegressor(verbosity=1, n_estimators=2)
```

(continues on next page)

(continued from previous page)

```

regressor.set_params(tree_method='hist') # trivial method, synchronous operation
regressor.client = client # accessing attribute, synchronous operation
regressor = await regressor.fit(X, y, eval_set=[(X, y)])
prediction = await regressor.predict(X)

# Use `client.compute` instead of the `compute` method from dask collection
print(await client.compute(prediction))

```

Evaluation and Early Stopping

New in version 1.3.0.

The Dask interface allows the use of validation sets that are stored in distributed collections (Dask DataFrame or Dask Array). These can be used for evaluation and early stopping.

To enable early stopping, pass one or more validation sets containing DaskDMatrix objects.

```

import dask.array as da
import xgboost as xgb

num_rows = 1e6
num_features = 100
num_partitions = 10
rows_per_chunk = num_rows / num_partitions

data = da.random.random(
    size=(num_rows, num_features),
    chunks=(rows_per_chunk, num_features)
)

labels = da.random.random(
    size=(num_rows, 1),
    chunks=(rows_per_chunk, 1)
)

X_eval = da.random.random(
    size=(num_rows, num_features),
    chunks=(rows_per_chunk, num_features)
)

y_eval = da.random.random(
    size=(num_rows, 1),
    chunks=(rows_per_chunk, 1)
)

dtrain = xgb.dask.DaskDMatrix(
    client=client,
    data=data,
    label=labels
)

dvalid = xgb.dask.DaskDMatrix(

```

(continues on next page)

(continued from previous page)

```

    client=client,
    data=X_eval,
    label=y_eval
)

result = xgb.dask.train(
    client=client,
    params={
        "objective": "reg:squarederror",
    },
    dtrain=dtrain,
    num_boost_round=10,
    evals=[(dvalid, "valid1")],
    early_stopping_rounds=3
)

```

When validation sets are provided to `xgb.dask.train()` in this way, the model object returned by `xgb.dask.train()` contains a history of evaluation metrics for each validation set, across all boosting rounds.

```

print(result["history"])
# {'valid1': OrderedDict([('rmse', [0.28857, 0.28858, 0.288592, 0.288598]))]}

```

If early stopping is enabled by also passing `early_stopping_rounds`, you can check the best iteration in the returned booster.

```

booster = result["booster"]
print(booster.best_iteration)
best_model = booster[: booster.best_iteration]

```

Other customization

XGBoost dask interface accepts other advanced features found in single node Python interface, including callback functions, custom evaluation metric and objective:

```

def eval_error_metric(predt, dtrain: xgb.DMatrix):
    label = dtrain.get_label()
    r = np.zeros(predt.shape)
    gt = predt > 0.5
    r[gt] = 1 - label[gt]
    le = predt <= 0.5
    r[le] = label[le]
    return 'CustomErr', np.sum(r)

# custom callback
early_stop = xgb.callback.EarlyStopping(
    rounds=early_stopping_rounds,
    metric_name="CustomErr",
    data_name="Train",
    save_best=True,
)

```

(continues on next page)

(continued from previous page)

```

booster = xgb.dask.train(
    client,
    params={
        "objective": "binary:logistic",
        "eval_metric": ["error", "rmse"],
        "tree_method": "hist",
    },
    dtrain=D_train,
    evals=[(D_train, "Train"), (D_valid, "Valid")],
    feval=eval_error_metric, # custom evaluation metric
    num_boost_round=100,
    callbacks=[early_stop],
)

```

Hyper-parameter tuning

See <https://github.com/coiled/dask-xgboost-nyctaxi> for a set of examples of using XGBoost with dask and optuna.

Troubleshooting

- In some environments XGBoost might fail to resolve the IP address of the scheduler, a symptom is user receiving `OSError: [Errno 99] Cannot assign requested address` error during training. A quick workaround is to specify the address explicitly. To do that dask config is used:

New in version 1.6.0.

```

import dask
from distributed import Client
from xgboost import dask as dxgb
# let xgboost know the scheduler address
dask.config.set({"xgboost.scheduler_address": "192.0.0.100"})

with Client(scheduler_file="sched.json") as client:
    reg = dxgb.DaskXGBRegressor()

# We can specify the port for XGBoost as well
with dask.config.set({"xgboost.scheduler_address": "192.0.0.100:12345"}):
    reg = dxgb.DaskXGBRegressor()

```

- Please note that XGBoost requires a different port than dask. By default, on a unix-like system XGBoost uses the port 0 to find available ports, which may fail if a user is running in a restricted docker environment. In this case, please open additional ports in the container and specify it as in the above snippet.
- If you encounter a NCCL system error while training with GPU enabled, which usually includes the error message *NCCL failure: unhandled system error*, you can specify its network configuration using one of the environment variables listed in the [NCCL document](#) such as the `NCCL_SOCKET_IFNAME`. In addition, you can use `NCCL_DEBUG` to obtain debug logs.
- If NCCL fails to initialize in a container environment, it might be caused by limited system shared memory. With docker, one can try the flag: `-shm-size=4g`.
- MIG (Multi-Instance GPU) is not yet supported by NCCL. You will receive an error message that includes *Multiple processes within a communication group ...* upon initialization.

IPv6 Support

New in version 1.7.0.

XGBoost has initial IPv6 support for the dask interface on Linux. Due to most of the cluster support for IPv6 is partial (dual stack instead of IPv6 only), we require additional user configuration similar to [Troubleshooting](#) to help XGBoost obtain the correct address information:

```
import dask
from distributed import Client
from xgboost import dask as dxgb
# let xgboost know the scheduler address, use the same bracket format as dask.
with dask.config.set({"xgboost.scheduler_address": "[fd20:b6f:f759:9800::]"}):
    with Client("[fd20:b6f:f759:9800::]") as client:
        reg = dxgb.DaskXGBRegressor(tree_method="hist")
```

When GPU is used, XGBoost employs [NCCL](#) as the underlying communication framework, which may require some additional configuration via environment variable depending on the setting of the cluster. Please note that IPv6 support is Unix only.

Why is the initialization of DaskDMatrix so slow and throws weird errors

The dask API in XGBoost requires construction of `DaskDMatrix`. With the Scikit-Learn interface, `DaskDMatrix` is implicitly constructed for all input data during the `fit` or `predict` steps. You might have observed that `DaskDMatrix` construction can take large amounts of time, and sometimes throws errors that don't seem to be relevant to `DaskDMatrix`. Here is a brief explanation for why. By default most dask computations are [lazily evaluated](#), which means that computation is not carried out until you explicitly ask for a result by, for example, calling `compute()`. See the previous link for details in dask, and [this wiki](#) for information on the general concept of lazy evaluation. The `DaskDMatrix` constructor forces lazy computations to be evaluated, which means it's where all your earlier computation actually being carried out, including operations like `dd.read_csv()`. To isolate the computation in `DaskDMatrix` from other lazy computations, one can explicitly wait for results of input data before constructing a `DaskDMatrix`. Also dask's [diagnostics dashboard](#) can be used to monitor what operations are currently being performed.

Reproducible Result

In a single node mode, we can always expect the same training result between runs as long as the underlying platforms are the same. However, it's difficult to obtain reproducible result in a distributed environment, since the tasks might get different machine allocation or have different amount of available resources during different sessions. There are heuristics and guidelines on how to achieve it but no proven method for guaranteeing such deterministic behavior. The Dask interface in XGBoost tries to provide reproducible result with best effort. This section highlights some known criteria and try to share some insights into the issue.

There are primarily two different tasks for XGBoost the carry out, training and inference. Inference is reproducible given the same software and hardware along with the same run-time configurations. The remaining of this section will focus on training.

Many of the challenges come from the fact that we are using approximation algorithms, The sketching algorithm used to find histogram bins is an approximation to the exact quantile algorithm, the *AUC* metric in a distributed environment is an approximation to the exact *AUC* score, and floating-point number is an approximation to real number. Floating-point is an issue as its summation is not associative, meaning $(a + b) + c$ does not necessarily equal to $a + (b + c)$, even though this property holds true for real number. As a result, whenever we change the order of a summation, the result can differ. This imposes the requirement that, in order to have reproducible output from XGBoost, the entire pipeline needs to be reproducible.

- The software stack is the same for each runs. This goes without saying. XGBoost might generate different outputs between different versions. This is expected as we might change the default value of hyper-parameter, or the parallel strategy that generates different floating-point result. We guarantee the correctness the algorithms, but there are lots of wiggle room for the final output. The situation is similar for many dependencies, for instance, the random number generator might differ from platform to platform.
- The hardware stack is the same for each runs. This includes the number of workers, and the amount of available resources on each worker. XGBoost can generate different results using different number of workers. This is caused by the approximation issue mentioned previously.
- Similar to the hardware constraint, the network topology is also a factor in final output. If we change topology the workers might be ordered differently, leading to different ordering of floating-point operations.
- The random seed used in various place of the pipeline.
- The partitioning of data needs to be reproducible. This is related to the available resources on each worker. Dask might partition the data differently for each run according to its own scheduling policy. For instance, if there are some additional tasks in the cluster while you are running the second training session for XGBoost, some of the workers might have constrained memory and Dask may not push the training data for XGBoost to that worker. This change in data partitioning can lead to different output models. If you are using a shared Dask cluster, then the result is likely to vary between runs.
- The operations performed on dataframes need to be reproducible. There are some operations like *DataFrame.merge* not being deterministic on parallel hardwares like GPU where the order of the index might differ from run to run.

It's expected to have different results when training the model in a distributed environment than training the model using a single node due to aforementioned criteria.

Memory Usage

Here are some practices on reducing memory usage with dask and xgboost.

- In a distributed work flow, data is best loaded by dask collections directly instead of loaded by client process. When loading with client process is unavoidable, use `client.scatter` to distribute data from client process to workers. See [2] for a nice summary.
- When using GPU input, like dataframe loaded by `dask_cudf`, you can try `xgboost.dask.DaskQuantileDMatrix` as a drop in replacement for `DaskDMatrix` to reduce overall memory usage. See *Example of training with Dask on GPU* for an example.
- Use in-place prediction when possible.

References:

1. <https://github.com/dask/dask/issues/6833>
2. <https://stackoverflow.com/questions/45941528/how-to-efficiently-send-a-large-numpy-array-to-the-cluster-with-dask-array>

1.4.13 Distributed XGBoost with PySpark

Starting from version 1.7.0, xgboost supports pyspark estimator APIs.

Note: The feature is still experimental and not yet ready for production use.

- *XGBoost PySpark Estimator*
 - *SparkXGBRegressor*
 - *SparkXGBClassifier*
- *XGBoost PySpark GPU support*
 - *Prepare the necessary packages*
 - *Write your PySpark application*
 - *Submit the PySpark application*
 - *Model Persistence*
 - *Accelerate the whole pipeline for xgboost pyspark*

XGBoost PySpark Estimator

SparkXGBRegressor

SparkXGBRegressor is a PySpark ML estimator. It implements the XGBoost classification algorithm based on XGBoost python library, and it can be used in PySpark Pipeline and PySpark ML meta algorithms like CrossValidator/TrainValidationSplit/OneVsRest.

We can create a SparkXGBRegressor estimator like:

```
from xgboost.spark import SparkXGBRegressor
spark_reg_estimator = SparkXGBRegressor(
    features_col="features",
    label_col="label",
    num_workers=2,
)
```

The above snippet creates a spark estimator which can fit on a spark dataset, and return a spark model that can transform a spark dataset and generate dataset with prediction column. We can set almost all of xgboost sklearn estimator parameters as SparkXGBRegressor parameters, but some parameter such as nthread is forbidden in spark estimator, and some parameters are replaced with pyspark specific parameters such as weight_col, validation_indicator_col, for details please see SparkXGBRegressor doc.

The following code snippet shows how to train a spark xgboost regressor model, first we need to prepare a training dataset as a spark dataframe contains “label” column and “features” column(s), the “features” column(s) must be pyspark.ml.linalg.Vector type or spark array type or a list of feature column names.

```
xgb_regressor_model = xgb_regressor.fit(train_spark_dataframe)
```

The following code snippet shows how to predict test data using a spark xgboost regressor model, first we need to prepare a test dataset as a spark dataframe contains “features” and “label” column, the “features” column must be

`pyspark.ml.linalg.Vector` type or spark array type.

```
transformed_test_spark_dataframe = xgb_regressor.predict(test_spark_dataframe)
```

The above snippet code returns a `transformed_test_spark_dataframe` that contains the input dataset columns and an appended column “prediction” representing the prediction results.

SparkXGBClassifier

`SparkXGBClassifier` estimator has similar API with `SparkXGBRegressor`, but it has some pyspark classifier specific params, e.g. `raw_prediction_col` and `probability_col` parameters. Correspondingly, by default, `SparkXGBClassifierModel` transforming test dataset will generate result dataset with 3 new columns:

- “prediction”: represents the predicted label.
- “raw_prediction”: represents the output margin values.
- “probability”: represents the prediction probability on each label.

XGBoost PySpark GPU support

XGBoost PySpark fully supports GPU acceleration. Users are not only able to enable efficient training but also utilize their GPUs for the whole PySpark pipeline including ETL and inference. In below sections, we will walk through an example of training on a PySpark standalone GPU cluster. To get started, first we need to install some additional packages, then we can set the device parameter to `cuda` or `gpu`.

Prepare the necessary packages

Aside from the PySpark and XGBoost modules, we also need the `cuDF` package for handling Spark dataframe. We recommend using either Conda or Virtualenv to manage python dependencies for PySpark jobs. Please refer to [How to Manage Python Dependencies in PySpark](#) for more details on PySpark dependency management.

In short, to create a Python environment that can be sent to a remote cluster using `virtualenv` and `pip`:

```
python -m venv xgboost_env
source xgboost_env/bin/activate
pip install pyarrow pandas venv-pack xgboost
# https://docs.rapids.ai/install#pip-install
pip install cudf-cu11 --extra-index-url=https://pypi.nvidia.com
venv-pack -o xgboost_env.tar.gz
```

With Conda:

```
conda create -y -n xgboost_env -c conda-forge conda-pack python=3.9
conda activate xgboost_env
# use conda when the supported version of xgboost (1.7) is released on conda-forge
pip install xgboost
conda install cudf pyarrow pandas -c rapids -c nvidia -c conda-forge
conda pack -f -o xgboost_env.tar.gz
```

Write your PySpark application

Below snippet is a small example for training xgboost model with PySpark. Notice that we are using a list of feature names and the additional parameter device:

```
from xgboost.spark import SparkXGBRegressor
spark = SparkSession.builder.getOrCreate()

# read data into spark dataframe
train_data_path = "xxxx/train"
train_df = spark.read.parquet(data_path)

test_data_path = "xxxx/test"
test_df = spark.read.parquet(test_data_path)

# assume the label column is named "class"
label_name = "class"

# get a list with feature column names
feature_names = [x.name for x in train_df.schema if x.name != label_name]

# create a xgboost pyspark regressor estimator and set device="cuda"
regressor = SparkXGBRegressor(
    features_col=feature_names,
    label_col=label_name,
    num_workers=2,
    device="cuda",
)

# train and return the model
model = regressor.fit(train_df)

# predict on test data
predict_df = model.transform(test_df)
predict_df.show()
```

Like other distributed interfaces, the `device` parameter doesn't support specifying ordinal as GPUs are managed by Spark instead of XGBoost (good: `device=cuda`, bad: `device=cuda:0`).

Submit the PySpark application

Assuming you have configured your Spark cluster with GPU support. Otherwise, please refer to [spark standalone configuration with GPU support](#).

```
export PYSARK_DRIVER_PYTHON=python
export PYSARK_PYTHON=./environment/bin/python

spark-submit \
  --master spark://<master-ip>:7077 \
  --conf spark.executor.resource.gpu.amount=1 \
  --conf spark.task.resource.gpu.amount=1 \
  --archives xgboost_env.tar.gz#environment \
  xgboost_app.py
```


The submit command sends the Python environment created by pip or conda along with the specification of GPU allocation. We will revisit this command later on.

Model Persistence

Similar to standard PySpark ml estimators, one can persist and reuse the model with `save`` and ``load` methods:

```
regressor = SparkXGBRegressor()
model = regressor.fit(train_df)
# save the model
model.save("/tmp/xgboost-pyspark-model")
# load the model
model2 = SparkXGBRankerModel.load("/tmp/xgboost-pyspark-model")
```

To export the underlying booster model used by XGBoost:

```
regressor = SparkXGBRegressor()
model = regressor.fit(train_df)
# the same booster object returned by xgboost.train
booster: xgb.Booster = model.get_booster()
booster.predict(...)
booster.save_model("model.json") # or model.ubj, depending on your choice of format.
```

This booster is not only shared by other Python interfaces but also used by all the XGBoost bindings including the C, Java, and the R package. Lastly, one can extract the booster file directly from a saved spark estimator without going through the getter:

```
import xgboost as xgb
bst = xgb.Booster()
# Loading the model saved in previous snippet
bst.load_model("/tmp/xgboost-pyspark-model/model/part-000000")
```

Accelerate the whole pipeline for xgboost pyspark

With [RAPIDS Accelerator for Apache Spark](#), you can leverage GPUs to accelerate the whole pipeline (ETL, Train, Transform) for xgboost pyspark without any Python code change. An example submit command is shown below with additional spark configurations and dependencies:

```
export PYSPARK_DRIVER_PYTHON=python
export PYSPARK_PYTHON=./environment/bin/python

spark-submit \
  --master spark://<master-ip>:7077 \
  --conf spark.executor.resource.gpu.amount=1 \
  --conf spark.task.resource.gpu.amount=1 \
  --packages com.nvidia:rapids-4-spark_2.12:23.04.0 \
  --conf spark.plugins=com.nvidia.spark.SQLPlugin \
  --conf spark.sql.execution.arrow.maxRecordsPerBatch=1000000 \
  --archives xgboost_env.tar.gz#environment \
  xgboost_app.py
```

When rapids plugin is enabled, both of the JVM rapids plugin and the cuDF Python package are required. More configuration options can be found in the [RAPIDS](#) link above along with details on the plugin.

1.4.14 Distributed XGBoost with Ray

Ray is a general purpose distributed execution framework. Ray can be used to scale computations from a single node to a cluster of hundreds of nodes without changing any code.

The Python bindings of Ray come with a collection of well maintained machine learning libraries for hyperparameter optimization and model serving.

The [XGBoost-Ray](#) project provides an interface to run XGBoost training and prediction jobs on a Ray cluster. It allows to utilize distributed data representations, such as [Modin](#) dataframes, as well as distributed loading from cloud storage (e.g. Parquet files).

XGBoost-Ray integrates well with hyperparameter optimization library Ray Tune, and implements advanced fault tolerance handling mechanisms. With Ray you can scale your training jobs to hundreds of nodes just by adding new nodes to a cluster. You can also use Ray to leverage multi GPU XGBoost training.

Installing and starting Ray

Ray can be installed from PyPI like this:

```
pip install ray
```

If you're using Ray on a single machine, you don't need to do anything else - XGBoost-Ray will automatically start a local Ray cluster when used.

If you want to use Ray on a cluster, you can use the [Ray cluster launcher](#).

Installing XGBoost-Ray

XGBoost-Ray is also available via PyPI:

```
pip install xgboost_ray
```

This will install all dependencies needed to run XGBoost on Ray, including Ray itself if it hasn't been installed before.

Using XGBoost-Ray for training and prediction

XGBoost-Ray uses the same API as core XGBoost. There are only two differences:

1. Instead of using a `xgboost.DMatrix`, you'll use a `xgboost_ray.RayDMatrix` object
2. There is an additional `ray_params` parameter that you can use to configure distributed training.

Simple training example

To run this simple example, you'll need to install `scikit-learn` (with `pip install sklearn`).

In this example, we will load the [breast cancer dataset](#) and train a binary classifier using two actors.

```
from xgboost_ray import RayDMatrix, RayParams, train
from sklearn.datasets import load_breast_cancer

train_x, train_y = load_breast_cancer(return_X_y=True)
train_set = RayDMatrix(train_x, train_y)
```

(continues on next page)

(continued from previous page)

```

evals_result = {}
bst = train(
    {
        "objective": "binary:logistic",
        "eval_metric": ["logloss", "error"],
    },
    train_set,
    evals_result=evals_result,
    evals=[(train_set, "train")],
    verbose_eval=False,
    ray_params=RayParams(num_actors=2, cpus_per_actor=1))

bst.save_model("model.xgb")
print("Final training error: {:.4f}".format(
    evals_result["train"]["error"][-1]))

```

The only differences compared to the non-distributed API are the import statement (`xgboost_ray` instead of `xgboost`), using the `RayDMatrix` instead of the `DMatrix`, and passing a `RayParams` object.

The return object is a regular `xgboost.Booster` instance.

Simple prediction example

```

from xgboost_ray import RayDMatrix, RayParams, predict
from sklearn.datasets import load_breast_cancer
import xgboost as xgb

data, labels = load_breast_cancer(return_X_y=True)

dpred = RayDMatrix(data, labels)

bst = xgb.Booster(model_file="model.xgb")
pred_ray = predict(bst, dpred, ray_params=RayParams(num_actors=2))

print(pred_ray)

```

In this example, the data will be split across two actors. The result array will integrate this data in the correct order.

The RayParams object

The RayParams object is used to configure various settings relating to the distributed training.

Multi GPU training

Ray automatically detects GPUs on cluster nodes. In order to start training on multiple GPUs, all you have to do is to set the `gpus_per_actor` parameter of the RayParams object, as well as the `num_actors` parameter for multiple GPUs:

```
ray_params = RayParams(  
    num_actors=4,  
    gpus_per_actor=1,  
)
```

This will train on four GPUs in parallel.

Note that it usually does not make sense to allocate more than one GPU per actor, as XGBoost relies on distributed libraries such as Dask or Ray to utilize multi GPU training.

Setting the number of CPUs per actor

XGBoost natively utilizes multi threading to speed up computations. Thus if you are training on CPUs only, there is likely no benefit in using more than one actor per node. In that case, assuming you have a cluster of homogeneous nodes, set the number of CPUs per actor to the number of CPUs available on each node, and the number of actors to the number of nodes.

If you are using multi GPU training on a single node, divide the number of available CPUs evenly across all actors. For instance, if you have 16 CPUs and 4 GPUs available, each actor should access 1 GPU and 4 CPUs.

If you are using a cluster of heterogeneous nodes (with different amounts of CPUs), you might just want to use the [greatest common divisor](#) for the number of CPUs per actor. E.g. if you have a cluster of three nodes with 4, 8, and 12 CPUs, respectively, you'd start 6 actors with 4 CPUs each for maximum CPU utilization.

Fault tolerance

XGBoost-Ray supports two fault tolerance modes. In **non-elastic training**, whenever a training actor dies (e.g. because the node goes down), the training job will stop, XGBoost-Ray will wait for the actor (or its resources) to become available again (this might be on a different node), and then continue training once all actors are back.

In **elastic-training**, whenever a training actor dies, the rest of the actors continue training without the dead actor. If the actor comes back, it will be re-integrated into training again.

Please note that in elastic-training this means that you will train on fewer data for some time. The benefit is that you can continue training even if a node goes away for the remainder of the training run, and don't have to wait until it is back up again. In practice this usually leads to a very minor decrease in accuracy but a much shorter training time compared to non-elastic training.

Both training modes can be configured using the respective RayParams parameters.

Hyperparameter optimization

XGBoost-Ray integrates well with [hyperparameter optimization framework Ray Tune](#). Ray Tune uses Ray to start multiple distributed trials with different hyperparameter configurations. If used with XGBoost-Ray, these trials will then start their own distributed training jobs.

XGBoost-Ray automatically reports evaluation results back to Ray Tune. There's only a few things you need to do:

1. Put your XGBoost-Ray training call into a function accepting parameter configurations (`train_model` in the example below).
2. Create a `RayParams` object (`ray_params` in the example below).
3. Define the parameter search space (`config` dict in the example below).
4. Call `tune.run()`:
 - The `metric` parameter should contain the metric you'd like to optimize. Usually this consists of the prefix passed to the `evals` argument of `xgboost_ray.train()`, and an `eval_metric` passed in the XGBoost parameters (`train-error` in the example below).
 - The `mode` should either be `min` or `max`, depending on whether you'd like to minimize or maximize the metric
 - The `resources_per_actor` should be set using `ray_params.get_tune_resources()`. This will make sure that each trial has the necessary resources available to start their distributed training jobs.

```
from xgboost_ray import RayDMatrix, RayParams, train
from sklearn.datasets import load_breast_cancer

num_actors = 4
num_cpus_per_actor = 1

ray_params = RayParams(
    num_actors=num_actors, cpus_per_actor=num_cpus_per_actor)

def train_model(config):
    train_x, train_y = load_breast_cancer(return_X_y=True)
    train_set = RayDMatrix(train_x, train_y)

    evals_result = {}
    bst = train(
        params=config,
        dtrain=train_set,
        evals_result=evals_result,
        evals=[(train_set, "train")],
        verbose_eval=False,
        ray_params=ray_params)
    bst.save_model("model.xgb")

from ray import tune

# Specify the hyperparameter search space.
config = {
    "tree_method": "approx",
    "objective": "binary:logistic",
    "eval_metric": ["logloss", "error"],
```

(continues on next page)

(continued from previous page)

```

    "eta": tune.loguniform(1e-4, 1e-1),
    "subsample": tune.uniform(0.5, 1.0),
    "max_depth": tune.randint(1, 9)
}

# Make sure to use the `get_tune_resources` method to set the `resources_per_trial`
analysis = tune.run(
    train_model,
    config=config,
    metric="train-error",
    mode="min",
    num_samples=4,
    resources_per_trial=ray_params.get_tune_resources())
print("Best hyperparameters", analysis.best_config)

```

Ray Tune supports various search algorithms and libraries (e.g. BayesOpt, Tree-Parzen estimators), smart schedulers like successive halving, and other features. Please refer to the Ray Tune documentation for more information.

Additional resources

- [XGBoost-Ray repository](#)
- [XGBoost-Ray documentation](#)
- [Ray core documentation](#)
- [Ray Tune documentation](#)

1.4.15 Using XGBoost External Memory Version

When working with large datasets, training XGBoost models can be challenging as the entire dataset needs to be loaded into memory. This can be costly and sometimes infeasible. Starting from 1.5, users can define a custom iterator to load data in chunks for running XGBoost algorithms. External memory can be used for both training and prediction, but training is the primary use case and it will be our focus in this tutorial. For prediction and evaluation, users can iterate through the data themselves while training requires the full dataset to be loaded into the memory.

During training, there are two different modes for external memory support available in XGBoost, one for CPU-based algorithms like `hist` and `approx`, another one for the GPU-based training algorithm. We will introduce them in the following sections.

Note: Training on data from external memory is not supported by the exact tree method.

Note: The feature is still experimental as of 2.0. The performance is not well optimized.

The external memory support has gone through multiple iterations and is still under heavy development. Like the *QuantileDMatrix* with *DataIter*, XGBoost loads data batch-by-batch using a custom iterator supplied by the user. However, unlike the *QuantileDMatrix*, external memory will not concatenate the batches unless GPU is used (it uses a hybrid approach, more details follow). Instead, it will cache all batches on the external memory and fetch them on-demand. Go to the end of the document to see a comparison between *QuantileDMatrix* and external memory.

Data Iterator

Starting from XGBoost 1.5, users can define their own data loader using Python or C interface. There are some examples in the demo directory for quick start. This is a generalized version of text input external memory, where users no longer need to prepare a text file that XGBoost recognizes. To enable the feature, users need to define a data iterator with 2 class methods: `next` and `reset`, then pass it into the `DMatrix` constructor.

```
import os
from typing import List, Callable
import xgboost
from sklearn.datasets import load_svmlight_file

class Iterator(xgboost.DataIter):
    def __init__(self, svm_file_paths: List[str]):
        self._file_paths = svm_file_paths
        self._it = 0
        # XGBoost will generate some cache files under current directory with the prefix
        # "cache"
        super().__init__(cache_prefix=os.path.join(".", "cache"))

    def next(self, input_data: Callable):
        """Advance the iterator by 1 step and pass the data to XGBoost. This function is
        called by XGBoost during the construction of ``DMatrix``

        """
        if self._it == len(self._file_paths):
            # return 0 to let XGBoost know this is the end of iteration
            return 0

        # input_data is a function passed in by XGBoost who has the exact same signature of
        # ``DMatrix``
        X, y = load_svmlight_file(self._file_paths[self._it])
        input_data(data=X, label=y)
        self._it += 1
        # Return 1 to let XGBoost know we haven't seen all the files yet.
        return 1

    def reset(self):
        """Reset the iterator to its beginning"""
        self._it = 0

it = Iterator(["file_0.svm", "file_1.svm", "file_2.svm"])
Xy = xgboost.DMatrix(it)

# The ``approx`` also work, but with low performance. GPU implementation is different,
# ↪ from CPU.
# as noted in following sections.
booster = xgboost.train({"tree_method": "hist"}, Xy)
```

The above snippet is a simplified version of *Experimental support for external memory*. For an example in C, please see `demo/c-api/external-memory/`. The iterator is the common interface for using external memory with XGBoost, you can pass the resulting `DMatrix` object for training, prediction, and evaluation.

It is important to set the batch size based on the memory available. A good starting point is to set the batch size to 10GB per batch if you have 64GB of memory. It is *not* recommended to set small batch sizes like 32 samples per batch,

as this can seriously hurt performance in gradient boosting.

CPU Version

In the previous section, we demonstrated how to train a tree-based model using the `hist` tree method on a CPU. This method involves iterating through data batches stored in a cache during tree construction. For optimal performance, we recommend using the `grow_policy=depthwise` setting, which allows XGBoost to build an entire layer of tree nodes with only a few batch iterations. Conversely, using the `lossguide` policy requires XGBoost to iterate over the data set for each tree node, resulting in slower performance.

If external memory is used, the performance of CPU training is limited by IO (input/output) speed. This means that the disk IO speed primarily determines the training speed. During benchmarking, we used an NVMe connected to a PCIe-4 slot, other types of storage can be too slow for practical usage. In addition, your system may perform caching to reduce the overhead of file reading.

GPU Version (GPU Hist tree method)

External memory is supported by GPU algorithms (i.e. when `device` is set to `cuda`). However, the algorithm used for GPU is different from the one used for CPU. When training on a CPU, the tree method iterates through all batches from external memory for each step of the tree construction algorithm. On the other hand, the GPU algorithm uses a hybrid approach. It iterates through the data during the beginning of each iteration and concatenates all batches into one in GPU memory for performance reasons. To reduce overall memory usage, users can utilize subsampling. The GPU hist tree method supports *gradient-based sampling*, enabling users to set a low sampling rate without compromising accuracy.

```
param = {  
    ...  
    'subsample': 0.2,  
    'sampling_method': 'gradient_based',  
}
```

For more information about the sampling algorithm and its use in external memory training, see [this paper](#).

Warning: When GPU is running out of memory during iteration on external memory, user might receive a segfault instead of an OOM exception.

Remarks

When using external memory with XGBoost, data is divided into smaller chunks so that only a fraction of it needs to be stored in memory at any given time. It's important to note that this method only applies to the predictor data (X), while other data, like labels and internal runtime structures are concatenated. This means that memory reduction is most effective when dealing with wide datasets where X is significantly larger in size compared to other data like y , while it has little impact on slim datasets.

As one might expect, fetching data on-demand puts significant pressure on the storage device. Today's computing device can process way more data than a storage can read in a single unit of time. The ratio is at order of magnitudes. An GPU is capable of processing hundred of Gigabytes of floating-point data in a split second. On the other hand, a four-lane NVMe storage connected to a PCIe-4 slot usually has about 6GB/s of data transfer rate. As a result, the training is likely to be severely bounded by your storage device. Before adopting the external memory solution, some back-of-envelope calculations might help you see whether it's viable. For instance, if your NVMe drive can transfer 4GB (a fairly practical number) of data per second and you have a 100GB of data in compressed XGBoost cache (which corresponds to a dense float32 numpy array with the size of 200GB, give or take). A tree with depth 8 needs at least

16 iterations through the data when the parameter is right. You need about 14 minutes to train a single tree without accounting for some other overheads and assume the computation overlaps with the IO. If your dataset happens to have TB-level size, then you might need thousands of trees to get a generalized model. These calculations can help you get an estimate on the expected training time.

However, sometimes we can ameliorate this limitation. One should also consider that the OS (mostly talking about the Linux kernel) can usually cache the data on host memory. It only evicts pages when new data comes in and there's no room left. In practice, at least some portion of the data can persist on the host memory throughout the entire training session. We are aware of this cache when optimizing the external memory fetcher. The compressed cache is usually smaller than the raw input data, especially when the input is dense without any missing value. If the host memory can fit a significant portion of this compressed cache, then the performance should be decent after initialization. Our development so far focus on two fronts of optimization for external memory:

- Avoid iterating through the data whenever appropriate.
- If the OS can cache the data, the performance should be close to in-core training.

Starting with XGBoost 2.0, the implementation of external memory uses `mmap`. It is not tested against system errors like disconnected network devices (*SIGBUS*). In the face of a bus error, you will see a hard crash and need to clean up the cache files. If the training session might take a long time and you are using solutions like NVMe-oF, we recommend checkpointing your model periodically. Also, it's worth noting that most tests have been conducted on Linux distributions.

Another important point to keep in mind is that creating the initial cache for XGBoost may take some time. The interface to external memory is through custom iterators, which we can not assume to be thread-safe. Therefore, initialization is performed sequentially. Using the `xgboost.config_context` with `verbosity=2` can give you some information on what XGBoost is doing during the wait if you don't mind the extra output.

Compared to the QuantileDmatrix

Passing an iterator to the `QuantileDmatrix` enables direct construction of `QuantileDmatrix` with data chunks. On the other hand, if it's passed to `DMatrix`, it instead enables the external memory feature. The `QuantileDmatrix` concatenates the data on memory after compression and doesn't fetch data during training. On the other hand, the external memory `DMatrix` fetches data batches from external memory on-demand. Use the `QuantileDmatrix` (with iterator if necessary) when you can fit most of your data in memory. The training would be an order of magnitude faster than using external memory.

Text File Inputs

This is the original form of external memory support, users are encouraged to use custom data iterator instead. There is no big difference between using external memory version of text input and the in-memory version. The only difference is the filename format.

The external memory version takes in the following `URI` format:

```
filename?format=libsvm#cacheprefix
```

The `filename` is the normal path to LIBSVM format file you want to load in, and `cacheprefix` is a path to a cache file that XGBoost will use for caching preprocessed data in binary form.

To load from csv files, use the following syntax:

```
filename.csv?format=csv&label_column=0#cacheprefix
```

where `label_column` should point to the csv column acting as the label.

If you have a dataset stored in a file similar to `demo/data/agaricus.txt.train` with LIBSVM format, the external memory support can be enabled by:

```
dtrain = DMatrix('../data/agaricus.txt.train?format=libsvm#dtrain.cache')
```

XGBoost will first load `agaricus.txt.train` in, preprocess it, then write to a new file named `dtrain.cache` as an on disk cache for storing preprocessed data in an internal binary format. For more notes about text input formats, see *Text Input Format of DMatrix*.

For CLI version, simply add the cache suffix, e.g. `"../data/agaricus.txt.train?format=libsvm#dtrain.cache"`.

1.4.16 C API Tutorial

In this tutorial, we are going to install XGBoost library & configure the `CMakeLists.txt` file of our C/C++ application to link XGBoost library with our application. Later on, we will see some useful tips for using C API and code snippets as examples to use various functions available in C API to perform basic task like loading, training model & predicting on test dataset. For API reference, please visit *XGBoost C Package*

- *Requirements*
- *Install XGBoost on conda environment*
- *Configure CMakeList.txt file of your application to link with XGBoost*
- *Useful Tips To Remember*
- *Sample examples along with Code snippet to use C API functions*

Requirements

Install CMake - Follow the [cmake installation documentation](#) for instructions. Install Conda - Follow the [conda installation documentation](#) for instructions

Install XGBoost on conda environment

Run the following commands on your terminal. The below commands will install the XGBoost in your XGBoost folder of the repository cloned

```
# clone the XGBoost repository & its submodules
git clone --recursive https://github.com/dmlc/xgboost
cd xgboost
mkdir build
cd build
# Activate the Conda environment, into which we'll install XGBoost
conda activate [env_name]
# Build the compiled version of XGBoost inside the build folder
cmake .. -DCMAKE_INSTALL_PREFIX=$CONDA_PREFIX
# install XGBoost in your conda environment (usually under [your home directory]/
↳ miniconda3)
make install
```

Configure CMakeList.txt file of your application to link with XGBoost

Here, we assume that your C++ application is using CMake for builds.

Use `find_package()` and `target_link_libraries()` in your application's CMakeList.txt to link with the XGBoost library:

```
cmake_minimum_required(VERSION 3.18)
project(your_project_name LANGUAGES C CXX VERSION your_project_version)
find_package(xgboost REQUIRED)
add_executable(your_project_name /path/to/project_file.c)
target_link_libraries(your_project_name xgboost::xgboost)
```

To ensure that CMake can locate the XGBoost library, supply `-DCMAKE_PREFIX_PATH=$CONDA_PREFIX` argument when invoking CMake. This option instructs CMake to locate the XGBoost library in `$CONDA_PREFIX`, which is where your Conda environment is located.

```
# Navigate to the build directory for your application
cd build
# Activate the Conda environment where we previously installed XGBoost
conda activate [env_name]
# Invoke CMake with CMAKE_PREFIX_PATH
cmake .. -DCMAKE_PREFIX_PATH=$CONDA_PREFIX
# Build your application
make
```

Useful Tips To Remember

Below are some useful tips while using C API:

1. Error handling: Always check the return value of the C API functions.
 - a. In a C application: Use the following macro to guard all calls to XGBoost's C API functions. The macro prints all the error/ exception occurred:

```
1 #define safe_xgboost(call) { \
2     int err = (call); \
3     if (err != 0) { \
4         fprintf(stderr, "%s:%d: error in %s: %s\n", __FILE__, __LINE__, #call, \
5         ↪ XGBGetLastError()); \
6         exit(1); \
7     } \
8 }
```

In your application, wrap all C API function calls with the macro as follows:

```
DMatrixHandle train;
safe_xgboost(XGDMatrixCreateFromFile("/path/to/training/dataset/", silent, &train));
```

- b. In a C++ application: modify the macro `safe_xgboost` to throw an exception upon an error.

```
1 #define safe_xgboost(call) { \
2     int err = (call); \
3     if (err != 0) { \
```

(continues on next page)

(continued from previous page)

```

4     throw new Exception(std::string(__FILE__) + ":" + std::to_string(__LINE__) + \
5                           ": error in " + #call + ":" + XGBGetLastError()); \
6 } \
7 }

```

- c. Assertion technique: It works both in C/ C++. If expression evaluates to 0 (false), then the expression, source code filename, and line number are sent to the standard error, and then abort() function is called. It can be used to test assumptions made by you in the code.

```

DMatrixHandle dmat;
assert( XGDMatrixCreateFromFile("training_data.libsvm", 0, &dmat) == 0);

```

2. Always remember to free the allocated space by BoosterHandle & DMatrixHandle appropriately:

```

1  #include <assert.h>
2  #include <stdio.h>
3  #include <stdlib.h>
4  #include <xgboost/c_api.h>
5
6  int main(int argc, char** argv) {
7      int silent = 0;
8
9      BoosterHandle booster;
10
11     // do something with booster
12
13     //free the memory
14     XGBoosterFree(booster);
15
16     DMatrixHandle DMatrixHandle_param;
17
18     // do something with DMatrixHandle_param
19
20     // free the memory
21     XGDMatrixFree(DMatrixHandle_param);
22
23     return 0;
24 }

```

3. For tree models, it is important to use consistent data formats during training and scoring/ predicting otherwise it will result in wrong outputs. Example if we our training data is in dense matrix format then your prediction dataset should also be a dense matrix or if training in libsvm format then dataset for prediction should also be in libsvm format.

4. Always use strings for setting values to the parameters in booster handle object. The parameter value can be of any data type (e.g. int, char, float, double, etc), but they should always be encoded as strings.

```

BoosterHandle booster;
XGBoosterSetParam(booster, "parameter_name", "0.1");

```

Sample examples along with Code snippet to use C API functions

1. If the dataset is available in a file, it can be loaded into a DMatrix object using the `XGDMatrixCreateFromFile()`

```
DMatrixHandle data; // handle to DMatrix
// Load the data from file & store it in data variable of DMatrixHandle datatype
safe_xgboost(XGDMatrixCreateFromFile("/path/to/file/filename", silent, &data));
```

2. You can also create a DMatrix object from a 2D Matrix using the `XGDMatrixCreateFromMat()`

```
1 // 1D matrix
2 const int data1[] = { 0, 0, 1, 0, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 1, 0, 0,
   ↪ 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0 };
3
4 // 2D matrix
5 const int ROWS = 5, COLS = 3;
6 const int data2[ROWS][COLS] = { {1, 2, 3}, {2, 4, 6}, {3, -1, 9}, {4, 8, -1}, {2, 5, 1},
   ↪ {0, 1, 5} };
7 DMatrixHandle dmatrix1, dmatrix2;
8 // Pass the matrix, no of rows & columns contained in the matrix variable
9 // here '0' represents the missing value in the matrix dataset
10 // dmatrix variable will contain the created DMatrix using it
11 safe_xgboost(XGDMatrixCreateFromMat(data1, 1, 50, 0, &dmatrix));
12 // here -1 represents the missing value in the matrix dataset
13 safe_xgboost(XGDMatrixCreateFromMat(data2, ROWS, COLS, -1, &dmatrix2));
```

3. Create a Booster object for training & testing on dataset using `XGBoosterCreate()`

```
1 BoosterHandle booster;
2 const int eval_dmats_size;
3 // We assume that training and test data have been loaded into 'train' and 'test'
4 DMatrixHandle eval_dmats[eval_dmats_size] = {train, test};
5 safe_xgboost(XGBoosterCreate(eval_dmats, eval_dmats_size, &booster));
```

4. For each DMatrix object, set the labels using `XGDMatrixSetFloatInfo()`. Later you can access the label using `XGDMatrixGetFloatInfo()`.

```
1 const int ROWS=5, COLS=3;
2 const int data[ROWS][COLS] = { {1, 2, 3}, {2, 4, 6}, {3, -1, 9}, {4, 8, -1}, {2, 5, 1},
   ↪ {0, 1, 5} };
3 DMatrixHandle dmatrix;
4
5 safe_xgboost(XGDMatrixCreateFromMat(data, ROWS, COLS, -1, &dmatrix));
6
7 // variable to store labels for the dataset created from above matrix
8 float labels[ROWS];
9
10 for (int i = 0; i < ROWS; i++) {
11     labels[i] = i;
12 }
13
14 // Loading the labels
15 safe_xgboost(XGDMatrixSetFloatInfo(dmatrix, "label", labels, ROWS));
```

(continues on next page)

(continued from previous page)

```

16 // reading the labels and store the length of the result
17 bst_ulong result_len;
18
19 // labels result
20 const float *result;
21
22 safe_xgboost(XGDMatrixGetFloatInfo(dmatrix, "label", &result_len, &result));
23
24 for(unsigned int i = 0; i < result_len; i++) {
25     printf("label[%i] = %f\n", i, result[i]);
26 }
27

```

5. Set the parameters for the Booster object according to the requirement using `XGBoosterSetParam()`. Check out the full list of parameters available [here](#).

```

1 BoosterHandle booster;
2 safe_xgboost(XGBoosterSetParam(booster, "booster", "gblinear"));
3 // default max_depth =6
4 safe_xgboost(XGBoosterSetParam(booster, "max_depth", "3"));
5 // default eta = 0.3
6 safe_xgboost(XGBoosterSetParam(booster, "eta", "0.1"));

```

6. Train & evaluate the model using `XGBoosterUpdateOneIter()` and `XGBoosterEvalOneIter()` respectively.

```

1 int num_of_iterations = 20;
2 const char* eval_names[eval_dmats_size] = {"train", "test"};
3 const char* eval_result = NULL;
4
5 for (int i = 0; i < num_of_iterations; ++i) {
6     // Update the model performance for each iteration
7     safe_xgboost(XGBoosterUpdateOneIter(booster, i, train));
8
9     // Give the statistics for the learner for training & testing dataset in terms of
10    ↪error after each iteration
11    safe_xgboost(XGBoosterEvalOneIter(booster, i, eval_dmats, eval_names, eval_dmats_size,
12    ↪&eval_result));
13    printf("%s\n", eval_result);
14 }

```

Note: For customized loss function, use `XGBoosterBoostOneIter()` instead and manually specify the gradient and 2nd order gradient.

7. Predict the result on a test set using `XGBoosterPredictFromDMatrix()`

```

1 char const config[] =
2     "{\"training\": false, \"type\": 0, \"
3     \"iteration_begin\": 0, \"iteration_end\": 0, \"strict_shape\": false}";
4 /* Shape of output prediction */
5 uint64_t const* out_shape;
6 /* Dimension of output prediction */

```

(continues on next page)

(continued from previous page)

```

7  uint64_t out_dim;
8  /* Pointer to a thread local contiguous array, assigned in prediction function. */
9  float const* out_result = NULL;
10 safe_xgboost(
11     XGBoosterPredictFromDMatrix(booster, dmatrix, config, &out_shape, &out_dim, &out_
12     ↪result));
13
14 for (unsigned int i = 0; i < output_length; i++){
15     printf("prediction[%i] = %f \n", i, output_result[i]);
16 }

```

8. Get the number of features in your dataset using `XGBoosterGetNumFeature()`.

```

1  bst_ulong num_of_features = 0;
2
3  // Assuming booster variable of type BoosterHandle is already declared
4  // and dataset is loaded and trained on booster
5  // storing the results in num_of_features variable
6  safe_xgboost(XGBoosterGetNumFeature(booster, &num_of_features));
7
8  // Printing number of features by type conversion of num_of_features variable from bst_
9  ↪ulong to unsigned long
10 printf("num_feature: %lu\n", (unsigned long)(num_of_features));

```

9. Save the model using `XGBoosterSaveModel()`

```

BoosterHandle booster;
const char *model_path = "/path/of/model.json";
safe_xgboost(XGBoosterSaveModel(booster, model_path));

```

10. Load the model using `XGBoosterLoadModel()`

```

1  BoosterHandle booster;
2  const char *model_path = "/path/of/model.json";
3
4  // create booster handle first
5  safe_xgboost(XGBoosterCreate(NULL, 0, &booster));
6
7  // set the model parameters here
8
9  // load model
10 safe_xgboost(XGBoosterLoadModel(booster, model_path));
11
12 // predict the model here

```

11. Free all the internal structure used in your code using `XGDMatrixFree()` and `XGBoosterFree()`. This step is important to prevent memory leak.

```

safe_xgboost(XGDMatrixFree(dmatrix));
safe_xgboost(XGBoosterFree(booster));

```

1.4.17 Text Input Format of DMatrix

Here we will briefly describe the text input formats for XGBoost. However, for users with access to a supported language environment like Python or R, it's recommended to use data parsers from that ecosystem instead. For instance, `sklearn.datasets.load_svmlight_file()`.

Basic Input Format

XGBoost currently supports two text formats for ingesting data: LIBSVM and CSV. The rest of this document will describe the LIBSVM format. (See [this Wikipedia article](#) for a description of the CSV format.). Please be careful that, XGBoost does **not** understand file extensions, nor try to guess the file format, as there is no universal agreement upon file extension of LIBSVM or CSV. Instead it employs **URI** format for specifying the precise input file type. For example if you provide a csv file `./data.train.csv` as input, XGBoost will blindly use the default LIBSVM parser to digest it and generate a parser error. Instead, users need to provide an URI in the form of `train.csv?format=csv` or `train.csv?format=libsvm`. For external memory input, the URI should of a form similar to `train.csv?format=csv#dtrain.cache`. See [Data Interface](#) and [Using XGBoost External Memory Version](#) also.

For training or predicting, XGBoost takes an instance file with the format as below:

Listing 18: train.txt

```
1 101:1.2 102:0.03
0 1:2.1 10001:300 10002:400
0 0:1.3 1:0.3
1 0:0.01 1:0.3
0 0:0.2 1:0.3
```

Each line represent a single instance, and in the first line '1' is the instance label, '101' and '102' are feature indices, '1.2' and '0.03' are feature values. In the binary classification case, '1' is used to indicate positive samples, and '0' is used to indicate negative samples. We also support probability values in [0,1] as label, to indicate the probability of the instance being positive.

Auxiliary Files for Additional Information

Note: all information below is applicable only to single-node version of the package. If you'd like to perform distributed training with multiple nodes, skip to the section [Embedding additional information inside LIBSVM file](#).

Group Input Format

For [ranking task](#), XGBoost supports the group input format. In ranking task, instances are categorized into *query groups* in real world scenarios. For example, in the learning to rank web pages scenario, the web page instances are grouped by their queries. XGBoost requires an file that indicates the group information. For example, if the instance file is the `train.txt` shown above, the group file should be named `train.txt.group` and be of the following format:

Listing 19: train.txt.group

```
2
3
```

This means that, the data set contains 5 instances, and the first two instances are in a group and the other three are in another group. The numbers in the group file are actually indicating the number of instances in each group in the instance file in order. At the time of configuration, you do not have to indicate the path of the group file. If the instance file name is `xxx`, XGBoost will check whether there is a file named `xxx.group` in the same directory.

Instance Weight File

Instances in the training data may be assigned weights to differentiate relative importance among them. For example, if we provide an instance weight file for the `train.txt` file in the example as below:

Listing 20: `train.txt.weight`

```
1
0.5
0.5
1
0.5
```

It means that XGBoost will emphasize more on the first and fourth instance (i.e. the positive instances) while training. The configuration is similar to configuring the group information. If the instance file name is `xxx`, XGBoost will look for a file named `xxx.weight` in the same directory. If the file exists, the instance weights will be extracted and used at the time of training.

Note: Binary buffer format and instance weights

If you choose to save the training data as a binary buffer (using `save_binary()`), keep in mind that the resulting binary buffer file will include the instance weights. To update the weights, use the `set_weight()` function.

Initial Margin File

XGBoost supports providing each instance an initial margin prediction. For example, if we have a initial prediction using logistic regression for `train.txt` file, we can create the following file:

Listing 21: train.txt.base_margin

```
-0.4  
1.0  
3.4
```

XGBoost will take these values as initial margin prediction and boost from that. An important note about `base_margin` is that it should be margin prediction before transformation, so if you are doing logistic loss, you will need to put in value before logistic transformation. If you are using XGBoost predictor, use `pred_margin=1` to output margin values.

Embedding additional information inside LIBSVM file

This section is applicable to both single- and multiple-node settings.

Query ID Columns

This is most useful for [ranking task](#), where the instances are grouped into query groups. You may embed query group ID for each instance in the LIBSVM file by adding a token of form `qid:xx` in each row:

Listing 22: train.txt

```
1 qid:1 101:1.2 102:0.03  
0 qid:1 1:2.1 10001:300 10002:400  
0 qid:2 0:1.3 1:0.3  
1 qid:2 0:0.01 1:0.3  
0 qid:3 0:0.2 1:0.3  
1 qid:3 3:-0.1 10:-0.3  
0 qid:3 6:0.2 10:0.15
```

Keep in mind the following restrictions:

- You are not allowed to specify query ID's for some instances but not for others. Either every row is assigned query ID's or none at all.
- The rows have to be sorted in ascending order by the query IDs. So, for instance, you may not have one row having large query ID than any of the following rows.

Instance weights

You may specify instance weights in the LIBSVM file by appending each instance label with the corresponding weight in the form of `[label]:[weight]`, as shown by the following example:

Listing 23: train.txt

```
1:1.0 101:1.2 102:0.03  
0:0.5 1:2.1 10001:300 10002:400  
0:0.5 0:1.3 1:0.3  
1:1.0 0:0.01 1:0.3  
0:0.5 0:0.2 1:0.3
```

where the negative instances are assigned half weights compared to the positive instances.

1.4.18 Notes on Parameter Tuning

Parameter tuning is a dark art in machine learning, the optimal parameters of a model can depend on many scenarios. So it is impossible to create a comprehensive guide for doing so.

This document tries to provide some guideline for parameters in XGBoost.

Understanding Bias-Variance Tradeoff

If you take a machine learning or statistics course, this is likely to be one of the most important concepts. When we allow the model to get more complicated (e.g. more depth), the model has better ability to fit the training data, resulting in a less biased model. However, such complicated model requires more data to fit.

Most of parameters in XGBoost are about bias variance tradeoff. The best model should trade the model complexity with its predictive power carefully. [Parameters Documentation](#) will tell you whether each parameter will make the model more conservative or not. This can be used to help you turn the knob between complicated model and simple model.

Control Overfitting

When you observe high training accuracy, but low test accuracy, it is likely that you encountered overfitting problem.

There are in general two ways that you can control overfitting in XGBoost:

- The first way is to directly control model complexity.
 - This includes `max_depth`, `min_child_weight` and `gamma`.
- The second way is to add randomness to make training robust to noise.
 - This includes `subsample` and `colsample_bytree`.
 - You can also reduce stepsize `eta`. Remember to increase `num_round` when you do so.

Handle Imbalanced Dataset

For common cases such as ads clickthrough log, the dataset is extremely imbalanced. This can affect the training of XGBoost model, and there are two ways to improve it.

- If you care only about the overall performance metric (AUC) of your prediction
 - Balance the positive and negative weights via `scale_pos_weight`
 - Use AUC for evaluation
- If you care about predicting the right probability
 - In such a case, you cannot re-balance the dataset
 - Set parameter `max_delta_step` to a finite number (say 1) to help convergence

Reducing Memory Usage

If you are using a HPO library like `sklearn.model_selection.GridSearchCV`, please control the number of threads it can use. It's best to let XGBoost to run in parallel instead of asking `GridSearchCV` to run multiple experiments at the same time. For instance, creating a fold of data for cross validation can consume a significant amount of memory:

```
# This creates a copy of dataset. X and X_train are both in memory at the same time.
```

```
# This happens for every thread at the same time if you run `GridSearchCV` with  
# `n_jobs` larger than 1
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y)
```

```
df = pd.DataFrame()
```

```
# This creates a new copy of the dataframe, even if you specify the inplace parameter  
new_df = df.drop(...)
```

```
array = np.array(...)
```

```
# This may or may not make a copy of the data, depending on the type of the data  
array.astype(np.float32)
```

```
# np by default uses double, do you actually need it?
```

```
array = np.array(...)
```

You can find some more specific memory reduction practices scattered through the documents For instances: *Distributed XGBoost with Dask*, *XGBoost GPU Support*. However, before going into these, being conscious about making data copies is a good starting point. It usually consumes a lot more memory than people expect.

1.4.19 Custom Objective and Evaluation Metric

Contents

- *Overview*
- *Customized Objective Function*
- *Customized Metric Function*
- *Reverse Link Function*
- *Scikit-Learn Interface*

Overview

XGBoost is designed to be an extensible library. One way to extend it is by providing our own objective function for training and corresponding metric for performance monitoring. This document introduces implementing a customized elementwise evaluation metric and objective for XGBoost. Although the introduction uses Python for demonstration, the concepts should be readily applicable to other language bindings.

Note:

- The ranking task does not support customized functions.

- Breaking change was made in XGBoost 1.6.

In the following two sections, we will provide a step by step walk through of implementing the Squared Log Error (SLE) objective function:

$$\frac{1}{2}[\log(pred + 1) - \log(label + 1)]^2$$

and its default metric Root Mean Squared Log Error(RMSLE):

$$\sqrt{\frac{1}{N}[\log(pred + 1) - \log(label + 1)]^2}$$

Although XGBoost has native support for said functions, using it for demonstration provides us the opportunity of comparing the result from our own implementation and the one from XGBoost internal for learning purposes. After finishing this tutorial, we should be able to provide our own functions for rapid experiments. And at the end, we will provide some notes on non-identity link function along with examples of using custom metric and objective with the *scikit-learn* interface.

If we compute the gradient of said objective function:

$$g = \frac{\partial objective}{\partial pred} = \frac{\log(pred + 1) - \log(label + 1)}{pred + 1}$$

As well as the hessian (the second derivative of the objective):

$$h = \frac{\partial^2 objective}{\partial pred} = \frac{-\log(pred + 1) + \log(label + 1) + 1}{(pred + 1)^2}$$

Customized Objective Function

During model training, the objective function plays an important role: provide gradient information, both first and second order gradient, based on model predictions and observed data labels (or targets). Therefore, a valid objective function should accept two inputs, namely prediction and labels. For implementing SLE, we define:

```
import numpy as np
import xgboost as xgb
from typing import Tuple

def gradient(predt: np.ndarray, dtrain: xgb.DMatrix) -> np.ndarray:
    """Compute the gradient squared log error."""
    y = dtrain.get_label()
    return (np.log1p(predt) - np.log1p(y)) / (predt + 1)

def hessian(predt: np.ndarray, dtrain: xgb.DMatrix) -> np.ndarray:
    """Compute the hessian for squared log error."""
    y = dtrain.get_label()
    return ((-np.log1p(predt) + np.log1p(y) + 1) /
            np.power(predt + 1, 2))

def squared_log(predt: np.ndarray,
                dtrain: xgb.DMatrix) -> Tuple[np.ndarray, np.ndarray]:
    """Squared Log Error objective. A simplified version for RMSLE used as
    objective function.
    """
```

(continues on next page)

(continued from previous page)

```
predt[predt < -1] = -1 + 1e-6
grad = gradient(predt, dtrain)
hess = hessian(predt, dtrain)
return grad, hess
```

In the above code snippet, `squared_log` is the objective function we want. It accepts a numpy array `predt` as model prediction, and the training `DMatrix` for obtaining required information, including labels and weights (not used here). This objective is then used as a callback function for XGBoost during training by passing it as an argument to `xgb.train`:

```
xgb.train({'tree_method': 'hist', 'seed': 1994}, # any other tree method is fine.
          dtrain=dtrain,
          num_boost_round=10,
          obj=squared_log)
```

Notice that in our definition of the objective, whether we subtract the labels from the prediction or the other way around is important. If you find the training error goes up instead of down, this might be the reason.

Customized Metric Function

So after having a customized objective, we might also need a corresponding metric to monitor our model's performance. As mentioned above, the default metric for SLE is RMSLE. Similarly we define another callback like function as the new metric:

```
def rmsle(predt: np.ndarray, dtrain: xgb.DMatrix) -> Tuple[str, float]:
    """ Root mean squared log error metric."""
    y = dtrain.get_label()
    predt[predt < -1] = -1 + 1e-6
    elements = np.power(np.log1p(y) - np.log1p(predt), 2)
    return 'PyRMSLE', float(np.sqrt(np.sum(elements) / len(y)))
```

Since we are demonstrating in Python, the metric or objective need not be a function, any callable object should suffice. Similar to the objective function, our metric also accepts `predt` and `dtrain` as inputs, but returns the name of the metric itself and a floating point value as the result. After passing it into XGBoost as argument of `feval` parameter:

```
xgb.train({'tree_method': 'hist', 'seed': 1994,
          'disable_default_eval_metric': 1},
          dtrain=dtrain,
          num_boost_round=10,
          obj=squared_log,
          feval=rmsle,
          evals=[(dtrain, 'dtrain'), (dtest, 'dtest')],
          evals_result=results)
```

We will be able to see XGBoost printing something like:

```
[0] dtrain-PyRMSLE:1.37153 dtest-PyRMSLE:1.31487
[1] dtrain-PyRMSLE:1.26619 dtest-PyRMSLE:1.20899
[2] dtrain-PyRMSLE:1.17508 dtest-PyRMSLE:1.11629
[3] dtrain-PyRMSLE:1.09836 dtest-PyRMSLE:1.03871
[4] dtrain-PyRMSLE:1.03557 dtest-PyRMSLE:0.977186
[5] dtrain-PyRMSLE:0.985783 dtest-PyRMSLE:0.93057
...
```

Notice that the parameter `disable_default_eval_metric` is used to suppress the default metric in XGBoost.

For fully reproducible source code and comparison plots, see [Demo for defining a custom regression objective and metric](#).

Reverse Link Function

When using builtin objective, the raw prediction is transformed according to the objective function. When a custom objective is provided XGBoost doesn't know its link function so the user is responsible for making the transformation for both objective and custom evaluation metric. For objective with identity link like `squared error` this is trivial, but for other link functions like log link or inverse link the difference is significant.

For the Python package, the behaviour of prediction can be controlled by the `output_margin` parameter in `predict` function. When using the `custom_metric` parameter without a custom objective, the metric function will receive transformed prediction since the objective is defined by XGBoost. However, when the custom objective is also provided along with that metric, then both the objective and custom metric will receive raw prediction. The following example provides a comparison between two different behavior with a multi-class classification model. Firstly we define 2 different Python metric functions implementing the same underlying metric for comparison, `merror_with_transform` is used when custom objective is also used, otherwise the simpler `merror` is preferred since XGBoost can perform the transformation itself.

```
import xgboost as xgb
import numpy as np

def merror_with_transform(predt: np.ndarray, dtrain: xgb.DMatrix):
    """Used when custom objective is supplied."""
    y = dtrain.get_label()
    n_classes = predt.size // y.shape[0]
    # Like custom objective, the predt is untransformed leaf weight when custom objective
    # is provided.

    # With the use of `custom_metric` parameter in train function, custom metric receives
    # raw input only when custom objective is also being used. Otherwise custom metric
    # will receive transformed prediction.
    assert predt.shape == (dtrain.num_row(), n_classes)
    out = np.zeros(dtrain.num_row())
    for r in range(predt.shape[0]):
        i = np.argmax(predt[r])
        out[r] = i

    assert y.shape == out.shape

    errors = np.zeros(dtrain.num_row())
    errors[y != out] = 1.0
    return 'PyMError', np.sum(errors) / dtrain.num_row()
```

The above function is only needed when we want to use custom objective and XGBoost doesn't know how to transform the prediction. The normal implementation for multi-class error function is:

```
def merror(predt: np.ndarray, dtrain: xgb.DMatrix):
    """Used when there's no custom objective."""
    # No need to do transform, XGBoost handles it internally.
    errors = np.zeros(dtrain.num_row())
```

(continues on next page)

(continued from previous page)

```
errors[y != out] = 1.0
return 'PyMError', np.sum(errors) / dtrain.num_row()
```

Next we need the custom softprob objective:

```
def softprob_obj(predt: np.ndarray, data: xgb.DMatrix):
    """Loss function. Computing the gradient and approximated hessian (diagonal).
    Reimplements the `multi:softprob` inside XGBoost.
    """

    # Full implementation is available in the Python demo script linked below
    ...

    return grad, hess
```

Lastly we can train the model using obj and custom_metric parameters:

```
Xy = xgb.DMatrix(X, y)
booster = xgb.train(
    {"num_class": kClasses, "disable_default_eval_metric": True},
    m,
    num_boost_round=kRounds,
    obj=softprob_obj,
    custom_metric=merror_with_transform,
    evals_result=custom_results,
    evals=[(m, "train")],
)
```

Or if you don't need the custom objective and just want to supply a metric that's not available in XGBoost:

```
booster = xgb.train(
    {
        "num_class": kClasses,
        "disable_default_eval_metric": True,
        "objective": "multi:softmax",
    },
    m,
    num_boost_round=kRounds,
    # Use a simpler metric implementation.
    custom_metric=merror,
    evals_result=custom_results,
    evals=[(m, "train")],
)
```

We use `multi:softmax` to illustrate the differences of transformed prediction. With `softprob` the output prediction array has shape `(n_samples, n_classes)` while for `softmax` it's `(n_samples,)`. A demo for multi-class objective function is also available at [Demo for creating customized multi-class objective function](#).

Scikit-Learn Interface

The scikit-learn interface of XGBoost has some utilities to improve the integration with standard scikit-learn functions. For instance, after XGBoost 1.6.0 users can use the cost function (not scoring functions) from scikit-learn out of the box:

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

Also, for custom objective function, users can define the objective without having to access DMatrix:

```
def softprob_obj(labels: np.ndarray, predt: np.ndarray) -> Tuple[np.ndarray, np.ndarray]:
    rows = labels.shape[0]
    classes = predt.shape[1]
    grad = np.zeros((rows, classes), dtype=float)
    hess = np.zeros((rows, classes), dtype=float)
    eps = 1e-6
    for r in range(predt.shape[0]):
        target = labels[r]
        p = softmax(predt[r, :])
        for c in range(predt.shape[1]):
            g = p[c] - 1.0 if c == target else p[c]
            h = max((2.0 * p[c] * (1.0 - p[c]))).item(), eps)
            grad[r, c] = g
            hess[r, c] = h

    grad = grad.reshape((rows * classes, 1))
    hess = hess.reshape((rows * classes, 1))
    return grad, hess

clf = xgb.XGBClassifier(tree_method="hist", objective=softprob_obj)
```

1.5 Frequently Asked Questions

This document contains frequently asked questions about XGBoost.

1.5.1 How to tune parameters

See *Parameter Tuning Guide*.

1.5.2 Description on the model

See *Introduction to Boosted Trees*.

1.5.3 I have a big dataset

XGBoost is designed to be memory efficient. Usually it can handle problems as long as the data fit into your memory. This usually means millions of instances.

If you are running out of memory, checkout the tutorial page for using *distributed training* with one of the many frameworks, or the *external memory version* for using external memory.

1.5.4 How to handle categorical feature?

Visit *this tutorial* for a walk through of categorical data handling and some worked examples.

1.5.5 Why not implement distributed XGBoost on top of X (Spark, Hadoop)?

The first fact we need to know is going distributed does not necessarily solve all the problems. Instead, it creates more problems such as more communication overhead and fault tolerance. The ultimate question will still come back to how to push the limit of each computation node and use less resources to complete the task (thus with less communication and chance of failure).

To achieve these, we decide to reuse the optimizations in the single node XGBoost and build the distributed version on top of it. The demand of communication in machine learning is rather simple, in the sense that we can depend on a limited set of APIs (in our case rabbit). Such design allows us to reuse most of the code, while being portable to major platforms such as Hadoop/Yarn, MPI, SGE. Most importantly, it pushes the limit of the computation resources we can use.

1.5.6 How can I port a model to my own system?

The model and data format of XGBoost is exchangeable, which means the model trained by one language can be loaded in another. This means you can train the model using R, while running prediction using Java or C++, which are more common in production systems. You can also train the model using distributed versions, and load them in from Python to do some interactive analysis. See *Model IO* for more information.

1.5.7 Do you support LambdaMART?

Yes, XGBoost implements LambdaMART. Checkout the objective section in *parameters*.

1.5.8 How to deal with missing values

XGBoost supports missing values by default. In tree algorithms, branch directions for missing values are learned during training. Note that the gblinear booster treats missing values as zeros.

When the `missing` parameter is specified, values in the input predictor that is equal to `missing` will be treated as missing and removed. By default it's set to `NaN`.

1.5.9 Slightly different result between runs

This could happen, due to non-determinism in floating point summation order and multi-threading. Also, data partitioning changes by distributed framework can be an issue as well. Though the general accuracy will usually remain the same.

1.5.10 Why do I see different results with sparse and dense data?

“Sparse” elements are treated as if they were “missing” by the tree booster, and as zeros by the linear booster. However, if we convert the sparse matrix back to dense matrix, the sparse matrix might fill the missing entries with 0, which is a valid value for xgboost.

1.6 XGBoost GPU Support

This page contains information about GPU algorithms supported in XGBoost.

Note: CUDA 11.0, Compute Capability 5.0 required (See [this list](#) to look up compute capability of your GPU card.)

1.6.1 CUDA Accelerated Tree Construction Algorithms

Most of the algorithms in XGBoost including training, prediction and evaluation can be accelerated with CUDA-capable GPUs.

Usage

To enable GPU acceleration, specify the `device` parameter as `cuda`. In addition, the device ordinal (which GPU to use if you have multiple devices in the same node) can be specified using the `cuda:<ordinal>` syntax, where `<ordinal>` is an integer that represents the device ordinal. XGBoost defaults to 0 (the first device reported by CUDA runtime).

The GPU algorithms currently work with CLI, Python, R, and JVM packages. See [Installation Guide](#) for details.

Listing 24: Python example

```
params = dict()
params["device"] = "cuda"
params["tree_method"] = "hist"
Xy = xgboost.QuantileDMatrix(X, y)
xgboost.train(params, Xy)
```

Listing 25: With the Scikit-Learn interface

```
XGBRegressor(tree_method="hist", device="cuda")
```

GPU-Accelerated SHAP values

XGBoost makes use of `GPUTreeShap` as a backend for computing shap values when the GPU is used.

```
booster.set_param({"device": "cuda:0"})
shap_values = booster.predict(dtrain, pred_contribs=True)
shap_interaction_values = model.predict(dtrain, pred_interactions=True)
```

See *Use GPU to speedup SHAP value computation* for a worked example.

Multi-node Multi-GPU Training

XGBoost supports fully distributed GPU training using [Dask](#), [Spark](#) and [PySpark](#). For getting started with Dask see our tutorial *Distributed XGBoost with Dask* and worked examples *XGBoost Dask Feature Walkthrough*, also Python documentation *Dask API* for complete reference. For usage with Spark using Scala see *XGBoost4J-Spark-GPU Tutorial (version 1.6.1+)*. Lastly for distributed GPU training with PySpark, see *Distributed XGBoost with PySpark*.

Memory usage

The following are some guidelines on the device memory usage of the `hist` tree method on GPU.

Memory inside xgboost training is generally allocated for two reasons - storing the dataset and working memory.

The dataset itself is stored on device in a compressed ELLPACK format. The ELLPACK format is a type of sparse matrix that stores elements with a constant row stride. This format is convenient for parallel computation when compared to CSR because the row index of each element is known directly from its address in memory. The disadvantage of the ELLPACK format is that it becomes less memory efficient if the maximum row length is significantly more than the average row length. Elements are quantised and stored as integers. These integers are compressed to a minimum bit length. Depending on the number of features, we usually don't need the full range of a 32 bit integer to store elements and so compress this down. The compressed, quantised ELLPACK format will commonly use 1/4 the space of a CSR matrix stored in floating point.

Working memory is allocated inside the algorithm proportional to the number of rows to keep track of gradients, tree positions and other per row statistics. Memory is allocated for histogram bins proportional to the number of bins, number of features and nodes in the tree. For performance reasons we keep histograms in memory from previous nodes in the tree, when a certain threshold of memory usage is passed we stop doing this to conserve memory at some performance loss.

If you are getting out-of-memory errors on a big dataset, try the or `xgboost.QuantileDMatrix` or *external memory version*. Note that when external memory is used for GPU hist, it's best to employ gradient based sampling as well. Last but not least, `inplace_predict` can be preferred over `predict` when data is already on GPU. Both `QuantileDMatrix` and `inplace_predict` are automatically enabled if you are using the scikit-learn interface.

CPU-GPU Interoperability

The model can be used on any device regardless of the one used to train it. For instance, a model trained using GPU can still work on a CPU-only machine and vice versa. For more information about model serialization, see [Introduction to Model IO](#).

Developer notes

The application may be profiled with annotations by specifying `USE_NTVX` to `cmake`. Regions covered by the ‘Monitor’ class in CUDA code will automatically appear in the `nsight` profiler when `verbosity` is set to 3.

1.6.2 References

Mitchell R, Frank E. (2017) Accelerating the XGBoost algorithm using GPU computing. *PeerJ Computer Science* 3:e127 <https://doi.org/10.7717/peerj-cs.127>

NVIDIA Parallel Forall: Gradient Boosting, Decision Trees and XGBoost with CUDA
Out-of-Core GPU Gradient Boosting

Contributors

Many thanks to the following contributors (alphabetical order):

- Andrey Adinets
- Jiaming Yuan
- Jonathan C. McKinney
- Matthew Jones
- Philip Cho
- Rong Ou
- Rory Mitchell
- Shankara Rao Thejaswi Nanditale
- Sriram Chandramouli
- Vinay Deshpande

Please report bugs to the XGBoost issues list: <https://github.com/dmlc/xgboost/issues>. For general questions please visit our user form: <https://discuss.xgboost.ai/>.

1.7 XGBoost Parameters

Before running XGBoost, we must set three types of parameters: general parameters, booster parameters and task parameters.

- **General parameters** relate to which booster we are using to do boosting, commonly tree or linear model
- **Booster parameters** depend on which booster you have chosen
- **Learning task parameters** decide on the learning scenario. For example, regression tasks may use different parameters with ranking tasks.

- **Command line parameters** relate to behavior of CLI version of XGBoost.

Note: Parameters in R package

In R-package, you can use `.` (dot) to replace underscore in the parameters, for example, you can use `max.depth` to indicate `max_depth`. The underscore parameters are also valid in R.

- *Global Configuration*
- *General Parameters*
 - *Parameters for Tree Booster*
 - *Parameters for Categorical Feature*
 - *Additional parameters for Dart Booster (`booster=dart`)*
 - *Parameters for Linear Booster (`booster=gblinear`)*
- *Learning Task Parameters*
 - *Parameters for Tweedie Regression (`objective=reg:tweedie`)*
 - *Parameter for using Pseudo-Huber (`reg:pseudohubererror`)*
 - *Parameter for using Quantile Loss (`reg:quantileerror`)*
 - *Parameter for using AFT Survival Loss (`survival:aft`) and Negative Log Likelihood of AFT metric (`aft-nloglik`)*
 - *Parameters for learning to rank (`rank:ndcg`, `rank:map`, `rank:pairwise`)*
- *Command Line Parameters*

1.7.1 Global Configuration

The following parameters can be set in the global scope, using `xgboost.config_context()` (Python) or `xgb.set_config()` (R).

- **verbosity**: Verbosity of printing messages. Valid values of 0 (silent), 1 (warning), 2 (info), and 3 (debug).
- **use_rmm**: Whether to use RAPIDS Memory Manager (RMM) to allocate GPU memory. This option is only applicable when XGBoost is built (compiled) with the RMM plugin enabled. Valid values are `true` and `false`.

1.7.2 General Parameters

- **booster** [default= `gbtree`]
 - Which booster to use. Can be `gbtree`, `gblinear` or `dart`; `gbtree` and `dart` use tree based models while `gblinear` uses linear functions.

- **device** [default= `cpu`]

New in version 2.0.0.

- Device for XGBoost to run. User can set it to one of the following values:
 - * `cpu`: Use CPU.
 - * `cuda`: Use a GPU (CUDA device).

- * `cuda:<ordinal>`: `<ordinal>` is an integer that specifies the ordinal of the GPU (which GPU do you want to use if you have more than one devices).
- * `gpu`: Default GPU device selection from the list of available and supported devices. Only cuda devices are supported currently.
- * `gpu:<ordinal>`: Default GPU device selection from the list of available and supported devices. Only cuda devices are supported currently.

For more information about GPU acceleration, see *XGBoost GPU Support*. In distributed environments, ordinal selection is handled by distributed frameworks instead of XGBoost. As a result, using `cuda:<ordinal>` will result in an error. Use `cuda` instead.

- `verbosity` [default=1]
 - Verbosity of printing messages. Valid values are 0 (silent), 1 (warning), 2 (info), 3 (debug). Sometimes XGBoost tries to change configurations based on heuristics, which is displayed as warning message. If there's unexpected behaviour, please try to increase value of verbosity.
- `validate_parameters` [default to false, except for Python, R and CLI interface]
 - When set to True, XGBoost will perform validation of input parameters to check whether a parameter is used or not. A warning is emitted when there's unknown parameter.
- `nthread` [default to maximum number of threads available if not set]
 - Number of parallel threads used to run XGBoost. When choosing it, please keep thread contention and hyperthreading in mind.
- `disable_default_eval_metric` [default= false]
 - Flag to disable default metric. Set to 1 or true to disable.

Parameters for Tree Booster

- `eta` [default=0.3, alias: `learning_rate`]
 - Step size shrinkage used in update to prevents overfitting. After each boosting step, we can directly get the weights of new features, and eta shrinks the feature weights to make the boosting process more conservative.
 - range: [0,1]
- `gamma` [default=0, alias: `min_split_loss`]
 - Minimum loss reduction required to make a further partition on a leaf node of the tree. The larger gamma is, the more conservative the algorithm will be.
 - range: [0,∞]
- `max_depth` [default=6]
 - Maximum depth of a tree. Increasing this value will make the model more complex and more likely to overfit. 0 indicates no limit on depth. Beware that XGBoost aggressively consumes memory when training a deep tree. exact tree method requires non-zero value.
 - range: [0,∞]
- `min_child_weight` [default=1]
 - Minimum sum of instance weight (hessian) needed in a child. If the tree partition step results in a leaf node with the sum of instance weight less than `min_child_weight`, then the building process will give up further partitioning. In linear regression task, this simply corresponds to minimum number of instances needed to be in each node. The larger `min_child_weight` is, the more conservative the algorithm will be.

- range: $[0, \infty]$
- `max_delta_step` [default=0]
 - Maximum delta step we allow each leaf output to be. If the value is set to 0, it means there is no constraint. If it is set to a positive value, it can help making the update step more conservative. Usually this parameter is not needed, but it might help in logistic regression when class is extremely imbalanced. Set it to value of 1-10 might help control the update.
 - range: $[0, \infty]$
- `subsample` [default=1]
 - Subsample ratio of the training instances. Setting it to 0.5 means that XGBoost would randomly sample half of the training data prior to growing trees. and this will prevent overfitting. Subsampling will occur once in every boosting iteration.
 - range: $(0, 1]$
- `sampling_method` [default= uniform]
 - The method to use to sample the training instances.
 - `uniform`: each training instance has an equal probability of being selected. Typically set `subsample` \geq 0.5 for good results.
 - `gradient_based`: the selection probability for each training instance is proportional to the *regularized absolute value* of gradients (more specifically, $\sqrt{g^2 + \lambda h^2}$). `subsample` may be set to as low as 0.1 without loss of model accuracy. Note that this sampling method is only supported when `tree_method` is set to `hist` and the device is `cuda`; other tree methods only support `uniform` sampling.
- `colsample_bytree`, `colsample_bylevel`, `colsample_bynode` [default=1]
 - This is a family of parameters for subsampling of columns.
 - All `colsample_by*` parameters have a range of $(0, 1]$, the default value of 1, and specify the fraction of columns to be subsampled.
 - `colsample_bytree` is the subsample ratio of columns when constructing each tree. Subsampling occurs once for every tree constructed.
 - `colsample_bylevel` is the subsample ratio of columns for each level. Subsampling occurs once for every new depth level reached in a tree. Columns are subsampled from the set of columns chosen for the current tree.
 - `colsample_bynode` is the subsample ratio of columns for each node (split). Subsampling occurs once every time a new split is evaluated. Columns are subsampled from the set of columns chosen for the current level.
 - `colsample_by*` parameters work cumulatively. For instance, the combination `{'colsample_bytree':0.5, 'colsample_bylevel':0.5, 'colsample_bynode':0.5}` with 64 features will leave 8 features to choose from at each split.

Using the Python or the R package, one can set the `feature_weights` for `DMatrix` to define the probability of each feature being selected when using column sampling. There's a similar parameter for `fit` method in `sklearn` interface.
- `lambda` [default=1, alias: `reg_lambda`]
 - L2 regularization term on weights. Increasing this value will make model more conservative.
 - range: $[0, \infty]$
- `alpha` [default=0, alias: `reg_alpha`]

- L1 regularization term on weights. Increasing this value will make model more conservative.
- range: $[0, \infty]$
- **tree_method** string [default= auto]
 - The tree construction algorithm used in XGBoost. See description in the [reference paper](#) and [Tree Methods](#).
 - Choices: `auto`, `exact`, `approx`, `hist`, this is a combination of commonly used updaters. For other updaters like `refresh`, set the parameter `updater` directly.
 - * `auto`: Same as the `hist` tree method.
 - * `exact`: Exact greedy algorithm. Enumerates all split candidates.
 - * `approx`: Approximate greedy algorithm using quantile sketch and gradient histogram.
 - * `hist`: Faster histogram optimized approximate greedy algorithm.
- **scale_pos_weight** [default=1]
 - Control the balance of positive and negative weights, useful for unbalanced classes. A typical value to consider: `sum(negative instances) / sum(positive instances)`. See [Parameters Tuning](#) for more discussion. Also, see Higgs Kaggle competition demo for examples: [R](#), [py1](#), [py2](#), [py3](#).
- **updater**
 - A comma separated string defining the sequence of tree updaters to run, providing a modular way to construct and to modify the trees. This is an advanced parameter that is usually set automatically, depending on some other parameters. However, it could be also set explicitly by a user. The following updaters exist:
 - * `grow_colmaker`: non-distributed column-based construction of trees.
 - * `grow_histmaker`: distributed tree construction with row-based data splitting based on global proposal of histogram counting.
 - * `grow_quantile_histmaker`: Grow tree using quantized histogram.
 - * `grow_gpu_hist`: Enabled when `tree_method` is set to `hist` along with `device=cuda`.
 - * `grow_gpu_approx`: Enabled when `tree_method` is set to `approx` along with `device=cuda`.
 - * `sync`: synchronizes trees in all distributed nodes.
 - * `refresh`: refreshes tree's statistics and/or leaf values based on the current data. Note that no random subsampling of data rows is performed.
 - * `prune`: prunes the splits where `loss < min_split_loss` (or `gamma`) and nodes that have depth greater than `max_depth`.
- **refresh_leaf** [default=1]
 - This is a parameter of the `refresh` updater. When this flag is 1, tree leaves as well as tree nodes' stats are updated. When it is 0, only node stats are updated.
- **process_type** [default= default]
 - A type of boosting process to run.
 - Choices: `default`, `update`
 - * `default`: The normal boosting process which creates new trees.
 - * `update`: Starts from an existing model and only updates its trees. In each boosting iteration, a tree from the initial model is taken, a specified sequence of updaters is run for that tree, and a modified tree is added to the new model. The new model would have either the same or smaller number of trees, depending on the number of boosting iterations performed. Currently, the following built-in updaters

could be meaningfully used with this process type: `refresh`, `prune`. With `process_type=update`, one cannot use updaters that create new trees.

- `grow_policy` [default= `depthwise`]
 - Controls a way new nodes are added to the tree.
 - Currently supported only if `tree_method` is set to `hist` or `approx`.
 - Choices: `depthwise`, `lossguide`
 - * `depthwise`: split at nodes closest to the root.
 - * `lossguide`: split at nodes with highest loss change.
- `max_leaves` [default=0]
 - Maximum number of nodes to be added. Not used by `exact` tree method.
- `max_bin`, [default=256]
 - Only used if `tree_method` is set to `hist` or `approx`.
 - Maximum number of discrete bins to bucket continuous features.
 - Increasing this number improves the optimality of splits at the cost of higher computation time.
- `num_parallel_tree`, [default=1]
 - Number of parallel trees constructed during each iteration. This option is used to support boosted random forest.
- `monotone_constraints`
 - Constraint of variable monotonicity. See [Monotonic Constraints](#) for more information.
- `interaction_constraints`
 - Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nest list, e.g. `[[0, 1], [2, 3, 4]]`, where each inner list is a group of indices of features that are allowed to interact with each other. See [Feature Interaction Constraints](#) for more information.
- `multi_strategy`, [default = `one_output_per_tree`]

New in version 2.0.0.

Note: This parameter is working-in-progress.

- The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.
 - * `one_output_per_tree`: One model for each target.
 - * `multi_output_tree`: Use multi-target trees.
- `max_cached_hist_node`, [default = 65536]

Maximum number of cached nodes for CPU histogram.

New in version 2.0.0.

 - For most of the cases this parameter should not be set except for growing deep trees on CPU.

Parameters for Categorical Feature

These parameters are only used for training with categorical data. See [Categorical Data](#) for more information.

Note: These parameters are experimental. `exact` tree method is not yet supported.

- `max_cat_to_onehot`

New in version 1.6.0.

- A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes.

- `max_cat_threshold`

New in version 1.7.0.

- Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting.

Additional parameters for Dart Booster (`booster=dart`)

Note: Using `predict()` with DART booster

If the booster object is DART type, `predict()` will perform dropouts, i.e. only some of the trees will be evaluated. This will produce incorrect results if data is not the training data. To obtain correct results on test sets, set `iteration_range` to a nonzero value, e.g.

```
preds = bst.predict(dtest, iteration_range=(0, num_round))
```

- `sample_type` [default= `uniform`]

- Type of sampling algorithm.
 - * `uniform`: dropped trees are selected uniformly.
 - * `weighted`: dropped trees are selected in proportion to weight.

- `normalize_type` [default= `tree`]

- Type of normalization algorithm.
 - * `tree`: new trees have the same weight of each of dropped trees.
 - Weight of new trees are $1 / (k + \text{learning_rate})$.
 - Dropped trees are scaled by a factor of $k / (k + \text{learning_rate})$.
 - * `forest`: new trees have the same weight of sum of dropped trees (forest).
 - Weight of new trees are $1 / (1 + \text{learning_rate})$.
 - Dropped trees are scaled by a factor of $1 / (1 + \text{learning_rate})$.

- `rate_drop` [default=0.0]

- Dropout rate (a fraction of previous trees to drop during the dropout).
- range: [0.0, 1.0]

- `one_drop` [default=0]
 - When this flag is enabled, at least one tree is always dropped during the dropout (allows Binomial-plus-one or epsilon-dropout from the original DART paper).
- `skip_drop` [default=0.0]
 - Probability of skipping the dropout procedure during a boosting iteration.
 - * If a dropout is skipped, new trees are added in the same manner as `gbtree`.
 - * Note that non-zero `skip_drop` has higher priority than `rate_drop` or `one_drop`.
 - range: [0.0, 1.0]

Parameters for Linear Booster (`booster=gblinear`)

- `lambda` [default=0, alias: `reg_lambda`]
 - L2 regularization term on weights. Increasing this value will make model more conservative. Normalised to number of training examples.
- `alpha` [default=0, alias: `reg_alpha`]
 - L1 regularization term on weights. Increasing this value will make model more conservative. Normalised to number of training examples.
- `updater` [default= `shotgun`]
 - Choice of algorithm to fit linear model
 - * `shotgun`: Parallel coordinate descent algorithm based on shotgun algorithm. Uses ‘hogwild’ parallelism and therefore produces a nondeterministic solution on each run.
 - * `coord_descent`: Ordinary coordinate descent algorithm. Also multithreaded but still produces a deterministic solution. When the `device` parameter is set to `cuda` or `gpu`, a GPU variant would be used.
- `feature_selector` [default= `cyclic`]
 - Feature selection and ordering method
 - * `cyclic`: Deterministic selection by cycling through features one at a time.
 - * `shuffle`: Similar to `cyclic` but with random feature shuffling prior to each update.
 - * `random`: A random (with replacement) coordinate selector.
 - * `greedy`: Select coordinate with the greatest gradient magnitude. It has $O(\text{num_feature}^2)$ complexity. It is fully deterministic. It allows restricting the selection to `top_k` features per group with the largest magnitude of univariate weight change, by setting the `top_k` parameter. Doing so would reduce the complexity to $O(\text{num_feature} * \text{top_k})$.
 - * `thrifty`: Thrifty, approximately-greedy feature selector. Prior to cyclic updates, reorders features in descending magnitude of their univariate weight changes. This operation is multithreaded and is a linear complexity approximation of the quadratic greedy selection. It allows restricting the selection to `top_k` features per group with the largest magnitude of univariate weight change, by setting the `top_k` parameter.
- `top_k` [default=0]
 - The number of top features to select in `greedy` and `thrifty` feature selector. The value of 0 means using all the features.

1.7.3 Learning Task Parameters

Specify the learning task and the corresponding learning objective. The objective options are below:

- **objective** [default=reg:squarederror]
 - **reg:squarederror**: regression with squared loss.
 - **reg:squaredlogerror**: regression with squared log loss $\frac{1}{2}[\log(pred + 1) - \log(label + 1)]^2$. All input labels are required to be greater than -1. Also, see metric `rmsle` for possible issue with this objective.
 - **reg:logistic**: logistic regression, output probability
 - **reg:pseudohubererror**: regression with Pseudo Huber loss, a twice differentiable alternative to absolute loss.
 - **reg:absoluteerror**: Regression with L1 error. When tree model is used, leaf value is refreshed after tree construction. If used in distributed training, the leaf value is calculated as the mean value from all workers, which is not guaranteed to be optimal.
New in version 1.7.0.
 - **reg:quantileerror**: Quantile loss, also known as `pinball` loss. See later sections for its parameter and [Quantile Regression](#) for a worked example.
New in version 2.0.0.
 - **binary:logistic**: logistic regression for binary classification, output probability
 - **binary:logitraw**: logistic regression for binary classification, output score before logistic transformation
 - **binary:hinge**: hinge loss for binary classification. This makes predictions of 0 or 1, rather than producing probabilities.
 - **count:poisson**: Poisson regression for count data, output mean of Poisson distribution.
* `max_delta_step` is set to 0.7 by default in Poisson regression (used to safeguard optimization)
 - **survival:cox**: Cox regression for right censored survival time data (negative values are considered right censored). Note that predictions are returned on the hazard ratio scale (i.e., as $HR = \exp(\text{marginal_prediction})$ in the proportional hazard function $h(t) = h_0(t) * HR$).
 - **survival:aft**: Accelerated failure time model for censored survival time data. See [Survival Analysis with Accelerated Failure Time](#) for details.
 - **multi:softmax**: set XGBoost to do multiclass classification using the softmax objective, you also need to set `num_class`(number of classes)
 - **multi:softprob**: same as softmax, but output a vector of `ndata * nclass`, which can be further reshaped to `ndata * nclass` matrix. The result contains predicted probability of each data point belonging to each class.
 - **rank:ndcg**: Use LambdaMART to perform pair-wise ranking where [Normalized Discounted Cumulative Gain \(NDCG\)](#) is maximized. This objective supports position debiasing for click data.
 - **rank:map**: Use LambdaMART to perform pair-wise ranking where [Mean Average Precision \(MAP\)](#) is maximized
 - **rank:pairwise**: Use LambdaRank to perform pair-wise ranking using the *ranknet* objective.
 - **reg:gamma**: gamma regression with log-link. Output is a mean of gamma distribution. It might be useful, e.g., for modeling insurance claims severity, or for any outcome that might be [gamma-distributed](#).
 - **reg:tweedie**: Tweedie regression with log-link. It might be useful, e.g., for modeling total loss in insurance, or for any outcome that might be [Tweedie-distributed](#).

- `base_score`
 - The initial prediction score of all instances, global bias
 - The parameter is automatically estimated for selected objectives before training. To disable the estimation, specify a real number argument.
 - For sufficient number of iterations, changing this value will not have too much effect.
- `eval_metric` [default according to objective]
 - Evaluation metrics for validation data, a default metric will be assigned according to objective (rmse for regression, and logloss for classification, *mean average precision* for `rank:map`, etc.)
 - User can add multiple evaluation metrics. Python users: remember to pass the metrics in as list of parameters pairs instead of map, so that latter `eval_metric` won't override previous ones
 - The choices are listed below:
 - * `rmse`: root mean square error
 - * `rmsle`: root mean square log error: $\sqrt{\frac{1}{N}[\log(pred + 1) - \log(label + 1)]^2}$. Default metric of `reg:squaredlogerror` objective. This metric reduces errors generated by outliers in dataset. But because `log` function is employed, `rmsle` might output `nan` when prediction value is less than -1. See `reg:squaredlogerror` for other requirements.
 - * `mae`: mean absolute error
 - * `mape`: mean absolute percentage error
 - * `mphe`: mean Pseudo Huber error. Default metric of `reg:pseudohubererror` objective.
 - * `logloss`: negative log-likelihood
 - * `error`: Binary classification error rate. It is calculated as `#(wrong cases) / #(all cases)`. For the predictions, the evaluation will regard the instances with prediction value larger than 0.5 as positive instances, and the others as negative instances.
 - * `error@t`: a different than 0.5 binary classification threshold value could be specified by providing a numerical value through 't'.
 - * `merror`: Multiclass classification error rate. It is calculated as `#(wrong cases) / #(all cases)`.
 - * `mlogloss`: Multiclass logloss.
 - * `auc`: Receiver Operating Characteristic Area under the Curve. Available for classification and learning-to-rank tasks.
 - When used with binary classification, the objective should be `binary:logistic` or similar functions that work on probability.
 - When used with multi-class classification, objective should be `multi:softprob` instead of `multi:softmax`, as the latter doesn't output probability. Also the AUC is calculated by 1-vs-rest with reference class weighted by class prevalence.
 - When used with LTR task, the AUC is computed by comparing pairs of documents to count correctly sorted pairs. This corresponds to pairwise learning to rank. The implementation has some issues with average AUC around groups and distributed workers not being well-defined.
 - On a single machine the AUC calculation is exact. In a distributed environment the AUC is a weighted average over the AUC of training rows on each node - therefore, distributed AUC is an approximation sensitive to the distribution of data across workers. Use another metric in distributed environments if precision and reproducibility are important.

- When input dataset contains only negative or positive samples, the output is *NaN*. The behavior is implementation defined, for instance, `scikit-learn` returns 0.5 instead.

* **aucpr**: [Area under the PR curve](#). Available for classification and learning-to-rank tasks.

After XGBoost 1.6, both of the requirements and restrictions for using **aucpr** in classification problem are similar to **auc**. For ranking task, only binary relevance label $y \in [0, 1]$ is supported. Different from **map** (mean average precision), **aucpr** calculates the *interpolated* area under precision recall curve using continuous interpolation.

* **pre**: Precision at k . Supports only learning to rank task.

* **ndcg**: [Normalized Discounted Cumulative Gain](#)

* **map**: [Mean Average Precision](#)

The *average precision* is defined as:

$$AP@l = \frac{1}{\min(l, N)} \sum_{k=1}^l P@k \cdot I_{(k)}$$

where $I_{(k)}$ is an indicator function that equals to 1 when the document at k is relevant and 0 otherwise. The $P@k$ is the precision at k , and N is the total number of relevant documents. Lastly, the *mean average precision* is defined as the weighted average across all queries.

* **ndcg@n**, **map@n**, **pre@n**: n can be assigned as an integer to cut off the top positions in the lists for evaluation.

* **ndcg-**, **map-**, **ndcg@n-**, **map@n-**: In XGBoost, the NDCG and MAP evaluate the score of a list without any positive samples as 1. By appending “-” to the evaluation metric name, we can ask XGBoost to evaluate these scores as 0 to be consistent under some conditions.

* **poisson-nloglik**: negative log-likelihood for Poisson regression

* **gamma-nloglik**: negative log-likelihood for gamma regression

* **cox-nloglik**: negative partial log-likelihood for Cox proportional hazards regression

* **gamma-deviance**: residual deviance for gamma regression

* **tweedie-nloglik**: negative log-likelihood for Tweedie regression (at a specified value of the `tweedie_variance_power` parameter)

* **aft-nloglik**: Negative log likelihood of Accelerated Failure Time model. See [Survival Analysis with Accelerated Failure Time](#) for details.

* **interval-regression-accuracy**: Fraction of data points whose predicted labels fall in the interval-censored labels. Only applicable for interval-censored data. See [Survival Analysis with Accelerated Failure Time](#) for details.

- **seed** [default=0]
 - Random number seed. This parameter is ignored in R package, use `set.seed()` instead.
- **seed_per_iteration** [default= false]
 - Seed PRNG deterministically via iterator number.

Parameters for Tweedie Regression (objective=reg:tweedie)

- `tweedie_variance_power` [default=1.5]
 - Parameter that controls the variance of the Tweedie distribution $\text{var}(y) \sim E(y)^{\text{tweedie_variance_power}}$
 - range: (1,2)
 - Set closer to 2 to shift towards a gamma distribution
 - Set closer to 1 to shift towards a Poisson distribution.

Parameter for using Pseudo-Huber (reg:pseudohubererror)

- `huber_slope` : A parameter used for Pseudo-Huber loss to define the δ term. [default = 1.0]

Parameter for using Quantile Loss (reg:quantileerror)

- `quantile_alpha`: A scala or a list of targeted quantiles.
New in version 2.0.0.

Parameter for using AFT Survival Loss (survival:aft) and Negative Log Likelihood of AFT metric (aft-nloglik)

- `aft_loss_distribution`: Probability Density Function, normal, logistic, or extreme.

Parameters for learning to rank (rank:ndcg, rank:map, rank:pairwise)

These are parameters specific to learning to rank task. See *Learning to Rank* for an in-depth explanation.

- `lambdarank_pair_method` [default = mean]
How to construct pairs for pair-wise learning.
 - `mean`: Sample `lambdarank_num_pair_per_sample` pairs for each document in the query list.
 - `topk`: Focus on top-`lambdarank_num_pair_per_sample` documents. Construct $|query|$ pairs for each document at the top-`lambdarank_num_pair_per_sample` ranked by the model.
- `lambdarank_num_pair_per_sample` [range = $[1, \infty]$]
It specifies the number of pairs sampled for each document when pair method is `mean`, or the truncation level for queries when the pair method is `topk`. For example, to train with `ndcg@6`, set `lambdarank_num_pair_per_sample` to 6 and `lambdarank_pair_method` to `topk`.
- `lambdarank_unbiased` [default = false]
Specify whether do we need to debias input click data.
- `lambdarank_bias_norm` [default = 2.0]
 L_p normalization for position debiasing, default is L_2 . Only relevant when `lambdarank_unbiased` is set to true.

- `ndcg_exp_gain` [default = `true`]

Whether we should use exponential gain function for NDCG. There are two forms of gain function for NDCG, one is using relevance value directly while the other is using $2^{rel} - 1$ to emphasize on retrieving relevant documents. When `ndcg_exp_gain` is true (the default), relevance degree cannot be greater than 31.

1.7.4 Command Line Parameters

The following parameters are only used in the console version of XGBoost

- `num_round`
 - The number of rounds for boosting
- `data`
 - The path of training data
- `test:data`
 - The path of test data to do prediction
- `save_period` [default=0]
 - The period to save the model. Setting `save_period=10` means that for every 10 rounds XGBoost will save the model. Setting it to 0 means not saving any model during the training.
- `task` [default= `train`] options: `train`, `pred`, `eval`, `dump`
 - `train`: training using data
 - `pred`: making prediction for test:data
 - `eval`: for evaluating statistics specified by `eval[name]=filename`
 - `dump`: for dump the learned model into text format
- `model_in` [default=NULL]
 - Path to input model, needed for `test`, `eval`, `dump` tasks. If it is specified in training, XGBoost will continue training from the input model.
- `model_out` [default=NULL]
 - Path to output model after training finishes. If not specified, XGBoost will output files with such names as `0003.model` where `0003` is number of boosting rounds.
- `model_dir` [default= `models/`]
 - The output directory of the saved models during training
- `fmap`
 - Feature map, used for dumping model
- `dump_format` [default= `text`] options: `text`, `json`
 - Format of model dump file
- `name_dump` [default= `dump.txt`]
 - Name of model dump file
- `name_pred` [default= `pred.txt`]
 - Name of prediction file, used in `pred` mode
- `pred_margin` [default=0]

- Predict margin instead of transformed probability

1.8 Prediction

There are a number of prediction functions in XGBoost with various parameters. This document attempts to clarify some of confusions around prediction with a focus on the Python binding, R package is similar when `strict_shape` is specified (see below).

1.8.1 Prediction Options

There are a number of different prediction options for the `xgboost.Booster.predict()` method, ranging from `pred_contribs` to `pred_leaf`. The output shape depends on types of prediction. Also for multi-class classification problem, XGBoost builds one tree for each class and the trees for each class are called a “group” of trees, so output dimension may change due to used model. After 1.4 release, we added a new parameter called `strict_shape`, one can set it to `True` to indicate a more restricted output is desired. Assuming you are using `xgboost.Booster`, here is a list of possible returns:

- When using normal prediction with `strict_shape` set to `True`:

Output is a 2-dim array with first dimension as rows and second as groups. For regression/survival/ranking/binary classification this is equivalent to a column vector with `shape[1] == 1`. But for multi-class with `multi:softprob` the number of columns equals to number of classes. If `strict_shape` is set to `False` then XGBoost might output 1 or 2 dim array.

- When using `output_margin` to avoid transformation and `strict_shape` is set to `True`:

Similar to the previous case, output is a 2-dim array, except for that `multi:softmax` has equivalent output shape of `multi:softprob` due to dropped transformation. If `strict_shape` is set to `False` then output can have 1 or 2 dim depending on used model.

- When using `pred_contribs` with `strict_shape` set to `True`:

Output is a 3-dim array, with `(rows, groups, columns + 1)` as shape. Whether `approx_contribs` is used does not change the output shape. If the `strict_shape` parameter is not set, it can be a 2 or 3 dimension array depending on whether multi-class model is being used.

- When using `pred_interactions` with `strict_shape` set to `True`:

Output is a 4-dim array, with `(rows, groups, columns + 1, columns + 1)` as shape. Like the predict contribution case, whether `approx_contribs` is used does not change the output shape. If `strict_shape` is set to `False`, it can have 3 or 4 dims depending on the underlying model.

- When using `pred_leaf` with `strict_shape` set to `True`:

Output is a 4-dim array with `(n_samples, n_iterations, n_classes, n_trees_in_forest)` as shape. `n_trees_in_forest` is specified by the `numb_parallel_tree` during training. When `strict_shape` is set to `False`, output is a 2-dim array with last 3 dims concatenated into 1. Also the last dimension is dropped if it equals to 1. When using `apply` method in scikit learn interface, this is set to `False` by default.

For R package, when `strict_shape` is specified, an array is returned, with the same value as Python except R array is column-major while Python numpy array is row-major, so all the dimensions are reversed. For example, for a Python `predict_leaf` output obtained by having `strict_shape=True` has 4 dimensions: `(n_samples, n_iterations, n_classes, n_trees_in_forest)`, while R with `strict_shape=TRUE` outputs `(n_trees_in_forest, n_classes, n_iterations, n_samples)`.

Other than these prediction types, there’s also a parameter called `iteration_range`, which is similar to model slicing. But instead of actually splitting up the model into multiple stacks, it simply returns the prediction formed by the trees

within range. Number of trees created in each iteration equals to $trees_i = num_class \times num_parallel_tree$. So if you are training a boosted random forest with size of 4, on the 3-class classification dataset, and want to use the first 2 iterations of trees for prediction, you need to provide `iteration_range=(0, 2)`. Then the first $2 \times 3 \times 4$ trees will be used in this prediction.

1.8.2 Early Stopping

When a model is trained with early stopping, there is an inconsistent behavior between native Python interface and sklearn/R interfaces. By default on R and sklearn interfaces, the `best_iteration` is automatically used so prediction comes from the best model. But with the native Python interface `xgboost.Booster.predict()` and `xgboost.Booster.inplace_predict()` uses the full model. Users can use `best_iteration` attribute with `iteration_range` parameter to achieve the same behavior. Also the `save_best` parameter from `xgboost.callback.EarlyStopping` might be useful.

1.8.3 Base Margin

There's a training parameter in XGBoost called `base_score`, and a meta data for `DMatrix` called `base_margin` (which can be set in `fit` method if you are using scikit-learn interface). They specifies the global bias for boosted model. If the latter is supplied then former is ignored. `base_margin` can be used to train XGBoost model based on other models. See demos on boosting from predictions.

1.8.4 Staged Prediction

Using the native interface with `DMatrix`, prediction can be staged (or cached). For example, one can first predict on the first 4 trees then run prediction on 8 trees. After running the first prediction, result from first 4 trees are cached so when you run the prediction with 8 trees XGBoost can reuse the result from previous prediction. The cache expires automatically upon next prediction, train or evaluation if the cached `DMatrix` object is expired (like going out of scope and being collected by garbage collector in your language environment).

1.8.5 In-place Prediction

Traditionally XGBoost accepts only `DMatrix` for prediction, with wrappers like scikit-learn interface the construction happens internally. We added support for in-place predict to bypass the construction of `DMatrix`, which is slow and memory consuming. The new predict function has limited features but is often sufficient for simple inference tasks. It accepts some commonly found data types in Python like `numpy.ndarray`, `scipy.sparse.csr_matrix` and `cudf.DataFrame` instead of `xgboost.DMatrix`. You can call `xgboost.Booster.inplace_predict()` to use it. Be aware that the output of in-place prediction depends on input data type, when input is on GPU data output is `cupy.ndarray`, otherwise a `numpy.ndarray` is returned.

1.8.6 Thread Safety

After 1.4 release, all prediction functions including normal `predict` with various parameters like shap value computation and `inplace_predict` are thread safe when underlying booster is `gbtree` or `dart`, which means as long as tree model is used, prediction itself should thread safe. But the safety is only guaranteed with prediction. If one tries to train a model in one thread and provide prediction at the other using the same model the behaviour is undefined. This happens easier than one might expect, for instance we might accidentally call `clf.set_params()` inside a predict function:

```
def predict_fn(clf: xgb.XGBClassifier, X):
    X = preprocess(X)
    clf.set_params(n_jobs=1)  # NOT safe!
    return clf.predict_proba(X, iteration_range=(0, 10))

with ThreadPoolExecutor(max_workers=10) as e:
    e.submit(predict_fn, ...)
```

1.9 Tree Methods

For training boosted tree models, there are 2 parameters used for choosing algorithms, namely `updater` and `tree_method`. XGBoost has 3 builtin tree methods, namely `exact`, `approx` and `hist`. Along with these tree methods, there are also some free standing updaters including `refresh`, `prune` and `sync`. The parameter `updater` is more primitive than `tree_method` as the latter is just a pre-configuration of the former. The difference is mostly due to historical reasons that each updater requires some specific configurations and might has missing features. As we are moving forward, the gap between them is becoming more and more irrelevant. We will collectively document them under tree methods.

1.9.1 Exact Solution

Exact means XGBoost considers all candidates from data for tree splitting, but underlying the objective is still interpreted as a Taylor expansion.

1. `exact`: The vanilla gradient boosting tree algorithm described in [reference paper](#). During split-finding, it iterates over all entries of input data. It's more accurate (among other greedy methods) but computationally slower in compared to other tree methods. Further more, its feature set is limited. Features like distributed training and external memory that require approximated quantiles are not supported. This tree method can be used with the parameter `tree_method` set to `exact`.

1.9.2 Approximated Solutions

As `exact` tree method is slow in computation performance and difficult to scale, we often employ approximated training algorithms. These algorithms build a gradient histogram for each node and iterate through the histogram instead of real dataset. Here we introduce the implementations in XGBoost.

1. `approx` tree method: An approximation tree method described in [reference paper](#). It runs sketching before building each tree using all the rows (rows belonging to the root). Hessian is used as weights during sketch. The algorithm can be accessed by setting `tree_method` to `approx`.
2. `hist` tree method: An approximation tree method used in LightGBM with slight differences in implementation. It runs sketching before training using only user provided weights instead of hessian. The subsequent per-node histogram is built upon this global sketch. This is the fastest algorithm as it runs sketching only once. The algorithm can be accessed by setting `tree_method` to `hist`.

1.9.3 Implications

Some objectives like `reg:squarederror` have constant hessian. In this case, the `hist` should be preferred as weighted sketching doesn't make sense with constant weights. When using non-constant hessian objectives, sometimes `approx` yields better accuracy, but with slower computation performance. Most of the time using `hist` with higher `max_bin` can achieve similar or even superior accuracy while maintaining good performance. However, as xgboost is largely driven by community effort, the actual implementations have some differences than pure math description. Result might be slightly different than expectation, which we are currently trying to overcome.

1.9.4 Other Updaters

1. **Prune:** It prunes the existing trees. `prune` is usually used as part of other tree methods. To use pruner independently, one needs to set the process type to update by: `{"process_type": "update", "updater": "prune"}`. With this set of parameters, during training, XGBoost will prune the existing trees according to 2 parameters `min_split_loss` (`gamma`) and `max_depth`.
2. **Refresh:** Refresh the statistic of built trees on a new training dataset. Like the pruner, To use refresh independently, one needs to set the process type to update: `{"process_type": "update", "updater": "refresh"}`. During training, the updater will change statistics like `cover` and `weight` according to the new training dataset. When `refresh_leaf` is also set to true (default), XGBoost will update the leaf value according to the new leaf weight, but the tree structure (split condition) itself doesn't change.

There are examples on both training continuation (adding new trees) and using update process on `demo/guide-python`. Also checkout the `process_type` parameter in [XGBoost Parameters](#).

3. **Sync:** Synchronize the tree among workers when running distributed training.

1.9.5 Removed Updaters

3 Updaters were removed during development due to maintainability. We describe them here solely for the interest of documentation.

1. **Distributed colmaker**, which was a distributed version of exact tree method. It required specialization for column based splitting strategy and a different prediction procedure. As the exact tree method is slow by itself and scaling is even less efficient, we removed it entirely.
2. **skmaker**. Per-node weighted sketching employed by `grow_local_histmaker` is slow, the `skmaker` was unmaintained and seems to be a workaround trying to eliminate the histogram creation step and uses sketching values directly during split evaluation. It was never tested and contained some unknown bugs, we decided to remove it and focus our resources on more promising algorithms instead. For accuracy, most of the time `approx` and `hist` are enough with some parameters tuning, so removing them don't have any real practical impact.
3. **grow_local_histmaker** updater: An approximation tree method described in [reference paper](#). This updater was rarely used in practice so it was still an updater rather than tree method. During split finding, it first runs a weighted GK sketching for data points belong to current node to find split candidates, using hessian as weights. The histogram is built upon this per-node sketch. It was faster than `exact` in some applications, but still slow in computation. It was removed because it depended on Rabbit's customized reduction function that handles all the data structure that can be serialized/deserialized into fixed size buffer, which is not directly supported by NCCL or federated learning gRPC, making it hard to refactor into a common allreducer interface.

1.9.6 Feature Matrix

Following table summarizes some differences in supported features between 4 tree methods, *T* means supported while *F* means unsupported.

	Exact	Approx	Approx (GPU)	Hist	Hist (GPU)
grow_policy	Depth-wise	depth-wise/lossguide	depthwise/lossguide	depth-wise/lossguide	depthwise/lossguide
max_leaves	F	T	T	T	T
sampling method	uniform	uniform	gradient_based/uniform	uniform	gradient_based/uniform
categorical data	F	T	T	T	T
External memory	F	T	P	T	P
Distributed	F	T	T	T	T

Features/parameters that are not mentioned here are universally supported for all 3 tree methods (for instance, column sampling and constraints). The *P* in external memory means special handling. Please note that both categorical data and external memory are experimental.

1.10 XGBoost Python Package

This page contains links to all the python related documents on python package. To install the package, checkout [Installation Guide](#).

1.10.1 Contents

Python Package Introduction

This document gives a basic walkthrough of the xgboost package for Python. The Python package is consisted of 3 different interfaces, including native interface, scikit-learn interface and dask interface. For introduction to dask interface please see [Distributed XGBoost with Dask](#).

List of other Helpful Links

- [XGBoost Python Feature Walkthrough](#)
- [Python API Reference](#)

Contents

- [Install XGBoost](#)
- [Data Interface](#)
 - [Supported data structures for various XGBoost functions](#)
 - * [Markers](#)
 - * [Table Header](#)
 - * [Support Matrix](#)

- [Setting Parameters](#)
- [Training](#)
- [Early Stopping](#)
- [Prediction](#)
- [Plotting](#)
- [Scikit-Learn interface](#)

Install XGBoost

To install XGBoost, follow instructions in [Installation Guide](#).

To verify your installation, run the following in Python:

```
import xgboost as xgb
```

Data Interface

The XGBoost Python module is able to load data from many different types of data format including both CPU and GPU data structures. For a complete list of supported data types, please reference the [Supported data structures for various XGBoost functions](#). For a detailed description of text input formats, please visit [Text Input Format of DMatrix](#).

The input data is stored in a *DMatrix* object. For the sklearn estimator interface, a *DMatrix* or a *QuantileDMatrix* is created depending on the chosen algorithm and the input, see the sklearn API reference for details. We will illustrate some of the basic input types with the *DMatrix* here.

- To load a NumPy array into *DMatrix*:

```
data = np.random.rand(5, 10) # 5 entities, each contains 10 features
label = np.random.randint(2, size=5) # binary target
dtrain = xgb.DMatrix(data, label=label)
```

- To load a `scipy.sparse` array into *DMatrix*:

```
csr = scipy.sparse.csr_matrix((dat, (row, col)))
dtrain = xgb.DMatrix(csr)
```

- To load a Pandas data frame into *DMatrix*:

```
data = pandas.DataFrame(np.arange(12).reshape((4,3)), columns=['a', 'b', 'c'])
label = pandas.DataFrame(np.random.randint(2, size=4))
dtrain = xgb.DMatrix(data, label=label)
```

- Saving *DMatrix* into a XGBoost binary file will make loading faster:

```
dtrain = xgb.DMatrix('train.svm.txt')
dtrain.save_binary('train.buffer')
```

- Missing values can be replaced by a default value in the *DMatrix* constructor:

```
dtrain = xgb.DMatrix(data, label=label, missing=np.NaN)
```

- Weights can be set when needed:

```
w = np.random.rand(5, 1)
dtrain = xgb.DMatrix(data, label=label, missing=np.NaN, weight=w)
```

When performing ranking tasks, the number of weights should be equal to number of groups.

- To load a LIBSVM text file or a XGBoost binary file into *DMatrix*:

```
dtrain = xgb.DMatrix('train.svm.txt')
dtest = xgb.DMatrix('test.svm.buffer')
```

The parser in XGBoost has limited functionality. When using Python interface, it's recommended to use `sklearn.load_svmlight_file` or other similar utilities than XGBoost's builtin parser.

- To load a CSV file into *DMatrix*:

```
# label_column specifies the index of the column containing the true label
dtrain = xgb.DMatrix('train.csv?format=csv&label_column=0')
dtest = xgb.DMatrix('test.csv?format=csv&label_column=0')
```

The parser in XGBoost has limited functionality. When using Python interface, it's recommended to use `pandas.read_csv` or other similar utilities than XGBoost's builtin parser.

Supported data structures for various XGBoost functions

Markers

- T: Supported.
- F: Not supported.
- NE: Invalid type for the use case. For instance, *pd.Series* can not be multi-target label.
- NPA: Support with the help of numpy array.
- CPA: Support with the help of cupy array.
- SciCSR: Support with the help of scipy sparse CSR. The conversion to scipy CSR may or may not be possible. Raise a type error if conversion fails.
- FF: We can look forward to having its support in recent future if requested.
- empty: To be filled in.

Table Header

- X means predictor matrix.
- Meta info: label, weight, etc.
- Multi Label: 2-dim label for multi-target.
- Others: Anything else that we don't list here explicitly including formats like *lil*, *dia*, *bsr*. XGBoost will try to convert it into scipy csr.

Support Matrix

Name	DMatrix X	QuantileDMatrix X	Sklearn X	Meta Info	Inplace predic- tion	Multi La- bel
numpy.ndarray	T	T	T	T	T	T
scipy.sparse.csr	T	T	T	NE	T	F
scipy.sparse.csc	T	F	T	NE	F	F
scipy.sparse.coo	SciCSR	F	SciCSR	NE	F	F
uri	T	F	F	F	NE	F
list	NPA	NPA	NPA	NPA	NPA	T
tuple	NPA	NPA	NPA	NPA	NPA	T
pandas.DataFrame	NPA	NPA	NPA	NPA	NPA	NPA
pandas.Series	NPA	NPA	NPA	NPA	NPA	NE
cudf.DataFrame	T	T	T	T	T	T
cudf.Series	T	T	T	T	FF	NE
cupy.ndarray	T	T	T	T	T	T
dlpack	CPA	CPA		CPA	FF	FF
datatable.Frame	T	FF		NPA	FF	
datatable.Table	T	FF		NPA	FF	
modin.DataFrame	NPA	FF	NPA	NPA	FF	
modin.Series	NPA	FF	NPA	NPA	FF	
pyarrow.Table	T	F		NPA	FF	
pyarrow.dataset.Dataset	T	F			F	
__array__	NPA	F	NPA	NPA	H	
Others	SciCSR	F		F	F	

Setting Parameters

XGBoost can use either a list of pairs or a dictionary to set *parameters*. For instance:

- Booster parameters

```
param = {'max_depth': 2, 'eta': 1, 'objective': 'binary:logistic'}
param['nthread'] = 4
param['eval_metric'] = 'auc'
```

- You can also specify multiple eval metrics:

```
param['eval_metric'] = ['auc', 'ams@0']
```

(continues on next page)

(continued from previous page)

```
# alternatively:
# plst = param.items()
# plst += [('eval_metric', 'ams@0001')]
```

- Specify validations set to watch performance

```
evallist = [(dtrain, 'train'), (dtest, 'eval')]
```

Training

Training a model requires a parameter list and data set.

```
num_round = 10
bst = xgb.train(param, dtrain, num_round, evallist)
```

After training, the model can be saved.

```
bst.save_model('0001.model')
```

The model and its feature map can also be dumped to a text file.

```
# dump model
bst.dump_model('dump.raw.txt')
# dump model with feature map
bst.dump_model('dump.raw.txt', 'featmap.txt')
```

A saved model can be loaded as follows:

```
bst = xgb.Booster({'nthread': 4}) # init model
bst.load_model('model.bin') # load data
```

Methods including *update* and *boost* from *xgboost.Booster* are designed for internal usage only. The wrapper function *xgboost.train* does some pre-configuration including setting up caches and some other parameters.

Early Stopping

If you have a validation set, you can use early stopping to find the optimal number of boosting rounds. Early stopping requires at least one set in *evals*. If there's more than one, it will use the last.

```
train(..., evals=evals, early_stopping_rounds=10)
```

The model will train until the validation score stops improving. Validation error needs to decrease at least every *early_stopping_rounds* to continue training.

If early stopping occurs, the model will have two additional fields: *bst.best_score*, *bst.best_iteration*. Note that *xgboost.train()* will return a model from the last iteration, not the best one.

This works with both metrics to minimize (RMSE, log loss, etc.) and to maximize (MAP, NDCG, AUC). Note that if you specify more than one evaluation metric the last one in *param['eval_metric']* is used for early stopping.

Prediction

A model that has been trained or loaded can perform predictions on data sets.

```
# 7 entities, each contains 10 features
data = np.random.rand(7, 10)
dtest = xgb.DMatrix(data)
ypred = bst.predict(dtest)
```

If early stopping is enabled during training, you can get predictions from the best iteration with `bst.best_iteration`:

```
ypred = bst.predict(dtest, iteration_range=(0, bst.best_iteration + 1))
```

Plotting

You can use plotting module to plot importance and output tree.

To plot importance, use `xgboost.plot_importance()`. This function requires `matplotlib` to be installed.

```
xgb.plot_importance(bst)
```

To plot the output tree via `matplotlib`, use `xgboost.plot_tree()`, specifying the ordinal number of the target tree. This function requires `graphviz` and `matplotlib`.

```
xgb.plot_tree(bst, num_trees=2)
```

When you use IPython, you can use the `xgboost.to_graphviz()` function, which converts the target tree to a `graphviz` instance. The `graphviz` instance is automatically rendered in IPython.

```
xgb.to_graphviz(bst, num_trees=2)
```

Scikit-Learn interface

XGBoost provides an easy to use scikit-learn interface for some pre-defined models including regression, classification and ranking. See *Using the Scikit-Learn Estimator Interface* for more info.

```
# Use "hist" for training the model.
reg = xgb.XGBRegressor(tree_method="hist", device="cuda")
# Fit the model using predictor X and response y.
reg.fit(X, y)
# Save model into JSON format.
reg.save_model("regressor.json")
```

User can still access the underlying booster model when needed:

```
booster: xgb.Booster = reg.get_booster()
```

Using the Scikit-Learn Estimator Interface

Contents

- *Overview*
- *Early Stopping*
- *Obtaining the native booster object*
- *Prediction*
- *Number of parallel threads*

Overview

In addition to the native interface, XGBoost features a sklearn estimator interface that conforms to [sklearn estimator guideline](#). It supports regression, classification, and learning to rank. Survival training for the sklearn estimator interface is still working in progress.

You can find some quick start examples at [Collection of examples for using sklearn interface](#). The main advantage of using sklearn interface is that it works with most of the utilities provided by sklearn like [sklearn.model_selection.cross_validate\(\)](#). Also, many other libraries recognize the sklearn estimator interface thanks to its popularity.

With the sklearn estimator interface, we can train a classification model with only a couple lines of Python code. Here's an example for training a classification model:

```
from sklearn.datasets import load_breast_cancer
from sklearn.model_selection import train_test_split

import xgboost as xgb

X, y = load_breast_cancer(return_X_y=True)
X_train, X_test, y_train, y_test = train_test_split(X, y, stratify=y, random_state=94)

# Use "hist" for constructing the trees, with early stopping enabled.
clf = xgb.XGBClassifier(tree_method="hist", early_stopping_rounds=2)
# Fit the model, test sets are used for early stopping.
clf.fit(X_train, y_train, eval_set=[(X_test, y_test)])
# Save model into JSON format.
clf.save_model("clf.json")
```

The `tree_method` parameter specifies the method to use for constructing the trees, and the `early_stopping_rounds` parameter enables early stopping. Early stopping can help prevent overfitting and save time during training.

Early Stopping

As demonstrated in the previous example, early stopping can be enabled by the parameter `early_stopping_rounds`. Alternatively, there's a callback function that can be used `xgboost.callback.EarlyStopping` to specify more details about the behavior of early stopping, including whether XGBoost should return the best model instead of the full stack of trees:

```
early_stop = xgb.callback.EarlyStopping(
    rounds=2, metric_name='logloss', data_name='Validation_0', save_best=True
)
clf = xgb.XGBClassifier(tree_method="hist", callbacks=[early_stop])
clf.fit(X_train, y_train, eval_set=[(X_test, y_test)])
```

At present, XGBoost doesn't implement data splitting logic within the estimator and relies on the `eval_set` parameter of the `xgboost.XGBModel.fit()` method. If you want to use early stopping to prevent overfitting, you'll need to manually split your data into training and testing sets using the `sklearn.model_selection.train_test_split()` function from the `sklearn` library. Some other machine learning algorithms, like those in `sklearn`, include early stopping as part of the estimator and may work with cross validation. However, using early stopping during cross validation may not be a perfect approach because it changes the model's number of trees for each validation fold, leading to different model. A better approach is to retrain the model after cross validation using the best hyperparameters along with early stopping. If you want to experiment with idea of using cross validation with early stopping, here is a snippet to begin with:

```
from sklearn.base import clone
from sklearn.datasets import load_breast_cancer
from sklearn.model_selection import StratifiedKFold, cross_validate

import xgboost as xgb

X, y = load_breast_cancer(return_X_y=True)

def fit_and_score(estimator, X_train, X_test, y_train, y_test):
    """Fit the estimator on the train set and score it on both sets"""
    estimator.fit(X_train, y_train, eval_set=[(X_test, y_test)])

    train_score = estimator.score(X_train, y_train)
    test_score = estimator.score(X_test, y_test)

    return estimator, train_score, test_score

cv = StratifiedKFold(n_splits=5, shuffle=True, random_state=94)

clf = xgb.XGBClassifier(tree_method="hist", early_stopping_rounds=3)

results = {}

for train, test in cv.split(X, y):
    X_train = X[train]
    X_test = X[test]
    y_train = y[train]
    y_test = y[test]
```

(continues on next page)

(continued from previous page)

```
est, train_score, test_score = fit_and_score(
    clone(clf), X_train, X_test, y_train, y_test
)
results[est] = (train_score, test_score)
```

Obtaining the native booster object

The sklearn estimator interface primarily facilitates training and doesn't implement all features available in XGBoost. For instance, in order to have cached predictions, `xgboost.DMatrix` needs to be used with `xgboost.Booster.predict()`. One can obtain the booster object from the sklearn interface using `xgboost.XGBModel.get_booster()`:

```
booster = clf.get_booster()
print(booster.num_boosted_rounds())
```

Prediction

When early stopping is enabled, prediction functions including the `xgboost.XGBModel.predict()`, `xgboost.XGBModel.score()`, and `xgboost.XGBModel.apply()` methods will use the best model automatically. Meaning the `xgboost.XGBModel.best_iteration` is used to specify the range of trees used in prediction.

To have cached results for incremental prediction, please use the `xgboost.Booster.predict()` method instead.

Number of parallel threads

When working with XGBoost and other sklearn tools, you can specify how many threads you want to use by using the `n_jobs` parameter. By default, XGBoost uses all the available threads on your computer, which can lead to some interesting consequences when combined with other sklearn functions like `sklearn.model_selection.cross_validate()`. If both XGBoost and sklearn are set to use all threads, your computer may start to slow down significantly due to something called “thread thrashing”. To avoid this, you can simply set the `n_jobs` parameter for XGBoost to `None` (which uses all threads) and the `n_jobs` parameter for sklearn to `1`. This way, both programs will be able to work together smoothly without causing any unnecessary computer strain.

Python API Reference

This page gives the Python API reference of xgboost, please also refer to Python Package Introduction for more information about the Python package.

- *Global Configuration*
- *Core Data Structure*
- *Learning API*
- *Scikit-Learn API*
- *Plotting API*
- *Callback API*

- *Dask API*
 - *Dask extensions for distributed training*
 - * *Optional dask configuration*
- *PySpark API*

Global Configuration

`xgboost.config_context(**new_config)`

Context manager for global XGBoost configuration.

Global configuration consists of a collection of parameters that can be applied in the global scope. See [Global Configuration](#) for the full list of parameters supported in the global configuration.

Note: All settings, not just those presently modified, will be returned to their previous values when the context manager is exited. This is not thread-safe.

New in version 1.4.0.

Parameters

new_config (*Dict*[*str*, *Any*]) – Keyword arguments representing the parameters and their values

Return type

Iterator[None]

Example

```
import xgboost as xgb

# Show all messages, including ones pertaining to debugging
xgb.set_config(verbosity=2)

# Get current value of global configuration
# This is a dict containing all parameters in the global configuration,
# including 'verbosity'
config = xgb.get_config()
assert config['verbosity'] == 2

# Example of using the context manager xgb.config_context().
# The context manager will restore the previous value of the global
# configuration upon exiting.
with xgb.config_context(verbosity=0):
    # Suppress warning caused by model generated with XGBoost version < 1.0.0
    bst = xgb.Booster(model_file='./old_model.bin')
assert xgb.get_config()['verbosity'] == 2 # old value restored
```

Nested configuration context is also supported:

Example

```
with xgb.config_context(verbosity=3):
    assert xgb.get_config()["verbosity"] == 3
    with xgb.config_context(verbosity=2):
        assert xgb.get_config()["verbosity"] == 2

xgb.set_config(verbosity=2)
assert xgb.get_config()["verbosity"] == 2
with xgb.config_context(verbosity=3):
    assert xgb.get_config()["verbosity"] == 3
```

See also:

`set_config`

Set global XGBoost configuration

`get_config`

Get current values of the global configuration

`xgboost.set_config(**new_config)`

Set global configuration.

Global configuration consists of a collection of parameters that can be applied in the global scope. See [Global Configuration](#) for the full list of parameters supported in the global configuration.

New in version 1.4.0.

Parameters

new_config (*Dict[str, Any]*) – Keyword arguments representing the parameters and their values

Return type

None

Example

```
import xgboost as xgb

# Show all messages, including ones pertaining to debugging
xgb.set_config(verbosity=2)

# Get current value of global configuration
# This is a dict containing all parameters in the global configuration,
# including 'verbosity'
config = xgb.get_config()
assert config['verbosity'] == 2

# Example of using the context manager xgb.config_context().
# The context manager will restore the previous value of the global
# configuration upon exiting.
with xgb.config_context(verbosity=0):
    # Suppress warning caused by model generated with XGBoost version < 1.0.0
    bst = xgb.Booster(model_file='./old_model.bin')
assert xgb.get_config()['verbosity'] == 2 # old value restored
```


Nested configuration context is also supported:

Example

```
with xgb.config_context(verbosity=3):
    assert xgb.get_config()["verbosity"] == 3
    with xgb.config_context(verbosity=2):
        assert xgb.get_config()["verbosity"] == 2

xgb.set_config(verbosity=2)
assert xgb.get_config()["verbosity"] == 2
with xgb.config_context(verbosity=3):
    assert xgb.get_config()["verbosity"] == 3
```

xgboost.get_config()

Get current values of the global configuration.

Global configuration consists of a collection of parameters that can be applied in the global scope. See [Global Configuration](#) for the full list of parameters supported in the global configuration.

New in version 1.4.0.

Returns

args – The list of global parameters and their values

Return type

Dict[str, Any]

Example

```
import xgboost as xgb

# Show all messages, including ones pertaining to debugging
xgb.set_config(verbosity=2)

# Get current value of global configuration
# This is a dict containing all parameters in the global configuration,
# including 'verbosity'
config = xgb.get_config()
assert config['verbosity'] == 2

# Example of using the context manager xgb.config_context().
# The context manager will restore the previous value of the global
# configuration upon exiting.
with xgb.config_context(verbosity=0):
    # Suppress warning caused by model generated with XGBoost version < 1.0.0
    bst = xgb.Booster(model_file='./old_model.bin')
assert xgb.get_config()['verbosity'] == 2 # old value restored
```

Nested configuration context is also supported:

Example

```
with xgb.config_context(verbosity=3):
    assert xgb.get_config()["verbosity"] == 3
    with xgb.config_context(verbosity=2):
        assert xgb.get_config()["verbosity"] == 2

xgb.set_config(verbosity=2)
assert xgb.get_config()["verbosity"] == 2
with xgb.config_context(verbosity=3):
    assert xgb.get_config()["verbosity"] == 3
```

Core Data Structure

Core XGBoost Library.

```
class xgboost.DMatrix(data, label=None, *, weight=None, base_margin=None, missing=None, silent=False,
                      feature_names=None, feature_types=None, nthread=None, group=None, qid=None,
                      label_lower_bound=None, label_upper_bound=None, feature_weights=None,
                      enable_categorical=False, data_split_mode=DataSplitMode.ROW)
```

Bases: `object`

Data Matrix used in XGBoost.

DMatrix is an internal data structure that is used by XGBoost, which is optimized for both memory efficiency and training speed. You can construct DMatrix from multiple different sources of data.

Parameters

- **data** (*Any*) – Data source of DMatrix. See [Supported data structures for various XGBoost functions](#) for a list of supported input types.
- **label** (*Any* / *None*) – Label of the training data.
- **weight** (*Any* / *None*) – Weight for each instance.

Note: For ranking task, weights are per-group. In ranking task, one weight is assigned to each group (not each data point). This is because we only care about the relative ordering of data points within each group, so it doesn't make sense to assign weights to individual data points.

- **base_margin** (*Any* / *None*) – Base margin used for boosting from existing model.
- **missing** (*float* / *None*) – Value in the input data which needs to be present as a missing value. If *None*, defaults to `np.nan`.
- **silent** (*bool*) – Whether print messages during construction
- **feature_names** (*Sequence[str]* / *None*) – Set names for features.
- **feature_types** (*Sequence[str]* / *None*) – Set types for features. When *enable_categorical* is set to *True*, string “c” represents categorical data type while “q” represents numerical feature type. For categorical features, the input is assumed to be preprocessed and encoded by the users. The encoding can be done via `sklearn.preprocessing.OrdinalEncoder` or pandas dataframe `.cat.codes` method. This is useful when users want to specify categorical features without having to construct a dataframe as input.

- **nthread** (*int* / *None*) – Number of threads to use for loading data when parallelization is applicable. If -1, uses maximum threads available on the system.
- **group** (*Any* / *None*) – Group size for all ranking group.
- **qid** (*Any* / *None*) – Query ID for data samples, used for ranking.
- **label_lower_bound** (*Any* / *None*) – Lower bound for survival training.
- **label_upper_bound** (*Any* / *None*) – Upper bound for survival training.
- **feature_weights** (*Any* / *None*) – Set feature weights for column sampling.
- **enable_categorical** (*bool*) – New in version 1.3.0.

Note: This parameter is experimental

Experimental support of specializing for categorical features. Do not set to True unless you are interested in development. Also, JSON/UBJSON serialization format is required.

- **data_split_mode** (*DataSplitMode*) –

property feature_names: *Sequence[str] | None*

Labels for features (column labels).

Setting it to None resets existing feature names.

property feature_types: *Sequence[str] | None*

Type of features (column types).

This is for displaying the results and categorical data support. See *DMatrix* for details.

Setting it to None resets existing feature types.

get_base_margin()

Get the base margin of the DMatrix.

Return type

base_margin

get_data()

Get the predictors from DMatrix as a CSR matrix. This getter is mostly for testing purposes. If this is a quantized DMatrix then quantized values are returned instead of input values.

New in version 1.7.0.

Return type

csr_matrix

get_float_info(*field*)

Get float property from the DMatrix.

Parameters

field (*str*) – The field name of the information

Returns

info – a numpy array of float information of the data

Return type

array

get_group()

Get the group of the DMatrix.

Return type

group

get_label()

Get the label of the DMatrix.

Returns

label

Return type

array

get_quantile_cut()

Get quantile cuts for quantization.

New in version 2.0.0.

Return type

Tuple[*ndarray*, *ndarray*]

get_uint_info(field)

Get unsigned integer property from the DMatrix.

Parameters

field (*str*) – The field name of the information

Returns

info – a numpy array of unsigned integer information of the data

Return type

array

get_weight()

Get the weight of the DMatrix.

Returns

weight

Return type

array

num_col()

Get the number of columns (features) in the DMatrix.

Return type

int

num_nonmissing()

Get the number of non-missing values in the DMatrix.

New in version 1.7.0.

Return type

int

num_row()

Get the number of rows in the DMatrix.

Return type

int

save_binary(*fname*, *silent=True*)

Save DMatrix to an XGBoost buffer. Saved binary can be later loaded by providing the path to `xgboost.DMatrix()` as input.

Parameters

- **fname** (*string* or *os.PathLike*) – Name of the output buffer file.
- **silent** (*bool* (optional; default: `True`)) – If set, the output is suppressed.

Return type

None

set_base_margin(*margin*)

Set base margin of booster to start from.

This can be used to specify a prediction value of existing model to be base_margin. However, remember margin is needed, instead of transformed prediction e.g. for logistic regression: need to put in value before logistic transformation see also example/demo.py

Parameters

margin (*array like*) – Prediction margin of each datapoint

Return type

None

set_float_info(*field*, *data*)

Set float type property into the DMatrix.

Parameters

- **field** (*str*) – The field name of the information
- **data** (*numpy array*) – The array of data to be set

Return type

None

set_float_info_np2d(*field*, *data*)

Set float type property into the DMatrix
for numpy 2d array input

Parameters

- **field** (*str*) – The field name of the information
- **data** (*numpy array*) – The array of data to be set

Return type

None

set_group(*group*)

Set group size of DMatrix (used for ranking).

Parameters

group (*array like*) – Group size of each group

Return type

None

set_info(*, label=None, weight=None, base_margin=None, group=None, qid=None, label_lower_bound=None, label_upper_bound=None, feature_names=None, feature_types=None, feature_weights=None)

Set meta info for DMatrix. See doc string for [xgboost.DMatrix](#).

Parameters

- **label** (*Any* | *None*) –
- **weight** (*Any* | *None*) –
- **base_margin** (*Any* | *None*) –
- **group** (*Any* | *None*) –
- **qid** (*Any* | *None*) –
- **label_lower_bound** (*Any* | *None*) –
- **label_upper_bound** (*Any* | *None*) –
- **feature_names** (*Sequence*[*str*] | *None*) –
- **feature_types** (*Sequence*[*str*] | *None*) –
- **feature_weights** (*Any* | *None*) –

Return type

None

set_label(*label*)

Set label of dmatrix

Parameters

label (*array like*) – The label information to be set into DMatrix

Return type

None

set_uint_info(*field*, *data*)

Set uint type property into the DMatrix.

Parameters

- **field** (*str*) – The field name of the information
- **data** (*numpy array*) – The array of data to be set

Return type

None

set_weight(*weight*)

Set weight of each instance.

Parameters

weight (*array like*) – Weight for each data point

Note: For ranking task, weights are per-group.

In ranking task, one weight is assigned to each group (not each data point). This is because we only care about the relative ordering of data points within each group, so it doesn't make sense to assign weights to individual data points.

Return type

None

`slice(rindex, allow_groups=False)`

Slice the DMatrix and return a new DMatrix that only contains *rindex*.

Parameters

- **rindex** (*List[int]* | *ndarray*) – List of indices to be selected.
- **allow_groups** (*bool*) – Allow slicing of a matrix with a groups attribute

Returns

A new DMatrix containing only selected indices.

Return type

res

```
class xgboost.QuantileDMatrix(data, label=None, *, weight=None, base_margin=None, missing=None,
                             silent=False, feature_names=None, feature_types=None, nthread=None,
                             max_bin=None, ref=None, group=None, qid=None,
                             label_lower_bound=None, label_upper_bound=None,
                             feature_weights=None, enable_categorical=False,
                             data_split_mode=DataSplitMode.ROW)
```

Bases: [DMatrix](#)

A DMatrix variant that generates quantilized data directly from input for the `hist` tree method. This DMatrix is primarily designed to save memory in training by avoiding intermediate storage. Set `max_bin` to control the number of bins during quantisation, which should be consistent with the training parameter `max_bin`. When `QuantileDMatrix` is used for validation/test dataset, `ref` should be another `QuantileDMatrix` (or `DMatrix`, but not recommended as it defeats the purpose of saving memory) constructed from training dataset. See [xgboost.DMatrix](#) for documents on meta info.

Note: Do not use `QuantileDMatrix` as validation/test dataset without supplying a reference (the training dataset) `QuantileDMatrix` using `ref` as some information may be lost in quantisation.

New in version 1.7.0.

Parameters

- **max_bin** (*int* | *None*) – The number of histogram bin, should be consistent with the training parameter `max_bin`.
- **ref** ([DMatrix](#) | *None*) – The training dataset that provides quantile information, needed when creating validation/test dataset with `QuantileDMatrix`. Supplying the training DMatrix as a reference means that the same quantisation applied to the training data is applied to the validation/test data
- **data** (*Any*) – Data source of DMatrix. See [Supported data structures for various XGBoost functions](#) for a list of supported input types.
- **label** (*Any* | *None*) – Label of the training data.
- **weight** (*Any* | *None*) – Weight for each instance.

Note: For ranking task, weights are per-group. In ranking task, one weight is assigned to each group (not each data point). This is because we only care about the relative

ordering of data points within each group, so it doesn't make sense to assign weights to individual data points.

- **base_margin** (*Any* / *None*) – Base margin used for boosting from existing model.
- **missing** (*float* / *None*) – Value in the input data which needs to be present as a missing value. If *None*, defaults to `np.nan`.
- **silent** (*bool*) – Whether print messages during construction
- **feature_names** (*Sequence[str]* / *None*) – Set names for features.
- **feature_types** (*Sequence[str]* / *None*) – Set types for features. When *enable_categorical* is set to *True*, string “c” represents categorical data type while “q” represents numerical feature type. For categorical features, the input is assumed to be preprocessed and encoded by the users. The encoding can be done via `sklearn.preprocessing.OrdinalEncoder` or pandas dataframe `.cat.codes` method. This is useful when users want to specify categorical features without having to construct a dataframe as input.
- **nthread** (*int* / *None*) – Number of threads to use for loading data when parallelization is applicable. If -1, uses maximum threads available on the system.
- **group** (*Any* / *None*) – Group size for all ranking group.
- **qid** (*Any* / *None*) – Query ID for data samples, used for ranking.
- **label_lower_bound** (*Any* / *None*) – Lower bound for survival training.
- **label_upper_bound** (*Any* / *None*) – Upper bound for survival training.
- **feature_weights** (*Any* / *None*) – Set feature weights for column sampling.
- **enable_categorical** (*bool*) – New in version 1.3.0.

Note: This parameter is experimental

Experimental support of specializing for categorical features. Do not set to *True* unless you are interested in development. Also, JSON/UBJSON serialization format is required.

- **data_split_mode** (*DataSplitMode*) –

class `xgboost.Booster`(*params=None, cache=None, model_file=None*)

Bases: `object`

A Booster of XGBoost.

Booster is the model of xgboost, that contains low level routines for training, prediction and evaluation.

Parameters

- **params** (*List* / *Dict[str, Any]* / *None*) – Parameters for boosters.
- **cache** (*Sequence[DMatrix]* / *None*) – List of cache items.
- **model_file** (*Booster* / *bytearray* / *PathLike* / *str* / *None*) – Path to the model file if it's string or *PathLike*.

attr(*key*)

Get attribute string from the Booster.

Parameters

- key** (*str*) – The key to get attribute from.

Returns

The attribute value of the key, returns None if attribute do not exist.

Return type

value

attributes()

Get attributes stored in the Booster as a dictionary.

Returns

result – Returns an empty dict if there's no attributes.

Return type

dictionary of attribute_name: attribute_value pairs of strings.

property best_iteration: int

The best iteration during training.

property best_score: float

The best evaluation score during training.

boost(dtrain, grad, hess)

Boost the booster for one iteration, with customized gradient statistics. Like `xgboost.Booster.update()`, this function should not be called directly by users.

Parameters

- **dtrain** (`DMatrix`) – The training DMatrix.
- **grad** (`ndarray`) – The first order of gradient.
- **hess** (`ndarray`) – The second order of gradient.

Return type

None

copy()

Copy the booster object.

Returns

A copied booster model

Return type

booster

dump_model(fout, fmap="", with_stats=False, dump_format='text')

Dump model into a text or JSON file. Unlike `save_model()`, the output format is primarily used for visualization or interpretation, hence it's more human readable but cannot be loaded back to XGBoost.

Parameters

- **fout** (`str` / `PathLike`) – Output file name.
- **fmap** (`str` / `PathLike`) – Name of the file containing feature map names.
- **with_stats** (`bool`) – Controls whether the split statistics are output.
- **dump_format** (`str`) – Format of model dump file. Can be 'text' or 'json'.

Return type

None

eval(*data*, *name*='eval', *iteration*=0)

Evaluate the model on mat.

Parameters

- **data** ([DMatrix](#)) – The dmatrix storing the input.
- **name** (*str*) – The name of the dataset.
- **iteration** (*int*) – The current iteration number.

Returns

result – Evaluation result string.

Return type

str

eval_set(*evals*, *iteration*=0, *feval*=None, *output_margin*=True)

Evaluate a set of data.

Parameters

- **evals** ([Sequence](#)[[Tuple](#)[[DMatrix](#), *str*]]) – List of items to be evaluated.
- **iteration** (*int*) – Current iteration.
- **feval** ([Callable](#)[[[ndarray](#), [DMatrix](#)], [Tuple](#)[*str*, *float*]] | None) – Custom evaluation function.
- **output_margin** (*bool*) –

Returns

result – Evaluation result string.

Return type

str

property feature_names: [Sequence](#)[*str*] | None

Feature names for this booster. Can be directly set by input data or by assignment.

property feature_types: [Sequence](#)[*str*] | None

Feature types for this booster. Can be directly set by input data or by assignment. See [DMatrix](#) for details.

get_dump(*fmap*="", *with_stats*=False, *dump_format*='text')

Returns the model dump as a list of strings. Unlike [save_model\(\)](#), the output format is primarily used for visualization or interpretation, hence it's more human readable but cannot be loaded back to XGBoost.

Parameters

- **fmap** (*str* | [PathLike](#)) – Name of the file containing feature map names.
- **with_stats** (*bool*) – Controls whether the split statistics are output.
- **dump_format** (*str*) – Format of model dump. Can be 'text', 'json' or 'dot'.

Return type

[List](#)[*str*]

get_fscore(*fmap*="")

Get feature importance of each feature.

Note: Zero-importance features will not be included

Keep in mind that this function does not include zero-importance feature, i.e. those features that have not been used in any split conditions.

Parameters

fmap (*str* | *PathLike*) – The name of feature map file

Return type

Dict[*str*, *float* | *List*[*float*]]

get_score(*fmap*="", *importance_type*='weight')

Get feature importance of each feature. For tree model Importance type can be defined as:

- 'weight': the number of times a feature is used to split the data across all trees.
- 'gain': the average gain across all splits the feature is used in.
- 'cover': the average coverage across all splits the feature is used in.
- 'total_gain': the total gain across all splits the feature is used in.
- 'total_cover': the total coverage across all splits the feature is used in.

Note: For linear model, only "weight" is defined and it's the normalized coefficients without bias.

Note: Zero-importance features will not be included

Keep in mind that this function does not include zero-importance feature, i.e. those features that have not been used in any split conditions.

Parameters

- **fmap** (*str* | *PathLike*) – The name of feature map file.
- **importance_type** (*str*) – One of the importance types defined above.

Returns

- A map between feature names and their scores. When *gblinear* is used for
- *multi-class classification the scores for each feature is a list with length*
- *n_classes*, otherwise they're scalars.

Return type

Dict[*str*, *float* | *List*[*float*]]

get_split_value_histogram(*feature*, *fmap*="", *bins*=None, *as_pandas*=True)

Get split value histogram of a feature

Parameters

- **feature** (*str*) – The name of the feature.
- **fmap** (*PathLike* | *str*) – The name of feature map file.
- **bin** – The maximum number of bins. Number of bins equals number of unique split values *n_unique*, if *bins* == None or *bins* > *n_unique*.

- **as_pandas** (*bool*) – Return `pd.DataFrame` when pandas is installed. If False or pandas is not installed, return numpy ndarray.
- **bins** (*int* | *None*) –

Returns

- *a histogram of used splitting values for the specified feature*
- *either as numpy array or pandas DataFrame.*

Return type*ndarray* | *DataFrame*

inplace_predict(*data*, *iteration_range*=(0, 0), *predict_type*='value', *missing*=nan, *validate_features*=True, *base_margin*=None, *strict_shape*=False)

Run prediction in-place when possible, Unlike `predict()` method, inplace prediction does not cache the prediction result.

Calling only `inplace_predict` in multiple threads is safe and lock free. But the safety does not hold when used in conjunction with other methods. E.g. you can't train the booster in one thread and perform prediction in the other.

Note: If the device ordinal of the input data doesn't match the one configured for the booster, data will be copied to the booster device.

```
booster.set_param({"device": "cuda:0"})
booster.inplace_predict(cupy_array)

booster.set_param({"device": "cpu"})
booster.inplace_predict(numpy_array)
```

New in version 1.1.0.

Parameters

- **data** (*Any*) – The input data.
- **iteration_range** (*Tuple[int, int]*) – See `predict()` for details.
- **predict_type** (*str*) –
 - *value* Output model prediction values.
 - *margin* Output the raw untransformed margin value.
- **missing** (*float*) – See `xgboost.DMatrix` for details.
- **validate_features** (*bool*) – See `xgboost.Booster.predict()` for details.
- **base_margin** (*Any* | *None*) – See `xgboost.DMatrix` for details.

New in version 1.4.0.

- **strict_shape** (*bool*) – See `xgboost.Booster.predict()` for details.

New in version 1.4.0.

Returns

prediction – The prediction result. When input data is on GPU, prediction result is stored in a cupy array.

Return type

numpy.ndarray/cupy.ndarray

load_config(*config*)Load configuration returned by *save_config*.

New in version 1.0.0.

Parameters**config** (*str*) –**Return type**

None

load_model(*fname*)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters**fname** (*str* / *bytearray* / *PathLike*) – Input file name or memory buffer(see also *save_raw*)**Return type**

None

num_boosted_rounds()

Get number of boosted rounds. For gblear this is reset to 0 after serializing the model.

Return type*int***num_features()**

Number of features in booster.

Return type*int*

predict (*data*, *output_margin=False*, *pred_leaf=False*, *pred_contribs=False*, *approx_contribs=False*, *pred_interactions=False*, *validate_features=True*, *training=False*, *iteration_range=(0, 0)*, *strict_shape=False*)

Predict with data. The full model will be used unless *iteration_range* is specified, meaning user have to either slice the model or use the *best_iteration* attribute to get prediction from best model returned from early stopping.

Note: See [Prediction](#) for issues like thread safety and a summary of outputs from this function.

Parameters

- **data** (*DMatrix*) – The dmatrix storing the input.

- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **pred_leaf** (*bool*) – When this option is on, the output will be a matrix of (nsample, ntrees) with each record indicating the predicted leaf index of each sample in each tree. Note that the leaf index of a tree is unique per tree, so you may find leaf 1 in both tree 1 and tree 0.
- **pred_contribs** (*bool*) – When this is True the output will be a matrix of size (nsample, nfeats + 1) with each record indicating the feature contributions (SHAP values) for that prediction. The sum of all feature contributions is equal to the raw untransformed margin value of the prediction. Note the final column is the bias term.
- **approx_contribs** (*bool*) – Approximate the contributions of each feature. Used when **pred_contribs** or **pred_interactions** is set to True. Changing the default of this parameter (False) is not recommended.
- **pred_interactions** (*bool*) – When this is True the output will be a matrix of size (nsample, nfeats + 1, nfeats + 1) indicating the SHAP interaction values for each pair of features. The sum of each row (or column) of the interaction values equals the corresponding SHAP value (from **pred_contribs**), and the sum of the entire matrix equals the raw untransformed margin value of the prediction. Note the last row and column correspond to the bias term.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's **feature_names** are identical. Otherwise, it is assumed that the **feature_names** are the same.
- **training** (*bool*) – Whether the prediction value is used for training. This can effect *dart* booster, which performs dropouts during training iterations but use all trees for inference. If you want to obtain result with dropouts, set this parameter to *True*. Also, the parameter is set to true when obtaining prediction for custom objective function.

New in version 1.0.0.

- **iteration_range** (*Tuple[int, int]*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying *iteration_range*=(10, 20), then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

- **strict_shape** (*bool*) – When set to True, output shape is invariant to whether classification is used. For both value and margin prediction, the output shape is (n_samples, n_groups), n_groups == 1 when multi-class is not used. Default to False, in which case the output shape can be (n_samples,) if multi-class is not used.

New in version 1.4.0.

Returns

prediction

Return type

numpy array

save_config()

Output internal parameter configuration of Booster as a JSON string.

New in version 1.0.0.

Return type

str

save_model(fname)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as `feature_names`) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* | *PathLike*) – Output file name

Return type

None

save_raw(raw_format='deprecated')

Save the model to a in memory buffer representation instead of file.

Parameters

raw_format (*str*) – Format of output buffer. Can be *json*, *ubj* or *deprecated*. Right now the default is *deprecated* but it will be changed to *ubj* (universal binary json) in the future.

Return type

An in memory buffer representation of the model

set_attr(kwargs)**

Set the attribute of the Booster.

Parameters

****kwargs** (*Any* | *None*) – The attributes to set. Setting a value to None deletes an attribute.

Return type

None

set_param(params, value=None)

Set parameters into the Booster.

Parameters

- **params** (*Dict* | *Iterable[Tuple[str, Any]]* | *str*) – list of key,value pairs, dict of key to value or simply str key
- **value** (*str* | *None*) – value of the specified parameter, when params is str key

Return type

None

trees_to_dataframe(fmap="")

Parse a boosted tree model text dump into a pandas DataFrame structure.

This feature is only defined when the decision tree model is chosen as base learner (*booster* in *{gbtree, dart}*). It is not defined for other base learner types, such as linear learners (*booster=gblinear*).

Parameters

fmap (*str* | *PathLike*) – The name of feature map file.

Return type

DataFrame

update(*dtrain*, *iteration*, *fobj*=None)

Update for one iteration, with objective function calculated internally. This function should not be called directly by users.

Parameters

- **dtrain** (*DMatrix*) – Training data.
- **iteration** (*int*) – Current iteration number.
- **fobj** (*Callable*[[*ndarray*, *DMatrix*], *Tuple*[*ndarray*, *ndarray*]] | None) – Customized objective function.

Return type

None

class `xgboost.DataIter`(*cache_prefix*=None, *release_data*=True)

Bases: *ABC*

The interface for user defined data iterator. The iterator facilitates distributed training, *QuantileDMatrix*, and external memory support using *DMatrix*. Most of time, users don't need to interact with this class directly.

Note: The class caches some intermediate results using the *data* input (predictor *X*) as key. Don't repeat the *X* for multiple batches with different meta data (like *label*), make a copy if necessary.

Parameters

- **cache_prefix** (*str* | None) – Prefix to the cache files, only used in external memory. It can be either an URI or a file path.
- **release_data** (*bool*) – Whether the iterator should release the data during reset. Set it to True if the data transformation (converting data to np.float32 type) is expensive.

get_callbacks(*allow_host*, *enable_categorical*)

Get callback functions for iterating in C. This is an internal function.

Parameters

- **allow_host** (*bool*) –
- **enable_categorical** (*bool*) –

Return type

Tuple[*Callable*, *Callable*]

abstract next(*input_data*)

Set the next batch of data.

Parameters

input_data (*Callable*) – A function with same data fields like *data*, *label* with *xgboost.DMatrix*.

Return type

0 if there's no more batch, otherwise 1.

property proxy: *_ProxyDMatrix*

Handle of *DMatrix* proxy.

reraise()

Reraise the exception thrown during iteration.

Return type

None

abstract reset()

Reset the data iterator. Prototype for user defined function.

Return type

None

Learning API

Training Library containing training routines.

`xgboost.train(params, dtrain, num_boost_round=10, *, evals=None, obj=None, feval=None, maximize=None, early_stopping_rounds=None, evals_result=None, verbose_eval=True, xgb_model=None, callbacks=None, custom_metric=None)`

Train a booster with given parameters.

Parameters

- **params** (*Dict*[*str*, *Any*]) – Booster params.
- **dtrain** (*DMatrix*) – Data to be trained.
- **num_boost_round** (*int*) – Number of boosting iterations.
- **evals** (*Sequence*[*Tuple*[*DMatrix*, *str*]] | *None*) – List of validation sets for which metrics will be evaluated during training. Validation metrics will help us track the performance of the model.
- **obj** (*Callable*[[*ndarray*, *DMatrix*], *Tuple*[*ndarray*, *ndarray*]] | *None*) – Custom objective function. See *Custom Objective* for details.
- **feval** (*Callable*[[*ndarray*, *DMatrix*], *Tuple*[*str*, *float*]] | *None*) – Deprecated since version 1.6.0: Use *custom_metric* instead.
- **maximize** (*bool* | *None*) – Whether to maximize feval.
- **early_stopping_rounds** (*int* | *None*) – Activates early stopping. Validation metric needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. Requires at least one item in **evals**. The method returns the model from the last iteration (not the best one). Use custom callback or model slicing if the best model is desired. If there's more than one item in **evals**, the last entry will be used for early stopping. If there's more than one metric in the **eval_metric** parameter given in **params**, the last metric will be used for early stopping. If early stopping occurs, the model will have two additional fields: `bst.best_score`, `bst.best_iteration`.
- **evals_result** (*Dict*[*str*, *Dict*[*str*, *List*[*float*]] | *List*[*Tuple*[*float*, *float*]]] | *None*) – This dictionary stores the evaluation results of all the items in watchlist.

Example: with a watchlist containing [(dtest, 'eval'), (dtrain, 'train')] and a parameter containing ('eval_metric': 'logloss'), the **evals_result** returns

```
{'train': {'logloss': ['0.48253', '0.35953']},
 'eval': {'logloss': ['0.480385', '0.357756']}}
```

- **verbose_eval** (*bool* | *int* | *None*) – Requires at least one item in **evals**. If **verbose_eval** is *True* then the evaluation metric on the validation set is printed at each boosting stage. If **verbose_eval** is an integer then the evaluation metric on the validation set is printed at every given **verbose_eval** boosting stage. The last boosting stage / the boosting stage found by using **early_stopping_rounds** is also printed. Example: with **verbose_eval**=4 and at least one item in **evals**, an evaluation metric is printed every 4 boosting stages, instead of every boosting stage.
- **xgb_model** (*str* | *PathLike* | *Booster* | *bytearray* | *None*) – Xgb model to be loaded before training (allows training continuation).
- **callbacks** (*Sequence*[*TrainingCallback*] | *None*) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using *Callback API*.

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    xgboost.train(params, Xy, callbacks=callbacks)
```

- **custom_metric** (*Callable*[[*ndarray*, *DMatrix*], *Tuple*[*str*, *float*]] | *None*) – Custom metric function. See *Custom Metric* for details.

Returns

Booster

Return type

a trained booster model

`xgboost.cv(params, dtrain, num_boost_round=10, nfold=3, stratified=False, folds=None, metrics=(), obj=None, feval=None, maximize=None, early_stopping_rounds=None, fpreproc=None, as_pandas=True, verbose_eval=None, show_stdv=True, seed=0, callbacks=None, shuffle=True, custom_metric=None)`

Cross-validation with given parameters.

Parameters

- **params** (*dict*) – Booster params.
- **dtrain** (*DMatrix*) – Data to be trained.
- **num_boost_round** (*int*) – Number of boosting iterations.
- **nfold** (*int*) – Number of folds in CV.
- **stratified** (*bool*) – Perform stratified sampling.
- **folds** (a *KFold* or *StratifiedKFold* instance or *list of fold indices*) – Sklearn *KFolds* or *StratifiedKFolds* object. Alternatively may explicitly pass sample indices for each fold. For *n* folds, **folds** should be a length *n* list of tuples. Each tuple is (*in*, *out*) where *in* is a list of indices to be used as the training samples for the *n* th fold and *out* is a list of indices to be used as the testing samples for the *n* th fold.
- **metrics** (*string* or *list of strings*) – Evaluation metrics to be watched in CV.
- **obj** (*Callable*[[*ndarray*, *DMatrix*], *Tuple*[*ndarray*, *ndarray*]] | *None*) – Custom objective function. See *Custom Objective* for details.

- **feval** (*function*) – Deprecated since version 1.6.0: Use *custom_metric* instead.
- **maximize** (*bool*) – Whether to maximize feval.
- **early_stopping_rounds** (*int*) – Activates early stopping. Cross-Validation metric (average of validation metric computed over CV folds) needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. The last entry in the evaluation history will represent the best iteration. If there's more than one metric in the **eval_metric** parameter given in **params**, the last metric will be used for early stopping.
- **fpreproc** (*function*) – Preprocessing function that takes (dtrain, dtest, param) and returns transformed versions of those.
- **as_pandas** (*bool*, *default True*) – Return pd.DataFrame when pandas is installed. If False or pandas is not installed, return np.ndarray
- **verbose_eval** (*bool*, *int*, or *None*, *default None*) – Whether to display the progress. If None, progress will be displayed when np.ndarray is returned. If True, progress will be displayed at boosting stage. If an integer is given, progress will be displayed at every given *verbose_eval* boosting stage.
- **show_stdv** (*bool*, *default True*) – Whether to display the standard deviation in progress. Results are not affected, and always contains std.
- **seed** (*int*) – Seed used to generate the folds (passed to numpy.random.seed).
- **callbacks** (*Sequence[TrainingCallback]* | *None*) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using *Callback API*.

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    xgboost.train(params, Xy, callbacks=callbacks)
```

- **shuffle** (*bool*) – Shuffle data before creating folds.
- **custom_metric** (*Callable[[ndarray, DMatrix], Tuple[str, float]]* | *None*) – Custom metric function. See *Custom Metric* for details.

Returns

evaluation history

Return type

list(string)

Scikit-Learn API

Scikit-Learn Wrapper interface for XGBoost.

class `xgboost.XGBRegressor`(*, *objective*='reg:squarederror', **kwargs)

Bases: `XGBModel`, `RegressorMixin`

Implementation of the scikit-learn API for XGBoost regression. See *Using the Scikit-Learn Estimator Interface* for more information.

Parameters

- **n_estimators** (*Optional*[`int`]) – Number of gradient boosted trees. Equivalent to number of boosting rounds.
- **max_depth** (*Optional*[`int`]) – Maximum tree depth for base learners.
- **max_leaves** – Maximum number of leaves; 0 indicates no limit.
- **max_bin** – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional*[`float`]) – Boosting learning rate (xgb’s “eta”)
- **verbosity** (*Optional*[`int`]) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** (*Union*[`str`, *Callable*[[`numpy.ndarray`, `numpy.ndarray`], *Tuple*[`numpy.ndarray`, `numpy.ndarray`]], `NoneType`]) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional*[`str`]) – Specify which booster to use: gbtrees, gblinear or dart.
- **tree_method** (*Optional*[`str`]) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It’s recommended to study this option from the parameters document *tree method*
- **n_jobs** (*Optional*[`int`]) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.
- **gamma** (*Optional*[`float`]) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
- **min_child_weight** (*Optional*[`float`]) – Minimum sum of instance weight(hessian) needed in a child.
- **max_delta_step** (*Optional*[`float`]) – Maximum delta step we allow each tree’s weight estimation to be.
- **subsample** (*Optional*[`float`]) – Subsample ratio of the training instance.
- **sampling_method** –

Sampling method. Used only by the GPU version of hist tree method.

- **uniform**: select random training instances uniformly.
- **gradient_based** select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)

- **colsample_bytree** (*Optional*[*float*]) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional*[*float*]) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional*[*float*]) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional*[*float*]) – L1 regularization term on weights (xgb’s alpha).
- **reg_lambda** (*Optional*[*float*]) – L2 regularization term on weights (xgb’s lambda).
- **scale_pos_weight** (*Optional*[*float*]) – Balancing of positive and negative weights.
- **base_score** (*Optional*[*float*]) – The initial prediction score of all instances, global bias.
- **random_state** (*Optional*[*Union*[*numpy.random.RandomState*, *int*]]) – Random number seed.

Note: Using gblinear booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*float*, *default np.nan*) – Value in the data which needs to be present as a missing value.
- **num_parallel_tree** (*Optional*[*int*]) – Used for boosting random forest.
- **monotone_constraints** (*Optional*[*Union*[*Dict*[*str*, *int*], *str*]]) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional*[*Union*[*str*, *List*[*Tuple*[*str*]]]]) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. `[[0, 1], [2, 3, 4]]`, where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional*[*str*]) – The feature importance type for the `feature_importances_` property:
 - For tree model, it’s either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it’s the normalized coefficients without bias.
- **device** (*Optional*[*str*]) – New in version 2.0.0.
Device ordinal, available options are *cpu*, *cuda*, and *gpu*.
- **validate_parameters** (*Optional*[*bool*]) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, `cudf/pandas.DataFrame` should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional*[*FeatureTypes*]) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See [DMatrix](#) for details.

- **max_cat_to_onehot** (*Optional*[*int*]) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **max_cat_threshold** (*Optional*[*int*]) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **multi_strategy** (*Optional*[*str*]) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.

– `one_output_per_tree`: One model for each target.

– `multi_output_tree`: Use multi-target trees.

- **eval_metric** (*Optional*[*Union*[*str*, *List*[*str*], *Callable*]]) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See [doc/parameter.rst](#)), one of the metrics in [sklearn.metrics](#), or any other user defined metric that looks like *sklearn.metrics*.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the *scoring* parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces *eval_metric* in *fit()* method. The old one receives untransformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
```

(continues on next page)

(continued from previous page)

```
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **early_stopping_rounds** (*Optional*[*int*]) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. Requires at least one item in **eval_set** in *fit()*.
 - If early stopping occurs, the model will have two additional attributes: *best_score* and *best_iteration*. These are used by the *predict()* and *apply()* methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the *iteration_range* in these inference methods. In addition, other utilities like model plotting can also use the entire model.
 - If you prefer to discard the trees after *best_iteration*, consider using the callback function *xgboost.callback.EarlyStopping*.
 - If there's more than one item in **eval_set**, the last entry will be used for early stopping. If there's more than one metric in **eval_metric**, the last metric will be used for early stopping.

Note: This parameter replaces *early_stopping_rounds* in *fit()* method.

- **callbacks** (*Optional*[*List*[*TrainingCallback*]]) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using *Callback API*.

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
    reg.fit(X, y)
```

- **kwargs** (*dict*, *optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found [here](#). Attempting to set a parameter via the constructor args and ****kwargs** dict simultaneously will result in a *TypeError*.

Note: ****kwargs** unsupported by scikit-learn

****kwargs** is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

Note: Custom objective function

A custom objective function can be provided for the `objective` parameter. In this case, it should have the signature `objective(y_true, y_pred) -> grad, hess:`

y_true: array_like of shape [n_samples]

The target values

y_pred: array_like of shape [n_samples]

The predicted values

grad: array_like of shape [n_samples]

The value of the gradient for each sample point.

hess: array_like of shape [n_samples]

The value of the second derivative for each sample point

apply(X, iteration_range=None)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then `best_iteration` is used automatically.

Parameters

- **X** (array_like, shape=[n_samples, n_features]) – Input features matrix.
- **iteration_range** (Tuple[int, int] | None) – See `predict()`.

Returns

X_leaves – For each datapoint x in X and for each tree, return the index of the leaf x ends up in. Leaves are numbered within `[0; 2**(self.max_depth+1))`, possibly with gaps in the numbering.

Return type

array_like, shape=[n_samples, n_trees]

property best_iteration: int

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then `best_iteration` is 0.

property best_score: float

The best score obtained by early stopping.

property coef_: ndarray

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (`booster=gblinear`). It is not defined for other base learner types, such as tree learners (`booster=gbtrees`).

Returns

coef_

Return type

array of shape [n_features] or [n_classes, n_features]

evals_result()

Return the evaluation results.

If `eval_set` is passed to the `fit()` function, you can call `evals_result()` to get evaluation results for all passed `eval_sets`. When `eval_metric` is also passed to the `fit()` function, the `evals_result` will contain the `eval_metrics` passed to the `fit()` function.

The returned evaluation result is a dictionary:

```
{'validation_0': {'logloss': ['0.604835', '0.531479']},
 'validation_1': {'logloss': ['0.41965', '0.17686']}}
```

Return type

`evals_result`

property `feature_importances_`: `ndarray`

Feature importances property, return depends on `importance_type` parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- `feature_importances_` (array of shape `[n_features]` except for multi-class)
- linear model, which returns an array with shape `(n_features, n_classes)`

property `feature_names_in_`: `ndarray`

Names of features seen during `fit()`. Defined only when `X` has feature names that are all strings.

fit(`X`, `y`, *, `sample_weight=None`, `base_margin=None`, `eval_set=None`, `eval_metric=None`, `early_stopping_rounds=None`, `verbose=True`, `xgb_model=None`, `sample_weight_eval_set=None`, `base_margin_eval_set=None`, `feature_weights=None`, `callbacks=None`)

Fit gradient boosting model.

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- **X** (*Any*) – Feature matrix. See *Supported data structures for various XGBoost functions* for a list of supported types.

When the `tree_method` is set to `hist`, internally, the `QuantileDMatrix` will be used instead of the `DMatrix` for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (*Any*) – Labels
- **sample_weight** (*Any* / *None*) – instance weights
- **base_margin** (*Any* / *None*) – global bias for each instance.
- **eval_set** (*Sequence* [*Tuple* [*Any*, *Any*]] / *None*) – A list of (X, y) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_metric** (*str*, *list of str*, or *callable*, *optional*) – Deprecated since version 1.6.0.

Use `eval_metric` in `__init__()` or `set_params()` instead.

- **early_stopping_rounds** (*int*) – Deprecated since version 1.6.0.
Use *early_stopping_rounds* in `__init__()` or `set_params()` instead.
- **verbose** (*bool* | *int* | *None*) – If *verbose* is *True* and an evaluation set is used, the evaluation metric measured on the validation set is printed to stdout at each boosting stage. If *verbose* is an integer, the evaluation metric is printed at each *verbose* boosting stage. The last boosting stage / the boosting stage found by using *early_stopping_rounds* is also printed.
- **xgb_model** (*Booster* | *XGBModel* | *str* | *None*) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (*Sequence[*Any*]* | *None*) – A list of the form [L_1, L_2, ..., L_n], where each L_i is an array like object storing instance weights for the i-th validation set.
- **base_margin_eval_set** (*Sequence[*Any*]* | *None*) – A list of the form [M_1, M_2, ..., M_n], where each M_i is an array like object storing base margin for the i-th validation set.
- **feature_weights** (*Any* | *None*) – Weight for each feature, defines the probability of each feature being selected when *colsample* is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence[*TrainingCallback*]* | *None*) – Deprecated since version 1.6.0: Use *callbacks* in `__init__()` or `set_params()` instead.

Return type

XGBModel

get_booster()

Get the underlying xgboost *Booster* of this model.

This will raise an exception when *fit* was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A *MetadataRequest* encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

int

get_params(*deep=True*)

Get parameters.

Parameters**deep** (*bool*) –**Return type***Dict*[*str*, *Any*]**get_xgb_params()**

Get xgboost specific parameters.

Return type*Dict*[*str*, *Any*]**property intercept_: ndarray**

Intercept (bias) property

Note: Intercept is defined only for linear learnersIntercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtree*).

Returns**intercept_****Return type**

array of shape (1,) or [n_classes]

load_model(fname)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See *Model IO* for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters**fname** (*str* | *bytearray* | *PathLike*) – Input file name or memory buffer(see also *save_raw*)**Return type**

None

property n_features_in_: intNumber of features seen during *fit()*.**predict(X, output_margin=False, validate_features=True, base_margin=None, iteration_range=None)**Predict with X. If the model is trained with early stopping, then *best_iteration* is used automatically. The estimator uses *inplace_predict* by default and falls back to using *DMatrix* if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*Any*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (*Any* / *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* / *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying `iteration_range=(10, 20)`, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type

prediction

save_model(fname)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as `feature_names`) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* / *PathLike*) – Output file name

Return type

None

score(X, y, sample_weight=None)

Return the coefficient of determination of the prediction.

The coefficient of determination R^2 is defined as $(1 - \frac{u}{v})$, where u is the residual sum of squares $((y_true - y_pred)**2).sum()$ and v is the total sum of squares $((y_true - y_true.mean())**2).sum()$. The best possible score is 1.0 and it can be negative (because the model can be arbitrarily worse). A constant model that always predicts the expected value of y , disregarding the input features, would get a R^2 score of 0.0.

Parameters

- **X** (*array-like of shape (n_samples, n_features)*) – Test samples. For some estimators this may be a precomputed kernel matrix or a list of generic objects instead with shape $(n_samples, n_samples_fitted)$, where `n_samples_fitted` is the number of samples used in the fitting for the estimator.
- **y** (*array-like of shape (n_samples,) or (n_samples, n_outputs)*) – True values for X .
- **sample_weight** (*array-like of shape (n_samples,)*, *default=None*) – Sample weights.

Returns

score – R^2 of `self.predict(X)` w.r.t. `y`.

Return type

float

Notes

The R^2 score used when calling `score` on a regressor uses `multioutput='uniform_average'` from version 0.23 to keep consistent with default value of `r2_score()`. This influences the `score` method of all the multioutput regressors (except for `MultiOutputRegressor`).

```
set_fit_request(* , base_margin='$UNCHANGED$', base_margin_eval_set='$UNCHANGED$',
                 callbacks='$UNCHANGED$', early_stopping_rounds='$UNCHANGED$',
                 eval_metric='$UNCHANGED$', eval_set='$UNCHANGED$',
                 feature_weights='$UNCHANGED$', sample_weight='$UNCHANGED$',
                 sample_weight_eval_set='$UNCHANGED$', verbose='$UNCHANGED$',
                 xgb_model='$UNCHANGED$')
```

Request metadata passed to the `fit` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `fit` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `fit`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in `fit`.
- **base_margin_eval_set** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin_eval_set` parameter in `fit`.
- **callbacks** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `callbacks` parameter in `fit`.

- **early_stopping_rounds** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `early_stopping_rounds` parameter in `fit`.
- **eval_metric** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_metric` parameter in `fit`.
- **eval_set** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_set` parameter in `fit`.
- **feature_weights** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `feature_weights` parameter in `fit`.
- **sample_weight** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in `fit`.
- **sample_weight_eval_set** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight_eval_set` parameter in `fit`.
- **verbose** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `verbose` parameter in `fit`.
- **xgb_model** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `xgb_model` parameter in `fit`.
- **self** (`XGBRegressor`) –

Returns

self – The updated object.

Return type

`object`

set_params(***params*)

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

`self`

Parameters

params (*Any*) –

set_predict_request(***, `base_margin`='UNCHANGED\$', `iteration_range`='UNCHANGED\$', `output_margin`='UNCHANGED\$', `validate_features`='UNCHANGED\$')

Request metadata passed to the `predict` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to `predict` if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to `predict`.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str, True, False, or None, default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `base_margin` parameter in `predict`.
- **iteration_range** (*str, True, False, or None, default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `iteration_range` parameter in `predict`.
- **output_margin** (*str, True, False, or None, default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `output_margin` parameter in `predict`.
- **validate_features** (*str, True, False, or None, default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `validate_features` parameter in `predict`.
- **self** (`XGBRegressor`) –

Returns

self – The updated object.

Return type

`object`

set_score_request(*, *sample_weight='UNCHANGED\$'*)

Request metadata passed to the `score` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to `score` if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to `score`.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **sample_weight** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in `score`.
- **self** (`XGBRegressor`) –

Returns

self – The updated object.

Return type

`object`

class `xgboost.XGBClassifier`(*, *objective='binary:logistic'*, **kwargs)

Bases: `XGBModel`, `ClassifierMixin`

Implementation of the scikit-learn API for XGBoost classification. See [Using the Scikit-Learn Estimator Interface](#) for more information.

Parameters

- **n_estimators** (*Optional* [`int`]) – Number of boosting rounds.
- **max_depth** (*Optional* [`int`]) – Maximum tree depth for base learners.
- **max_leaves** – Maximum number of leaves; 0 indicates no limit.
- **max_bin** – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional* [`float`]) – Boosting learning rate (xgb’s “eta”)
- **verbosity** (*Optional* [`int`]) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** (*Union* [`str`, *Callable* [`[numpy.ndarray, numpy.ndarray]`, *Tuple* [`[numpy.ndarray, numpy.ndarray]`], `NoneType`]) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional* [`str`]) – Specify which booster to use: `gbtree`, `gblinear` or `dart`.
- **tree_method** (*Optional* [`str`]) – Specify which tree method to use. Default to `auto`. If this parameter is set to default, XGBoost will choose the most conservative option available. It’s recommended to study this option from the parameters document [tree method](#)
- **n_jobs** (*Optional* [`int`]) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.

- **gamma** (*Optional[[float](#)]*) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
- **min_child_weight** (*Optional[[float](#)]*) – Minimum sum of instance weight(hessian) needed in a child.
- **max_delta_step** (*Optional[[float](#)]*) – Maximum delta step we allow each tree’s weight estimation to be.
- **subsample** (*Optional[[float](#)]*) – Subsample ratio of the training instance.
- **sampling_method** –

Sampling method. Used only by the GPU version of hist tree method.

- **uniform**: select random training instances uniformly.
- **gradient_based** select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
- **colsample_bytree** (*Optional[[float](#)]*) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional[[float](#)]*) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional[[float](#)]*) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional[[float](#)]*) – L1 regularization term on weights (xgb’s alpha).
- **reg_lambda** (*Optional[[float](#)]*) – L2 regularization term on weights (xgb’s lambda).
- **scale_pos_weight** (*Optional[[float](#)]*) – Balancing of positive and negative weights.
- **base_score** (*Optional[[float](#)]*) – The initial prediction score of all instances, global bias.
- **random_state** (*Optional[Union[[numpy.random.RandomState](#), [int](#)]]*) – Random number seed.

Note: Using gblinear booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*[float](#), default np.nan*) – Value in the data which needs to be present as a missing value.
- **num_parallel_tree** (*Optional[[int](#)]*) – Used for boosting random forest.
- **monotone_constraints** (*Optional[Union[Dict[[str](#), [int](#)], [str](#)]]*) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional[Union[[str](#), List[Tuple[[str](#)]]]]*) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. `[[0, 1], [2, 3, 4]]`, where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional[[str](#)]*) – The feature importance type for the feature_importances_ property:
 - For tree model, it’s either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it’s the normalized coefficients without bias.

- **device** (*Optional*[*str*]) – New in version 2.0.0.
Device ordinal, available options are *cpu*, *cuda*, and *gpu*.
- **validate_parameters** (*Optional*[*bool*]) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, *cudf/pandas.DataFrame* should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional*[*FeatureTypes*]) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See *DMatrix* for details.
- **max_cat_to_onehot** (*Optional*[*int*]) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, *enable_categorical* needs to be set to have categorical feature support. See *Categorical Data* and *Parameters for Categorical Feature* for details.

- **max_cat_threshold** (*Optional*[*int*]) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, *enable_categorical* needs to be set to have categorical feature support. See *Categorical Data* and *Parameters for Categorical Feature* for details.

- **multi_strategy** (*Optional*[*str*]) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See *Multiple Outputs* for more information.

- *one_output_per_tree*: One model for each target.
- *multi_output_tree*: Use multi-target trees.

- **eval_metric** (*Optional*[*Union*[*str*, *List*[*str*], *Callable*]]) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See *doc/parameter.rst*), one of the metrics in *sklearn.metrics*, or any other user defined metric that looks like *sklearn.metrics*.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the *scoring* parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces *eval_metric* in *fit()* method. The old one receives untransformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **early_stopping_rounds** (*Optional*[*int*]) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. Requires at least one item in **eval_set** in *fit()*.
 - If early stopping occurs, the model will have two additional attributes: *best_score* and *best_iteration*. These are used by the *predict()* and *apply()* methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the *iteration_range* in these inference methods. In addition, other utilities like model plotting can also use the entire model.
 - If you prefer to discard the trees after *best_iteration*, consider using the callback function [xgboost.callback.EarlyStopping](#).
 - If there's more than one item in **eval_set**, the last entry will be used for early stopping. If there's more than one metric in **eval_metric**, the last metric will be used for early stopping.

Note: This parameter replaces *early_stopping_rounds* in *fit()* method.

- **callbacks** (*Optional*[*List*[*TrainingCallback*]]) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using [Callback API](#).

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
```

(continues on next page)

(continued from previous page)

```
reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
reg.fit(X, y)
```

- **kwargs** (*dict*, *optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found [here](#). Attempting to set a parameter via the constructor args and **kwargs** dict simultaneously will result in a `TypeError`.

Note: **kwargs** unsupported by scikit-learn

kwargs is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

Note: Custom objective function

A custom objective function can be provided for the `objective` parameter. In this case, it should have the signature `objective(y_true, y_pred) -> grad, hess`:

y_true: `array_like` of shape `[n_samples]`

The target values

y_pred: `array_like` of shape `[n_samples]`

The predicted values

grad: `array_like` of shape `[n_samples]`

The value of the gradient for each sample point.

hess: `array_like` of shape `[n_samples]`

The value of the second derivative for each sample point

apply(*X*, *iteration_range=None*)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then `best_iteration` is used automatically.

Parameters

- **X** (`array_like`, `shape=[n_samples, n_features]`) – Input features matrix.
- **iteration_range** (`Tuple[int, int]` | `None`) – See `predict()`.

Returns

X_leaves – For each datapoint *x* in *X* and for each tree, return the index of the leaf *x* ends up in. Leaves are numbered within `[0; 2**(self.max_depth+1))`, possibly with gaps in the numbering.

Return type

`array_like`, `shape=[n_samples, n_trees]`

property best_iteration: `int`

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then `best_iteration` is 0.

property best_score: `float`

The best score obtained by early stopping.

property coef_: `ndarray`

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

`coef_`

Return type

array of shape `[n_features]` or `[n_classes, n_features]`

evals_result()

Return the evaluation results.

If `eval_set` is passed to the `fit()` function, you can call `evals_result()` to get evaluation results for all passed `eval_sets`. When `eval_metric` is also passed to the `fit()` function, the `evals_result` will contain the `eval_metrics` passed to the `fit()` function.

The returned evaluation result is a dictionary:

```
{'validation_0': {'logloss': ['0.604835', '0.531479']},
 'validation_1': {'logloss': ['0.41965', '0.17686']}}
```

Return type

`evals_result`

property feature_importances_: `ndarray`

Feature importances property, return depends on *importance_type* parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- `feature_importances_` (array of shape `[n_features]` except for multi-class)
- linear model, which returns an array with shape `(n_features, n_classes)`

property feature_names_in_: `ndarray`

Names of features seen during `fit()`. Defined only when `X` has feature names that are all strings.

fit(`X`, `y`, `*`, `sample_weight=None`, `base_margin=None`, `eval_set=None`, `eval_metric=None`, `early_stopping_rounds=None`, `verbose=True`, `xgb_model=None`, `sample_weight_eval_set=None`, `base_margin_eval_set=None`, `feature_weights=None`, `callbacks=None`)

Fit gradient boosting classifier.

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- `X` (*Any*) – Feature matrix. See *Supported data structures for various XGBoost functions* for a list of supported types.

When the `tree_method` is set to `hist`, internally, the *QuantileDMatrix* will be used instead of the *DMatrix* for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (*Any*) – Labels
- **sample_weight** (*Any* / *None*) – instance weights
- **base_margin** (*Any* / *None*) – global bias for each instance.
- **eval_set** (*Sequence*[*Tuple*[*Any*, *Any*]] / *None*) – A list of (X, y) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_metric** (*str*, *list of str*, or *callable*, *optional*) – Deprecated since version 1.6.0.

Use *eval_metric* in `__init__()` or *set_params()* instead.

- **early_stopping_rounds** (*int*) – Deprecated since version 1.6.0.

Use *early_stopping_rounds* in `__init__()` or *set_params()* instead.

- **verbose** (*bool* / *int* / *None*) – If *verbose* is `True` and an evaluation set is used, the evaluation metric measured on the validation set is printed to `stdout` at each boosting stage. If *verbose* is an integer, the evaluation metric is printed at each *verbose* boosting stage. The last boosting stage / the boosting stage found by using *early_stopping_rounds* is also printed.
- **xgb_model** (*Booster* / *str* / *XGBModel* / *None*) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (*Sequence*[*Any*] / *None*) – A list of the form [L_1, L_2, ..., L_n], where each L_i is an array like object storing instance weights for the i-th validation set.
- **base_margin_eval_set** (*Sequence*[*Any*] / *None*) – A list of the form [M_1, M_2, ..., M_n], where each M_i is an array like object storing base margin for the i-th validation set.
- **feature_weights** (*Any* / *None*) – Weight for each feature, defines the probability of each feature being selected when `colsample` is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence*[*TrainingCallback*] / *None*) – Deprecated since version 1.6.0: Use *callbacks* in `__init__()` or *set_params()* instead.

Return type

XGBClassifier

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when `fit` was not called

Returns

booster

Return type

a xgboost booster of underlying model

`get_metadata_routing()`

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A MetadataRequest encapsulating routing information.

Return type

MetadataRequest

`get_num_boosting_rounds()`

Gets the number of xgboost boosting rounds.

Return type

int

`get_params(deep=True)`

Get parameters.

Parameters

deep (*bool*) –

Return type

Dict[str, Any]

`get_xgb_params()`

Get xgboost specific parameters.

Return type

Dict[str, Any]

`property intercept_: ndarray`

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

intercept_

Return type

array of shape (1,) or [n_classes]

`load_model(fname)`

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* / *bytearray* / *PathLike*) – Input file name or memory buffer(see also `save_raw`)

Return type

None

property n_features_in_: *int*

Number of features seen during `fit()`.

predict(*X*, *output_margin=False*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict with *X*. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for `gbtree` and `dart`.

Parameters

- **X** (*Any*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (*Any* / *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* / *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying `iteration_range=(10, 20)`, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type

prediction

predict_proba(*X*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict the probability of each *X* example being of a given class. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for `gbtree` and `dart`.

Parameters

- **X** (*Any*) – Feature matrix. See *Supported data structures for various XGBoost functions* for a list of supported types.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (*Any* / *None*) – Margin added to prediction.

- **iteration_range** (*Tuple[int, int] | None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying *iteration_range=(10, 20)*, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

Returns

a numpy array of shape array-like of shape (n_samples, n_classes) with the probability of each data example being of a given class.

Return type

prediction

save_model(fname)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str | PathLike*) – Output file name

Return type

None

score(X, y, sample_weight=None)

Return the mean accuracy on the given test data and labels.

In multi-label classification, this is the subset accuracy which is a harsh metric since you require for each sample that each label set be correctly predicted.

Parameters

- **X** (*array-like of shape (n_samples, n_features)*) – Test samples.
- **y** (*array-like of shape (n_samples,) or (n_samples, n_outputs)*) – True labels for X.
- **sample_weight** (*array-like of shape (n_samples,)*, *default=None*) – Sample weights.

Returns

score – Mean accuracy of *self.predict(X)* w.r.t. y.

Return type

float

set_fit_request(*, base_margin='\$UNCHANGED\$', base_margin_eval_set='\$UNCHANGED\$', callbacks='\$UNCHANGED\$', early_stopping_rounds='\$UNCHANGED\$', eval_metric='\$UNCHANGED\$', eval_set='\$UNCHANGED\$', feature_weights='\$UNCHANGED\$', sample_weight='\$UNCHANGED\$', sample_weight_eval_set='\$UNCHANGED\$', verbose='\$UNCHANGED\$', xgb_model='\$UNCHANGED\$')

Request metadata passed to the fit method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `fit` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `fit`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in `fit`.
- **base_margin_eval_set** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin_eval_set` parameter in `fit`.
- **callbacks** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `callbacks` parameter in `fit`.
- **early_stopping_rounds** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `early_stopping_rounds` parameter in `fit`.
- **eval_metric** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_metric` parameter in `fit`.
- **eval_set** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_set` parameter in `fit`.
- **feature_weights** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `feature_weights` parameter in `fit`.
- **sample_weight** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in `fit`.
- **sample_weight_eval_set** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight_eval_set` parameter in `fit`.

- **verbose** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for verbose parameter in fit.
- **xgb_model** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for xgb_model parameter in fit.
- **self** (`XGBClassifier`) –

Returns

self – The updated object.

Return type

`object`

set_params(params)**

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

`self`

Parameters

params (*Any*) –

set_predict_proba_request(*, base_margin='\$UNCHANGED\$', iteration_range='\$UNCHANGED\$', validate_features='\$UNCHANGED\$')

Request metadata passed to the `predict_proba` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- True: metadata is requested, and passed to `predict_proba` if provided. The request is ignored if metadata is not provided.
- False: metadata is not requested and the meta-estimator will not pass it to `predict_proba`.
- None: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- str: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for base_margin parameter in `predict_proba`.

- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *iteration_range* parameter in *predict_proba*.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *validate_features* parameter in *predict_proba*.
- **self** (*XGBClassifier*) –

Returns

self – The updated object.

Return type

object

```
set_predict_request(*, base_margin='$UNCHANGED$', iteration_range='$UNCHANGED$',  
                    output_margin='$UNCHANGED$', validate_features='$UNCHANGED$')
```

Request metadata passed to the *predict* method.

Note that this method is only relevant if *enable_metadata_routing=True* (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- *True*: metadata is requested, and passed to *predict* if provided. The request is ignored if metadata is not provided.
- *False*: metadata is not requested and the meta-estimator will not pass it to *predict*.
- *None*: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- *str*: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (*sklearn.utils.metadata_routing.UNCHANGED*) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *base_margin* parameter in *predict*.
- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *iteration_range* parameter in *predict*.
- **output_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *output_margin* parameter in *predict*.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *validate_features* parameter in *predict*.

- **self** (`XGBClassifier`) –

Returns

self – The updated object.

Return type

object

set_score_request(*, *sample_weight*='\$UNCHANGED\$')

Request metadata passed to the `score` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `score` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `score`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **sample_weight** (`str`, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in `score`.
- **self** (`XGBClassifier`) –

Returns

self – The updated object.

Return type

object

class `xgboost.XGBRanker`(*, *objective*='rank:ndcg', ***kwargs*)

Bases: `XGBModel`, `XGBRankerMixIn`

Implementation of the Scikit-Learn API for XGBoost Ranking.

See [Learning to Rank](#) for an introduction.

See [Using the Scikit-Learn Estimator Interface](#) for more information.

Parameters

- **n_estimators** (*Optional* [`int`]) – Number of gradient boosted trees. Equivalent to number of boosting rounds.

- **max_depth** (*Optional*[*int*]) – Maximum tree depth for base learners.
- **max_leaves** – Maximum number of leaves; 0 indicates no limit.
- **max_bin** – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional*[*float*]) – Boosting learning rate (xgb’s “eta”)
- **verbosity** (*Optional*[*int*]) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** (*Union*[*str*, *Callable*[[*numpy.ndarray*, *numpy.ndarray*], *Tuple*[*numpy.ndarray*, *numpy.ndarray*]], *NoneType*]) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional*[*str*]) – Specify which booster to use: gbtrees, gblinear or dart.
- **tree_method** (*Optional*[*str*]) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It’s recommended to study this option from the parameters document [tree method](#)
- **n_jobs** (*Optional*[*int*]) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.
- **gamma** (*Optional*[*float*]) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
- **min_child_weight** (*Optional*[*float*]) – Minimum sum of instance weight(hessian) needed in a child.
- **max_delta_step** (*Optional*[*float*]) – Maximum delta step we allow each tree’s weight estimation to be.
- **subsample** (*Optional*[*float*]) – Subsample ratio of the training instance.
- **sampling_method** –
Sampling method. Used only by the GPU version of **hist** tree method.
 - **uniform**: select random training instances uniformly.
 - **gradient_based** select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
- **colsample_bytree** (*Optional*[*float*]) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional*[*float*]) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional*[*float*]) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional*[*float*]) – L1 regularization term on weights (xgb’s alpha).
- **reg_lambda** (*Optional*[*float*]) – L2 regularization term on weights (xgb’s lambda).
- **scale_pos_weight** (*Optional*[*float*]) – Balancing of positive and negative weights.
- **base_score** (*Optional*[*float*]) – The initial prediction score of all instances, global bias.

- **random_state** (*Optional[Union[numpy.random.RandomState, int]]*) – Random number seed.

Note: Using gblinear booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*float, default np.nan*) – Value in the data which needs to be present as a missing value.
- **num_parallel_tree** (*Optional[int]*) – Used for boosting random forest.
- **monotone_constraints** (*Optional[Union[Dict[str, int], str]]*) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional[Union[str, List[Tuple[str]]]]*) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. `[[0, 1], [2, 3, 4]]`, where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information.
- **importance_type** (*Optional[str]*) – The feature importance type for the `feature_importances_` property:
 - For tree model, it's either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it's the normalized coefficients without bias.
- **device** (*Optional[str]*) – New in version 2.0.0.
Device ordinal, available options are `cpu`, `cuda`, and `gpu`.
- **validate_parameters** (*Optional[bool]*) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, `cudf/pandas.DataFrame` should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional[FeatureTypes]*) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See [DMatrix](#) for details.
- **max_cat_to_onehot** (*Optional[int]*) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, `enable_categorical` needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **max_cat_threshold** (*Optional[int]*) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **multi_strategy** (*Optional*[*str*]) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.

- `one_output_per_tree`: One model for each target.
- `multi_output_tree`: Use multi-target trees.

- **eval_metric** (*Optional*[*Union*[*str*, *List*[*str*], *Callable*]]) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See [doc/parameter.rst](#)), one of the metrics in [sklearn.metrics](#), or any other user defined metric that looks like *sklearn.metrics*.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the *scoring* parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces *eval_metric* in *fit()* method. The old one receives un-transformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **early_stopping_rounds** (*Optional*[*int*]) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. Requires at least one item in *eval_set* in *fit()*.

- If early stopping occurs, the model will have two additional attributes: `best_score` and `best_iteration`. These are used by the `predict()` and `apply()` methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the `iteration_range` in these inference methods. In addition, other utilities like model plotting can also use the entire model.
- If you prefer to discard the trees after `best_iteration`, consider using the callback function `xgboost.callback.EarlyStopping`.
- If there's more than one item in `eval_set`, the last entry will be used for early stopping. If there's more than one metric in `eval_metric`, the last metric will be used for early stopping.

Note: This parameter replaces `early_stopping_rounds` in `fit()` method.

- **callbacks** (*Optional* [`List` [`TrainingCallback`]]) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using [Callback API](#).

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
    reg.fit(X, y)
```

- **kwargs** (*dict*, *optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found [here](#). Attempting to set a parameter via the constructor args and `**kwargs` dict simultaneously will result in a `TypeError`.

Note: `**kwargs` unsupported by scikit-learn

`**kwargs` is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

Note: A custom objective function is currently not supported by XGBRanker.

Note: Query group information is only required for ranking training but not prediction. Multiple groups can be predicted on a single call to `predict()`.

When fitting the model with the `group` parameter, your data need to be sorted by the query group first. `group` is an array that contains the size of each query group.

Similarly, when fitting the model with the `qid` parameter, the data should be sorted according to query index and `qid` is an array that contains the query index for each training sample.

For example, if your original data look like:

qid	label	features
1	0	x_1
1	1	x_2
1	0	x_3
2	0	x_4
2	1	x_5
2	1	x_6
2	1	x_7

then `fit()` method can be called with either `group` array as `[3, 4]` or with `qid` as `[1, 1, 1, 2, 2, 2, 2]`, that is the `qid` column. Also, the `qid` can be a special column of input `X` instead of a separated parameter, see `fit()` for more info.

apply(`X`, `iteration_range=None`)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then `best_iteration` is used automatically.

Parameters

- `X` (`array_like`, `shape=[n_samples, n_features]`) – Input features matrix.
- `iteration_range` (`Tuple[int, int]` | `None`) – See `predict()`.

Returns

X_leaves – For each datapoint `x` in `X` and for each tree, return the index of the leaf `x` ends up in. Leaves are numbered within `[0; 2**(self.max_depth+1))`, possibly with gaps in the numbering.

Return type

`array_like`, `shape=[n_samples, n_trees]`

property best_iteration: `int`

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then `best_iteration` is 0.

property best_score: `float`

The best score obtained by early stopping.

property coef_: `ndarray`

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (`booster=gblinear`). It is not defined for other base learner types, such as tree learners (`booster=gbtrees`).

Returns

coef_

Return type

array of shape `[n_features]` or `[n_classes, n_features]`

evals_result()

Return the evaluation results.

If `eval_set` is passed to the `fit()` function, you can call `evals_result()` to get evaluation results for all passed `eval_sets`. When `eval_metric` is also passed to the `fit()` function, the `evals_result` will contain the `eval_metrics` passed to the `fit()` function.

The returned evaluation result is a dictionary:

```
{'validation_0': {'logloss': ['0.604835', '0.531479']},
 'validation_1': {'logloss': ['0.41965', '0.17686']}}
```

Return type

`evals_result`

property `feature_importances_`: `ndarray`

Feature importances property, return depends on `importance_type` parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- `feature_importances_` (array of shape `[n_features]` except for multi-class)
- linear model, which returns an array with shape `(n_features, n_classes)`

property `feature_names_in_`: `ndarray`

Names of features seen during `fit()`. Defined only when `X` has feature names that are all strings.

`fit(X, y, *, group=None, qid=None, sample_weight=None, base_margin=None, eval_set=None, eval_group=None, eval_qid=None, eval_metric=None, early_stopping_rounds=None, verbose=False, xgb_model=None, sample_weight_eval_set=None, base_margin_eval_set=None, feature_weights=None, callbacks=None)`

Fit gradient boosting ranker

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- `X (Any)` – Feature matrix. See *Supported data structures for various XGBoost functions* for a list of supported types.

When this is a `pandas.DataFrame` or a `cudf.DataFrame`, it may contain a special column called `qid` for specifying the query index. Using a special column is the same as using the `qid` parameter, except for being compatible with sklearn utility functions like `sklearn.model_selection.cross_validation()`. The same convention applies to the `XGBRanker.score()` and `XGBRanker.predict()`.

qid	feat_0	feat_1
0	x_{00}	x_{01}
1	x_{10}	x_{11}
1	x_{20}	x_{21}

When the `tree_method` is set to `hist`, internally, the `QuantileDMatrix` will be used instead of the `DMatrix` for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (*Any*) – Labels
- **group** (*Any* / *None*) – Size of each query group of training data. Should have as many elements as the query groups in the training data. If this is set to *None*, then user must provide *qid*.
- **qid** (*Any* / *None*) – Query ID for each training sample. Should have the size of *n_samples*. If this is set to *None*, then user must provide *group* or a special column in *X*.
- **sample_weight** (*Any* / *None*) – Query group weights

Note: Weights are per-group for ranking tasks

In ranking task, one weight is assigned to each query group/id (not each data point). This is because we only care about the relative ordering of data points within each group, so it doesn't make sense to assign weights to individual data points.

- **base_margin** (*Any* / *None*) – Global bias for each instance.
- **eval_set** (*Sequence*[*Tuple*[*Any*, *Any*]] / *None*) – A list of (*X*, *y*) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_group** (*Sequence*[*Any*] / *None*) – A list in which *eval_group*[*i*] is the list containing the sizes of all query groups in the *i*-th pair in *eval_set*.
- **eval_qid** (*Sequence*[*Any*] / *None*) – A list in which *eval_qid*[*i*] is the array containing query ID of *i*-th pair in *eval_set*. The special column convention in *X* applies to validation datasets as well.
- **eval_metric** (*str*, *list of str*, *optional*) – Deprecated since version 1.6.0: use *eval_metric* in *__init__*() or *set_params*() instead.
- **early_stopping_rounds** (*int*) – Deprecated since version 1.6.0: use *early_stopping_rounds* in *__init__*() or *set_params*() instead.
- **verbose** (*bool* / *int* / *None*) – If *verbose* is *True* and an evaluation set is used, the evaluation metric measured on the validation set is printed to *stdout* at each boosting stage. If *verbose* is an integer, the evaluation metric is printed at each *verbose* boosting stage. The last boosting stage / the boosting stage found by using *early_stopping_rounds* is also printed.
- **xgb_model** (*Booster* / *str* / *XGBModel* / *None*) – file name of stored XGBoost model or 'Booster' instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (*Sequence*[*Any*] / *None*) – A list of the form [*L*₁, *L*₂, ..., *L*_{*n*}], where each *L*_{*i*} is a list of group weights on the *i*-th validation set.

Note: Weights are per-group for ranking tasks

In ranking task, one weight is assigned to each query group (not each data point). This is because we only care about the relative ordering of data points within each group, so it doesn't make sense to assign weights to individual data points.

- **base_margin_eval_set** (*Sequence*[*Any*] / *None*) – A list of the form [M_1, M_2, ..., M_n], where each M_i is an array like object storing base margin for the i-th validation set.
- **feature_weights** (*Any* / *None*) – Weight for each feature, defines the probability of each feature being selected when colsample is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence*[*TrainingCallback*] / *None*) – Deprecated since version 1.6.0: Use *callbacks* in `__init__()` or `set_params()` instead.

Return type

XGBRanker

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when fit was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A *MetadataRequest* encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

int

get_params(*deep=True*)

Get parameters.

Parameters

deep (*bool*) –

Return type

Dict[*str*, *Any*]

get_xgb_params()

Get xgboost specific parameters.

Return type

Dict[*str*, *Any*]

property intercept_: *ndarray*

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtree*).

Returns

intercept_

Return type

array of shape (1,) or [n_classes]

load_model(fname)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* / *bytearray* / *PathLike*) – Input file name or memory buffer(see also *save_raw*)

Return type

None

property n_features_in_: int

Number of features seen during *fit()*.

predict(X, output_margin=False, validate_features=True, base_margin=None, iteration_range=None)

Predict with X. If the model is trained with early stopping, then *best_iteration* is used automatically. The estimator uses *inplace_predict* by default and falls back to using *DMatrix* if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*Any*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's *feature_names* are identical. Otherwise, it is assumed that the *feature_names* are the same.
- **base_margin** (*Any* / *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* / *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying *iteration_range*=(10, 20), then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type
prediction

save_model(fname)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as `feature_names`) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* / *PathLike*) – Output file name

Return type

None

score(X, y)

Evaluate score for data using the last evaluation metric. If the model is trained with early stopping, then [best_iteration](#) is used automatically.

Parameters

- **X** (*Union[pd.DataFrame, cudf.DataFrame]*) – Feature matrix. A DataFrame with a special *qid* column.
- **y** (*Any*) – Labels

Returns

The result of the first evaluation metric for the ranker.

Return type

score

set_fit_request(*, *base_margin*='\$UNCHANGED\$', *base_margin_eval_set*='\$UNCHANGED\$', *callbacks*='\$UNCHANGED\$', *early_stopping_rounds*='\$UNCHANGED\$', *eval_group*='\$UNCHANGED\$', *eval_metric*='\$UNCHANGED\$', *eval_qid*='\$UNCHANGED\$', *eval_set*='\$UNCHANGED\$', *feature_weights*='\$UNCHANGED\$', *group*='\$UNCHANGED\$', *qid*='\$UNCHANGED\$', *sample_weight*='\$UNCHANGED\$', *sample_weight_eval_set*='\$UNCHANGED\$', *verbose*='\$UNCHANGED\$', *xgb_model*='\$UNCHANGED\$')

Request metadata passed to the `fit` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to `fit` if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to `fit`.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in fit.
- **base_margin_eval_set** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin_eval_set` parameter in fit.
- **callbacks** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `callbacks` parameter in fit.
- **early_stopping_rounds** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `early_stopping_rounds` parameter in fit.
- **eval_group** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_group` parameter in fit.
- **eval_metric** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_metric` parameter in fit.
- **eval_qid** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_qid` parameter in fit.
- **eval_set** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_set` parameter in fit.
- **feature_weights** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `feature_weights` parameter in fit.
- **group** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `group` parameter in fit.
- **qid** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `qid` parameter in fit.
- **sample_weight** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in fit.
- **sample_weight_eval_set** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight_eval_set` parameter in fit.

- **verbose** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for verbose parameter in fit.
- **xgb_model** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for xgb_model parameter in fit.
- **self** (*XGBRanker*) –

Returns

self – The updated object.

Return type

object

set_params(params)**

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

self

Parameters

params (*Any*) –

set_predict_request(*, *base_margin*='\$UNCHANGED\$', *iteration_range*='\$UNCHANGED\$', *output_margin*='\$UNCHANGED\$', *validate_features*='\$UNCHANGED\$')

Request metadata passed to the `predict` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- *True*: metadata is requested, and passed to `predict` if provided. The request is ignored if metadata is not provided.
- *False*: metadata is not requested and the meta-estimator will not pass it to `predict`.
- *None*: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- *str*: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for base_margin parameter in `predict`.

- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for iteration_range parameter in predict.
- **output_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for output_margin parameter in predict.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for validate_features parameter in predict.
- **self** (*XGBRanker*) –

Returns

self – The updated object.

Return type

object

```
class xgboost.XGBRFRegressor(*, learning_rate=1.0, subsample=0.8, colsample_bynode=0.8,
                             reg_lambda=1e-05, **kwargs)
```

Bases: *XGBRegressor*

scikit-learn API for XGBoost random forest regression. See [Using the Scikit-Learn Estimator Interface](#) for more information.

Parameters

- **n_estimators** (*Optional[int]*) – Number of trees in random forest to fit.
- **max_depth** (*Optional[int]*) – Maximum tree depth for base learners.
- **max_leaves** – Maximum number of leaves; 0 indicates no limit.
- **max_bin** – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional[float]*) – Boosting learning rate (xgb’s “eta”)
- **verbosity** (*Optional[int]*) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** (*Union[str, Callable[[numpy.ndarray, numpy.ndarray], Tuple[numpy.ndarray, numpy.ndarray]], NoneType]*) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional[str]*) – Specify which booster to use: gbtree, gblinear or dart.
- **tree_method** (*Optional[str]*) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It’s recommended to study this option from the parameters document [tree method](#)
- **n_jobs** (*Optional[int]*) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.
- **gamma** (*Optional[float]*) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.

- **min_child_weight** (*Optional[[float](#)]*) – Minimum sum of instance weight(hessian) needed in a child.
- **max_delta_step** (*Optional[[float](#)]*) – Maximum delta step we allow each tree’s weight estimation to be.
- **subsample** (*Optional[[float](#)]*) – Subsample ratio of the training instance.
- **sampling_method** –
Sampling method. Used only by the GPU version of hist tree method.
 - **uniform**: select random training instances uniformly.
 - **gradient_based** select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
- **colsample_bytree** (*Optional[[float](#)]*) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional[[float](#)]*) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional[[float](#)]*) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional[[float](#)]*) – L1 regularization term on weights (xgb’s alpha).
- **reg_lambda** (*Optional[[float](#)]*) – L2 regularization term on weights (xgb’s lambda).
- **scale_pos_weight** (*Optional[[float](#)]*) – Balancing of positive and negative weights.
- **base_score** (*Optional[[float](#)]*) – The initial prediction score of all instances, global bias.
- **random_state** (*Optional[Union[[numpy.random.RandomState](#), [int](#)]]*) – Random number seed.

Note: Using gblinear booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*[float](#), default [np.nan](#)*) – Value in the data which needs to be present as a missing value.
- **num_parallel_tree** (*Optional[[int](#)]*) – Used for boosting random forest.
- **monotone_constraints** (*Optional[Union[Dict[[str](#), [int](#)], [str](#)]]*) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional[Union[[str](#), List[Tuple[[str](#)]]]]*) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. [[0, 1], [2, 3, 4]], where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional[[str](#)]*) – The feature importance type for the `feature_importances_` property:
 - For tree model, it’s either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it’s the normalized coefficients without bias.
- **device** (*Optional[[str](#)]*) – New in version 2.0.0.
 Device ordinal, available options are *cpu*, *cuda*, and *gpu*.

- **validate_parameters** (*Optional*[*bool*]) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, `cudf/pandas.DataFrame` should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional*[*FeatureTypes*]) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See [DMatrix](#) for details.
- **max_cat_to_onehot** (*Optional*[*int*]) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, `enable_categorical` needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **max_cat_threshold** (*Optional*[*int*]) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, `enable_categorical` needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **multi_strategy** (*Optional*[*str*]) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.

- `one_output_per_tree`: One model for each target.
- `multi_output_tree`: Use multi-target trees.

- **eval_metric** (*Optional*[*Union*[*str*, *List*[*str*], *Callable*]]) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See `doc/parameter.rst`), one of the metrics in `sklearn.metrics`, or any other user defined metric that looks like `sklearn.metrics`.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the `scoring` parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces `eval_metric` in `fit()` method. The old one receives untransformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **early_stopping_rounds** (*Optional*[`int`]) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. Requires at least one item in **eval_set** in `fit()`.
 - If early stopping occurs, the model will have two additional attributes: `best_score` and `best_iteration`. These are used by the `predict()` and `apply()` methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the `iteration_range` in these inference methods. In addition, other utilities like model plotting can also use the entire model.
 - If you prefer to discard the trees after `best_iteration`, consider using the callback function [xgboost.callback.EarlyStopping](#).
 - If there's more than one item in **eval_set**, the last entry will be used for early stopping. If there's more than one metric in **eval_metric**, the last metric will be used for early stopping.

Note: This parameter replaces `early_stopping_rounds` in `fit()` method.

- **callbacks** (*Optional*[`List`[`TrainingCallback`]]) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using [Callback API](#).

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
    reg.fit(X, y)
```

- **kwargs** (*dict*, *optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found [here](#). Attempting to set a parameter via the constructor

args and ****kwargs** dict simultaneously will result in a `TypeError`.

Note: ****kwargs** unsupported by scikit-learn

****kwargs** is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

Note: Custom objective function

A custom objective function can be provided for the `objective` parameter. In this case, it should have the signature `objective(y_true, y_pred) -> grad, hess:`

y_true: array_like of shape `[n_samples]`

The target values

y_pred: array_like of shape `[n_samples]`

The predicted values

grad: array_like of shape `[n_samples]`

The value of the gradient for each sample point.

hess: array_like of shape `[n_samples]`

The value of the second derivative for each sample point

apply(*X*, *iteration_range=None*)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then `best_iteration` is used automatically.

Parameters

- **X** (array_like, shape=`[n_samples, n_features]`) – Input features matrix.
- **iteration_range** (`Tuple[int, int] | None`) – See `predict()`.

Returns

X_leaves – For each datapoint *x* in *X* and for each tree, return the index of the leaf *x* ends up in. Leaves are numbered within `[0; 2**(self.max_depth+1))`, possibly with gaps in the numbering.

Return type

array_like, shape=`[n_samples, n_trees]`

property best_iteration: `int`

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then `best_iteration` is 0.

property best_score: `float`

The best score obtained by early stopping.

property coef_: `ndarray`

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (`booster=gblinear`). It is not defined for other base learner types, such as tree learners (`booster=gbtrees`).

Returns**coef_****Return type**array of shape `[n_features]` or `[n_classes, n_features]`**evals_result()**

Return the evaluation results.

If **eval_set** is passed to the `fit()` function, you can call `evals_result()` to get evaluation results for all passed **eval_sets**. When **eval_metric** is also passed to the `fit()` function, the **evals_result** will contain the **eval_metrics** passed to the `fit()` function.

The returned evaluation result is a dictionary:

```
{'validation_0': {'logloss': ['0.604835', '0.531479']},
 'validation_1': {'logloss': ['0.41965', '0.17686']}}
```

Return type**evals_result****property feature_importances_: ndarray**

Feature importances property, return depends on *importance_type* parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- **feature_importances_** (array of shape `[n_features]` except for multi-class)
- linear model, which returns an array with shape `(n_features, n_classes)`

property feature_names_in_: ndarray

Names of features seen during `fit()`. Defined only when *X* has feature names that are all strings.

fit(*X*, *y*, *, *sample_weight*=None, *base_margin*=None, *eval_set*=None, *eval_metric*=None, *early_stopping_rounds*=None, *verbose*=True, *xgb_model*=None, *sample_weight_eval_set*=None, *base_margin_eval_set*=None, *feature_weights*=None, *callbacks*=None)

Fit gradient boosting model.

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- **X** (*Any*) – Feature matrix. See *Supported data structures for various XGBoost functions* for a list of supported types.

When the `tree_method` is set to `hist`, internally, the *QuantileDMatrix* will be used instead of the *DMatrix* for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (*Any*) – Labels
- **sample_weight** (*Any* / None) – instance weights
- **base_margin** (*Any* / None) – global bias for each instance.

- **eval_set** (*Sequence*[*Tuple*[*Any*, *Any*]] | *None*) – A list of (X, y) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_metric** (*str*, *list of str*, or *callable*, *optional*) – Deprecated since version 1.6.0.
Use *eval_metric* in `__init__()` or *set_params()* instead.
- **early_stopping_rounds** (*int*) – Deprecated since version 1.6.0.
Use *early_stopping_rounds* in `__init__()` or *set_params()* instead.
- **verbose** (*bool* | *int* | *None*) – If *verbose* is True and an evaluation set is used, the evaluation metric measured on the validation set is printed to stdout at each boosting stage. If *verbose* is an integer, the evaluation metric is printed at each *verbose* boosting stage. The last boosting stage / the boosting stage found by using *early_stopping_rounds* is also printed.
- **xgb_model** (*Booster* | *str* | *XGBModel* | *None*) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (*Sequence*[*Any*] | *None*) – A list of the form [L_1, L_2, ..., L_n], where each L_i is an array like object storing instance weights for the i-th validation set.
- **base_margin_eval_set** (*Sequence*[*Any*] | *None*) – A list of the form [M_1, M_2, ..., M_n], where each M_i is an array like object storing base margin for the i-th validation set.
- **feature_weights** (*Any* | *None*) – Weight for each feature, defines the probability of each feature being selected when *colsample* is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence*[*TrainingCallback*] | *None*) – Deprecated since version 1.6.0: Use *callbacks* in `__init__()` or *set_params()* instead.

Return type

XGBRFRegressor

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when fit was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A *MetadataRequest* encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

`int`

get_params(*deep=True*)

Get parameters.

Parameters

deep (*bool*) –

Return type

`Dict[str, Any]`

get_xgb_params()

Get xgboost specific parameters.

Return type

`Dict[str, Any]`

property intercept_: ndarray

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

intercept_

Return type

array of shape (1,) or [n_classes]

load_model(*fname*)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* / *bytearray* / *PathLike*) – Input file name or memory buffer(see also *save_raw*)

Return type

`None`

property n_features_in_: int

Number of features seen during *fit()*.

predict(*X*, *output_margin=False*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict with *X*. If the model is trained with early stopping, then *best_iteration* is used automatically. The estimator uses *inplace_predict* by default and falls back to using *DMatrix* if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*Any*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's *feature_names* are identical. Otherwise, it is assumed that the *feature_names* are the same.
- **base_margin** (*Any* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying *iteration_range=(10, 20)*, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type

prediction

save_model(*fname*)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See *Model IO* for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* | *PathLike*) – Output file name

Return type

None

score(*X*, *y*, *sample_weight=None*)

Return the coefficient of determination of the prediction.

The coefficient of determination R^2 is defined as $(1 - \frac{u}{v})$, where u is the residual sum of squares $((y_true - y_pred)** 2).sum()$ and v is the total sum of squares $((y_true - y_true.mean())** 2).sum()$. The best possible score is 1.0 and it can be negative (because the model can be arbitrarily worse). A constant model that always predicts the expected value of y , disregarding the input features, would get a R^2 score of 0.0.

Parameters

- **X** (*array-like of shape (n_samples, n_features)*) – Test samples. For some estimators this may be a precomputed kernel matrix or a list of generic objects instead with shape (n_samples, n_samples_fitted), where n_samples_fitted is the number of samples used in the fitting for the estimator.
- **y** (*array-like of shape (n_samples,) or (n_samples, n_outputs)*) – True values for X.
- **sample_weight** (*array-like of shape (n_samples,)*, default=None) – Sample weights.

Returns

score – R^2 of self.predict(X) w.r.t. y.

Return type

float

Notes

The R^2 score used when calling **score** on a regressor uses `multioutput='uniform_average'` from version 0.23 to keep consistent with default value of `r2_score()`. This influences the **score** method of all the multioutput regressors (except for `MultiOutputRegressor`).

```
set_fit_request(*, base_margin='$UNCHANGED$', base_margin_eval_set='$UNCHANGED$',
                 callbacks='$UNCHANGED$', early_stopping_rounds='$UNCHANGED$',
                 eval_metric='$UNCHANGED$', eval_set='$UNCHANGED$',
                 feature_weights='$UNCHANGED$', sample_weight='$UNCHANGED$',
                 sample_weight_eval_set='$UNCHANGED$', verbose='$UNCHANGED$',
                 xgb_model='$UNCHANGED$')
```

Request metadata passed to the **fit** method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to **fit** if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to **fit**.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *base_margin* parameter in fit.
- **base_margin_eval_set** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *base_margin_eval_set* parameter in fit.
- **callbacks** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *callbacks* parameter in fit.
- **early_stopping_rounds** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *early_stopping_rounds* parameter in fit.
- **eval_metric** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *eval_metric* parameter in fit.
- **eval_set** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *eval_set* parameter in fit.
- **feature_weights** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *feature_weights* parameter in fit.
- **sample_weight** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *sample_weight* parameter in fit.
- **sample_weight_eval_set** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *sample_weight_eval_set* parameter in fit.
- **verbose** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *verbose* parameter in fit.
- **xgb_model** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *xgb_model* parameter in fit.
- **self** (*XGBRFRegressor*) –

Returns

self – The updated object.

Return type

object

set_params(params)**

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

self

Parameters

params (*Any*) –

set_predict_request(**, base_margin*='UNCHANGED\$', *iteration_range*='UNCHANGED\$',
output_margin='UNCHANGED\$', *validate_features*='UNCHANGED\$')

Request metadata passed to the `predict` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `predict` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `predict`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in `predict`.
- **iteration_range** (*str*, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `iteration_range` parameter in `predict`.
- **output_margin** (*str*, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `output_margin` parameter in `predict`.
- **validate_features** (*str*, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `validate_features` parameter in `predict`.
- **self** (`XGBRFRegressor`) –

Returns

self – The updated object.

Return type

object

set_score_request(**, sample_weight*='UNCHANGED\$')

Request metadata passed to the `score` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `score` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `score`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **sample_weight** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in `score`.
- **self** (`XGBRFRegressor`) –

Returns

self – The updated object.

Return type

`object`

```
class xgboost.XGBRFClassifier(*, learning_rate=1.0, subsample=0.8, colsample_bynode=0.8,
                             reg_lambda=1e-05, **kwargs)
```

Bases: [XGBClassifier](#)

scikit-learn API for XGBoost random forest classification. See [Using the Scikit-Learn Estimator Interface](#) for more information.

Parameters

- **n_estimators** (*Optional* [`int`]) – Number of trees in random forest to fit.
- **max_depth** (*Optional* [`int`]) – Maximum tree depth for base learners.
- **max_leaves** – Maximum number of leaves; 0 indicates no limit.
- **max_bin** – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional* [`float`]) – Boosting learning rate (xgb’s “eta”)
- **verbosity** (*Optional* [`int`]) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).

- **objective** (*Union*[*str*, *Callable*[[*numpy.ndarray*, *numpy.ndarray*], *Tuple*[*numpy.ndarray*, *numpy.ndarray*]], *NoneType*]) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
 - **booster** (*Optional*[*str*]) – Specify which booster to use: gbtrees, gblinear or dart.
 - **tree_method** (*Optional*[*str*]) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It's recommended to study this option from the parameters document [tree method](#)
 - **n_jobs** (*Optional*[*int*]) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.
 - **gamma** (*Optional*[*float*]) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
 - **min_child_weight** (*Optional*[*float*]) – Minimum sum of instance weight(hessian) needed in a child.
 - **max_delta_step** (*Optional*[*float*]) – Maximum delta step we allow each tree's weight estimation to be.
 - **subsample** (*Optional*[*float*]) – Subsample ratio of the training instance.
 - **sampling_method** –
Sampling method. Used only by the GPU version of hist tree method.
 - uniform: select random training instances uniformly.
 - gradient_based select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
 - **colsample_bytree** (*Optional*[*float*]) – Subsample ratio of columns when constructing each tree.
 - **colsample_bylevel** (*Optional*[*float*]) – Subsample ratio of columns for each level.
 - **colsample_bynode** (*Optional*[*float*]) – Subsample ratio of columns for each split.
 - **reg_alpha** (*Optional*[*float*]) – L1 regularization term on weights (xgb's alpha).
 - **reg_lambda** (*Optional*[*float*]) – L2 regularization term on weights (xgb's lambda).
 - **scale_pos_weight** (*Optional*[*float*]) – Balancing of positive and negative weights.
 - **base_score** (*Optional*[*float*]) – The initial prediction score of all instances, global bias.
 - **random_state** (*Optional*[*Union*[*numpy.random.RandomState*, *int*]]) – Random number seed.
-
- Note:** Using gblinear booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.
-
- **missing** (*float*, *default np.nan*) – Value in the data which needs to be present as a missing value.
 - **num_parallel_tree** (*Optional*[*int*]) – Used for boosting random forest.

- **monotone_constraints** (*Optional[Union[Dict[str, int], str]]*) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional[Union[str, List[Tuple[str]]]]*) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. `[[0, 1], [2, 3, 4]]`, where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional[str]*) – The feature importance type for the `feature_importances_` property:
 - For tree model, it's either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it's the normalized coefficients without bias.
- **device** (*Optional[str]*) – New in version 2.0.0.
Device ordinal, available options are `cpu`, `cuda`, and `gpu`.
- **validate_parameters** (*Optional[bool]*) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, `cudf/pandas.DataFrame` should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional[FeatureTypes]*) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See [DMatrix](#) for details.
- **max_cat_to_onehot** (*Optional[int]*) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, `enable_categorical` needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **max_cat_threshold** (*Optional[int]*) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, `enable_categorical` needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **multi_strategy** (*Optional[str]*) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.

- `one_output_per_tree`: One model for each target.
- `multi_output_tree`: Use multi-target trees.

- **`eval_metric`** (*Optional[Union[str, List[str], Callable]]*) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See [doc/parameter.rst](#)), one of the metrics in [sklearn.metrics](#), or any other user defined metric that looks like [sklearn.metrics](#).

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the `scoring` parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces `eval_metric` in `fit()` method. The old one receives untransformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **`early_stopping_rounds`** (*Optional[int]*) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **`early_stopping_rounds`** round(s) to continue training. Requires at least one item in `eval_set` in `fit()`.
 - If early stopping occurs, the model will have two additional attributes: `best_score` and `best_iteration`. These are used by the `predict()` and `apply()` methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the `iteration_range` in these inference methods. In addition, other utilities like model plotting can also use the entire model.
 - If you prefer to discard the trees after `best_iteration`, consider using the callback function [xgboost.callback.EarlyStopping](#).
 - If there's more than one item in `eval_set`, the last entry will be used for early stopping. If there's more than one metric in `eval_metric`, the last metric will be used for early stopping.

Note: This parameter replaces *early_stopping_rounds* in *fit()* method.

- **callbacks** (*Optional [List [TrainingCallback]]*) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using *Callback API*.

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
    reg.fit(X, y)
```

- **kwargs** (*dict, optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found *here*. Attempting to set a parameter via the constructor args and **kwargs** dict simultaneously will result in a *TypeError*.

Note: **kwargs** unsupported by scikit-learn

kwargs is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

Note: Custom objective function

A custom objective function can be provided for the objective parameter. In this case, it should have the signature `objective(y_true, y_pred) -> grad, hess:`

y_true: *array_like* of shape `[n_samples]`

The target values

y_pred: *array_like* of shape `[n_samples]`

The predicted values

grad: *array_like* of shape `[n_samples]`

The value of the gradient for each sample point.

hess: *array_like* of shape `[n_samples]`

The value of the second derivative for each sample point

apply(*X, iteration_range=None*)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then *best_iteration* is used automatically.

Parameters

- **X** (*array_like, shape=[n_samples, n_features]*) – Input features matrix.
- **iteration_range** (*Tuple[int, int] | None*) – See *predict()*.

Returns

X_leaves – For each datapoint *x* in *X* and for each tree, return the index of the leaf *x* ends up

in. Leaves are numbered within $[0; 2^{**}(\text{self.max_depth}+1))$, possibly with gaps in the numbering.

Return type

array_like, shape=[n_samples, n_trees]

property best_iteration: `int`

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then best_iteration is 0.

property best_score: `float`

The best score obtained by early stopping.

property coef_: `ndarray`

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

coef_

Return type

array of shape [n_features] or [n_classes, n_features]

evals_result()

Return the evaluation results.

If **eval_set** is passed to the `fit()` function, you can call `evals_result()` to get evaluation results for all passed **eval_sets**. When **eval_metric** is also passed to the `fit()` function, the **evals_result** will contain the **eval_metrics** passed to the `fit()` function.

The returned evaluation result is a dictionary:

```
{'validation_0': {'logloss': ['0.604835', '0.531479']},
 'validation_1': {'logloss': ['0.41965', '0.17686']}}
```

Return type

evals_result

property feature_importances_: `ndarray`

Feature importances property, return depends on *importance_type* parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- **feature_importances_** (array of shape [n_features] except for multi-class)
- linear model, which returns an array with shape (n_features, n_classes)

property feature_names_in_: `ndarray`

Names of features seen during `fit()`. Defined only when X has feature names that are all strings.

```
fit(X, y, *, sample_weight=None, base_margin=None, eval_set=None, eval_metric=None,
    early_stopping_rounds=None, verbose=True, xgb_model=None, sample_weight_eval_set=None,
    base_margin_eval_set=None, feature_weights=None, callbacks=None)
```

Fit gradient boosting classifier.

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- **X** (*Any*) – Feature matrix. See *Supported data structures for various XGBoost functions* for a list of supported types.

When the `tree_method` is set to `hist`, internally, the *QuantileDMatrix* will be used instead of the *DMatrix* for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (*Any*) – Labels
- **sample_weight** (*Any* / *None*) – instance weights
- **base_margin** (*Any* / *None*) – global bias for each instance.
- **eval_set** (*Sequence*[*Tuple*[*Any*, *Any*]] / *None*) – A list of (X, y) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_metric** (*str*, *list of str*, or *callable*, *optional*) – Deprecated since version 1.6.0.

Use `eval_metric` in `__init__()` or `set_params()` instead.

- **early_stopping_rounds** (*int*) – Deprecated since version 1.6.0.

Use `early_stopping_rounds` in `__init__()` or `set_params()` instead.

- **verbose** (*bool* / *int* / *None*) – If `verbose` is `True` and an evaluation set is used, the evaluation metric measured on the validation set is printed to stdout at each boosting stage. If `verbose` is an integer, the evaluation metric is printed at each `verbose` boosting stage. The last boosting stage / the boosting stage found by using `early_stopping_rounds` is also printed.
- **xgb_model** (*Booster* / *str* / *XGBModel* / *None*) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (*Sequence*[*Any*] / *None*) – A list of the form [L_1, L_2, ..., L_n], where each L_i is an array like object storing instance weights for the i-th validation set.
- **base_margin_eval_set** (*Sequence*[*Any*] / *None*) – A list of the form [M_1, M_2, ..., M_n], where each M_i is an array like object storing base margin for the i-th validation set.
- **feature_weights** (*Any* / *None*) – Weight for each feature, defines the probability of each feature being selected when `colsample` is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence*[*TrainingCallback*] / *None*) – Deprecated since version 1.6.0: Use `callbacks` in `__init__()` or `set_params()` instead.

Return type

`XGBRFClassifier`

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when fit was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A MetadataRequest encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

`int`

get_params(deep=True)

Get parameters.

Parameters

deep (*bool*) –

Return type

`Dict[str, Any]`

get_xgb_params()

Get xgboost specific parameters.

Return type

`Dict[str, Any]`

property intercept_: ndarray

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

intercept_

Return type

array of shape (1,) or [n_classes]

load_model(*fname*)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as `feature_names`) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* | *bytearray* | *PathLike*) – Input file name or memory buffer(see also `save_raw`)

Return type

None

property `n_features_in_`: *int*

Number of features seen during `fit()`.

predict(*X*, *output_margin=False*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict with *X*. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*Any*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (*Any* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying `iteration_range=(10, 20)`, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type

prediction

predict_proba(*X*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict the probability of each *X* example being of a given class. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*Any*) – Feature matrix. See *Supported data structures for various XGBoost functions* for a list of supported types.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's feature_names are identical. Otherwise, it is assumed that the feature_names are the same.
- **base_margin** (*Any* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying *iteration_range=(10, 20)*, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

Returns

a numpy array of shape array-like of shape (n_samples, n_classes) with the probability of each data example being of a given class.

Return type

prediction

save_model(fname)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as feature_names) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See *Model IO* for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* | *PathLike*) – Output file name

Return type

None

score(X, y, sample_weight=None)

Return the mean accuracy on the given test data and labels.

In multi-label classification, this is the subset accuracy which is a harsh metric since you require for each sample that each label set be correctly predicted.

Parameters

- **X** (*array-like of shape (n_samples, n_features)*) – Test samples.
- **y** (*array-like of shape (n_samples,) or (n_samples, n_outputs)*) – True labels for X.
- **sample_weight** (*array-like of shape (n_samples,)*, *default=None*) – Sample weights.

Returns

score – Mean accuracy of `self.predict(X)` w.r.t. y.

Return type

float

```
set_fit_request(*, base_margin='$UNCHANGED$', base_margin_eval_set='$UNCHANGED$',
               callbacks='$UNCHANGED$', early_stopping_rounds='$UNCHANGED$',
               eval_metric='$UNCHANGED$', eval_set='$UNCHANGED$',
               feature_weights='$UNCHANGED$', sample_weight='$UNCHANGED$',
               sample_weight_eval_set='$UNCHANGED$', verbose='$UNCHANGED$',
               xgb_model='$UNCHANGED$')
```

Request metadata passed to the fit method.

Note that this method is only relevant if `enable_metadata_routing=True` (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to fit if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to fit.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in fit.
- **base_margin_eval_set** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin_eval_set` parameter in fit.
- **callbacks** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `callbacks` parameter in fit.
- **early_stopping_rounds** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `early_stopping_rounds` parameter in fit.
- **eval_metric** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_metric` parameter in fit.
- **eval_set** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_set` parameter in fit.
- **feature_weights** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `feature_weights` parameter in fit.

- **sample_weight** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `sample_weight` parameter in `fit`.
- **sample_weight_eval_set** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `sample_weight_eval_set` parameter in `fit`.
- **verbose** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `verbose` parameter in `fit`.
- **xgb_model** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `xgb_model` parameter in `fit`.
- **self** (`XGBRFClassifier`) –

Returns

self – The updated object.

Return type

object

set_params(***params*)

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

self

Parameters

params (*Any*) –

set_predict_proba_request(**, base_margin='\$UNCHANGED\$', iteration_range='\$UNCHANGED\$', validate_features='\$UNCHANGED\$'*)

Request metadata passed to the `predict_proba` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- *True*: metadata is requested, and passed to `predict_proba` if provided. The request is ignored if metadata is not provided.
- *False*: metadata is not requested and the meta-estimator will not pass it to `predict_proba`.
- *None*: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- *str*: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for base_margin parameter in predict_proba.
- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for iteration_range parameter in predict_proba.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for validate_features parameter in predict_proba.
- **self** ([XGBRFClassifier](#)) –

Returns

self – The updated object.

Return type

object

set_predict_request(*, *base_margin*='UNCHANGED\$', *iteration_range*='UNCHANGED\$', *output_margin*='UNCHANGED\$', *validate_features*='UNCHANGED\$')

Request metadata passed to the predict method.

Note that this method is only relevant if `enable_metadata_routing=True` (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to predict if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to predict.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for base_margin parameter in predict.

- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `iteration_range` parameter in `predict`.
- **output_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `output_margin` parameter in `predict`.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `validate_features` parameter in `predict`.
- **self** (`XGBRFClassifier`) –

Returns

self – The updated object.

Return type

`object`

set_score_request(*, *sample_weight*='UNCHANGED\$')

Request metadata passed to the `score` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `score` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `score`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **sample_weight** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `sample_weight` parameter in `score`.
- **self** (`XGBRFClassifier`) –

Returns

self – The updated object.

Return type

`object`

Plotting API

Plotting Library.

```
xgboost.plot_importance(booster, ax=None, height=0.2, xlim=None, ylim=None, title='Feature importance',
                        xlabel='F score', ylabel='Features', fmap="", importance_type='weight',
                        max_num_features=None, grid=True, show_values=True, values_format='{v}',
                        **kwargs)
```

Plot importance based on fitted trees.

Parameters

- **booster** (*XGBModel* / *Booster* / *dict*) – Booster or XGBModel instance, or dict taken by `Booster.get_fscore()`
- **ax** (*matplotlib Axes*) – Target axes instance. If None, new figure and axes will be created.
- **grid** (*bool*) – Turn the axes grids on or off. Default is True (On).
- **importance_type** (*str*) – How the importance is calculated: either “weight”, “gain”, or “cover”
 - “weight” is the number of times a feature appears in a tree
 - “gain” is the average gain of splits which use the feature
 - “cover” is the average coverage of splits which use the feature where coverage is defined as the number of samples affected by the split
- **max_num_features** (*int* / *None*) – Maximum number of top features displayed on plot. If None, all features will be displayed.
- **height** (*float*) – Bar height, passed to `ax.barh()`
- **xlim** (*tuple* / *None*) – Tuple passed to `axes.xlim()`
- **ylim** (*tuple* / *None*) – Tuple passed to `axes.ylim()`
- **title** (*str*) – Axes title. To disable, pass None.
- **xlabel** (*str*) – X axis title label. To disable, pass None.
- **ylabel** (*str*) – Y axis title label. To disable, pass None.
- **fmap** (*str* / *PathLike*) – The name of feature map file.
- **show_values** (*bool*) – Show values on plot. To disable, pass False.
- **values_format** (*str*) – Format string for values. “v” will be replaced by the value of the feature importance. e.g. Pass “{v:.2f}” in order to limit the number of digits after the decimal point to two, for each value printed on the graph.
- **kwargs** (*Any*) – Other keywords passed to `ax.barh()`

Returns

`ax`

Return type

`matplotlib Axes`

```
xgboost.plot_tree(booster, fmap="", num_trees=0, rankdir=None, ax=None, **kwargs)
```

Plot specified tree.

Parameters

- **booster** (*Booster*, *XGBModel*) – Booster or XGBModel instance

- **fmap** (*str* (optional)) – The name of feature map file
- **num_trees** (*int*, default 0) – Specify the ordinal number of target tree
- **rankdir** (*str*, default "TB") – Passed to graphviz via graph_attr
- **ax** (*matplotlib Axes*, default None) – Target axes instance. If None, new figure and axes will be created.
- **kwargs** (*Any*) – Other keywords passed to to_graphviz

Returns

ax

Return type

matplotlib Axes

`xgboost.to_graphviz(booster, fmap="", num_trees=0, rankdir=None, yes_color=None, no_color=None, condition_node_params=None, leaf_node_params=None, **kwargs)`

Convert specified tree to graphviz instance. IPython can automatically plot the returned graphviz instance. Otherwise, you should call `.render()` method of the returned graphviz instance.

Parameters

- **booster** (*Booster* | *XGBModel*) – Booster or XGBModel instance
- **fmap** (*str* | *PathLike*) – The name of feature map file
- **num_trees** (*int*) – Specify the ordinal number of target tree
- **rankdir** (*str* | *None*) – Passed to graphviz via graph_attr
- **yes_color** (*str* | *None*) – Edge color when meets the node condition.
- **no_color** (*str* | *None*) – Edge color when doesn't meet the node condition.
- **condition_node_params** (*dict* | *None*) – Condition node configuration for for graphviz. Example:

```
{'shape': 'box',
 'style': 'filled,rounded',
 'fillcolor': '#78bceb'}
```

- **leaf_node_params** (*dict* | *None*) – Leaf node configuration for graphviz. Example:

```
{'shape': 'box',
 'style': 'filled',
 'fillcolor': '#e48038'}
```

- **kwargs** (*Any*) – Other keywords passed to graphviz graph_attr, e.g. `graph [{key} = {value}]`

Returns

graph

Return type

graphviz.Source

Callback API

Callback library containing training routines. See [Callback Functions](#) for a quick introduction.

class xgboost.callback.**TrainingCallback**

Interface for training callback.

New in version 1.3.0.

after_iteration(*model*, *epoch*, *evals_log*)

Run after each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –
- **evals_log** (*Dict[str, Dict[str, List[float]] | List[Tuple[float, float]]]*) –

Return type

bool

after_training(*model*)

Run after training is finished.

Parameters

- **model** (*Any*) –

Return type

Any

before_iteration(*model*, *epoch*, *evals_log*)

Run before each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –
- **evals_log** (*Dict[str, Dict[str, List[float]] | List[Tuple[float, float]]]*) –

Return type

bool

before_training(*model*)

Run before training starts.

Parameters

- **model** (*Any*) –

Return type

Any

class xgboost.callback.**EvaluationMonitor**(*rank=0*, *period=1*, *show_stdv=False*)

Bases: [TrainingCallback](#)

Print the evaluation result at each iteration.

New in version 1.3.0.

Parameters

- **rank** (*int*) – Which worker should be used for printing the result.
- **period** (*int*) – How many epoches between printing.
- **show_stdv** (*bool*) – Used in cv to show standard deviation. Users should not specify it.

after_iteration(*model*, *epoch*, *evals_log*)

Run after each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –
- **evals_log** (*(Dict[str, Dict[str, List[float]] | List[Tuple[float, float]]])*) –

Return type

bool

after_training(*model*)

Run after training is finished.

Parameters

- **model** (*Any*) –

Return type

Any

before_iteration(*model*, *epoch*, *evals_log*)

Run before each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –
- **evals_log** (*(Dict[str, Dict[str, List[float]] | List[Tuple[float, float]]])*) –

Return type

bool

before_training(*model*)

Run before training starts.

Parameters

- **model** (*Any*) –

Return type

Any

class xgboost.callback.**EarlyStopping**(*rounds*, *metric_name=None*, *data_name=None*, *maximize=None*, *save_best=False*, *min_delta=0.0*)

Bases: *TrainingCallback*

Callback function for early stopping

New in version 1.3.0.

Parameters

- **rounds** (*int*) – Early stopping rounds.
- **metric_name** (*str* / *None*) – Name of metric that is used for early stopping.
- **data_name** (*str* / *None*) – Name of dataset that is used for early stopping.
- **maximize** (*bool* / *None*) – Whether to maximize evaluation metric. *None* means auto (discouraged).
- **save_best** (*bool* / *None*) – Whether training should return the best model or the last model.
- **min_delta** (*float*) – New in version 1.5.0.

Minimum absolute change in score to be qualified as an improvement.

Examples

```
es = xgboost.callback.EarlyStopping(
    rounds=2,
    min_delta=1e-3,
    save_best=True,
    maximize=False,
    data_name="validation_0",
    metric_name="mlogloss",
)
clf = xgboost.XGBClassifier(tree_method="hist", device="cuda", callbacks=[es])

X, y = load_digits(return_X_y=True)
clf.fit(X, y, eval_set=[(X, y)])
```

after_iteration(*model*, *epoch*, *evals_log*)

Run after each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –
- **evals_log** (*Dict[str, Dict[str, List[float]]* / *List[Tuple[float, float]]*) –

Return type

bool

after_training(*model*)

Run after training is finished.

Parameters

- **model** (*Any*) –

Return type

Any

before_iteration(*model*, *epoch*, *evals_log*)

Run before each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –
- **evals_log** (*Dict[str, Dict[str, List[float]] | List[Tuple[float, float]]]*) –

Return type

bool

before_training(*model*)

Run before training starts.

Parameters

model (*Any*) –

Return type

Any

class xgboost.callback.**LearningRateScheduler**(*learning_rates*)

Bases: *TrainingCallback*

Callback function for scheduling learning rate.

New in version 1.3.0.

Parameters

learning_rates (*Callable[[int], float] | Sequence[float]*) – If it's a callable object, then it should accept an integer parameter *epoch* and returns the corresponding learning rate. Otherwise it should be a sequence like list or tuple with the same size of boosting rounds.

after_iteration(*model, epoch, evals_log*)

Run after each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –
- **evals_log** (*Dict[str, Dict[str, List[float]] | List[Tuple[float, float]]]*) –

Return type

bool

after_training(*model*)

Run after training is finished.

Parameters

model (*Any*) –

Return type

Any

before_iteration(*model, epoch, evals_log*)

Run before each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –

- **evals_log** (*Dict[str, Dict[str, List[float] | List[Tuple[float, float]]]]*) –

Return type

bool

before_training(*model*)

Run before training starts.

Parameters

- **model** (*Any*) –

Return type

Any

class xgboost.callback.**TrainingCheckpoint**(*directory*, *name*='model', *as_pickle*=False, *iterations*=100)

Bases: *TrainingCallback*

Checkpointing operation.

New in version 1.3.0.

Parameters

- **directory** (*str* | *PathLike*) – Output model directory.
- **name** (*str*) – pattern of output model file. Models will be saved as name_0.json, name_1.json, name_2.json
- **as_pickle** (*bool*) – When set to True, all training parameters will be saved in pickle format, instead of saving only the model.
- **iterations** (*int*) – Interval of checkpointing. Checkpointing is slow so setting a larger number can reduce performance hit.

after_iteration(*model*, *epoch*, *evals_log*)

Run after each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –
- **epoch** (*int*) –
- **evals_log** (*Dict[str, Dict[str, List[float] | List[Tuple[float, float]]]]*) –

Return type

bool

after_training(*model*)

Run after training is finished.

Parameters

- **model** (*Any*) –

Return type

Any

before_iteration(*model*, *epoch*, *evals_log*)

Run before each iteration. Return True when training should stop.

Parameters

- **model** (*Any*) –

- **epoch** (*int*) –
- **evals_log** (*Dict[str, Dict[str, List[float] | List[Tuple[float, float]]]]*) –

Return type

bool

before_training(*model*)

Run before training starts.

Parameters

model (*Any*) –

Return type

Any

Dask API

Dask extensions for distributed training

See *Distributed XGBoost with Dask* for simple tutorial. Also *XGBoost Dask Feature Walkthrough* for some examples.

There are two sets of APIs in this module, one is the functional API including `train` and `predict` methods. Another is stateful Scikit-Learner wrapper inherited from single-node Scikit-Learn interface.

The implementation is heavily influenced by `dask_xgboost`: <https://github.com/dask/dask-xgboost>

Optional dask configuration

- **xgboost.scheduler_address**: Specify the scheduler address, see *Troubleshooting*.

New in version 1.6.0.

```
dask.config.set({"xgboost.scheduler_address": "192.0.0.100"})
# We can also specify the port.
dask.config.set({"xgboost.scheduler_address": "192.0.0.100:12345"})
```

class `xgboost.dask.DaskDMatrix`(*client*, *data*, *label=None*, *, *weight=None*, *base_margin=None*, *missing=None*, *silent=False*, *feature_names=None*, *feature_types=None*, *group=None*, *qid=None*, *label_lower_bound=None*, *label_upper_bound=None*, *feature_weights=None*, *enable_categorical=False*)

Bases: `object`

DMatrix holding on references to Dask DataFrame or Dask Array. Constructing a *DaskDMatrix* forces all lazy computation to be carried out. Wait for the input data explicitly if you want to see actual computation of constructing *DaskDMatrix*.

See doc for `xgboost.DMatrix` constructor for other parameters. *DaskDMatrix* accepts only dask collection.

Note: *DaskDMatrix* does not repartition or move data between workers. It's the caller's responsibility to balance the data.

New in version 1.0.0.

Parameters

- **client** (*distributed.Client*) – Specify the dask client used for training. Use default client returned from dask if it's set to None.
- **data** (*da.Array* | *dd.DataFrame*) –
- **label** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **weight** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **missing** (*float* | *None*) –
- **silent** (*bool*) –
- **feature_names** (*Sequence[str]* | *None*) –
- **feature_types** (*Sequence[str]* | *None*) –
- **group** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **qid** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **label_lower_bound** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **label_upper_bound** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **feature_weights** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **enable_categorical** (*bool*) –

num_col()

Get the number of columns (features) in the DMatrix.

Return type

number of columns

```
class xgboost.dask.DaskQuantileDMatrix(client, data, label=None, *, weight=None, base_margin=None,
                                       missing=None, silent=False, feature_names=None,
                                       feature_types=None, max_bin=None, ref=None, group=None,
                                       qid=None, label_lower_bound=None, label_upper_bound=None,
                                       feature_weights=None, enable_categorical=False)
```

Bases: [DaskDMatrix](#)

A dask version of QuantileDMatrix.

Parameters

- **client** (*distributed.Client*) –
- **data** (*da.Array* | *dd.DataFrame*) –
- **label** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **weight** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) –
- **missing** (*float* | *None*) –
- **silent** (*bool*) –
- **feature_names** (*Sequence[str]* | *None*) –
- **feature_types** (*Any* | *List[Any]* | *None*) –

- `max_bin` (`int` | `None`) –
- `ref` (`DMatrix` | `None`) –
- `group` (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) –
- `qid` (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) –
- `label_lower_bound` (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) –
- `label_upper_bound` (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) –
- `feature_weights` (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) –
- `enable_categorical` (`bool`) –

`num_col()`

Get the number of columns (features) in the DMatrix.

Return type

number of columns

```
xgboost.dask.train(client, params, dtrain, num_boost_round=10, *, evals=None, obj=None, feval=None,
                    early_stopping_rounds=None, xgb_model=None, verbose_eval=True, callbacks=None,
                    custom_metric=None)
```

Train XGBoost model.

New in version 1.0.0.

Note: Other parameters are the same as `xgboost.train()` except for `evals_result`, which is returned as part of function return value instead of argument.

Parameters

- `client` (`distributed.Client`) – Specify the dask client used for training. Use default client returned from dask if it's set to None.
- `params` (`Dict[str, Any]`) –
- `dtrain` (`DaskDMatrix`) –
- `num_boost_round` (`int`) –
- `evals` (`Sequence[Tuple[DaskDMatrix, str]]` | `None`) –
- `obj` (`Callable[[ndarray, DMatrix], Tuple[ndarray, ndarray]]` | `None`) –
- `feval` (`Callable[[ndarray, DMatrix], Tuple[str, float]]` | `None`) –
- `early_stopping_rounds` (`int` | `None`) –
- `xgb_model` (`Booster` | `None`) –
- `verbose_eval` (`int` | `bool`) –
- `callbacks` (`Sequence[TrainingCallback]` | `None`) –
- `custom_metric` (`Callable[[ndarray, DMatrix], Tuple[str, float]]` | `None`) –

Returns

results – A dictionary containing trained booster and evaluation history. *history* field is the same as *eval_result* from `xgboost.train`.

```
{'booster': xgboost.Booster,  
  'history': {'train': {'logloss': ['0.48253', '0.35953']},  
             'eval': {'logloss': ['0.480385', '0.357756']}}}
```

Return type

dict

```
xgboost.dask.predict(client, model, data, output_margin=False, missing=nan, pred_leaf=False,  
                    pred_contribs=False, approx_contribs=False, pred_interactions=False,  
                    validate_features=True, iteration_range=(0, 0), strict_shape=False)
```

Run prediction with a trained booster.

Note: Using `inplace_predict` might be faster when some features are not needed. See [xgboost.Booster.predict\(\)](#) for details on various parameters. When output has more than 2 dimensions (shap value, leaf with `strict_shape`), input should be `da.Array` or `DaskDMatrix`.

New in version 1.0.0.

Parameters

- **client** (*distributed.Client* / *None*) – Specify the dask client used for training. Use default client returned from dask if it's set to *None*.
- **model** (*TrainReturnT* / *Booster* / *distributed.Future*) – The trained model. It can be a *distributed.Future* so user can pre-scatter it onto all workers.
- **data** (*DaskDMatrix* / *da.Array* / *dd.DataFrame*) – Input data used for prediction. When input is a dataframe object, prediction output is a series.
- **missing** (*float*) – Used when input data is not *DaskDMatrix*. Specify the value considered as missing.
- **output_margin** (*bool*) –
- **pred_leaf** (*bool*) –
- **pred_contribs** (*bool*) –
- **approx_contribs** (*bool*) –
- **pred_interactions** (*bool*) –
- **validate_features** (*bool*) –
- **iteration_range** (*Tuple[int, int]*) –
- **strict_shape** (*bool*) –

Returns

prediction – When input data is `dask.array.Array` or `DaskDMatrix`, the return value is an array, when input data is `dask.dataframe.DataFrame`, return value can be `dask.dataframe.Series`, `dask.dataframe.DataFrame`, depending on the output shape.

Return type`dask.array.Array/dask.dataframe.Series`

```
xgboost.dask.inplace_predict(client, model, data, iteration_range=(0, 0), predict_type='value', missing=nan,  
                             validate_features=True, base_margin=None, strict_shape=False)
```

Inplace prediction. See doc in [xgboost.Booster.inplace_predict\(\)](#) for details.

New in version 1.1.0.

Parameters

- **client** (*distributed.Client* | *None*) – Specify the dask client used for training. Use default client returned from dask if it's set to *None*.
- **model** (*TrainReturnT* | *Booster* | *distributed.Future*) – See [xgboost.dask.predict\(\)](#) for details.
- **data** (*da.Array* | *dd.DataFrame*) – dask collection.
- **iteration_range** (*Tuple[int, int]*) – See [xgboost.Booster.predict\(\)](#) for details.
- **predict_type** (*str*) – See [xgboost.Booster.inplace_predict\(\)](#) for details.
- **missing** (*float*) – Value in the input data which needs to be present as a missing value. If *None*, defaults to *np.nan*.
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – See [xgboost.DMatrix](#) for details.

New in version 1.4.0.

- **strict_shape** (*bool*) – See [xgboost.Booster.predict\(\)](#) for details.

New in version 1.4.0.

- **validate_features** (*bool*) –

Returns

When input data is *dask.array.Array*, the return value is an array, when input data is *dask.dataframe.DataFrame*, return value can be *dask.dataframe.Series*, *dask.dataframe.DataFrame*, depending on the output shape.

Return type

prediction

```
class xgboost.dask.DaskXGBClassifier(max_depth=None, max_leaves=None, max_bin=None,
                                     grow_policy=None, learning_rate=None, n_estimators=None,
                                     verbosity=None, objective=None, booster=None,
                                     tree_method=None, n_jobs=None, gamma=None,
                                     min_child_weight=None, max_delta_step=None, subsample=None,
                                     sampling_method=None, colsample_bytree=None,
                                     colsample_bylevel=None, colsample_bynode=None,
                                     reg_alpha=None, reg_lambda=None, scale_pos_weight=None,
                                     base_score=None, random_state=None, missing=nan,
                                     num_parallel_tree=None, monotone_constraints=None,
                                     interaction_constraints=None, importance_type=None,
                                     device=None, validate_parameters=None,
                                     enable_categorical=False, feature_types=None,
                                     max_cat_to_onehot=None, max_cat_threshold=None,
                                     multi_strategy=None, eval_metric=None,
                                     early_stopping_rounds=None, callbacks=None, **kwargs)
```

Bases: *DaskScikitLearnBase*, *ClassifierMixin*

Implementation of the scikit-learn API for XGBoost classification. See [Using the Scikit-Learn Estimator Interface](#) for more information.

Parameters

- **n_estimators** (*Optional*[*int*]) – Number of gradient boosted trees. Equivalent to number of boosting rounds.
- **max_depth** (*Optional*[*int*]) – Maximum tree depth for base learners.
- **max_leaves** (*int* | *None*) – Maximum number of leaves; 0 indicates no limit.
- **max_bin** (*int* | *None*) – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** (*str* | *None*) – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional*[*float*]) – Boosting learning rate (xgb’s “eta”)
- **verbosity** (*Optional*[*int*]) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** (*Union*[*str*, *Callable*[[*numpy.ndarray*, *numpy.ndarray*], *Tuple*[*numpy.ndarray*, *numpy.ndarray*]], *NoneType*]) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional*[*str*]) – Specify which booster to use: gbtrees, gblines or dart.
- **tree_method** (*Optional*[*str*]) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It’s recommended to study this option from the parameters document [tree method](#)
- **n_jobs** (*Optional*[*int*]) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.
- **gamma** (*Optional*[*float*]) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
- **min_child_weight** (*Optional*[*float*]) – Minimum sum of instance weight(hessian) needed in a child.
- **max_delta_step** (*Optional*[*float*]) – Maximum delta step we allow each tree’s weight estimation to be.
- **subsample** (*Optional*[*float*]) – Subsample ratio of the training instance.
- **sampling_method** (*str* | *None*) –
Sampling method. Used only by the GPU version of hist tree method.
 - uniform: select random training instances uniformly.
 - gradient_based select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
- **colsample_bytree** (*Optional*[*float*]) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional*[*float*]) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional*[*float*]) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional*[*float*]) – L1 regularization term on weights (xgb’s alpha).
- **reg_lambda** (*Optional*[*float*]) – L2 regularization term on weights (xgb’s lambda).
- **scale_pos_weight** (*Optional*[*float*]) – Balancing of positive and negative weights.

- **base_score** (*Optional*[*float*]) – The initial prediction score of all instances, global bias.
- **random_state** (*Optional*[*Union*[*numpy.random.RandomState*, *int*]]) – Random number seed.

Note: Using gblinear booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*float*, *default np.nan*) – Value in the data which needs to be present as a missing value.
- **num_parallel_tree** (*Optional*[*int*]) – Used for boosting random forest.
- **monotone_constraints** (*Optional*[*Union*[*Dict*[*str*, *int*], *str*]]) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional*[*Union*[*str*, *List*[*Tuple*[*str*]]]]) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. `[[0, 1], [2, 3, 4]]`, where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional*[*str*]) – The feature importance type for the feature importances_ property:
 - For tree model, it's either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it's the normalized coefficients without bias.
- **device** (*Optional*[*str*]) – New in version 2.0.0.
Device ordinal, available options are *cpu*, *cuda*, and *gpu*.
- **validate_parameters** (*Optional*[*bool*]) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, cudf/pandas.DataFrame should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional*[*FeatureTypes*]) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See `DMatrix` for details.
- **max_cat_to_onehot** (*Optional*[*int*]) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **max_cat_threshold** (*Optional*[*int*]) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **multi_strategy** (*Optional*[*str*]) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.

- `one_output_per_tree`: One model for each target.
- `multi_output_tree`: Use multi-target trees.

- **eval_metric** (*Optional*[*Union*[*str*, *List*[*str*], *Callable*]]) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See `doc/parameter.rst`), one of the metrics in `sklearn.metrics`, or any other user defined metric that looks like *sklearn.metrics*.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the *scoring* parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces *eval_metric* in *fit()* method. The old one receives un-transformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **early_stopping_rounds** (*Optional*[*int*]) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. Requires at least one item in *eval_set* in *fit()*.

- If early stopping occurs, the model will have two additional attributes: `best_score` and `best_iteration`. These are used by the `predict()` and `apply()` methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the `iteration_range` in these inference methods. In addition, other utilities like model plotting can also use the entire model.
- If you prefer to discard the trees after `best_iteration`, consider using the callback function `xgboost.callback.EarlyStopping`.
- If there's more than one item in `eval_set`, the last entry will be used for early stopping. If there's more than one metric in `eval_metric`, the last metric will be used for early stopping.

Note: This parameter replaces `early_stopping_rounds` in `fit()` method.

- **callbacks** (*Optional* [`List` [`TrainingCallback`]]) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using [Callback API](#).

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
    reg.fit(X, y)
```

- **kwargs** (*dict*, *optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found [here](#). Attempting to set a parameter via the constructor args and `**kwargs` dict simultaneously will result in a `TypeError`.

Note: `**kwargs` unsupported by scikit-learn

`**kwargs` is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

apply(`X`, `iteration_range=None`)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then `best_iteration` is used automatically.

Parameters

- **X** (*array_like*, `shape=[n_samples, n_features]`) – Input features matrix.
- **iteration_range** (*Tuple* [`int`, `int`] | `None`) – See `predict()`.

Returns

X_leaves – For each datapoint `x` in `X` and for each tree, return the index of the leaf `x` ends up in. Leaves are numbered within `[0; 2**(self.max_depth+1))`, possibly with gaps in the numbering.

Return type

`array_like`, `shape=[n_samples, n_trees]`

property best_iteration: `int`

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then `best_iteration` is 0.

property best_score: `float`

The best score obtained by early stopping.

property client: `distributed.Client`

The dask client used in this model. The *Client* object can not be serialized for transmission, so if task is launched from a worker instead of directly from the client process, this attribute needs to be set at that worker.

property coef_: `ndarray`

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

`coef_`

Return type

array of shape `[n_features]` or `[n_classes, n_features]`

evals_result()

Return the evaluation results.

If `eval_set` is passed to the `fit()` function, you can call `evals_result()` to get evaluation results for all passed `eval_sets`. When `eval_metric` is also passed to the `fit()` function, the `evals_result` will contain the `eval_metrics` passed to the `fit()` function.

The returned evaluation result is a dictionary:

```
{ 'validation_0': { 'logloss': ['0.604835', '0.531479'] },  
  'validation_1': { 'logloss': ['0.41965', '0.17686'] } }
```

Return type

`evals_result`

property feature_importances_: `ndarray`

Feature importances property, return depends on *importance_type* parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- `feature_importances_` (array of shape `[n_features]` except for multi-class)
- linear model, which returns an array with shape `(n_features, n_classes)`

property feature_names_in_: `ndarray`

Names of features seen during `fit()`. Defined only when *X* has feature names that are all strings.

```
fit(X, y, *, sample_weight=None, base_margin=None, eval_set=None, eval_metric=None,
    early_stopping_rounds=None, verbose=True, xgb_model=None, sample_weight_eval_set=None,
    base_margin_eval_set=None, feature_weights=None, callbacks=None)
```

Fit gradient boosting model.

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- **X** (`da.Array` | `dd.DataFrame`) – Feature matrix. See [Supported data structures for various XGBoost functions](#) for a list of supported types.

When the `tree_method` is set to `hist`, internally, the `QuantileDMatrix` will be used instead of the `DMatrix` for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (`da.Array` | `dd.DataFrame` | `dd.Series`) – Labels
- **sample_weight** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – instance weights
- **base_margin** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – global bias for each instance.
- **eval_set** (`Sequence[Tuple[da.Array | dd.DataFrame | dd.Series, da.Array | dd.DataFrame | dd.Series]]` | `None`) – A list of (X, y) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_metric** (`str`, `list of str`, or `callable`, `optional`) – Deprecated since version 1.6.0.

Use `eval_metric` in `__init__()` or `set_params()` instead.

- **early_stopping_rounds** (`int`) – Deprecated since version 1.6.0.
Use `early_stopping_rounds` in `__init__()` or `set_params()` instead.
- **verbose** (`int` | `bool`) – If `verbose` is `True` and an evaluation set is used, the evaluation metric measured on the validation set is printed to stdout at each boosting stage. If `verbose` is an integer, the evaluation metric is printed at each `verbose` boosting stage. The last boosting stage / the boosting stage found by using `early_stopping_rounds` is also printed.
- **xgb_model** (`Booster` | `XGBModel` | `None`) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (`Sequence[da.Array | dd.DataFrame | dd.Series]` | `None`) – A list of the form `[L_1, L_2, ..., L_n]`, where each `L_i` is an array like object storing instance weights for the `i`-th validation set.
- **base_margin_eval_set** (`Sequence[da.Array | dd.DataFrame | dd.Series]` | `None`) – A list of the form `[M_1, M_2, ..., M_n]`, where each `M_i` is an array like object storing base margin for the `i`-th validation set.
- **feature_weights** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – Weight for each feature, defines the probability of each feature being selected when `colsample` is being used. All values must be greater than 0, otherwise a `ValueError` is thrown.

- **callbacks** (*Sequence*[*TrainingCallback*] / *None*) – Deprecated since version 1.6.0: Use *callbacks* in `__init__()` or `set_params()` instead.

Return type

DaskXGBClassifier

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when fit was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A MetadataRequest encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

int

get_params(deep=True)

Get parameters.

Parameters

deep (*bool*) –

Return type

Dict[*str*, *Any*]

get_xgb_params()

Get xgboost specific parameters.

Return type

Dict[*str*, *Any*]

property intercept_: ndarray

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

intercept_

Return type

array of shape (1,) or [n_classes]

load_model(fname)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as `feature_names`) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* | *bytearray* | *PathLike*) – Input file name or memory buffer(see also `save_raw`)

Return type

None

property n_features_in_: *int*

Number of features seen during `fit()`.

predict(X, output_margin=False, validate_features=True, base_margin=None, iteration_range=None)

Predict with X. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*da.Array* | *dd.DataFrame*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying `iteration_range=(10, 20)`, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type

prediction

predict_proba(*X*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict the probability of each *X* example being of a given class. If the model is trained with early stopping, then *best_iteration* is used automatically. The estimator uses *inplace_predict* by default and falls back to using *DMatrix* if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*da.Array* | *dd.DataFrame* | *dd.Series*) – Feature matrix. See [Supported data structures for various XGBoost functions](#) for a list of supported types.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's *feature_names* are identical. Otherwise, it is assumed that the *feature_names* are the same.
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying *iteration_range=(10, 20)*, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

Returns

a numpy array of shape array-like of shape (n_samples, n_classes) with the probability of each data example being of a given class.

Return type

prediction

save_model(*fname*)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* | *PathLike*) – Output file name

Return type

None

score(*X*, *y*, *sample_weight=None*)

Return the mean accuracy on the given test data and labels.

In multi-label classification, this is the subset accuracy which is a harsh metric since you require for each sample that each label set be correctly predicted.

Parameters

- **X** (array-like of shape (n_samples, n_features)) – Test samples.

- **y** (array-like of shape (n_samples,) or (n_samples, n_outputs)) – True labels for X.
- **sample_weight** (array-like of shape (n_samples,), default=None) – Sample weights.

Returns

score – Mean accuracy of `self.predict(X)` w.r.t. y.

Return type

float

```
set_fit_request(* , base_margin='$UNCHANGED$', base_margin_eval_set='$UNCHANGED$',
                 callbacks='$UNCHANGED$', early_stopping_rounds='$UNCHANGED$',
                 eval_metric='$UNCHANGED$', eval_set='$UNCHANGED$',
                 feature_weights='$UNCHANGED$', sample_weight='$UNCHANGED$',
                 sample_weight_eval_set='$UNCHANGED$', verbose='$UNCHANGED$',
                 xgb_model='$UNCHANGED$')
```

Request metadata passed to the fit method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to fit if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to fit.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in fit.
- **base_margin_eval_set** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin_eval_set` parameter in fit.
- **callbacks** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `callbacks` parameter in fit.
- **early_stopping_rounds** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `early_stopping_rounds` parameter in fit.

- **eval_metric** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_metric` parameter in fit.
- **eval_set** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_set` parameter in fit.
- **feature_weights** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `feature_weights` parameter in fit.
- **sample_weight** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in fit.
- **sample_weight_eval_set** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight_eval_set` parameter in fit.
- **verbose** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `verbose` parameter in fit.
- **xgb_model** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `xgb_model` parameter in fit.
- **self** (`DaskXGBClassifier`) –

Returns

self – The updated object.

Return type

`object`

set_params(params)**

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

`self`

Parameters

params (*Any*) –

set_predict_proba_request(*, *base_margin*='UNCHANGED\$', *iteration_range*='UNCHANGED\$', *validate_features*='UNCHANGED\$')

Request metadata passed to the `predict_proba` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- True: metadata is requested, and passed to `predict_proba` if provided. The request is ignored if metadata is not provided.
- False: metadata is not requested and the meta-estimator will not pass it to `predict_proba`.
- None: metadata is not requested, and the meta-estimator will raise an error if the user provides it.

- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `base_margin` parameter in `predict_proba`.
- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `iteration_range` parameter in `predict_proba`.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `validate_features` parameter in `predict_proba`.
- **self** ([DaskXGBClassifier](#)) –

Returns

self – The updated object.

Return type

object

set_predict_request(**args*, *base_margin*='UNCHANGED\$', *iteration_range*='UNCHANGED\$', *output_margin*='UNCHANGED\$', *validate_features*='UNCHANGED\$')

Request metadata passed to the `predict` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to `predict` if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to `predict`.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for base_margin parameter in predict.
- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for iteration_range parameter in predict.
- **output_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for output_margin parameter in predict.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for validate_features parameter in predict.
- **self** (*DaskXGBClassifier*) –

Returns

self – The updated object.

Return type

object

set_score_request(*, *sample_weight*='UNCHANGED\$')

Request metadata passed to the score method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- *True*: metadata is requested, and passed to `score` if provided. The request is ignored if metadata is not provided.
- *False*: metadata is not requested and the meta-estimator will not pass it to `score`.
- *None*: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- *str*: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **sample_weight** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for sample_weight parameter in score.
- **self** (*DaskXGBClassifier*) –

Returns

self – The updated object.

Return type

object

```
class xgboost.dask.DaskXGBRegressor(max_depth=None, max_leaves=None, max_bin=None,
                                     grow_policy=None, learning_rate=None, n_estimators=None,
                                     verbosity=None, objective=None, booster=None, tree_method=None,
                                     n_jobs=None, gamma=None, min_child_weight=None,
                                     max_delta_step=None, subsample=None, sampling_method=None,
                                     colsample_bytree=None, colsample_bylevel=None,
                                     colsample_bynode=None, reg_alpha=None, reg_lambda=None,
                                     scale_pos_weight=None, base_score=None, random_state=None,
                                     missing=nan, num_parallel_tree=None,
                                     monotone_constraints=None, interaction_constraints=None,
                                     importance_type=None, device=None, validate_parameters=None,
                                     enable_categorical=False, feature_types=None,
                                     max_cat_to_onehot=None, max_cat_threshold=None,
                                     multi_strategy=None, eval_metric=None,
                                     early_stopping_rounds=None, callbacks=None, **kwargs)
```

Bases: DaskScikitLearnBase, [RegressorMixin](#)

Implementation of the Scikit-Learn API for XGBoost. See [Using the Scikit-Learn Estimator Interface](#) for more information.

Parameters

- **n_estimators** (*Optional*[[int](#)]) – Number of gradient boosted trees. Equivalent to number of boosting rounds.
- **max_depth** (*Optional*[[int](#)]) – Maximum tree depth for base learners.
- **max_leaves** ([int](#) / *None*) – Maximum number of leaves; 0 indicates no limit.
- **max_bin** ([int](#) / *None*) – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** ([str](#) / *None*) – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional*[[float](#)]) – Boosting learning rate (xgb’s “eta”)
- **verbosity** (*Optional*[[int](#)]) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** ([Union](#)[[str](#), [Callable](#)[[[numpy.ndarray](#), [numpy.ndarray](#)], [Tuple](#)[[numpy.ndarray](#), [numpy.ndarray](#)]], [NoneType](#)]) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional*[[str](#)]) – Specify which booster to use: gbtree, gblinear or dart.
- **tree_method** (*Optional*[[str](#)]) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It’s recommended to study this option from the parameters document [tree method](#)
- **n_jobs** (*Optional*[[int](#)]) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.

- **gamma** (*Optional[[float](#)]*) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
- **min_child_weight** (*Optional[[float](#)]*) – Minimum sum of instance weight(hessian) needed in a child.
- **max_delta_step** (*Optional[[float](#)]*) – Maximum delta step we allow each tree’s weight estimation to be.
- **subsample** (*Optional[[float](#)]*) – Subsample ratio of the training instance.
- **sampling_method** (*[str](#) | None*) –

Sampling method. Used only by the GPU version of hist tree method.

- **uniform**: select random training instances uniformly.
- **gradient_based** select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
- **colsample_bytree** (*Optional[[float](#)]*) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional[[float](#)]*) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional[[float](#)]*) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional[[float](#)]*) – L1 regularization term on weights (xgb’s alpha).
- **reg_lambda** (*Optional[[float](#)]*) – L2 regularization term on weights (xgb’s lambda).
- **scale_pos_weight** (*Optional[[float](#)]*) – Balancing of positive and negative weights.
- **base_score** (*Optional[[float](#)]*) – The initial prediction score of all instances, global bias.
- **random_state** (*Optional[Union[[numpy.random.RandomState](#), [int](#)]]*) – Random number seed.

Note: Using gblinear booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*[float](#), default [np.nan](#)*) – Value in the data which needs to be present as a missing value.
- **num_parallel_tree** (*Optional[[int](#)]*) – Used for boosting random forest.
- **monotone_constraints** (*Optional[Union[Dict[[str](#), [int](#)], [str](#)]]*) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional[Union[[str](#), List[Tuple[[str](#)]]]]*) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. [[0, 1], [2, 3, 4]], where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional[[str](#)]*) – The feature importance type for the feature_importances_ property:
 - For tree model, it’s either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it’s the normalized coefficients without bias.

- **device** (*Optional*[*str*]) – New in version 2.0.0.
Device ordinal, available options are *cpu*, *cuda*, and *gpu*.
- **validate_parameters** (*Optional*[*bool*]) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, *cudf/pandas.DataFrame* should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional*[*FeatureTypes*]) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See *DMatrix* for details.
- **max_cat_to_onehot** (*Optional*[*int*]) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, *enable_categorical* needs to be set to have categorical feature support. See *Categorical Data* and *Parameters for Categorical Feature* for details.

- **max_cat_threshold** (*Optional*[*int*]) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, *enable_categorical* needs to be set to have categorical feature support. See *Categorical Data* and *Parameters for Categorical Feature* for details.

- **multi_strategy** (*Optional*[*str*]) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See *Multiple Outputs* for more information.

- *one_output_per_tree*: One model for each target.
- *multi_output_tree*: Use multi-target trees.

- **eval_metric** (*Optional*[*Union*[*str*, *List*[*str*], *Callable*]]) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See *doc/parameter.rst*), one of the metrics in *sklearn.metrics*, or any other user defined metric that looks like *sklearn.metrics*.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the *scoring* parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces *eval_metric* in *fit()* method. The old one receives untransformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **early_stopping_rounds** (*Optional*[*int*]) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. Requires at least one item in **eval_set** in *fit()*.
 - If early stopping occurs, the model will have two additional attributes: *best_score* and *best_iteration*. These are used by the *predict()* and *apply()* methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the *iteration_range* in these inference methods. In addition, other utilities like model plotting can also use the entire model.
 - If you prefer to discard the trees after *best_iteration*, consider using the callback function [xgboost.callback.EarlyStopping](#).
 - If there's more than one item in **eval_set**, the last entry will be used for early stopping. If there's more than one metric in **eval_metric**, the last metric will be used for early stopping.

Note: This parameter replaces *early_stopping_rounds* in *fit()* method.

- **callbacks** (*Optional*[*List*[*TrainingCallback*]]) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using [Callback API](#).

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
```

(continues on next page)

(continued from previous page)

```
reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
reg.fit(X, y)
```

- **kwargs** (*dict*, *optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found [here](#). Attempting to set a parameter via the constructor args and **kwargs dict simultaneously will result in a `TypeError`.

Note: **kwargs unsupported by scikit-learn

**kwargs is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

apply(*X*, *iteration_range=None*)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then *best_iteration* is used automatically.

Parameters

- **X** (*array_like*, *shape=[n_samples, n_features]*) – Input features matrix.
- **iteration_range** (*Tuple[int, int]* | *None*) – See [predict\(\)](#).

Returns

X_leaves – For each datapoint *x* in *X* and for each tree, return the index of the leaf *x* ends up in. Leaves are numbered within $[0; 2^{**}(\text{self.max_depth}+1))$, possibly with gaps in the numbering.

Return type

array_like, shape=[n_samples, n_trees]

property best_iteration: *int*

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then *best_iteration* is 0.

property best_score: *float*

The best score obtained by early stopping.

property client: *distributed.Client*

The dask client used in this model. The *Client* object can not be serialized for transmission, so if task is launched from a worker instead of directly from the client process, this attribute needs to be set at that worker.

property coef_: *ndarray*

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

coef_

Return type

array of shape [n_features] or [n_classes, n_features]

evals_result()

Return the evaluation results.

If `eval_set` is passed to the `fit()` function, you can call `evals_result()` to get evaluation results for all passed `eval_sets`. When `eval_metric` is also passed to the `fit()` function, the `evals_result` will contain the `eval_metrics` passed to the `fit()` function.

The returned evaluation result is a dictionary:

```
{'validation_0': {'logloss': ['0.604835', '0.531479']},
 'validation_1': {'logloss': ['0.41965', '0.17686']}}
```

Return type

`evals_result`

property feature_importances_: ndarray

Feature importances property, return depends on `importance_type` parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- `feature_importances_` (array of shape `[n_features]` except for multi-class)
- linear model, which returns an array with shape `(n_features, n_classes)`

property feature_names_in_: ndarray

Names of features seen during `fit()`. Defined only when `X` has feature names that are all strings.

fit(`X`, `y`, *, `sample_weight=None`, `base_margin=None`, `eval_set=None`, `eval_metric=None`, `early_stopping_rounds=None`, `verbose=True`, `xgb_model=None`, `sample_weight_eval_set=None`, `base_margin_eval_set=None`, `feature_weights=None`, `callbacks=None`)

Fit gradient boosting model.

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- **X** (`da.Array` | `dd.DataFrame`) – Feature matrix. See [Supported data structures for various XGBoost functions](#) for a list of supported types.

When the `tree_method` is set to `hist`, internally, the `QuantileDMatrix` will be used instead of the `DMatrix` for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (`da.Array` | `dd.DataFrame` | `dd.Series`) – Labels
- **sample_weight** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – instance weights
- **base_margin** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – global bias for each instance.
- **eval_set** (`Sequence[Tuple[da.Array | dd.DataFrame | dd.Series, da.Array | dd.DataFrame | dd.Series]]` | `None`) – A list of (`X`, `y`) tuple pairs to use

as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.

- **eval_metric** (*str*, *list of str*, or *callable*, *optional*) – Deprecated since version 1.6.0.

Use *eval_metric* in `__init__()` or `set_params()` instead.

- **early_stopping_rounds** (*int*) – Deprecated since version 1.6.0.

Use *early_stopping_rounds* in `__init__()` or `set_params()` instead.

- **verbose** (*int* | *bool*) – If *verbose* is True and an evaluation set is used, the evaluation metric measured on the validation set is printed to stdout at each boosting stage. If *verbose* is an integer, the evaluation metric is printed at each *verbose* boosting stage. The last boosting stage / the boosting stage found by using *early_stopping_rounds* is also printed.
- **xgb_model** (*Booster* | *XGBModel* | *None*) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (*Sequence*[*da.Array* | *dd.DataFrame* | *dd.Series*] | *None*) – A list of the form [L₁, L₂, ..., L_n], where each L_i is an array like object storing instance weights for the i-th validation set.
- **base_margin_eval_set** (*Sequence*[*da.Array* | *dd.DataFrame* | *dd.Series*] | *None*) – A list of the form [M₁, M₂, ..., M_n], where each M_i is an array like object storing base margin for the i-th validation set.
- **feature_weights** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Weight for each feature, defines the probability of each feature being selected when `colsample` is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence*[*TrainingCallback*] | *None*) – Deprecated since version 1.6.0: Use *callbacks* in `__init__()` or `set_params()` instead.

Return type

DaskXGBRegressor

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when fit was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A *MetadataRequest* encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

`int`

get_params(*deep=True*)

Get parameters.

Parameters

deep (*bool*) –

Return type

`Dict[str, Any]`

get_xgb_params()

Get xgboost specific parameters.

Return type

`Dict[str, Any]`

property intercept_: ndarray

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

intercept_

Return type

array of shape (1,) or [n_classes]

load_model(*fname*)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* / *bytearray* / *PathLike*) – Input file name or memory buffer(see also *save_raw*)

Return type

`None`

property n_features_in_: int

Number of features seen during *fit()*.

predict(*X*, *output_margin=False*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict with *X*. If the model is trained with early stopping, then *best_iteration* is used automatically. The estimator uses *inplace_predict* by default and falls back to using *DMatrix* if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*da.Array* | *dd.DataFrame*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's *feature_names* are identical. Otherwise, it is assumed that the *feature_names* are the same.
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying *iteration_range*=(10, 20), then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type

prediction

save_model(*fname*)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* | *PathLike*) – Output file name

Return type

None

score(*X*, *y*, *sample_weight=None*)

Return the coefficient of determination of the prediction.

The coefficient of determination R^2 is defined as $(1 - \frac{u}{v})$, where u is the residual sum of squares $((y_true - y_pred)**2).sum()$ and v is the total sum of squares $((y_true - y_true.mean())**2).sum()$. The best possible score is 1.0 and it can be negative (because the model can be arbitrarily worse). A constant model that always predicts the expected value of y , disregarding the input features, would get a R^2 score of 0.0.

Parameters

- **X** (*array-like of shape (n_samples, n_features)*) – Test samples. For some estimators this may be a precomputed kernel matrix or a list of generic objects instead with shape (n_samples, n_samples_fitted), where n_samples_fitted is the number of samples used in the fitting for the estimator.
- **y** (*array-like of shape (n_samples,) or (n_samples, n_outputs)*) – True values for X.
- **sample_weight** (*array-like of shape (n_samples,)*, default=None) – Sample weights.

Returns

score – R^2 of self.predict(X) w.r.t. y.

Return type

float

Notes

The R^2 score used when calling **score** on a regressor uses `multioutput='uniform_average'` from version 0.23 to keep consistent with default value of `r2_score()`. This influences the **score** method of all the multioutput regressors (except for `MultiOutputRegressor`).

```
set_fit_request(*, base_margin='$UNCHANGED$', base_margin_eval_set='$UNCHANGED$',  
                 callbacks='$UNCHANGED$', early_stopping_rounds='$UNCHANGED$',  
                 eval_metric='$UNCHANGED$', eval_set='$UNCHANGED$',  
                 feature_weights='$UNCHANGED$', sample_weight='$UNCHANGED$',  
                 sample_weight_eval_set='$UNCHANGED$', verbose='$UNCHANGED$',  
                 xgb_model='$UNCHANGED$')
```

Request metadata passed to the **fit** method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to **fit** if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to **fit**.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `base_margin` parameter in fit.
- **base_margin_eval_set** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `base_margin_eval_set` parameter in fit.
- **callbacks** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `callbacks` parameter in fit.
- **early_stopping_rounds** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `early_stopping_rounds` parameter in fit.
- **eval_metric** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `eval_metric` parameter in fit.
- **eval_set** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `eval_set` parameter in fit.
- **feature_weights** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `feature_weights` parameter in fit.
- **sample_weight** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `sample_weight` parameter in fit.
- **sample_weight_eval_set** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `sample_weight_eval_set` parameter in fit.
- **verbose** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `verbose` parameter in fit.
- **xgb_model** (*str*, True, False, or None, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `xgb_model` parameter in fit.
- **self** (*DaskXGBRegressor*) –

Returns

self – The updated object.

Return type

object

set_params(params)**

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

self

Parameters**params** (*Any*) –**set_predict_request**(**, base_margin*='\$UNCHANGED\$', *iteration_range*='\$UNCHANGED\$',
output_margin='\$UNCHANGED\$', *validate_features*='\$UNCHANGED\$')

Request metadata passed to the `predict` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `predict` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `predict`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in `predict`.
- **iteration_range** (*str*, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `iteration_range` parameter in `predict`.
- **output_margin** (*str*, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `output_margin` parameter in `predict`.
- **validate_features** (*str*, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `validate_features` parameter in `predict`.
- **self** (`DaskXGBRegressor`) –

Returns

self – The updated object.

Return type

object

set_score_request(**, sample_weight*='\$UNCHANGED\$')

Request metadata passed to the `score` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `score` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `score`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **sample_weight** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in `score`.
- **self** (`DaskXGBRegressor`) –

Returns

self – The updated object.

Return type

`object`

```
class xgboost.dask.DaskXGBRanker(*, objective='rank:pairwise', **kwargs)
```

Bases: `DaskScikitLearnBase`, `XGBRankerMixin`

Implementation of the Scikit-Learn API for XGBoost Ranking.

New in version 1.4.0.

See [Using the Scikit-Learn Estimator Interface](#) for more information.

Parameters

- **n_estimators** (*Optional* [`int`]) – Number of gradient boosted trees. Equivalent to number of boosting rounds.
- **max_depth** (*Optional* [`int`]) – Maximum tree depth for base learners.
- **max_leaves** – Maximum number of leaves; 0 indicates no limit.
- **max_bin** – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional* [`float`]) – Boosting learning rate (xgb’s “eta”)

- **verbosity** (*Optional*[*int*]) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** (*Union*[*str*, *Callable*[[*numpy.ndarray*, *numpy.ndarray*], *Tuple*[*numpy.ndarray*, *numpy.ndarray*]], *NoneType*]) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional*[*str*]) – Specify which booster to use: gbt, gbm or dart.
- **tree_method** (*Optional*[*str*]) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It's recommended to study this option from the parameters document [tree method](#)
- **n_jobs** (*Optional*[*int*]) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.
- **gamma** (*Optional*[*float*]) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
- **min_child_weight** (*Optional*[*float*]) – Minimum sum of instance weight(hessian) needed in a child.
- **max_delta_step** (*Optional*[*float*]) – Maximum delta step we allow each tree's weight estimation to be.
- **subsample** (*Optional*[*float*]) – Subsample ratio of the training instance.
- **sampling_method** –

Sampling method. Used only by the GPU version of hist tree method.

- **uniform**: select random training instances uniformly.
- **gradient_based** select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
- **colsample_bytree** (*Optional*[*float*]) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional*[*float*]) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional*[*float*]) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional*[*float*]) – L1 regularization term on weights (xgb's alpha).
- **reg_lambda** (*Optional*[*float*]) – L2 regularization term on weights (xgb's lambda).
- **scale_pos_weight** (*Optional*[*float*]) – Balancing of positive and negative weights.
- **base_score** (*Optional*[*float*]) – The initial prediction score of all instances, global bias.
- **random_state** (*Optional*[*Union*[*numpy.random.RandomState*, *int*]]) – Random number seed.

Note: Using gbm booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*float*, *default np.nan*) – Value in the data which needs to be present as a missing value.

- **num_parallel_tree** (*Optional[int]*) – Used for boosting random forest.
- **monotone_constraints** (*Optional[Union[Dict[str, int], str]]*) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional[Union[str, List[Tuple[str]]]]*) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. `[[0, 1], [2, 3, 4]]`, where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional[str]*) – The feature importance type for the `feature_importances_` property:
 - For tree model, it's either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it's the normalized coefficients without bias.
- **device** (*Optional[str]*) – New in version 2.0.0.
Device ordinal, available options are `cpu`, `cuda`, and `gpu`.
- **validate_parameters** (*Optional[bool]*) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, `cudf/pandas.DataFrame` should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional[FeatureTypes]*) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See `DMatrix` for details.
- **max_cat_to_onehot** (*Optional[int]*) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, `enable_categorical` needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **max_cat_threshold** (*Optional[int]*) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, `enable_categorical` needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **multi_strategy** (*Optional[str]*) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.

- `one_output_per_tree`: One model for each target.
- `multi_output_tree`: Use multi-target trees.

- **`eval_metric`** (*Optional[Union[str, List[str], Callable]]*) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See `doc/parameter.rst`), one of the metrics in `sklearn.metrics`, or any other user defined metric that looks like `sklearn.metrics`.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the `scoring` parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces `eval_metric` in `fit()` method. The old one receives untransformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **`early_stopping_rounds`** (*Optional[int]*) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **`early_stopping_rounds`** round(s) to continue training. Requires at least one item in `eval_set` in `fit()`.
 - If early stopping occurs, the model will have two additional attributes: `best_score` and `best_iteration`. These are used by the `predict()` and `apply()` methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the `iteration_range` in these inference methods. In addition, other utilities like model plotting can also use the entire model.
 - If you prefer to discard the trees after `best_iteration`, consider using the callback function [xgboost.callback.EarlyStopping](#).

- If there's more than one item in **eval_set**, the last entry will be used for early stopping. If there's more than one metric in **eval_metric**, the last metric will be used for early stopping.

Note: This parameter replaces *early_stopping_rounds* in *fit()* method.

- **callbacks** (*Optional [List [TrainingCallback]]*) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using *Callback API*.

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
    reg.fit(X, y)
```

- **kwargs** (*dict, optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found *here*. Attempting to set a parameter via the constructor args and ****kwargs** dict simultaneously will result in a *TypeError*.

Note: ****kwargs** unsupported by scikit-learn

****kwargs** is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

Note: For dask implementation, group is not supported, use qid instead.

apply(*X, iteration_range=None*)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then *best_iteration* is used automatically.

Parameters

- **X** (*array_like, shape=[n_samples, n_features]*) – Input features matrix.
- **iteration_range** (*Tuple[int, int] | None*) – See *predict()*.

Returns

X_leaves – For each datapoint *x* in *X* and for each tree, return the index of the leaf *x* ends up in. Leaves are numbered within $[0; 2^{**}(\text{self.max_depth}+1))$, possibly with gaps in the numbering.

Return type

array_like, shape=[n_samples, n_trees]

property best_iteration: *int*

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then *best_iteration* is 0.

property best_score: `float`

The best score obtained by early stopping.

property client: `distributed.Client`

The dask client used in this model. The *Client* object can not be serialized for transmission, so if task is launched from a worker instead of directly from the client process, this attribute needs to be set at that worker.

property coef_: `ndarray`

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

coef_

Return type

array of shape `[n_features]` or `[n_classes, n_features]`

evals_result()

Return the evaluation results.

If **eval_set** is passed to the *fit()* function, you can call *evals_result()* to get evaluation results for all passed **eval_sets**. When **eval_metric** is also passed to the *fit()* function, the **evals_result** will contain the **eval_metrics** passed to the *fit()* function.

The returned evaluation result is a dictionary:

```
{'validation_0': {'logloss': ['0.604835', '0.531479']},
 'validation_1': {'logloss': ['0.41965', '0.17686']}}
```

Return type

evals_result

property feature_importances_: `ndarray`

Feature importances property, return depends on *importance_type* parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- **feature_importances_** (array of shape `[n_features]` except for multi-class)
- linear model, which returns an array with shape `(n_features, n_classes)`

property feature_names_in_: `ndarray`

Names of features seen during *fit()*. Defined only when *X* has feature names that are all strings.

fit(*X*, *y*, *, *group=None*, *qid=None*, *sample_weight=None*, *base_margin=None*, *eval_set=None*, *eval_group=None*, *eval_qid=None*, *eval_metric=None*, *early_stopping_rounds=None*, *verbose=False*, *xgb_model=None*, *sample_weight_eval_set=None*, *base_margin_eval_set=None*, *feature_weights=None*, *callbacks=None*)

Fit gradient boosting ranker

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- **X** (`da.Array` | `dd.DataFrame`) – Feature matrix. See [Supported data structures for various XGBoost functions](#) for a list of supported types.

When this is a `pandas.DataFrame` or a `cudf.DataFrame`, it may contain a special column called `qid` for specifying the query index. Using a special column is the same as using the `qid` parameter, except for being compatible with sklearn utility functions like `sklearn.model_selection.cross_validation()`. The same convention applies to the `XGBRanker.score()` and `XGBRanker.predict()`.

qid	feat_0	feat_1
0	x_{00}	x_{01}
1	x_{10}	x_{11}
1	x_{20}	x_{21}

When the `tree_method` is set to `hist`, internally, the `QuantileDMatrix` will be used instead of the `DMatrix` for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (`da.Array` | `dd.DataFrame` | `dd.Series`) – Labels
- **group** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – Size of each query group of training data. Should have as many elements as the query groups in the training data. If this is set to `None`, then user must provide `qid`.
- **qid** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – Query ID for each training sample. Should have the size of `n_samples`. If this is set to `None`, then user must provide group or a special column in X.
- **sample_weight** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – Query group weights

Note: Weights are per-group for ranking tasks

In ranking task, one weight is assigned to each query group/id (not each data point). This is because we only care about the relative ordering of data points within each group, so it doesn't make sense to assign weights to individual data points.

- **base_margin** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – Global bias for each instance.
- **eval_set** (`Sequence[Tuple[da.Array | dd.DataFrame | dd.Series, da.Array | dd.DataFrame | dd.Series]]` | `None`) – A list of (X, y) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_group** (`Sequence[da.Array | dd.DataFrame | dd.Series]` | `None`) – A list in which `eval_group[i]` is the list containing the sizes of all query groups in the *i*-th pair in `eval_set`.

- **eval_qid** (*Sequence*[*da.Array* | *dd.DataFrame* | *dd.Series*] | *None*) – A list in which `eval_qid[i]` is the array containing query ID of *i*-th pair in `eval_set`. The special column convention in *X* applies to validation datasets as well.
- **eval_metric** (*str*, *list of str*, *optional*) – Deprecated since version 1.6.0: use `eval_metric` in `__init__()` or `set_params()` instead.
- **early_stopping_rounds** (*int*) – Deprecated since version 1.6.0: use `early_stopping_rounds` in `__init__()` or `set_params()` instead.
- **verbose** (*int* | *bool*) – If *verbose* is *True* and an evaluation set is used, the evaluation metric measured on the validation set is printed to stdout at each boosting stage. If *verbose* is an integer, the evaluation metric is printed at each *verbose* boosting stage. The last boosting stage / the boosting stage found by using `early_stopping_rounds` is also printed.
- **xgb_model** (*Booster* | *XGBModel* | *None*) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (*Sequence*[*da.Array* | *dd.DataFrame* | *dd.Series*] | *None*) – A list of the form [*L*₁, *L*₂, ..., *L*_{*n*}], where each *L*_{*i*} is a list of group weights on the *i*-th validation set.

Note: Weights are per-group for ranking tasks

In ranking task, one weight is assigned to each query group (not each data point). This is because we only care about the relative ordering of data points within each group, so it doesn’t make sense to assign weights to individual data points.

- **base_margin_eval_set** (*Sequence*[*da.Array* | *dd.DataFrame* | *dd.Series*] | *None*) – A list of the form [*M*₁, *M*₂, ..., *M*_{*n*}], where each *M*_{*i*} is an array like object storing base margin for the *i*-th validation set.
- **feature_weights** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Weight for each feature, defines the probability of each feature being selected when `colsample` is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence*[*TrainingCallback*] | *None*) – Deprecated since version 1.6.0: Use `callbacks` in `__init__()` or `set_params()` instead.

Return type

DaskXGBRanker

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when `fit` was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A `MetadataRequest` encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

int

get_params(deep=True)

Get parameters.

Parameters

deep (*bool*) –

Return type

Dict[str, *Any*]

get_xgb_params()

Get xgboost specific parameters.

Return type

Dict[str, *Any*]

property intercept_: ndarray

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

intercept_

Return type

array of shape (1,) or [n_classes]

load_model(fname)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* / *bytearray* / *PathLike*) – Input file name or memory buffer(see also *save_raw*)

Return type

None

property `n_features_in_`: `int`

Number of features seen during `fit()`.

predict(*X*, *output_margin=False*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict with *X*. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for `gbtree` and `dart`.

Parameters

- **X** (`da.Array` | `dd.DataFrame`) – Data to predict with.
- **output_margin** (`bool`) – Whether to output the raw untransformed margin value.
- **validate_features** (`bool`) – When this is `True`, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – Margin added to prediction.
- **iteration_range** (`Tuple[int, int]` | `None`) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying `iteration_range=(10, 20)`, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type

prediction

save_model(*fname*)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as `feature_names`) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (`str` | `PathLike`) – Output file name

Return type

None

set_fit_request(***, *base_margin='\$UNCHANGED\$'*, *base_margin_eval_set='\$UNCHANGED\$'*, *callbacks='\$UNCHANGED\$'*, *early_stopping_rounds='\$UNCHANGED\$'*, *eval_group='\$UNCHANGED\$'*, *eval_metric='\$UNCHANGED\$'*, *eval_qid='\$UNCHANGED\$'*, *eval_set='\$UNCHANGED\$'*, *feature_weights='\$UNCHANGED\$'*, *group='\$UNCHANGED\$'*, *qid='\$UNCHANGED\$'*, *sample_weight='\$UNCHANGED\$'*, *sample_weight_eval_set='\$UNCHANGED\$'*, *verbose='\$UNCHANGED\$'*, *xgb_model='\$UNCHANGED\$'*)

Request metadata passed to the `fit` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `fit` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `fit`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in `fit`.
- **base_margin_eval_set** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin_eval_set` parameter in `fit`.
- **callbacks** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `callbacks` parameter in `fit`.
- **early_stopping_rounds** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `early_stopping_rounds` parameter in `fit`.
- **eval_group** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_group` parameter in `fit`.
- **eval_metric** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_metric` parameter in `fit`.
- **eval_qid** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_qid` parameter in `fit`.
- **eval_set** (`str`, `True`, `False`, or `None`, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_set` parameter in `fit`.

- **feature_weights** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `feature_weights` parameter in fit.
- **group** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `group` parameter in fit.
- **qid** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `qid` parameter in fit.
- **sample_weight** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in fit.
- **sample_weight_eval_set** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight_eval_set` parameter in fit.
- **verbose** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `verbose` parameter in fit.
- **xgb_model** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `xgb_model` parameter in fit.
- **self** (`DaskXGBRanker`) –

Returns

self – The updated object.

Return type

object

`set_params(**params)`

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

self

Parameters

params (*Any*) –

set_predict_request(*, *base_margin*='\$UNCHANGED\$', *iteration_range*='\$UNCHANGED\$', *output_margin*='\$UNCHANGED\$', *validate_features*='\$UNCHANGED\$')

Request metadata passed to the `predict` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- True: metadata is requested, and passed to `predict` if provided. The request is ignored if metadata is not provided.
- False: metadata is not requested and the meta-estimator will not pass it to `predict`.
- None: metadata is not requested, and the meta-estimator will raise an error if the user provides it.

- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `base_margin` parameter in `predict`.
- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `iteration_range` parameter in `predict`.
- **output_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `output_margin` parameter in `predict`.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `validate_features` parameter in `predict`.
- **self** ([DaskXGBRanker](#)) –

Returns

self – The updated object.

Return type

object

```
class xgboost.dask.DaskXGBRFRegressor(*, learning_rate=1, subsample=0.8, colsample_bynode=0.8,
                                     reg_lambda=1e-05, **kwargs)
```

Bases: [DaskXGBRegressor](#)

Implementation of the Scikit-Learn API for XGBoost Random Forest Regressor.

New in version 1.4.0.

See [Using the Scikit-Learn Estimator Interface](#) for more information.

Parameters

- **n_estimators** (*int*) – Number of trees in random forest to fit.
- **max_depth** (*Optional[int]*) – Maximum tree depth for base learners.
- **max_leaves** – Maximum number of leaves; 0 indicates no limit.
- **max_bin** – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional[float]*) – Boosting learning rate (xgb’s “eta”)

- **verbosity** (*Optional*[*int*]) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** (*Union*[*str*, *Callable*[[*numpy.ndarray*, *numpy.ndarray*], *Tuple*[*numpy.ndarray*, *numpy.ndarray*]], *NoneType*]) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional*[*str*]) – Specify which booster to use: gbt, gbm or dart.
- **tree_method** (*Optional*[*str*]) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It's recommended to study this option from the parameters document [tree method](#)
- **n_jobs** (*Optional*[*int*]) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.
- **gamma** (*Optional*[*float*]) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
- **min_child_weight** (*Optional*[*float*]) – Minimum sum of instance weight(hessian) needed in a child.
- **max_delta_step** (*Optional*[*float*]) – Maximum delta step we allow each tree's weight estimation to be.
- **subsample** (*Optional*[*float*]) – Subsample ratio of the training instance.
- **sampling_method** –

Sampling method. Used only by the GPU version of hist tree method.

- **uniform**: select random training instances uniformly.
- **gradient_based** select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
- **colsample_bytree** (*Optional*[*float*]) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional*[*float*]) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional*[*float*]) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional*[*float*]) – L1 regularization term on weights (xgb's alpha).
- **reg_lambda** (*Optional*[*float*]) – L2 regularization term on weights (xgb's lambda).
- **scale_pos_weight** (*Optional*[*float*]) – Balancing of positive and negative weights.
- **base_score** (*Optional*[*float*]) – The initial prediction score of all instances, global bias.
- **random_state** (*Optional*[*Union*[*numpy.random.RandomState*, *int*]]) – Random number seed.

Note: Using gbm booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*float*, *default np.nan*) – Value in the data which needs to be present as a missing value.

- **num_parallel_tree** (*Optional*[*int*]) – Used for boosting random forest.
- **monotone_constraints** (*Optional*[*Union*[*Dict*[*str*, *int*], *str*]]) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional*[*Union*[*str*, *List*[*Tuple*[*str*]]]]) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. [[0, 1], [2, 3, 4]], where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional*[*str*]) – The feature importance type for the feature_importances_ property:
 - For tree model, it’s either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it’s the normalized coefficients without bias.
- **device** (*Optional*[*str*]) – New in version 2.0.0.
Device ordinal, available options are *cpu*, *cuda*, and *gpu*.
- **validate_parameters** (*Optional*[*bool*]) – Give warnings for unknown parameter.
- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, cudf/pandas.DataFrame should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional*[*FeatureTypes*]) – New in version 1.7.0.
Used for specifying feature types without constructing a dataframe. See *DMatrix* for details.
- **max_cat_to_onehot** (*Optional*[*int*]) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **max_cat_threshold** (*Optional*[*int*]) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **multi_strategy** (*Optional*[*str*]) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.

- `one_output_per_tree`: One model for each target.
- `multi_output_tree`: Use multi-target trees.

- **`eval_metric`** (*Optional[Union[str, List[str], Callable]]*) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See `doc/parameter.rst`), one of the metrics in `sklearn.metrics`, or any other user defined metric that looks like `sklearn.metrics`.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the `scoring` parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See [Custom Objective and Evaluation Metric](#) for more.

Note: This parameter replaces `eval_metric` in `fit()` method. The old one receives untransformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **`early_stopping_rounds`** (*Optional[int]*) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **`early_stopping_rounds`** round(s) to continue training. Requires at least one item in `eval_set` in `fit()`.
 - If early stopping occurs, the model will have two additional attributes: `best_score` and `best_iteration`. These are used by the `predict()` and `apply()` methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the `iteration_range` in these inference methods. In addition, other utilities like model plotting can also use the entire model.
 - If you prefer to discard the trees after `best_iteration`, consider using the callback function [xgboost.callback.EarlyStopping](#).

- If there's more than one item in **eval_set**, the last entry will be used for early stopping. If there's more than one metric in **eval_metric**, the last metric will be used for early stopping.

Note: This parameter replaces *early_stopping_rounds* in *fit()* method.

- **callbacks** (*Optional [List [TrainingCallback]]*) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using [Callback API](#).

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
    reg.fit(X, y)
```

- **kwargs** (*dict, optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found [here](#). Attempting to set a parameter via the constructor args and ****kwargs** dict simultaneously will result in a `TypeError`.

Note: ****kwargs** unsupported by scikit-learn

****kwargs** is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

Note: Custom objective function

A custom objective function can be provided for the objective parameter. In this case, it should have the signature `objective(y_true, y_pred) -> grad, hess`:

y_true: `array_like` of shape `[n_samples]`

The target values

y_pred: `array_like` of shape `[n_samples]`

The predicted values

grad: `array_like` of shape `[n_samples]`

The value of the gradient for each sample point.

hess: `array_like` of shape `[n_samples]`

The value of the second derivative for each sample point

apply(*X, iteration_range=None*)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then *best_iteration* is used automatically.

Parameters

- **X** (`array_like`, `shape=[n_samples, n_features]`) – Input features matrix.
- **iteration_range** (`Tuple[int, int]` | `None`) – See *predict()*.

Returns

X_leaves – For each datapoint x in X and for each tree, return the index of the leaf x ends up in. Leaves are numbered within $[0; 2^{**}(\text{self.max_depth}+1))$, possibly with gaps in the numbering.

Return type

array_like, shape=[n_samples, n_trees]

property best_iteration: `int`

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then `best_iteration` is 0.

property best_score: `float`

The best score obtained by early stopping.

property client: `distributed.Client`

The dask client used in this model. The *Client* object can not be serialized for transmission, so if task is launched from a worker instead of directly from the client process, this attribute needs to be set at that worker.

property coef_: `ndarray`

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

coef_

Return type

array of shape [n_features] or [n_classes, n_features]

evals_result()

Return the evaluation results.

If `eval_set` is passed to the `fit()` function, you can call `evals_result()` to get evaluation results for all passed `eval_sets`. When `eval_metric` is also passed to the `fit()` function, the `evals_result` will contain the `eval_metrics` passed to the `fit()` function.

The returned evaluation result is a dictionary:

```
{ 'validation_0': { 'logloss': ['0.604835', '0.531479'] },  
  'validation_1': { 'logloss': ['0.41965', '0.17686'] } }
```

Return type

evals_result

property feature_importances_: `ndarray`

Feature importances property, return depends on *importance_type* parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- **feature_importances_** (array of shape `[n_features]` except for multi-class)
- linear model, which returns an array with shape `(n_features, n_classes)`

property feature_names_in_: `ndarray`

Names of features seen during `fit()`. Defined only when `X` has feature names that are all strings.

fit(`X`, `y`, *, `sample_weight=None`, `base_margin=None`, `eval_set=None`, `eval_metric=None`, `early_stopping_rounds=None`, `verbose=True`, `xgb_model=None`, `sample_weight_eval_set=None`, `base_margin_eval_set=None`, `feature_weights=None`, `callbacks=None`)

Fit gradient boosting model.

Note that calling `fit()` multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass `xgb_model` argument.

Parameters

- **X** (`da.Array` | `dd.DataFrame`) – Feature matrix. See [Supported data structures for various XGBoost functions](#) for a list of supported types.

When the `tree_method` is set to `hist`, internally, the `QuantileDMatrix` will be used instead of the `DMatrix` for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but `cuda` is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (`da.Array` | `dd.DataFrame` | `dd.Series`) – Labels
- **sample_weight** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – instance weights
- **base_margin** (`da.Array` | `dd.DataFrame` | `dd.Series` | `None`) – global bias for each instance.
- **eval_set** (`Sequence[Tuple[da.Array | dd.DataFrame | dd.Series, da.Array | dd.DataFrame | dd.Series]]` | `None`) – A list of (X, y) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_metric** (`str`, `list of str`, or `callable`, `optional`) – Deprecated since version 1.6.0.

Use `eval_metric` in `__init__()` or `set_params()` instead.

- **early_stopping_rounds** (`int`) – Deprecated since version 1.6.0.

Use `early_stopping_rounds` in `__init__()` or `set_params()` instead.

- **verbose** (`int` | `bool`) – If `verbose` is `True` and an evaluation set is used, the evaluation metric measured on the validation set is printed to stdout at each boosting stage. If `verbose` is an integer, the evaluation metric is printed at each `verbose` boosting stage. The last boosting stage / the boosting stage found by using `early_stopping_rounds` is also printed.
- **xgb_model** (`Booster` | `XGBModel` | `None`) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (`Sequence[da.Array | dd.DataFrame | dd.Series]` | `None`) – A list of the form `[L_1, L_2, ..., L_n]`, where each `L_i` is an array like object storing instance weights for the `i`-th validation set.

- **base_margin_eval_set** (*Sequence*[*da.Array* | *dd.DataFrame* | *dd.Series*] | *None*) – A list of the form [M_1, M_2, ..., M_n], where each M_i is an array like object storing base margin for the i-th validation set.
- **feature_weights** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Weight for each feature, defines the probability of each feature being selected when *colsample* is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence*[*TrainingCallback*] | *None*) – Deprecated since version 1.6.0: Use *callbacks* in *__init__()* or *set_params()* instead.

Return type

DaskXGBRFRegressor

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when fit was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A *MetadataRequest* encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

int

get_params(*deep=True*)

Get parameters.

Parameters

deep (*bool*) –

Return type

Dict[*str*, *Any*]

get_xgb_params()

Get xgboost specific parameters.

Return type

Dict[*str*, *Any*]

property intercept_: *ndarray*

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtree*).

Returns**intercept_****Return type**

array of shape (1,) or [n_classes]

load_model(fname)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as `feature_names`) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* | *bytearray* | *PathLike*) – Input file name or memory buffer(see also `save_raw`)

Return type

None

property n_features_in_: int

Number of features seen during `fit()`.

predict(X, output_margin=False, validate_features=True, base_margin=None, iteration_range=None)

Predict with X. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*da.Array* | *dd.DataFrame*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying `iteration_range=(10, 20)`, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type
prediction

save_model(*fname*)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as `feature_names`) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* | *PathLike*) – Output file name

Return type

None

score(*X*, *y*, *sample_weight=None*)

Return the coefficient of determination of the prediction.

The coefficient of determination R^2 is defined as $(1 - \frac{u}{v})$, where u is the residual sum of squares $((y_true - y_pred)** 2).sum()$ and v is the total sum of squares $((y_true - y_true.mean()) ** 2).sum()$. The best possible score is 1.0 and it can be negative (because the model can be arbitrarily worse). A constant model that always predicts the expected value of y , disregarding the input features, would get a R^2 score of 0.0.

Parameters

- **X** (*array-like of shape (n_samples, n_features)*) – Test samples. For some estimators this may be a precomputed kernel matrix or a list of generic objects instead with shape $(n_samples, n_samples_fitted)$, where `n_samples_fitted` is the number of samples used in the fitting for the estimator.
- **y** (*array-like of shape (n_samples,) or (n_samples, n_outputs)*) – True values for X .
- **sample_weight** (*array-like of shape (n_samples,)*, *default=None*) – Sample weights.

Returns

score – R^2 of `self.predict(X)` w.r.t. y .

Return type

float

Notes

The R^2 score used when calling `score` on a regressor uses `multioutput='uniform_average'` from version 0.23 to keep consistent with default value of `r2_score()`. This influences the score method of all the multioutput regressors (except for `MultiOutputRegressor`).

```
set_fit_request(*, base_margin='$UNCHANGED$', base_margin_eval_set='$UNCHANGED$',
               callbacks='$UNCHANGED$', early_stopping_rounds='$UNCHANGED$',
               eval_metric='$UNCHANGED$', eval_set='$UNCHANGED$',
               feature_weights='$UNCHANGED$', sample_weight='$UNCHANGED$',
               sample_weight_eval_set='$UNCHANGED$', verbose='$UNCHANGED$',
               xgb_model='$UNCHANGED$')
```

Request metadata passed to the fit method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to `fit` if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to `fit`.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in `fit`.
- **base_margin_eval_set** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin_eval_set` parameter in `fit`.
- **callbacks** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `callbacks` parameter in `fit`.
- **early_stopping_rounds** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `early_stopping_rounds` parameter in `fit`.
- **eval_metric** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_metric` parameter in `fit`.

- **eval_set** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_set` parameter in fit.
- **feature_weights** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `feature_weights` parameter in fit.
- **sample_weight** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in fit.
- **sample_weight_eval_set** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight_eval_set` parameter in fit.
- **verbose** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `verbose` parameter in fit.
- **xgb_model** (*str*, True, False, or None, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `xgb_model` parameter in fit.
- **self** (`DaskXGBRFRegressor`) –

Returns

self – The updated object.

Return type

`object`

set_params(params)**

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

`self`

Parameters

params (*Any*) –

set_predict_request(*, `base_margin`='UNCHANGED\$', `iteration_range`='UNCHANGED\$', `output_margin`='UNCHANGED\$', `validate_features`='UNCHANGED\$')

Request metadata passed to the `predict` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- True: metadata is requested, and passed to `predict` if provided. The request is ignored if metadata is not provided.
- False: metadata is not requested and the meta-estimator will not pass it to `predict`.
- None: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- str: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in `predict`.
- **iteration_range** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `iteration_range` parameter in `predict`.
- **output_margin** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `output_margin` parameter in `predict`.
- **validate_features** (`str`, `True`, `False`, or `None`, `default=sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `validate_features` parameter in `predict`.
- **self** (`DaskXGBRFRegressor`) –

Returns

self – The updated object.

Return type

`object`

set_score_request(`*`, `sample_weight='UNCHANGED$'`)

Request metadata passed to the `score` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `score` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `score`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **sample_weight** (*str*, *True*, *False*, or *None*, default=*sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for *sample_weight* parameter in score.
- **self** (*DaskXGBRFRegressor*) –

Returns

self – The updated object.

Return type

object

```
class xgboost.dask.DaskXGBRFClassifier(*, learning_rate=1, subsample=0.8, colsample_bynode=0.8,
                                     reg_lambda=1e-05, **kwargs)
```

Bases: *DaskXGBClassifier*

Implementation of the Scikit-Learn API for XGBoost Random Forest Classifier.

New in version 1.4.0.

See *Using the Scikit-Learn Estimator Interface* for more information.

Parameters

- **n_estimators** (*int*) – Number of trees in random forest to fit.
- **max_depth** (*Optional[int]*) – Maximum tree depth for base learners.
- **max_leaves** – Maximum number of leaves; 0 indicates no limit.
- **max_bin** – If using histogram-based algorithm, maximum number of bins per feature
- **grow_policy** – Tree growing policy. 0: favor splitting at nodes closest to the node, i.e. grow depth-wise. 1: favor splitting at nodes with highest loss change.
- **learning_rate** (*Optional[float]*) – Boosting learning rate (xgb’s “eta”)
- **verbosity** (*Optional[int]*) – The degree of verbosity. Valid values are 0 (silent) - 3 (debug).
- **objective** (*Union[str, Callable[[numpy.ndarray, numpy.ndarray], Tuple[numpy.ndarray, numpy.ndarray]], NoneType]*) – Specify the learning task and the corresponding learning objective or a custom objective function to be used (see note below).
- **booster** (*Optional[str]*) – Specify which booster to use: gbtrees, gblinear or dart.
- **tree_method** (*Optional[str]*) – Specify which tree method to use. Default to auto. If this parameter is set to default, XGBoost will choose the most conservative option available. It’s recommended to study this option from the parameters document *tree method*
- **n_jobs** (*Optional[int]*) – Number of parallel threads used to run xgboost. When used with other Scikit-Learn algorithms like grid search, you may choose which algorithm to parallelize and balance the threads. Creating thread contention will significantly slow down both algorithms.
- **gamma** (*Optional[float]*) – (min_split_loss) Minimum loss reduction required to make a further partition on a leaf node of the tree.
- **min_child_weight** (*Optional[float]*) – Minimum sum of instance weight(hessian) needed in a child.

- **max_delta_step** (*Optional*[*float*]) – Maximum delta step we allow each tree’s weight estimation to be.
- **subsample** (*Optional*[*float*]) – Subsample ratio of the training instance.
- **sampling_method** –
Sampling method. Used only by the GPU version of hist tree method.
 - **uniform**: select random training instances uniformly.
 - **gradient_based** select random training instances with higher probability when the gradient and hessian are larger. (cf. CatBoost)
- **colsample_bytree** (*Optional*[*float*]) – Subsample ratio of columns when constructing each tree.
- **colsample_bylevel** (*Optional*[*float*]) – Subsample ratio of columns for each level.
- **colsample_bynode** (*Optional*[*float*]) – Subsample ratio of columns for each split.
- **reg_alpha** (*Optional*[*float*]) – L1 regularization term on weights (xxb’s alpha).
- **reg_lambda** (*Optional*[*float*]) – L2 regularization term on weights (xxb’s lambda).
- **scale_pos_weight** (*Optional*[*float*]) – Balancing of positive and negative weights.
- **base_score** (*Optional*[*float*]) – The initial prediction score of all instances, global bias.
- **random_state** (*Optional*[*Union*[*numpy.random.RandomState*, *int*]]) – Random number seed.

Note: Using gblinear booster with shotgun updater is nondeterministic as it uses Hogwild algorithm.

- **missing** (*float*, *default np.nan*) – Value in the data which needs to be present as a missing value.
- **num_parallel_tree** (*Optional*[*int*]) – Used for boosting random forest.
- **monotone_constraints** (*Optional*[*Union*[*Dict*[*str*, *int*], *str*]]) – Constraint of variable monotonicity. See [tutorial](#) for more information.
- **interaction_constraints** (*Optional*[*Union*[*str*, *List*[*Tuple*[*str*]]]]) – Constraints for interaction representing permitted interactions. The constraints must be specified in the form of a nested list, e.g. `[[0, 1], [2, 3, 4]]`, where each inner list is a group of indices of features that are allowed to interact with each other. See [tutorial](#) for more information
- **importance_type** (*Optional*[*str*]) – The feature importance type for the `feature_importances_` property:
 - For tree model, it’s either “gain”, “weight”, “cover”, “total_gain” or “total_cover”.
 - For linear model, only “weight” is defined and it’s the normalized coefficients without bias.
- **device** (*Optional*[*str*]) – New in version 2.0.0.
 Device ordinal, available options are *cpu*, *cuda*, and *gpu*.
- **validate_parameters** (*Optional*[*bool*]) – Give warnings for unknown parameter.

- **enable_categorical** (*bool*) – New in version 1.5.0.

Note: This parameter is experimental

Experimental support for categorical data. When enabled, `cudf/pandas.DataFrame` should be used to specify categorical data type. Also, JSON/UBJSON serialization format is required.

- **feature_types** (*Optional[FeatureTypes]*) – New in version 1.7.0.

Used for specifying feature types without constructing a dataframe. See `DMatrix` for details.

- **max_cat_to_onehot** (*Optional[int]*) – New in version 1.6.0.

Note: This parameter is experimental

A threshold for deciding whether XGBoost should use one-hot encoding based split for categorical data. When number of categories is lesser than the threshold then one-hot encoding is chosen, otherwise the categories will be partitioned into children nodes. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **max_cat_threshold** (*Optional[int]*) – New in version 1.7.0.

Note: This parameter is experimental

Maximum number of categories considered for each split. Used only by partition-based splits for preventing over-fitting. Also, *enable_categorical* needs to be set to have categorical feature support. See [Categorical Data](#) and [Parameters for Categorical Feature](#) for details.

- **multi_strategy** (*Optional[str]*) – New in version 2.0.0.

Note: This parameter is working-in-progress.

The strategy used for training multi-target models, including multi-target regression and multi-class classification. See [Multiple Outputs](#) for more information.

- `one_output_per_tree`: One model for each target.
- `multi_output_tree`: Use multi-target trees.

- **eval_metric** (*Optional[Union[str, List[str], Callable]]*) – New in version 1.6.0.

Metric used for monitoring the training result and early stopping. It can be a string or list of strings as names of predefined metric in XGBoost (See `doc/parameter.rst`), one of the metrics in `sklearn.metrics`, or any other user defined metric that looks like *sklearn.metrics*.

If custom objective is also provided, then custom metric should implement the corresponding reverse link function.

Unlike the *scoring* parameter commonly used in scikit-learn, when a callable object is provided, it's assumed to be a cost function and by default XGBoost will minimize the result during early stopping.

For advanced usage on Early stopping like directly choosing to maximize instead of minimize, see [xgboost.callback.EarlyStopping](#).

See *Custom Objective and Evaluation Metric* for more.

Note: This parameter replaces *eval_metric* in *fit()* method. The old one receives untransformed prediction regardless of whether custom objective is being used.

```
from sklearn.datasets import load_diabetes
from sklearn.metrics import mean_absolute_error
X, y = load_diabetes(return_X_y=True)
reg = xgb.XGBRegressor(
    tree_method="hist",
    eval_metric=mean_absolute_error,
)
reg.fit(X, y, eval_set=[(X, y)])
```

- **early_stopping_rounds** (*Optional*[*int*]) – New in version 1.6.0.
 - Activates early stopping. Validation metric needs to improve at least once in every **early_stopping_rounds** round(s) to continue training. Requires at least one item in **eval_set** in *fit()*.
 - If early stopping occurs, the model will have two additional attributes: *best_score* and *best_iteration*. These are used by the *predict()* and *apply()* methods to determine the optimal number of trees during inference. If users want to access the full model (including trees built after early stopping), they can specify the *iteration_range* in these inference methods. In addition, other utilities like model plotting can also use the entire model.
 - If you prefer to discard the trees after *best_iteration*, consider using the callback function *xgboost.callback.EarlyStopping*.
 - If there's more than one item in **eval_set**, the last entry will be used for early stopping. If there's more than one metric in **eval_metric**, the last metric will be used for early stopping.

Note: This parameter replaces *early_stopping_rounds* in *fit()* method.

- **callbacks** (*Optional*[*List*[*TrainingCallback*]]) – List of callback functions that are applied at end of each iteration. It is possible to use predefined callbacks by using *Callback API*.

Note: States in callback are not preserved during training, which means callback objects can not be reused for multiple training sessions without reinitialization or deepcopy.

```
for params in parameters_grid:
    # be sure to (re)initialize the callbacks before each run
    callbacks = [xgb.callback.LearningRateScheduler(custom_rates)]
    reg = xgboost.XGBRegressor(**params, callbacks=callbacks)
    reg.fit(X, y)
```

- **kwargs** (*dict*, *optional*) – Keyword arguments for XGBoost Booster object. Full documentation of parameters can be found [here](#). Attempting to set a parameter via the constructor args and **kwargs** dict simultaneously will result in a *TypeError*.

Note: `**kwargs` unsupported by scikit-learn

`**kwargs` is unsupported by scikit-learn. We do not guarantee that parameters passed via this argument will interact properly with scikit-learn.

Note: Custom objective function

A custom objective function can be provided for the `objective` parameter. In this case, it should have the signature `objective(y_true, y_pred) -> grad, hess`:

y_true: array_like of shape [n_samples]

The target values

y_pred: array_like of shape [n_samples]

The predicted values

grad: array_like of shape [n_samples]

The value of the gradient for each sample point.

hess: array_like of shape [n_samples]

The value of the second derivative for each sample point

apply(X, iteration_range=None)

Return the predicted leaf every tree for each sample. If the model is trained with early stopping, then `best_iteration` is used automatically.

Parameters

- **X** (array_like, shape=[n_samples, n_features]) – Input features matrix.
- **iteration_range** (Tuple[int, int] | None) – See `predict()`.

Returns

X_leaves – For each datapoint `x` in `X` and for each tree, return the index of the leaf `x` ends up in. Leaves are numbered within `[0; 2**(self.max_depth+1))`, possibly with gaps in the numbering.

Return type

array_like, shape=[n_samples, n_trees]

property best_iteration: `int`

The best iteration obtained by early stopping. This attribute is 0-based, for instance if the best iteration is the first round, then `best_iteration` is 0.

property best_score: `float`

The best score obtained by early stopping.

property client: `distributed.Client`

The dask client used in this model. The *Client* object can not be serialized for transmission, so if task is launched from a worker instead of directly from the client process, this attribute needs to be set at that worker.

property coef_: `ndarray`

Coefficients property

Note: Coefficients are defined only for linear learners

Coefficients are only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

coef_

Return type

array of shape [n_features] or [n_classes, n_features]

evals_result()

Return the evaluation results.

If **eval_set** is passed to the *fit()* function, you can call *evals_result()* to get evaluation results for all passed **eval_sets**. When **eval_metric** is also passed to the *fit()* function, the **evals_result** will contain the **eval_metrics** passed to the *fit()* function.

The returned evaluation result is a dictionary:

```
{'validation_0': {'logloss': ['0.604835', '0.531479']},
 'validation_1': {'logloss': ['0.41965', '0.17686']}}
```

Return type

evals_result

property feature_importances_: ndarray

Feature importances property, return depends on *importance_type* parameter. When model trained with multi-class/multi-label/multi-target dataset, the feature importance is “averaged” over all targets. The “average” is defined based on the importance type. For instance, if the importance type is “total_gain”, then the score is sum of loss change for each split from all trees.

Returns

- **feature_importances_** (array of shape [n_features] except for multi-class)
- linear model, which returns an array with shape (n_features, n_classes)

property feature_names_in_: ndarray

Names of features seen during *fit()*. Defined only when *X* has feature names that are all strings.

fit(*X*, *y*, *, *sample_weight=None*, *base_margin=None*, *eval_set=None*, *eval_metric=None*, *early_stopping_rounds=None*, *verbose=True*, *xgb_model=None*, *sample_weight_eval_set=None*, *base_margin_eval_set=None*, *feature_weights=None*, *callbacks=None*)

Fit gradient boosting model.

Note that calling *fit()* multiple times will cause the model object to be re-fit from scratch. To resume training from a previous checkpoint, explicitly pass *xgb_model* argument.

Parameters

- **X** (*da.Array* | *dd.DataFrame*) – Feature matrix. See *Supported data structures for various XGBoost functions* for a list of supported types.

When the *tree_method* is set to *hist*, internally, the *QuantileDMatrix* will be used instead of the *DMatrix* for conserving memory. However, this has performance implications when the device of input data is not matched with algorithm. For instance, if the input is a numpy array on CPU but *cuda* is used for training, then the data is first processed on CPU then transferred to GPU.

- **y** (*da.Array* | *dd.DataFrame* | *dd.Series*) – Labels
- **sample_weight** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – instance weights
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – global bias for each instance.
- **eval_set** (*Sequence*[*Tuple*[*da.Array* | *dd.DataFrame* | *dd.Series*, *da.Array* | *dd.DataFrame* | *dd.Series*]] | *None*) – A list of (X, y) tuple pairs to use as validation sets, for which metrics will be computed. Validation metrics will help us track the performance of the model.
- **eval_metric** (*str*, *list of str*, or *callable*, *optional*) – Deprecated since version 1.6.0.
Use *eval_metric* in *__init__()* or *set_params()* instead.
- **early_stopping_rounds** (*int*) – Deprecated since version 1.6.0.
Use *early_stopping_rounds* in *__init__()* or *set_params()* instead.
- **verbose** (*int* | *bool*) – If *verbose* is True and an evaluation set is used, the evaluation metric measured on the validation set is printed to stdout at each boosting stage. If *verbose* is an integer, the evaluation metric is printed at each *verbose* boosting stage. The last boosting stage / the boosting stage found by using *early_stopping_rounds* is also printed.
- **xgb_model** (*Booster* | *XGBModel* | *None*) – file name of stored XGBoost model or ‘Booster’ instance XGBoost model to be loaded before training (allows training continuation).
- **sample_weight_eval_set** (*Sequence*[*da.Array* | *dd.DataFrame* | *dd.Series*] | *None*) – A list of the form [L_1, L_2, ..., L_n], where each L_i is an array like object storing instance weights for the i-th validation set.
- **base_margin_eval_set** (*Sequence*[*da.Array* | *dd.DataFrame* | *dd.Series*] | *None*) – A list of the form [M_1, M_2, ..., M_n], where each M_i is an array like object storing base margin for the i-th validation set.
- **feature_weights** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Weight for each feature, defines the probability of each feature being selected when *colsample* is being used. All values must be greater than 0, otherwise a *ValueError* is thrown.
- **callbacks** (*Sequence*[*TrainingCallback*] | *None*) – Deprecated since version 1.6.0: Use *callbacks* in *__init__()* or *set_params()* instead.

Return type

DaskXGBRFClassifier

get_booster()

Get the underlying xgboost Booster of this model.

This will raise an exception when fit was not called

Returns

booster

Return type

a xgboost booster of underlying model

get_metadata_routing()

Get metadata routing of this object.

Please check [User Guide](#) on how the routing mechanism works.

Returns

routing – A MetadataRequest encapsulating routing information.

Return type

MetadataRequest

get_num_boosting_rounds()

Gets the number of xgboost boosting rounds.

Return type

int

get_params(deep=True)

Get parameters.

Parameters

deep (*bool*) –

Return type

Dict[str, Any]

get_xgb_params()

Get xgboost specific parameters.

Return type

Dict[str, Any]

property intercept_: ndarray

Intercept (bias) property

Note: Intercept is defined only for linear learners

Intercept (bias) is only defined when the linear model is chosen as base learner (*booster=gblinear*). It is not defined for other base learner types, such as tree learners (*booster=gbtrees*).

Returns

intercept_

Return type

array of shape (1,) or [n_classes]

load_model(fname)

Load the model from a file or bytearray. Path to file can be local or as an URI.

The model is loaded from XGBoost format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as *feature_names*) will not be loaded when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.load_model("model.json")
# or
model.load_model("model.ubj")
```

Parameters

fname (*str* / *bytearray* / *PathLike*) – Input file name or memory buffer(see also *save_raw*)

Return type

None

property `n_features_in_`: `int`

Number of features seen during `fit()`.

predict(*X*, *output_margin=False*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict with *X*. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*da.Array* | *dd.DataFrame*) – Data to predict with.
- **output_margin** (*bool*) – Whether to output the raw untransformed margin value.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying `iteration_range=(10, 20)`, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

New in version 1.4.0.

Return type

prediction

predict_proba(*X*, *validate_features=True*, *base_margin=None*, *iteration_range=None*)

Predict the probability of each *X* example being of a given class. If the model is trained with early stopping, then `best_iteration` is used automatically. The estimator uses `inplace_predict` by default and falls back to using `DMatrix` if devices between the data and the estimator don't match.

Note: This function is only thread safe for *gbtree* and *dart*.

Parameters

- **X** (*da.Array* | *dd.DataFrame* | *dd.Series*) – Feature matrix. See [Supported data structures for various XGBoost functions](#) for a list of supported types.
- **validate_features** (*bool*) – When this is True, validate that the Booster's and data's `feature_names` are identical. Otherwise, it is assumed that the `feature_names` are the same.
- **base_margin** (*da.Array* | *dd.DataFrame* | *dd.Series* | *None*) – Margin added to prediction.
- **iteration_range** (*Tuple[int, int]* | *None*) – Specifies which layer of trees are used in prediction. For example, if a random forest is trained with 100 rounds. Specifying `iteration_range=(10, 20)`, then only the forests built during [10, 20) (half open set) rounds are used in this prediction.

Returns

a numpy array of shape array-like of shape (n_samples, n_classes) with the probability of each data example being of a given class.

Return type

prediction

save_model(fname)

Save the model to a file.

The model is saved in an XGBoost internal format which is universal among the various XGBoost interfaces. Auxiliary attributes of the Python Booster object (such as feature_names) will not be saved when using binary format. To save those attributes, use JSON/UBJ instead. See [Model IO](#) for more info.

```
model.save_model("model.json")
# or
model.save_model("model.ubj")
```

Parameters

fname (*str* | *PathLike*) – Output file name

Return type

None

score(X, y, sample_weight=None)

Return the mean accuracy on the given test data and labels.

In multi-label classification, this is the subset accuracy which is a harsh metric since you require for each sample that each label set be correctly predicted.

Parameters

- **X** (array-like of shape (n_samples, n_features)) – Test samples.
- **y** (array-like of shape (n_samples,) or (n_samples, n_outputs)) – True labels for X.
- **sample_weight** (array-like of shape (n_samples,), default=None) – Sample weights.

Returns

score – Mean accuracy of self.predict(X) w.r.t. y.

Return type

float

```
set_fit_request(*, base_margin='$UNCHANGED$', base_margin_eval_set='$UNCHANGED$',
               callbacks='$UNCHANGED$', early_stopping_rounds='$UNCHANGED$',
               eval_metric='$UNCHANGED$', eval_set='$UNCHANGED$',
               feature_weights='$UNCHANGED$', sample_weight='$UNCHANGED$',
               sample_weight_eval_set='$UNCHANGED$', verbose='$UNCHANGED$',
               xgb_model='$UNCHANGED$')
```

Request metadata passed to the fit method.

Note that this method is only relevant if enable_metadata_routing=True (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to `fit` if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to `fit`.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin` parameter in `fit`.
- **base_margin_eval_set** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `base_margin_eval_set` parameter in `fit`.
- **callbacks** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `callbacks` parameter in `fit`.
- **early_stopping_rounds** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `early_stopping_rounds` parameter in `fit`.
- **eval_metric** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_metric` parameter in `fit`.
- **eval_set** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `eval_set` parameter in `fit`.
- **feature_weights** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `feature_weights` parameter in `fit`.
- **sample_weight** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in `fit`.
- **sample_weight_eval_set** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight_eval_set` parameter in `fit`.
- **verbose** (*str*, *True*, *False*, or *None*, default=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `verbose` parameter in `fit`.

- **xgb_model** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for xgb_model parameter in fit.
- **self** (*DaskXGBRFClassifier*) –

Returns

self – The updated object.

Return type

object

set_params(params)**

Set the parameters of this estimator. Modification of the sklearn method to allow unknown kwargs. This allows using the full range of xgboost parameters that are not defined as member variables in sklearn grid search.

Return type

self

Parameters

params (*Any*) –

set_predict_proba_request(*, *base_margin*='UNCHANGED\$', *iteration_range*='UNCHANGED\$', *validate_features*='UNCHANGED\$')

Request metadata passed to the `predict_proba` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see `sklearn.set_config()`). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- *True*: metadata is requested, and passed to `predict_proba` if provided. The request is ignored if metadata is not provided.
- *False*: metadata is not requested and the meta-estimator will not pass it to `predict_proba`.
- *None*: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- *str*: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for base_margin parameter in `predict_proba`.
- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for iteration_range parameter in `predict_proba`.

- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `validate_features` parameter in `predict_proba`.
- **self** (*DaskXGBRFClassifier*) –

Returns

self – The updated object.

Return type

object

set_predict_request(***, *base_margin*='\$UNCHANGED\$', *iteration_range*='\$UNCHANGED\$', *output_margin*='\$UNCHANGED\$', *validate_features*='\$UNCHANGED\$')

Request metadata passed to the `predict` method.

Note that this method is only relevant if `enable_metadata_routing=True` (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- **True**: metadata is requested, and passed to `predict` if provided. The request is ignored if metadata is not provided.
- **False**: metadata is not requested and the meta-estimator will not pass it to `predict`.
- **None**: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- **str**: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **base_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `base_margin` parameter in `predict`.
- **iteration_range** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `iteration_range` parameter in `predict`.
- **output_margin** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `output_margin` parameter in `predict`.
- **validate_features** (*str*, *True*, *False*, or *None*, *default=sklearn.utils.metadata_routing.UNCHANGED*) – Metadata routing for `validate_features` parameter in `predict`.
- **self** (*DaskXGBRFClassifier*) –

Returns

self – The updated object.

Return type

object

set_score_request(*, *sample_weight*='\$UNCHANGED\$')

Request metadata passed to the score method.

Note that this method is only relevant if `enable_metadata_routing=True` (see [sklearn.set_config\(\)](#)). Please see [User Guide](#) on how the routing mechanism works.

The options for each parameter are:

- `True`: metadata is requested, and passed to `score` if provided. The request is ignored if metadata is not provided.
- `False`: metadata is not requested and the meta-estimator will not pass it to `score`.
- `None`: metadata is not requested, and the meta-estimator will raise an error if the user provides it.
- `str`: metadata should be passed to the meta-estimator with this given alias instead of the original name.

The default (`sklearn.utils.metadata_routing.UNCHANGED`) retains the existing request. This allows you to change the request for some parameters and not others.

New in version 1.3.

Note: This method is only relevant if this estimator is used as a sub-estimator of a meta-estimator, e.g. used inside a [Pipeline](#). Otherwise it has no effect.

Parameters

- **sample_weight** (`str`, `True`, `False`, or `None`, *default*=`sklearn.utils.metadata_routing.UNCHANGED`) – Metadata routing for `sample_weight` parameter in `score`.
- **self** (`DaskXGBRFClassifier`) –

Returns

self – The updated object.

Return type

object

PySpark API

PySpark XGBoost integration interface

```
class xgboost.spark.SparkXGBClassifier(*, features_col='features', label_col='label',
                                       prediction_col='prediction', probability_col='probability',
                                       raw_prediction_col='rawPrediction', pred_contrib_col=None,
                                       validation_indicator_col=None, weight_col=None,
                                       base_margin_col=None, num_workers=1, use_gpu=None,
                                       device=None, force_repartition=False,
                                       repartition_random_shuffle=False,
                                       enable_sparse_data_optim=False, **kwargs)
```

Bases: `_SparkXGBEstimator`, `HasProbabilityCol`, `HasRawPredictionCol`

SparkXGBClassifier is a PySpark ML estimator. It implements the XGBoost classification algorithm based on XGBoost python library, and it can be used in PySpark Pipeline and PySpark ML meta algorithms like - [CrossValidator](#)/ - [TrainValidationSplit](#)/ - [OneVsRest](#)

SparkXGBClassifier automatically supports most of the parameters in [xgboost.XGBClassifier](#) constructor and most of the parameters used in [xgboost.XGBClassifier.fit\(\)](#) and [xgboost.XGBClassifier.predict\(\)](#) method.

To enable GPU support, set *device* to *cuda* or *gpu*.

SparkXGBClassifier doesn't support setting *base_margin* explicitly as well, but support another param called *base_margin_col*. see doc below for more details.

SparkXGBClassifier doesn't support setting *output_margin*, but we can get output margin from the raw prediction column. See *raw_prediction_col* param doc below for more details.

SparkXGBClassifier doesn't support *validate_features* and *output_margin* param.

SparkXGBClassifier doesn't support setting *nthread* xgboost param, instead, the *nthread* param for each xgboost worker will be set equal to *spark.task.cpus* config value.

Parameters

- **features_col** – When the value is string, it requires the features column name to be vector type. When the value is a list of string, it requires all the feature columns to be numeric types.
- **label_col** – Label column name. Default to “label”.
- **prediction_col** – Prediction column name. Default to “prediction”
- **probability_col** – Column name for predicted class conditional probabilities. Default to `probabilityCol`
- **raw_prediction_col** – The *output_margin=True* is implicitly supported by the *rawPredictionCol* output column, which is always returned with the predicted margin values.
- **pred_contrib_col** ([pyspark.ml.param.Param\[str\]](#)) – Contribution prediction column name.
- **validation_indicator_col** – For params related to [xgboost.XGBClassifier](#) training with evaluation dataset's supervision, set [xgboost.spark.SparkXGBClassifier.validation_indicator_col](#) parameter instead of setting the *eval_set* parameter in [xgboost.XGBClassifier](#) fit method.
- **weight_col** – To specify the weight of the training and validation dataset, set [xgboost.spark.SparkXGBClassifier.weight_col](#) parameter instead of setting *sample_weight* and *sample_weight_eval_set* parameter in [xgboost.XGBClassifier](#) fit method.
- **base_margin_col** – To specify the base margins of the training and validation dataset, set [xgboost.spark.SparkXGBClassifier.base_margin_col](#) parameter instead of setting *base_margin* and *base_margin_eval_set* in the [xgboost.XGBClassifier](#) fit method.
- **num_workers** – How many XGBoost workers to be used to train. Each XGBoost worker corresponds to one spark task.
- **use_gpu** – Deprecated since version 2.0.0.
Use *device* instead.
- **device** – New in version 2.0.0.
Device for XGBoost workers, available options are *cpu*, *cuda*, and *gpu*.

- **force_repartition** – Boolean value to specify if forcing the input dataset to be repartitioned before XGBoost training.
- **repartition_random_shuffle** – Boolean value to specify if randomly shuffling the dataset when repartitioning is required.
- **enable_sparse_data_optim** – Boolean value to specify if enabling sparse data optimization, if True, Xgboost DMatrix object will be constructed from sparse matrix instead of dense matrix.
- **kwargs** – A dictionary of xgboost parameters, please refer to <https://xgboost.readthedocs.io/en/stable/parameter.html>

Note: The Parameters chart above contains parameters that need special handling. For a full list of parameters, see entries with *Param(parent=...* below.

This API is experimental.

Examples

```
>>> from xgboost.spark import SparkXGBClassifier
>>> from pyspark.ml.linalg import Vectors
>>> df_train = spark.createDataFrame([
...     (Vectors.dense(1.0, 2.0, 3.0), 0, False, 1.0),
...     (Vectors.sparse(3, {1: 1.0, 2: 5.5}), 1, False, 2.0),
...     (Vectors.dense(4.0, 5.0, 6.0), 0, True, 1.0),
...     (Vectors.sparse(3, {1: 6.0, 2: 7.5}), 1, True, 2.0),
... ], ["features", "label", "isVal", "weight"])
>>> df_test = spark.createDataFrame([
...     (Vectors.dense(1.0, 2.0, 3.0), ),
... ], ["features"])
>>> xgb_classifier = SparkXGBClassifier(max_depth=5, missing=0.0,
...     validation_indicator_col='isVal', weight_col='weight',
...     early_stopping_rounds=1, eval_metric='logloss')
>>> xgb_clf_model = xgb_classifier.fit(df_train)
>>> xgb_clf_model.transform(df_test).show()
```

clear(*param*)

Clears a param from the param map if it has been explicitly set.

Parameters

param (*Param*) –

Return type

None

copy(*extra=None*)

Creates a copy of this instance with the same uid and some extra params. The default implementation creates a shallow copy using `copy.copy()`, and then copies the embedded and extra parameters over and returns the copy. Subclasses should override this method if the default approach is not sufficient.

Parameters

- **extra** (*dict*, *optional*) – Extra parameters to copy to the new instance
- **self** (*P*) –

Returns

Copy of this instance

Return type

Params

explainParam(*param*)

Explains a single param and returns its name, doc, and optional default value and user-supplied value in a string.

Parameters

param (*str* | *Param*) –

Return type

str

explainParams()

Returns the documentation of all params with their optionally default values and user-supplied values.

Return type

str

extractParamMap(*extra=None*)

Extracts the embedded default param values and user-supplied values, and then merges them with extra values from input into a flat param map, where the latter value is used if there exist conflicts, i.e., with ordering: default param values < user-supplied values < extra.

Parameters

extra (*dict*, *optional*) – extra param values

Returns

merged param map

Return type

dict

fit(*dataset*, *params=None*)

Fits a model to the input dataset with optional parameters.

New in version 1.3.0.

Parameters

- **dataset** (*pyspark.sql.DataFrame*) – input dataset.
- **params** (*dict* or *list* or *tuple*, *optional*) – an optional param map that overrides embedded params. If a list/tuple of param maps is given, this calls fit on each param map and returns a list of models.

Returns

fitted model(s)

Return type

Transformer or a list of Transformer

fitMultiple(*dataset*, *paramMaps*)

Fits a model to the input dataset for each param map in *paramMaps*.

New in version 2.3.0.

Parameters

- **dataset** (*pyspark.sql.DataFrame*) – input dataset.

- **paramMaps** (`collections.abc.Sequence`) – A Sequence of param maps.

Returns

A thread safe iterable which contains one model for each param map. Each call to `next(modelIterator)` will return `(index, model)` where model was fit using `paramMaps[index]`. `index` values may not be sequential.

Return type

`_FitMultipleIterator`

getFeaturesCol()

Gets the value of featuresCol or its default value.

Return type

`str`

getLabelCol()

Gets the value of labelCol or its default value.

Return type

`str`

getOrDefault(param)

Gets the value of a param in the user-supplied param map or its default value. Raises an error if neither is set.

Parameters

param (`str` | `Param[T]`) –

Return type

`Any` | `T`

getParam(paramName)

Gets a param by its name.

Parameters

paramName (`str`) –

Return type

`Param`

getPredictionCol()

Gets the value of predictionCol or its default value.

Return type

`str`

getProbabilityCol()

Gets the value of probabilityCol or its default value.

Return type

`str`

getRawPredictionCol()

Gets the value of rawPredictionCol or its default value.

Return type

`str`

getValidationIndicatorCol()

Gets the value of validationIndicatorCol or its default value.

Return type

`str`

getWeightCol()

Gets the value of `weightCol` or its default value.

Return type

`str`

hasDefault(*param*)

Checks whether a param has a default value.

Parameters

param (`str` | `Param[Any]`) –

Return type

`bool`

hasParam(*paramName*)

Tests whether this instance contains a param with a given (string) name.

Parameters

paramName (`str`) –

Return type

`bool`

isDefined(*param*)

Checks whether a param is explicitly set by user or has a default value.

Parameters

param (`str` | `Param[Any]`) –

Return type

`bool`

isSet(*param*)

Checks whether a param is explicitly set by user.

Parameters

param (`str` | `Param[Any]`) –

Return type

`bool`

classmethod load(*path*)

Reads an ML instance from the input path, a shortcut of `read().load(path)`.

Parameters

path (`str`) –

Return type

`RL`

property params: List[Param]

Returns all params ordered by name. The default implementation uses `dir()` to get all attributes of type `Param`.

classmethod read()

Return the reader for loading the estimator.

Return type*SparkXGBReader***save(path)**

Save this ML instance to the given path, a shortcut of ‘write().save(path)’.

Parameters**path** (*str*) –**Return type**

None

set(param, value)

Sets a parameter in the embedded param map.

Parameters

- **param** (*Param*) –
- **value** (*Any*) –

Return type

None

setParams(kwargs)**

Set params for the estimator.

Parameters**kwargs** (*Any*) –**Return type**

None

set_device(value)

Set device, optional value: cpu, cuda, gpu

Parameters**value** (*str*) –**Return type***_SparkXGBParams***uid**

A unique id for the object.

write()

Return the writer for saving the estimator.

Return type*SparkXGBWriter*

class xgboost.spark.**SparkXGBClassifierModel**(xgb_sklern_model=None)

Bases: *_ClassificationModel*

The model returned by *xgboost.spark.SparkXGBClassifier.fit()*

Note: This API is experimental.

clear(*param*)

Clears a param from the param map if it has been explicitly set.

Parameters

param (*Param*) –

Return type

None

copy(*extra=None*)

Creates a copy of this instance with the same uid and some extra params. The default implementation creates a shallow copy using `copy.copy()`, and then copies the embedded and extra parameters over and returns the copy. Subclasses should override this method if the default approach is not sufficient.

Parameters

- **extra** (*dict*, *optional*) – Extra parameters to copy to the new instance
- **self** (*P*) –

Returns

Copy of this instance

Return type

Params

explainParam(*param*)

Explains a single param and returns its name, doc, and optional default value and user-supplied value in a string.

Parameters

param (*str* | *Param*) –

Return type

str

explainParams()

Returns the documentation of all params with their optionally default values and user-supplied values.

Return type

str

extractParamMap(*extra=None*)

Extracts the embedded default param values and user-supplied values, and then merges them with extra values from input into a flat param map, where the latter value is used if there exist conflicts, i.e., with ordering: default param values < user-supplied values < extra.

Parameters

extra (*dict*, *optional*) – extra param values

Returns

merged param map

Return type

dict

getFeaturesCol()

Gets the value of featuresCol or its default value.

Return type

str

getLabelCol()

Gets the value of labelCol or its default value.

Return type

str

getOrDefault(*param*)

Gets the value of a param in the user-supplied param map or its default value. Raises an error if neither is set.

Parameters

param (*str* | *Param*[*T*]) –

Return type

Any | *T*

getParam(*paramName*)

Gets a param by its name.

Parameters

paramName (*str*) –

Return type

Param

getPredictionCol()

Gets the value of predictionCol or its default value.

Return type

str

getProbabilityCol()

Gets the value of probabilityCol or its default value.

Return type

str

getRawPredictionCol()

Gets the value of rawPredictionCol or its default value.

Return type

str

getValidationIndicatorCol()

Gets the value of validationIndicatorCol or its default value.

Return type

str

getWeightCol()

Gets the value of weightCol or its default value.

Return type

str

get_booster()

Return the *xgboost.core.Booster* instance.

Return type

Booster

get_feature_importances(*importance_type*='weight')

Get feature importance of each feature. Importance type can be defined as:

- 'weight': the number of times a feature is used to split the data across all trees.
- 'gain': the average gain across all splits the feature is used in.
- 'cover': the average coverage across all splits the feature is used in.
- 'total_gain': the total gain across all splits the feature is used in.
- 'total_cover': the total coverage across all splits the feature is used in.

Parameters

importance_type (*str*, default 'weight') – One of the importance types defined above.

Return type

Dict[*str*, float | *List*[float]]

hasDefault(*param*)

Checks whether a param has a default value.

Parameters

param (*str* | *Param*[*Any*]) –

Return type

bool

hasParam(*paramName*)

Tests whether this instance contains a param with a given (string) name.

Parameters

paramName (*str*) –

Return type

bool

isDefined(*param*)

Checks whether a param is explicitly set by user or has a default value.

Parameters

param (*str* | *Param*[*Any*]) –

Return type

bool

isSet(*param*)

Checks whether a param is explicitly set by user.

Parameters

param (*str* | *Param*[*Any*]) –

Return type

bool

classmethod load(*path*)

Reads an ML instance from the input path, a shortcut of *read().load(path)*.

Parameters

path (*str*) –

Return type

RL

property params: `List[Param]`

Returns all params ordered by name. The default implementation uses `dir()` to get all attributes of type `Param`.

classmethod read()

Return the reader for loading the model.

Return type

SparkXGBModelReader

save(path)

Save this ML instance to the given path, a shortcut of `'write().save(path)'`.

Parameters

path (*str*) –

Return type

None

set(param, value)

Sets a parameter in the embedded param map.

Parameters

- **param** (*Param*) –
- **value** (*Any*) –

Return type

None

set_device(value)

Set device, optional value: `cpu`, `cuda`, `gpu`

Parameters

value (*str*) –

Return type

_SparkXGBParams

transform(dataset, params=None)

Transforms the input dataset with optional parameters.

New in version 1.3.0.

Parameters

- **dataset** (`pyspark.sql.DataFrame`) – input dataset
- **params** (*dict*, *optional*) – an optional param map that overrides embedded params.

Returns

transformed dataset

Return type

`pyspark.sql.DataFrame`

uid

A unique id for the object.

write()

Return the writer for saving the model.

Return type

SparkXGBModelWriter

```
class xgboost.spark.SparkXGBRegressor(* , features_col='features', label_col='label',
                                     prediction_col='prediction', pred_contrib_col=None,
                                     validation_indicator_col=None, weight_col=None,
                                     base_margin_col=None, num_workers=1, use_gpu=None,
                                     device=None, force_repartition=False,
                                     repartition_random_shuffle=False,
                                     enable_sparse_data_optim=False, **kwargs)
```

Bases: *_SparkXGBEstimator*

SparkXGBRegressor is a PySpark ML estimator. It implements the XGBoost regression algorithm based on XGBoost python library, and it can be used in PySpark Pipeline and PySpark ML meta algorithms like - [CrossValidator](#)/ - [TrainValidationSplit](#)/ - [OneVsRest](#)

SparkXGBRegressor automatically supports most of the parameters in [xgboost.XGBRegressor](#) constructor and most of the parameters used in [xgboost.XGBRegressor.fit\(\)](#) and [xgboost.XGBRegressor.predict\(\)](#) method.

To enable GPU support, set *device* to *cuda* or *gpu*.

SparkXGBRegressor doesn't support setting *base_margin* explicitly as well, but support another param called *base_margin_col*. see doc below for more details.

SparkXGBRegressor doesn't support *validate_features* and *output_margin* param.

SparkXGBRegressor doesn't support setting *nthread* xgboost param, instead, the *nthread* param for each xgboost worker will be set equal to *spark.task.cpus* config value.

Parameters

- **features_col** – When the value is string, it requires the features column name to be vector type. When the value is a list of string, it requires all the feature columns to be numeric types.
- **label_col** – Label column name. Default to “label”.
- **prediction_col** – Prediction column name. Default to “prediction”
- **pred_contrib_col** ([pyspark.ml.param.Param\[str\]](#)) – Contribution prediction column name.
- **validation_indicator_col** – For params related to [xgboost.XGBRegressor](#) training with evaluation dataset's supervision, set [xgboost.spark.SparkXGBRegressor.validation_indicator_col](#) parameter instead of setting the *eval_set* parameter in [xgboost.XGBRegressor](#) fit method.
- **weight_col** – To specify the weight of the training and validation dataset, set [xgboost.spark.SparkXGBRegressor.weight_col](#) parameter instead of setting *sample_weight* and *sample_weight_eval_set* parameter in [xgboost.XGBRegressor](#) fit method.
- **base_margin_col** – To specify the base margins of the training and validation dataset, set [xgboost.spark.SparkXGBRegressor.base_margin_col](#) parameter instead of setting *base_margin* and *base_margin_eval_set* in the [xgboost.XGBRegressor](#) fit method.
- **num_workers** – How many XGBoost workers to be used to train. Each XGBoost worker corresponds to one spark task.

- **use_gpu** – Deprecated since version 2.0.0.
Use *device* instead.
- **device** – New in version 2.0.0.
Device for XGBoost workers, available options are *cpu*, *cuda*, and *gpu*.
- **force_repartition** – Boolean value to specify if forcing the input dataset to be repartitioned before XGBoost training.
- **repartition_random_shuffle** – Boolean value to specify if randomly shuffling the dataset when repartitioning is required.
- **enable_sparse_data_optim** – Boolean value to specify if enabling sparse data optimization, if True, Xgboost DMatrix object will be constructed from sparse matrix instead of dense matrix.
- **kwargs** – A dictionary of xgboost parameters, please refer to <https://xgboost.readthedocs.io/en/stable/parameter.html>

Note: The Parameters chart above contains parameters that need special handling. For a full list of parameters, see entries with *Param(parent=...* below.

This API is experimental.

Examples

```
>>> from xgboost.spark import SparkXGBRegressor
>>> from pyspark.ml.linalg import Vectors
>>> df_train = spark.createDataFrame([
...     (Vectors.dense(1.0, 2.0, 3.0), 0, False, 1.0),
...     (Vectors.sparse(3, {1: 1.0, 2: 5.5}), 1, False, 2.0),
...     (Vectors.dense(4.0, 5.0, 6.0), 2, True, 1.0),
...     (Vectors.sparse(3, {1: 6.0, 2: 7.5}), 3, True, 2.0),
... ], ["features", "label", "isVal", "weight"])
>>> df_test = spark.createDataFrame([
...     (Vectors.dense(1.0, 2.0, 3.0), ),
...     (Vectors.sparse(3, {1: 1.0, 2: 5.5}), )
... ], ["features"])
>>> xgb_regressor = SparkXGBRegressor(max_depth=5, missing=0.0,
... validation_indicator_col='isVal', weight_col='weight',
... early_stopping_rounds=1, eval_metric='rmse')
>>> xgb_reg_model = xgb_regressor.fit(df_train)
>>> xgb_reg_model.transform(df_test)
```

clear(*param*)

Clears a param from the param map if it has been explicitly set.

Parameters

param (*Param*) –

Return type

None

copy(*extra=None*)

Creates a copy of this instance with the same uid and some extra params. The default implementation creates a shallow copy using `copy.copy()`, and then copies the embedded and extra parameters over and returns the copy. Subclasses should override this method if the default approach is not sufficient.

Parameters

- **extra** (*dict*, *optional*) – Extra parameters to copy to the new instance
- **self** (*P*) –

Returns

Copy of this instance

Return type

Params

explainParam(*param*)

Explains a single param and returns its name, doc, and optional default value and user-supplied value in a string.

Parameters

param (*str* | *Param*) –

Return type

str

explainParams()

Returns the documentation of all params with their optionally default values and user-supplied values.

Return type

str

extractParamMap(*extra=None*)

Extracts the embedded default param values and user-supplied values, and then merges them with extra values from input into a flat param map, where the latter value is used if there exist conflicts, i.e., with ordering: default param values < user-supplied values < extra.

Parameters

extra (*dict*, *optional*) – extra param values

Returns

merged param map

Return type

dict

fit(*dataset*, *params=None*)

Fits a model to the input dataset with optional parameters.

New in version 1.3.0.

Parameters

- **dataset** (*pyspark.sql.DataFrame*) – input dataset.
- **params** (*dict* or *list* or *tuple*, *optional*) – an optional param map that overrides embedded params. If a list/tuple of param maps is given, this calls fit on each param map and returns a list of models.

Returns

fitted model(s)

Return type

Transformer or a list of Transformer

fitMultiple(*dataset*, *paramMaps*)

Fits a model to the input dataset for each param map in *paramMaps*.

New in version 2.3.0.

Parameters

- **dataset** (`pyspark.sql.DataFrame`) – input dataset.
- **paramMaps** (`collections.abc.Sequence`) – A Sequence of param maps.

Returns

A thread safe iterable which contains one model for each param map. Each call to *next(modelIterator)* will return (*index*, *model*) where model was fit using *paramMaps[index]*. *index* values may not be sequential.

Return type

`_FitMultipleIterator`

getFeaturesCol()

Gets the value of featuresCol or its default value.

Return type

`str`

getLabelCol()

Gets the value of labelCol or its default value.

Return type

`str`

getOrDefault(*param*)

Gets the value of a param in the user-supplied param map or its default value. Raises an error if neither is set.

Parameters

param (`str` | `Param[T]`) –

Return type

`Any` | `T`

getParam(*paramName*)

Gets a param by its name.

Parameters

paramName (`str`) –

Return type

`Param`

getPredictionCol()

Gets the value of predictionCol or its default value.

Return type

`str`

getValidationIndicatorCol()

Gets the value of validationIndicatorCol or its default value.

Return type

`str`

getWeightCol()

Gets the value of `weightCol` or its default value.

Return type

`str`

hasDefault(*param*)

Checks whether a param has a default value.

Parameters

param (`str` | `Param[Any]`) –

Return type

`bool`

hasParam(*paramName*)

Tests whether this instance contains a param with a given (string) name.

Parameters

paramName (`str`) –

Return type

`bool`

isDefined(*param*)

Checks whether a param is explicitly set by user or has a default value.

Parameters

param (`str` | `Param[Any]`) –

Return type

`bool`

isSet(*param*)

Checks whether a param is explicitly set by user.

Parameters

param (`str` | `Param[Any]`) –

Return type

`bool`

classmethod load(*path*)

Reads an ML instance from the input path, a shortcut of `read().load(path)`.

Parameters

path (`str`) –

Return type

`RL`

property params: List[Param]

Returns all params ordered by name. The default implementation uses `dir()` to get all attributes of type `Param`.

classmethod read()

Return the reader for loading the estimator.

Return type
SparkXGBReader

save(path)

Save this ML instance to the given path, a shortcut of ‘write().save(path)’.

Parameters
path (*str*) –

Return type
 None

set(param, value)

Sets a parameter in the embedded param map.

Parameters

- **param** (*Param*) –
- **value** (*Any*) –

Return type
 None

setParams(kwargs)**

Set params for the estimator.

Parameters
kwargs (*Any*) –

Return type
 None

set_device(value)

Set device, optional value: cpu, cuda, gpu

Parameters
value (*str*) –

Return type
_SparkXGBParams

uid

A unique id for the object.

write()

Return the writer for saving the estimator.

Return type
SparkXGBWriter

class xgboost.spark.**SparkXGBRegressorModel**(xgb_sklearn_model=None)

Bases: *_SparkXGBModel*

The model returned by *xgboost.spark.SparkXGBRegressor.fit()*

Note: This API is experimental.

clear(*param*)

Clears a param from the param map if it has been explicitly set.

Parameters

param (*Param*) –

Return type

None

copy(*extra=None*)

Creates a copy of this instance with the same uid and some extra params. The default implementation creates a shallow copy using `copy.copy()`, and then copies the embedded and extra parameters over and returns the copy. Subclasses should override this method if the default approach is not sufficient.

Parameters

- **extra** (*dict*, *optional*) – Extra parameters to copy to the new instance
- **self** (*P*) –

Returns

Copy of this instance

Return type

Params

explainParam(*param*)

Explains a single param and returns its name, doc, and optional default value and user-supplied value in a string.

Parameters

param (*str* | *Param*) –

Return type

str

explainParams()

Returns the documentation of all params with their optionally default values and user-supplied values.

Return type

str

extractParamMap(*extra=None*)

Extracts the embedded default param values and user-supplied values, and then merges them with extra values from input into a flat param map, where the latter value is used if there exist conflicts, i.e., with ordering: default param values < user-supplied values < extra.

Parameters

extra (*dict*, *optional*) – extra param values

Returns

merged param map

Return type

dict

getFeaturesCol()

Gets the value of featuresCol or its default value.

Return type

str

getLabelCol()

Gets the value of labelCol or its default value.

Return type

str

getOrDefault(*param*)

Gets the value of a param in the user-supplied param map or its default value. Raises an error if neither is set.

Parameters

param (*str* | *Param*[*T*]) –

Return type

Any | *T*

getParam(*paramName*)

Gets a param by its name.

Parameters

paramName (*str*) –

Return type

Param

getPredictionCol()

Gets the value of predictionCol or its default value.

Return type

str

getValidationIndicatorCol()

Gets the value of validationIndicatorCol or its default value.

Return type

str

getWeightCol()

Gets the value of weightCol or its default value.

Return type

str

get_booster()

Return the *xgboost.core.Booster* instance.

Return type

Booster

get_feature_importances(*importance_type*='weight')

Get feature importance of each feature. Importance type can be defined as:

- ‘weight’: the number of times a feature is used to split the data across all trees.
- ‘gain’: the average gain across all splits the feature is used in.
- ‘cover’: the average coverage across all splits the feature is used in.
- ‘total_gain’: the total gain across all splits the feature is used in.
- ‘total_cover’: the total coverage across all splits the feature is used in.

Parameters

importance_type (*str*, default 'weight') – One of the importance types defined above.

Return type

Dict[*str*, float | *List*[float]]

hasDefault(*param*)

Checks whether a param has a default value.

Parameters

param (*str* | *Param*[*Any*]) –

Return type

bool

hasParam(*paramName*)

Tests whether this instance contains a param with a given (string) name.

Parameters

paramName (*str*) –

Return type

bool

isDefined(*param*)

Checks whether a param is explicitly set by user or has a default value.

Parameters

param (*str* | *Param*[*Any*]) –

Return type

bool

isSet(*param*)

Checks whether a param is explicitly set by user.

Parameters

param (*str* | *Param*[*Any*]) –

Return type

bool

classmethod load(*path*)

Reads an ML instance from the input path, a shortcut of *read().load(path)*.

Parameters

path (*str*) –

Return type

RL

property params: *List*[*Param*]

Returns all params ordered by name. The default implementation uses *dir()* to get all attributes of type *Param*.

classmethod read()

Return the reader for loading the model.

Return type

SparkXGBModelReader

save(*path*)

Save this ML instance to the given path, a shortcut of 'write().save(path)'.

Parameters

path (*str*) –

Return type

None

set(*param, value*)

Sets a parameter in the embedded param map.

Parameters

• **param** (*Param*) –

• **value** (*Any*) –

Return type

None

set_device(*value*)

Set device, optional value: cpu, cuda, gpu

Parameters

value (*str*) –

Return type

_SparkXGBParams

transform(*dataset, params=None*)

Transforms the input dataset with optional parameters.

New in version 1.3.0.

Parameters

• **dataset** (*pyspark.sql.DataFrame*) – input dataset

• **params** (*dict, optional*) – an optional param map that overrides embedded params.

Returns

transformed dataset

Return type

pyspark.sql.DataFrame

uid

A unique id for the object.

write()

Return the writer for saving the model.

Return type

SparkXGBModelWriter

```
class xgboost.spark.SparkXGBRanker(*,features_col='features', label_col='label',
prediction_col='prediction', pred_contrib_col=None,
validation_indicator_col=None, weight_col=None,
base_margin_col=None, qid_col=None, num_workers=1,
use_gpu=None, device=None, force_repartition=False,
repartition_random_shuffle=False, enable_sparse_data_optim=False,
**kwargs)
```

Bases: `_SparkXGBEstimator`

SparkXGBRanker is a PySpark ML estimator. It implements the XGBoost ranking algorithm based on XGBoost python library, and it can be used in PySpark Pipeline and PySpark ML meta algorithms like `CrossValidator/TrainValidationSplit/OneVsRest`

SparkXGBRanker automatically supports most of the parameters in `xgboost.XGBRanker` constructor and most of the parameters used in `xgboost.XGBRanker.fit()` and `xgboost.XGBRanker.predict()` method.

To enable GPU support, set *device* to *cuda* or *gpu*.

SparkXGBRanker doesn't support setting *base_margin* explicitly as well, but support another param called *base_margin_col*. see doc below for more details.

SparkXGBRanker doesn't support setting *output_margin*, but we can get output margin from the raw prediction column. See *raw_prediction_col* param doc below for more details.

SparkXGBRanker doesn't support *validate_features* and *output_margin* param.

SparkXGBRanker doesn't support setting *nthread* xgboost param, instead, the *nthread* param for each xgboost worker will be set equal to *spark.task.cpus* config value.

Parameters

- **features_col** – When the value is string, it requires the features column name to be vector type. When the value is a list of string, it requires all the feature columns to be numeric types.
- **label_col** – Label column name. Default to “label”.
- **prediction_col** – Prediction column name. Default to “prediction”
- **pred_contrib_col** (`pyspark.ml.param.Param[str]`) – Contribution prediction column name.
- **validation_indicator_col** – For params related to `xgboost.XGBRanker` training with evaluation dataset's supervision, set `xgboost.spark.SparkXGBRanker.validation_indicator_col` parameter instead of setting the *eval_set* parameter in `xgboost.XGBRanker` fit method.
- **weight_col** – To specify the weight of the training and validation dataset, set `xgboost.spark.SparkXGBRanker.weight_col` parameter instead of setting *sample_weight* and *sample_weight_eval_set* parameter in `xgboost.XGBRanker` fit method.
- **base_margin_col** – To specify the base margins of the training and validation dataset, set `xgboost.spark.SparkXGBRanker.base_margin_col` parameter instead of setting *base_margin* and *base_margin_eval_set* in the `xgboost.XGBRanker` fit method.
- **qid_col** – Query id column name.
- **num_workers** – How many XGBoost workers to be used to train. Each XGBoost worker corresponds to one spark task.
- **use_gpu** – Deprecated since version 2.0.0.
Use *device* instead.
- **device** – New in version 2.0.0.
Device for XGBoost workers, available options are *cpu*, *cuda*, and *gpu*.
- **force_repartition** – Boolean value to specify if forcing the input dataset to be repartitioned before XGBoost training.

- **repartition_random_shuffle** – Boolean value to specify if randomly shuffling the dataset when repartitioning is required.
- **enable_sparse_data_optim** – Boolean value to specify if enabling sparse data optimization, if True, Xgboost DMatrix object will be constructed from sparse matrix instead of dense matrix.
- **kwargs** – A dictionary of xgboost parameters, please refer to <https://xgboost.readthedocs.io/en/stable/parameter.html>
- **Note:** (..) – The Parameters chart above contains parameters that need special handling.: For a full list of parameters, see entries with *Param(parent=...* below.
- **Note:** – This API is experimental.:

Examples

```
>>> from xgboost.spark import SparkXGBRanker
>>> from pyspark.ml.linalg import Vectors
>>> ranker = SparkXGBRanker(qid_col="qid")
>>> df_train = spark.createDataFrame(
...     [
...         (Vectors.dense(1.0, 2.0, 3.0), 0, 0),
...         (Vectors.dense(4.0, 5.0, 6.0), 1, 0),
...         (Vectors.dense(9.0, 4.0, 8.0), 2, 0),
...         (Vectors.sparse(3, {1: 1.0, 2: 5.5}), 0, 1),
...         (Vectors.sparse(3, {1: 6.0, 2: 7.5}), 1, 1),
...         (Vectors.sparse(3, {1: 8.0, 2: 9.5}), 2, 1),
...     ],
...     ["features", "label", "qid"],
... )
>>> df_test = spark.createDataFrame(
...     [
...         (Vectors.dense(1.5, 2.0, 3.0), 0),
...         (Vectors.dense(4.5, 5.0, 6.0), 0),
...         (Vectors.dense(9.0, 4.5, 8.0), 0),
...         (Vectors.sparse(3, {1: 1.0, 2: 6.0}), 1),
...         (Vectors.sparse(3, {1: 6.0, 2: 7.0}), 1),
...         (Vectors.sparse(3, {1: 8.0, 2: 10.5}), 1),
...     ],
...     ["features", "qid"],
... )
>>> model = ranker.fit(df_train)
>>> model.transform(df_test).show()
```

clear(*param*)

Clears a param from the param map if it has been explicitly set.

Parameters

param (*Param*) –

Return type

None

copy(*extra=None*)

Creates a copy of this instance with the same uid and some extra params. The default implementation

creates a shallow copy using `copy.copy()`, and then copies the embedded and extra parameters over and returns the copy. Subclasses should override this method if the default approach is not sufficient.

Parameters

- **extra** (*dict*, *optional*) – Extra parameters to copy to the new instance
- **self** (*P*) –

Returns

Copy of this instance

Return type

Params

explainParam(*param*)

Explains a single param and returns its name, doc, and optional default value and user-supplied value in a string.

Parameters

param (*str* | *Param*) –

Return type

str

explainParams()

Returns the documentation of all params with their optionally default values and user-supplied values.

Return type

str

extractParamMap(*extra=None*)

Extracts the embedded default param values and user-supplied values, and then merges them with extra values from input into a flat param map, where the latter value is used if there exist conflicts, i.e., with ordering: default param values < user-supplied values < extra.

Parameters

extra (*dict*, *optional*) – extra param values

Returns

merged param map

Return type

dict

fit(*dataset*, *params=None*)

Fits a model to the input dataset with optional parameters.

New in version 1.3.0.

Parameters

- **dataset** (*pyspark.sql.DataFrame*) – input dataset.
- **params** (*dict* or *list* or *tuple*, *optional*) – an optional param map that overrides embedded params. If a list/tuple of param maps is given, this calls fit on each param map and returns a list of models.

Returns

fitted model(s)

Return type

Transformer or a list of Transformer

fitMultiple(*dataset*, *paramMaps*)

Fits a model to the input dataset for each param map in *paramMaps*.

New in version 2.3.0.

Parameters

- **dataset** (`pyspark.sql.DataFrame`) – input dataset.
- **paramMaps** (`collections.abc.Sequence`) – A Sequence of param maps.

Returns

A thread safe iterable which contains one model for each param map. Each call to *next(modelIterator)* will return (*index*, *model*) where model was fit using *paramMaps[index]*. *index* values may not be sequential.

Return type

`_FitMultipleIterator`

getFeaturesCol()

Gets the value of featuresCol or its default value.

Return type

`str`

getLabelCol()

Gets the value of labelCol or its default value.

Return type

`str`

getOrDefault(*param*)

Gets the value of a param in the user-supplied param map or its default value. Raises an error if neither is set.

Parameters

param (`str` | `Param[T]`) –

Return type

`Any` | `T`

getParam(*paramName*)

Gets a param by its name.

Parameters

paramName (`str`) –

Return type

`Param`

getPredictionCol()

Gets the value of predictionCol or its default value.

Return type

`str`

getValidationIndicatorCol()

Gets the value of validationIndicatorCol or its default value.

Return type

`str`

getWeightCol()

Gets the value of weightCol or its default value.

Return type

str

hasDefault(param)

Checks whether a param has a default value.

Parameters

param (str | Param[Any]) –

Return type

bool

hasParam(paramName)

Tests whether this instance contains a param with a given (string) name.

Parameters

paramName (str) –

Return type

bool

isDefined(param)

Checks whether a param is explicitly set by user or has a default value.

Parameters

param (str | Param[Any]) –

Return type

bool

isSet(param)

Checks whether a param is explicitly set by user.

Parameters

param (str | Param[Any]) –

Return type

bool

classmethod load(path)

Reads an ML instance from the input path, a shortcut of *read().load(path)*.

Parameters

path (str) –

Return type

RL

property params: List[Param]

Returns all params ordered by name. The default implementation uses *dir()* to get all attributes of type Param.

classmethod read()

Return the reader for loading the estimator.

Return type

SparkXGBReader

save(*path*)

Save this ML instance to the given path, a shortcut of ‘write().save(path)’.

Parameters

path (*str*) –

Return type

None

set(*param, value*)

Sets a parameter in the embedded param map.

Parameters

- **param** (*Param*) –

- **value** (*Any*) –

Return type

None

setParams(***kwargs*)

Set params for the estimator.

Parameters

kwargs (*Any*) –

Return type

None

set_device(*value*)

Set device, optional value: cpu, cuda, gpu

Parameters

value (*str*) –

Return type

_SparkXGBParams

uid

A unique id for the object.

write()

Return the writer for saving the estimator.

Return type

SparkXGBWriter

class xgboost.spark.**SparkXGBRankerModel**(*xgb_sklearn_model=None*)

Bases: *_SparkXGBModel*

The model returned by *xgboost.spark.SparkXGBRanker.fit()*

Note: This API is experimental.

clear(*param*)

Clears a param from the param map if it has been explicitly set.

Parameters

param (*Param*) –

Return type

None

copy(*extra=None*)

Creates a copy of this instance with the same uid and some extra params. The default implementation creates a shallow copy using `copy.copy()`, and then copies the embedded and extra parameters over and returns the copy. Subclasses should override this method if the default approach is not sufficient.

Parameters

- **extra** (*dict*, *optional*) – Extra parameters to copy to the new instance
- **self** (*P*) –

Returns

Copy of this instance

Return type

Params

explainParam(*param*)

Explains a single param and returns its name, doc, and optional default value and user-supplied value in a string.

Parameters

param (*str* | *Param*) –

Return type

str

explainParams()

Returns the documentation of all params with their optionally default values and user-supplied values.

Return type

str

extractParamMap(*extra=None*)

Extracts the embedded default param values and user-supplied values, and then merges them with extra values from input into a flat param map, where the latter value is used if there exist conflicts, i.e., with ordering: default param values < user-supplied values < extra.

Parameters

extra (*dict*, *optional*) – extra param values

Returns

merged param map

Return type

dict

getFeaturesCol()

Gets the value of featuresCol or its default value.

Return type

str

getLabelCol()

Gets the value of labelCol or its default value.

Return type

str

getOrDefault(*param*)

Gets the value of a param in the user-supplied param map or its default value. Raises an error if neither is set.

Parameters

param (*str* | *Param*[*T*]) –

Return type

Any | *T*

getParam(*paramName*)

Gets a param by its name.

Parameters

paramName (*str*) –

Return type

Param

getPredictionCol()

Gets the value of predictionCol or its default value.

Return type

str

getValidationIndicatorCol()

Gets the value of validationIndicatorCol or its default value.

Return type

str

getWeightCol()

Gets the value of weightCol or its default value.

Return type

str

get_booster()

Return the *xgboost.core.Booster* instance.

Return type

Booster

get_feature_importances(*importance_type*='weight')

Get feature importance of each feature. Importance type can be defined as:

- ‘weight’: the number of times a feature is used to split the data across all trees.
- ‘gain’: the average gain across all splits the feature is used in.
- ‘cover’: the average coverage across all splits the feature is used in.
- ‘total_gain’: the total gain across all splits the feature is used in.
- ‘total_cover’: the total coverage across all splits the feature is used in.

Parameters

importance_type (*str*, default ‘weight’) – One of the importance types defined above.

Return type

Dict[*str*, *float* | *List*[*float*]]

hasDefault(*param*)

Checks whether a param has a default value.

Parameters

param (*str* | *Param[Any]*) –

Return type

bool

hasParam(*paramName*)

Tests whether this instance contains a param with a given (string) name.

Parameters

paramName (*str*) –

Return type

bool

isDefined(*param*)

Checks whether a param is explicitly set by user or has a default value.

Parameters

param (*str* | *Param[Any]*) –

Return type

bool

isSet(*param*)

Checks whether a param is explicitly set by user.

Parameters

param (*str* | *Param[Any]*) –

Return type

bool

classmethod load(*path*)

Reads an ML instance from the input path, a shortcut of *read().load(path)*.

Parameters

path (*str*) –

Return type

RL

property params: *List[Param]*

Returns all params ordered by name. The default implementation uses *dir()* to get all attributes of type *Param*.

classmethod read()

Return the reader for loading the model.

Return type

SparkXGBModelReader

save(*path*)

Save this ML instance to the given path, a shortcut of *'write().save(path)'*.

Parameters

path (*str*) –

Return type

None

set(*param*, *value*)

Sets a parameter in the embedded param map.

Parameters

- **param** (*Param*) –
- **value** (*Any*) –

Return type

None

set_device(*value*)

Set device, optional value: cpu, cuda, gpu

Parameters

value (*str*) –

Return type

_SparkXGBParams

transform(*dataset*, *params=None*)

Transforms the input dataset with optional parameters.

New in version 1.3.0.

Parameters

- **dataset** (*pyspark.sql.DataFrame*) – input dataset
- **params** (*dict*, *optional*) – an optional param map that overrides embedded params.

Returns

transformed dataset

Return type

pyspark.sql.DataFrame

uid

A unique id for the object.

write()

Return the writer for saving the model.

Return type

SparkXGBModelWriter

Callback Functions

This document gives a basic walkthrough of *callback API* used in XGBoost Python package. In XGBoost 1.3, a new callback interface is designed for Python package, which provides the flexibility of designing various extension for training. Also, XGBoost has a number of pre-defined callbacks for supporting early stopping, checkpoints etc.

Using builtin callbacks

By default, training methods in XGBoost have parameters like `early_stopping_rounds` and `verbose/verbose_eval`, when specified the training procedure will define the corresponding callbacks internally. For example, when `early_stopping_rounds` is specified, [EarlyStopping](#) callback is invoked inside iteration loop. You can also pass this callback function directly into XGBoost:

```
D_train = xgb.DMatrix(X_train, y_train)
D_valid = xgb.DMatrix(X_valid, y_valid)

# Define a custom evaluation metric used for early stopping.
def eval_error_metric(predt, dtrain: xgb.DMatrix):
    label = dtrain.get_label()
    r = np.zeros(predt.shape)
    gt = predt > 0.5
    r[gt] = 1 - label[gt]
    le = predt <= 0.5
    r[le] = label[le]
    return 'CustomErr', np.sum(r)

# Specify which dataset and which metric should be used for early stopping.
early_stop = xgb.callback.EarlyStopping(rounds=early_stopping_rounds,
                                         metric_name='CustomErr',
                                         data_name='Train')

booster = xgb.train(
    {'objective': 'binary:logistic',
     'eval_metric': ['error', 'rmse'],
     'tree_method': 'hist'}, D_train,
    evals=[(D_train, 'Train'), (D_valid, 'Valid')],
    feval=eval_error_metric,
    num_boost_round=1000,
    callbacks=[early_stop],
    verbose_eval=False)

dump = booster.get_dump(dump_format='json')
assert len(early_stop.stopping_history['Valid']['CustomErr']) == len(dump)
```

Defining your own callback

XGBoost provides an callback interface class: [TrainingCallback](#), user defined callbacks should inherit this class and override corresponding methods. There's a working example in [Demo for using and defining callback functions](#).

Model

Slice tree model

When booster is set to gbtree or dart, XGBoost builds a tree model, which is a list of trees and can be sliced into multiple sub-models.

```
from sklearn.datasets import make_classification
num_classes = 3
X, y = make_classification(n_samples=1000, n_informative=5,
                          n_classes=num_classes)
dtrain = xgb.DMatrix(data=X, label=y)
num_parallel_tree = 4
num_boost_round = 16
# total number of built trees is num_parallel_tree * num_classes * num_boost_round

# We build a boosted random forest for classification here.
booster = xgb.train({
    'num_parallel_tree': 4, 'subsample': 0.5, 'num_class': 3},
                    num_boost_round=num_boost_round, dtrain=dtrain)

# This is the sliced model, containing [3, 7) forests
# step is also supported with some limitations like negative step is invalid.
sliced: xgb.Booster = booster[3:7]

# Access individual tree layer
trees = [_ for _ in booster]
assert len(trees) == num_boost_round
```

The sliced model is a copy of selected trees, that means the model itself is immutable during slicing. This feature is the basis of `save_best` option in early stopping callback. See *Demo for prediction using individual trees and model slices* for a worked example on how to combine prediction with sliced trees.

Note: The returned model slice doesn't contain attributes like `best_iteration` and `best_score`.

XGBoost Python Feature Walkthrough

This is a collection of examples for using the XGBoost Python package.

Demo for using xgboost with sklearn

```
import multiprocessing

from sklearn.datasets import fetch_california_housing
from sklearn.model_selection import GridSearchCV

import xgboost as xgb

if __name__ == "__main__":
    print("Parallel Parameter optimization")
```

(continues on next page)

(continued from previous page)

```

X, y = fetch_california_housing(return_X_y=True)
xgb_model = xgb.XGBRegressor(
    n_jobs=multiprocessing.cpu_count() // 2, tree_method="hist"
)
clf = GridSearchCV(
    xgb_model,
    {"max_depth": [2, 4, 6], "n_estimators": [50, 100, 200]},
    verbose=1,
    n_jobs=2,
)
clf.fit(X, y)
print(clf.best_score_)
print(clf.best_params_)

```

Demo for obtaining leaf index

```

import os

import xgboost as xgb

# load data in do training
CURRENT_DIR = os.path.dirname(__file__)
dtrain = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.train?format=libsvm")
)
dtest = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.test?format=libsvm")
)
param = {"max_depth": 2, "eta": 1, "objective": "binary:logistic"}
watchlist = [(dtest, "eval"), (dtrain, "train")]
num_round = 3
bst = xgb.train(param, dtrain, num_round, watchlist)

print("start testing predict the leaf indices")
# predict using first 2 tree
leafindex = bst.predict(
    dtest, iteration_range=(0, 2), pred_leaf=True, strict_shape=True
)
print(leafindex.shape)
print(leafindex)
# predict all trees
leafindex = bst.predict(dtest, pred_leaf=True)
print(leafindex.shape)

```


This script demonstrate how to access the eval metrics

```
import os

import xgboost as xgb

CURRENT_DIR = os.path.dirname(__file__)
dtrain = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.train?format=libsvm")
)
dtest = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.test?format=libsvm")
)

param = [
    ("max_depth", 2),
    ("objective", "binary:logistic"),
    ("eval_metric", "logloss"),
    ("eval_metric", "error"),
]

num_round = 2
watchlist = [(dtest, "eval"), (dtrain, "train")]

evals_result = {}
bst = xgb.train(param, dtrain, num_round, watchlist, evals_result=evals_result)

print("Access logloss metric directly from evals_result:")
print(evals_result["eval"]["logloss"])

print("")
print("Access metrics through a loop:")
for e_name, e_mtrs in evals_result.items():
    print("- {}".format(e_name))
    for e_mtr_name, e_mtr_vals in e_mtrs.items():
        print("    - {}".format(e_mtr_name))
        print("        - {}".format(e_mtr_vals))

print("")
print("Access complete dictionary:")
print(evals_result)
```

Demo for gamma regression

```
import numpy as np

import xgboost as xgb

# this script demonstrates how to fit gamma regression model (with log link function)
# in xgboost, before running the demo you need to generate the autoclaims dataset
# by running gen_autoclaims.R located in xgboost/demo/data.
```

(continues on next page)

(continued from previous page)

```

data = np.genfromtxt('../data/autoclaims.csv', delimiter=',')
dtrain = xgb.DMatrix(data[0:4741, 0:34], data[0:4741, 34])
dtest = xgb.DMatrix(data[4741:6773, 0:34], data[4741:6773, 34])

# for gamma regression, we need to set the objective to 'reg:gamma', it also suggests
# to set the base_score to a value between 1 to 5 if the number of iteration is small
param = {'objective':'reg:gamma', 'booster':'gbtree', 'base_score':3}

# the rest of settings are the same
watchlist = [(dtest, 'eval'), (dtrain, 'train')]
num_round = 30

# training and evaluation
bst = xgb.train(param, dtrain, num_round, watchlist)
preds = bst.predict(dtest)
labels = dtest.get_label()
print('test deviance=%f' % (2 * np.sum((labels - preds) / preds - np.log(labels) + np.
↪ log(preds))))

```

Demo for boosting from prediction

```

import os

import xgboost as xgb

CURRENT_DIR = os.path.dirname(__file__)
dtrain = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.train?format=libsvm")
)
dtest = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.test?format=libsvm")
)
watchlist = [(dtest, "eval"), (dtrain, "train")]
###
# advanced: start from a initial base prediction
#
print("start running example to start from a initial prediction")
# specify parameters via map, definition are same as c++ version
param = {"max_depth": 2, "eta": 1, "objective": "binary:logistic"}
# train xgboost for 1 round
bst = xgb.train(param, dtrain, 1, watchlist)
# Note: we need the margin value instead of transformed prediction in
# set_base_margin
# do predict with output_margin=True, will always give you margin values
# before logistic transformation
ptrain = bst.predict(dtrain, output_margin=True)
ptest = bst.predict(dtest, output_margin=True)
dtrain.set_base_margin(ptrain)
dtest.set_base_margin(ptest)

```

(continues on next page)

(continued from previous page)

```
print("this is result of running from initial prediction")
bst = xgb.train(param, dtrain, 1, watchlist)
```

Demo for accessing the xgboost eval metrics by using sklearn interface

```
import numpy as np
from sklearn.datasets import make_hastie_10_2

import xgboost as xgb

X, y = make_hastie_10_2(n_samples=2000, random_state=42)

# Map labels from {-1, 1} to {0, 1}
labels, y = np.unique(y, return_inverse=True)

X_train, X_test = X[:1600], X[1600:]
y_train, y_test = y[:1600], y[1600:]

param_dist = {'objective': 'binary:logistic', 'n_estimators': 2}

clf = xgb.XGBModel(**param_dist)
# Or you can use: clf = xgb.XGBClassifier(**param_dist)

clf.fit(X_train, y_train,
        eval_set=[(X_train, y_train), (X_test, y_test)],
        eval_metric='logloss',
        verbose=True)

# Load evals result by calling the evals_result() function
evals_result = clf.evals_result()

print('Access logloss metric directly from validation_0:')
print(evals_result['validation_0']['logloss'])

print('')
print('Access metrics through a loop:')
for e_name, e_mtrs in evals_result.items():
    print('- {}'.format(e_name))
    for e_mtr_name, e_mtr_vals in e_mtrs.items():
        print('    - {}'.format(e_mtr_name))
        print('        - {}'.format(e_mtr_vals))

print('')
print('Access complete dict:')
print(evals_result)
```

Demo for using feature weight to change column sampling

New in version 1.3.0.

```
import argparse

import numpy as np
from matplotlib import pyplot as plt

import xgboost

def main(args: argparse.Namespace) -> None:
    rng = np.random.RandomState(1994)

    kRows = 4196
    kCols = 10

    X = rng.randn(kRows, kCols)
    y = rng.randn(kRows)
    fw = np.ones(shape=(kCols,))
    for i in range(kCols):
        fw[i] *= float(i)

    dtrain = xgboost.DMatrix(X, y)
    dtrain.set_info(feature_weights=fw)

    # Perform column sampling for each node split evaluation, the sampling process is
    # weighted by feature weights.
    bst = xgboost.train(
        {"tree_method": "hist", "colsample_bynode": 0.2},
        dtrain,
        num_boost_round=10,
        evals=[(dtrain, "d")],
    )
    feature_map = bst.get_fscore()

    # feature zero has 0 weight
    assert feature_map.get("f0", None) is None
    assert max(feature_map.values()) == feature_map.get("f9")

    if args.plot:
        xgboost.plot_importance(bst)
        plt.show()

if __name__ == "__main__":
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--plot",
        type=int,
        default=1,
        help="Set to 0 to disable plotting the evaluation history.",
    )
```

(continues on next page)

(continued from previous page)

```
)
args = parser.parse_args()
main(args)
```

Demo for GLM

```
import os

import xgboost as xgb

##
# this script demonstrate how to fit generalized linear model in xgboost
# basically, we are using linear model, instead of tree for our boosters
##
CURRENT_DIR = os.path.dirname(__file__)
dtrain = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.train?format=libsvm")
)
dtest = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.test?format=libsvm")
)
# change booster to gblinear, so that we are fitting a linear model
# alpha is the L1 regularizer
# lambda is the L2 regularizer
# you can also set lambda_bias which is L2 regularizer on the bias term
param = {
    "objective": "binary:logistic",
    "booster": "gblinear",
    "alpha": 0.0001,
    "lambda": 1,
}

# normally, you do not need to set eta (step_size)
# XGBoost uses a parallel coordinate descent algorithm (shotgun),
# there could be affection on convergence with parallelization on certain cases
# setting eta to be smaller value, e.g 0.5 can make the optimization more stable
# param['eta'] = 1

##
# the rest of settings are the same
##
watchlist = [(dtest, "eval"), (dtrain, "train")]
num_round = 4
bst = xgb.train(param, dtrain, num_round, watchlist)
preds = bst.predict(dtest)
labels = dtest.get_label()
print(
    "error=%f"
    % (
        sum(1 for i in range(len(preds)) if int(preds[i] > 0.5) != labels[i])
    )
)
```

(continues on next page)

(continued from previous page)

```

        / float(len(preds))
    )
)

```

Demo for prediction using number of trees

```

import os

import numpy as np
from sklearn.datasets import load_svmlight_file

import xgboost as xgb

CURRENT_DIR = os.path.dirname(__file__)
train = os.path.join(CURRENT_DIR, "../data/agaricus.txt.train")
test = os.path.join(CURRENT_DIR, "../data/agaricus.txt.test")

def native_interface():
    # load data in do training
    dtrain = xgb.DMatrix(train + "?format=libsvm")
    dtest = xgb.DMatrix(test + "?format=libsvm")
    param = {"max_depth": 2, "eta": 1, "objective": "binary:logistic"}
    watchlist = [(dtest, "eval"), (dtrain, "train")]
    num_round = 3
    bst = xgb.train(param, dtrain, num_round, watchlist)

    print("start testing prediction from first n trees")
    # predict using first 1 tree
    label = dtest.get_label()
    ypred1 = bst.predict(dtest, iteration_range=(0, 1))
    # by default, we predict using all the trees
    ypred2 = bst.predict(dtest)

    print("error of ypred1=%f" % (np.sum((ypred1 > 0.5) != label) / float(len(label))))
    print("error of ypred2=%f" % (np.sum((ypred2 > 0.5) != label) / float(len(label))))

def sklearn_interface():
    X_train, y_train = load_svmlight_file(train)
    X_test, y_test = load_svmlight_file(test)
    clf = xgb.XGBClassifier(n_estimators=3, max_depth=2, eta=1)
    clf.fit(X_train, y_train, eval_set=[(X_test, y_test)])
    assert clf.n_classes_ == 2

    print("start testing prediction from first n trees")
    # predict using first 1 tree
    ypred1 = clf.predict(X_test, iteration_range=(0, 1))
    # by default, we predict using all the trees
    ypred2 = clf.predict(X_test)

```

(continues on next page)

(continued from previous page)

```

print(
    "error of ypred1=%f" % (np.sum((ypred1 > 0.5) != y_test) / float(len(y_test)))
)
print(
    "error of ypred2=%f" % (np.sum((ypred2 > 0.5) != y_test) / float(len(y_test)))
)

if __name__ == "__main__":
    native_interface()
    sklearn_interface()

```

Getting started with XGBoost

This is a simple example of using the native XGBoost interface, there are other interfaces in the Python package like scikit-learn interface and Dask interface.

See *Python Package Introduction* and *XGBoost Tutorials* for other references.

```

import os
import pickle

import numpy as np
from sklearn.datasets import load_svmlight_file

import xgboost as xgb

# Make sure the demo knows where to load the data.
CURRENT_DIR = os.path.dirname(os.path.abspath(__file__))
XGBOOST_ROOT_DIR = os.path.dirname(os.path.dirname(CURRENT_DIR))
DEMO_DIR = os.path.join(XGBOOST_ROOT_DIR, "demo")

# X is a scipy csr matrix, XGBoost supports many other input types,
X, y = load_svmlight_file(os.path.join(DEMO_DIR, "data", "agaricus.txt.train"))
dtrain = xgb.DMatrix(X, y)
# validation set
X_test, y_test = load_svmlight_file(os.path.join(DEMO_DIR, "data", "agaricus.txt.test"))
dtest = xgb.DMatrix(X_test, y_test)

# specify parameters via map, definition are same as c++ version
param = {"max_depth": 2, "eta": 1, "objective": "binary:logistic"}

# specify validations set to watch performance
watchlist = [(dtest, "eval"), (dtrain, "train")]
# number of boosting rounds
num_round = 2
bst = xgb.train(param, dtrain, num_boost_round=num_round, evals=watchlist)

# run prediction
preds = bst.predict(dtest)

```

(continues on next page)

(continued from previous page)

```

labels = dtest.get_label()
print(
    "error=%f"
    % (
        sum(1 for i in range(len(preds)) if int(preds[i] > 0.5) != labels[i])
        / float(len(preds))
    )
)
bst.save_model("model-0.json")
# dump model
bst.dump_model("dump.raw.txt")
# dump model with feature map
bst.dump_model("dump.nice.txt", os.path.join(DEMO_DIR, "data/featmap.txt"))

# save dmatrix into binary buffer
dtest.save_binary("dtest.dmatrix")
# save model
bst.save_model("model-1.json")
# load model and data in
bst2 = xgb.Booster(model_file="model-1.json")
dtest2 = xgb.DMatrix("dtest.dmatrix")
preds2 = bst2.predict(dtest2)
# assert they are the same
assert np.sum(np.abs(preds2 - preds)) == 0

# alternatively, you can pickle the booster
pks = pickle.dumps(bst2)
# load model and data in
bst3 = pickle.loads(pks)
preds3 = bst3.predict(dtest2)
# assert they are the same
assert np.sum(np.abs(preds3 - preds)) == 0

```

Getting started with categorical data

Experimental support for categorical data.

In before, users need to run an encoder themselves before passing the data into XGBoost, which creates a sparse matrix and potentially increase memory usage. This demo showcases the experimental categorical data support, more advanced features are planned.

Also, see [the tutorial](#) for using XGBoost with categorical data.

New in version 1.5.0.

```

from typing import Tuple

import numpy as np
import pandas as pd

import xgboost as xgb

```

(continues on next page)

(continued from previous page)

```

def make_categorical(
    n_samples: int, n_features: int, n_categories: int, onehot: bool
) -> Tuple[pd.DataFrame, pd.Series]:
    """Make some random data for demo."""
    rng = np.random.RandomState(1994)

    pd_dict = {}
    for i in range(n_features + 1):
        c = rng.randint(low=0, high=n_categories, size=n_samples)
        pd_dict[str(i)] = pd.Series(c, dtype=np.int64)

    df = pd.DataFrame(pd_dict)
    label = df.iloc[:, 0]
    df = df.iloc[:, 1:]
    for i in range(0, n_features):
        label += df.iloc[:, i]
    label += 1

    df = df.astype("category")
    categories = np.arange(0, n_categories)
    for col in df.columns:
        df[col] = df[col].cat.set_categories(categories)

    if onehot:
        return pd.get_dummies(df), label
    return df, label

def main() -> None:
    # Use builtin categorical data support
    # For scikit-learn interface, the input data must be pandas DataFrame or cudf
    # DataFrame with categorical features
    X, y = make_categorical(100, 10, 4, False)
    # Specify `enable_categorical` to True, also we use onehot encoding based split
    # here for demonstration. For details see the document of `max_cat_to_onehot`.
    reg = xgb.XGBRegressor(
        tree_method="hist", enable_categorical=True, max_cat_to_onehot=5, device="cuda"
    )
    reg.fit(X, y, eval_set=[(X, y)])

    # Pass in already encoded data
    X_enc, y_enc = make_categorical(100, 10, 4, True)
    reg_enc = xgb.XGBRegressor(tree_method="hist", device="cuda")
    reg_enc.fit(X_enc, y_enc, eval_set=[(X_enc, y_enc)])

    reg_results = np.array(reg.evals_result()["validation_0"]["rmse"])
    reg_enc_results = np.array(reg_enc.evals_result()["validation_0"]["rmse"])

    # Check that they have same results
    np.testing.assert_allclose(reg_results, reg_enc_results)

```

(continues on next page)

(continued from previous page)

```

# Convert to DMatrix for SHAP value
booster: xgb.Booster = reg.get_booster()
m = xgb.DMatrix(X, enable_categorical=True) # specify categorical data support.
SHAP = booster.predict(m, pred_contribs=True)
margin = booster.predict(m, output_margin=True)
np.testing.assert_allclose(
    np.sum(SHAP, axis=len(SHAP.shape) - 1), margin, rtol=1e-3
)

if __name__ == "__main__":
    main()

```

Collection of examples for using sklearn interface

For an introduction to XGBoost's scikit-learn estimator interface, see *Using the Scikit-Learn Estimator Interface*.

Created on 1 Apr 2015

@author: Jamie Hall

```

import pickle

import numpy as np
from sklearn.datasets import fetch_california_housing, load_digits, load_iris
from sklearn.metrics import confusion_matrix, mean_squared_error
from sklearn.model_selection import GridSearchCV, KFold, train_test_split

import xgboost as xgb

rng = np.random.RandomState(31337)

print("Zeros and Ones from the Digits dataset: binary classification")
digits = load_digits(n_class=2)
y = digits['target']
X = digits['data']
kf = KFold(n_splits=2, shuffle=True, random_state=rng)
for train_index, test_index in kf.split(X):
    xgb_model = xgb.XGBClassifier(n_jobs=1).fit(X[train_index], y[train_index])
    predictions = xgb_model.predict(X[test_index])
    actuals = y[test_index]
    print(confusion_matrix(actuals, predictions))

print("Iris: multiclass classification")
iris = load_iris()
y = iris['target']
X = iris['data']
kf = KFold(n_splits=2, shuffle=True, random_state=rng)
for train_index, test_index in kf.split(X):
    xgb_model = xgb.XGBClassifier(n_jobs=1).fit(X[train_index], y[train_index])
    predictions = xgb_model.predict(X[test_index])
    actuals = y[test_index]

```

(continues on next page)

(continued from previous page)

```

print(confusion_matrix(actuals, predictions))

print("California Housing: regression")
X, y = fetch_california_housing(return_X_y=True)
kf = KFold(n_splits=2, shuffle=True, random_state=rng)
for train_index, test_index in kf.split(X):
    xgb_model = xgb.XGBRegressor(n_jobs=1).fit(X[train_index], y[train_index])
    predictions = xgb_model.predict(X[test_index])
    actuals = y[test_index]
    print(mean_squared_error(actuals, predictions))

print("Parameter optimization")
xgb_model = xgb.XGBRegressor(n_jobs=1)
clf = GridSearchCV(xgb_model,
                   {'max_depth': [2, 4],
                    'n_estimators': [50, 100]}, verbose=1, n_jobs=1, cv=3)
clf.fit(X, y)
print(clf.best_score_)
print(clf.best_params_)

# The sklearn API models are picklable
print("Pickling sklearn API models")
# must open in binary format to pickle
pickle.dump(clf, open("best_calif.pkl", "wb"))
clf2 = pickle.load(open("best_calif.pkl", "rb"))
print(np.allclose(clf.predict(X), clf2.predict(X)))

# Early-stopping

X = digits['data']
y = digits['target']
X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=0)
clf = xgb.XGBClassifier(n_jobs=1)
clf.fit(X_train, y_train, early_stopping_rounds=10, eval_metric="auc",
        eval_set=[(X_test, y_test)])

```

Demo for using cross validation

```

import os

import numpy as np

import xgboost as xgb

# load data in do training
CURRENT_DIR = os.path.dirname(__file__)
dtrain = xgb.DMatrix(
    os.path.join(CURRENT_DIR, "../data/agaricus.txt.train?format=libsvm")
)
param = {"max_depth": 2, "eta": 1, "objective": "binary:logistic"}

```

(continues on next page)

(continued from previous page)

```

num_round = 2

print("running cross validation")
# do cross validation, this will print result out as
# [iteration]  metric_name:mean_value+std_value
# std_value is standard deviation of the metric
xgb.cv(
    param,
    dtrain,
    num_round,
    nfold=5,
    metrics={"error"},
    seed=0,
    callbacks=[xgb.callback.EvaluationMonitor(show_stdv=True)],
)

print("running cross validation, disable standard deviation display")
# do cross validation, this will print result out as
# [iteration]  metric_name:mean_value
res = xgb.cv(
    param,
    dtrain,
    num_boost_round=10,
    nfold=5,
    metrics={"error"},
    seed=0,
    callbacks=[
        xgb.callback.EvaluationMonitor(show_stdv=False),
        xgb.callback.EarlyStopping(3),
    ],
)
print(res)
print("running cross validation, with preprocessing function")

# define the preprocessing function
# used to return the preprocessed training, test data, and parameter
# we can use this to do weight rescale, etc.
# as a example, we try to set scale_pos_weight
def fpreproc(dtrain, dtest, param):
    label = dtrain.get_label()
    ratio = float(np.sum(label == 0)) / np.sum(label == 1)
    param["scale_pos_weight"] = ratio
    return (dtrain, dtest, param)

# do cross validation, for each fold
# the dtrain, dtest, param will be passed into fpreproc
# then the return value of fpreproc will be used to generate
# results of that fold
xgb.cv(param, dtrain, num_round, nfold=5, metrics={"auc"}, seed=0, fpreproc=fpreproc)

```

(continues on next page)

(continued from previous page)

```

###
# you can also do cross validation with customized loss function
# See custom_objective.py
##
print("running cross validation, with customized loss function")

def logregobj(preds, dtrain):
    labels = dtrain.get_label()
    preds = 1.0 / (1.0 + np.exp(-preds))
    grad = preds - labels
    hess = preds * (1.0 - preds)
    return grad, hess

def evalerror(preds, dtrain):
    labels = dtrain.get_label()
    return "error", float(sum(labels != (preds > 0.0))) / len(labels)

param = {"max_depth": 2, "eta": 1}
# train with customized objective
xgb.cv(param, dtrain, num_round, nfold=5, seed=0, obj=logregobj, feval=evalerror)

```

Experimental support for external memory

This is similar to the one in *quantile_data_iterator.py*, but for external memory instead of Quantile DMatrix. The feature is not ready for production use yet.

New in version 1.5.0.

See *the tutorial* for more details.

```

import os
import tempfile
from typing import Callable, List, Tuple

import numpy as np
from sklearn.datasets import make_regression

import xgboost

def make_batches(
    n_samples_per_batch: int,
    n_features: int,
    n_batches: int,
    tmpdir: str,
) -> List[Tuple[str, str]]:
    files: List[Tuple[str, str]] = []
    rng = np.random.RandomState(1994)
    for i in range(n_batches):

```

(continues on next page)

(continued from previous page)

```

X, y = make_regression(n_samples_per_batch, n_features, random_state=rng)
X_path = os.path.join(tmpdir, "X-" + str(i) + ".npz")
y_path = os.path.join(tmpdir, "y-" + str(i) + ".npz")
np.save(X_path, X)
np.save(y_path, y)
files.append((X_path, y_path))
return files

class Iterator(xgboost.DataIter):
    """A custom iterator for loading files in batches."""

    def __init__(self, file_paths: List[Tuple[str, str]]):
        self._file_paths = file_paths
        self._it = 0
        # XGBoost will generate some cache files under current directory with the prefix
        # "cache"
        super().__init__(cache_prefix=os.path.join(".", "cache"))

    def load_file(self) -> Tuple[np.ndarray, np.ndarray]:
        X_path, y_path = self._file_paths[self._it]
        X = np.load(X_path)
        y = np.load(y_path)
        assert X.shape[0] == y.shape[0]
        return X, y

    def next(self, input_data: Callable) -> int:
        """Advance the iterator by 1 step and pass the data to XGBoost. This function is
        called by XGBoost during the construction of ``DMatrix``

        """
        if self._it == len(self._file_paths):
            # return 0 to let XGBoost know this is the end of iteration
            return 0

        # input_data is a function passed in by XGBoost who has the similar signature to
        # the ``DMatrix`` constructor.
        X, y = self.load_file()
        input_data(data=X, label=y)
        self._it += 1
        return 1

    def reset(self) -> None:
        """Reset the iterator to its beginning"""
        self._it = 0

def main(tmpdir: str) -> xgboost.Booster:
    # generate some random data for demo
    files = make_batches(1024, 17, 31, tmpdir)
    it = Iterator(files)
    # For non-data arguments, specify it here once instead of passing them by the `next`

```

(continues on next page)

(continued from previous page)

```

# method.
missing = np.NaN
Xy = xgboost.DMatrix(it, missing=missing, enable_categorical=False)

# ``approx`` is also supported, but less efficient due to sketching. GPU behaves
# differently than CPU tree methods as it uses a hybrid approach. See tutorial in
# doc for details.
booster = xgboost.train(
    {"tree_method": "hist", "max_depth": 4},
    Xy,
    evals=[(Xy, "Train")],
    num_boost_round=10,
)
return booster

if __name__ == "__main__":
    with tempfile.TemporaryDirectory() as tmpdir:
        main(tmpdir)

```

Demo for using data iterator with Quantile DMatrix

New in version 1.2.0.

The demo that defines a customized iterator for passing batches of data into `xgboost.QuantileDMatrix` and use this `QuantileDMatrix` for training. The feature is used primarily designed to reduce the required GPU memory for training on distributed environment.

After going through the demo, one might ask why don't we use more native Python iterator? That's because XGBoost requires a `reset` function, while using `itertools.tee` might incur significant memory usage according to:

<https://docs.python.org/3/library/itertools.html#itertools.tee>.

```

import cupy
import numpy

import xgboost

COLS = 64
ROWS_PER_BATCH = 1000 # data is splited by rows
BATCHES = 32

class IterForDMatrixDemo(xgboost.core.DataIter):
    """A data iterator for XGBoost DMatrix.

    `reset` and `next` are required for any data iterator, other functions here
    are utilites for demonstration's purpose.

    """

    def __init__(self):

```

(continues on next page)

(continued from previous page)

```

"""Generate some random data for demonstration.

Actual data can be anything that is currently supported by XGBoost.
"""

self.rows = ROWS_PER_BATCH
self.cols = COLS
rng = cupy.random.RandomState(1994)
self._data = [rng.randn(self.rows, self.cols)] * BATCHES
self._labels = [rng.randn(self.rows)] * BATCHES
self._weights = [rng.uniform(size=self.rows)] * BATCHES

self.it = 0 # set iterator to 0
super().__init__()

def as_array(self):
    return cupy.concatenate(self._data)

def as_array_labels(self):
    return cupy.concatenate(self._labels)

def as_array_weights(self):
    return cupy.concatenate(self._weights)

def data(self):
    """Utility function for obtaining current batch of data."""
    return self._data[self.it]

def labels(self):
    """Utility function for obtaining current batch of label."""
    return self._labels[self.it]

def weights(self):
    return self._weights[self.it]

def reset(self):
    """Reset the iterator"""
    self.it = 0

def next(self, input_data):
    """Yield next batch of data."""
    if self.it == len(self._data):
        # Return 0 when there's no more batch.
        return 0
    input_data(data=self.data(), label=self.labels(), weight=self.weights())
    self.it += 1
    return 1

def main():
    rounds = 100
    it = IterForDMatrixDemo()

```

(continues on next page)

(continued from previous page)

```

# Use iterator, must be `QuantileDMatrix`.

# In this demo, the input batches are created using cupy, and the data processing
# (quantile sketching) will be performed on GPU. If data is loaded with CPU based
# data structures like numpy or pandas, then the processing step will be performed
# on CPU instead.
m_with_it = xgboost.QuantileDMatrix(it)

# Use regular DMatrix.
m = xgboost.DMatrix(
    it.as_array(), it.as_array_labels(), weight=it.as_array_weights()
)

assert m_with_it.num_col() == m.num_col()
assert m_with_it.num_row() == m.num_row()
# Tree method must be `hist`.
reg_with_it = xgboost.train(
    {"tree_method": "hist", "device": "cuda"}, m_with_it, num_boost_round=rounds
)
predict_with_it = reg_with_it.predict(m_with_it)

reg = xgboost.train(
    {"tree_method": "hist", "device": "cuda"}, m, num_boost_round=rounds
)
predict = reg.predict(m)

numpy.testing.assert_allclose(predict_with_it, predict, rtol=1e6)

if __name__ == "__main__":
    main()

```

Demo for using *process_type* with *prune* and *refresh*

Modifying existing trees is not a well established use for XGBoost, so feel free to experiment.

```

import numpy as np
from sklearn.datasets import fetch_california_housing

import xgboost as xgb

def main():
    n_rounds = 32

    X, y = fetch_california_housing(return_X_y=True)

    # Train a model first
    X_train = X[: X.shape[0] // 2]
    y_train = y[: y.shape[0] // 2]
    Xy = xgb.DMatrix(X_train, y_train)

```

(continues on next page)

(continued from previous page)

```

evals_result: xgb.callback.EvaluationMonitor.EvalsLog = {}
booster = xgb.train(
    {"tree_method": "hist", "max_depth": 6, "device": "cuda"},
    Xy,
    num_boost_round=n_rounds,
    evals=[(Xy, "Train")],
    evals_result=evals_result,
)
SHAP = booster.predict(Xy, pred_contribs=True)

# Refresh the leaf value and tree statistic
X_refresh = X[X.shape[0] // 2 :]
y_refresh = y[y.shape[0] // 2 :]
Xy_refresh = xgb.DMatrix(X_refresh, y_refresh)
# The model will adapt to other half of the data by changing leaf value (no change in
# split condition) with refresh_leaf set to True.
refresh_result: xgb.callback.EvaluationMonitor.EvalsLog = {}
refreshed = xgb.train(
    {"process_type": "update", "updater": "refresh", "refresh_leaf": True},
    Xy_refresh,
    num_boost_round=n_rounds,
    xgb_model=booster,
    evals=[(Xy, "Original"), (Xy_refresh, "Train")],
    evals_result=refresh_result,
)

# Refresh the model without changing the leaf value, but tree statistic including
# cover and weight are refreshed.
refresh_result: xgb.callback.EvaluationMonitor.EvalsLog = {}
refreshed = xgb.train(
    {"process_type": "update", "updater": "refresh", "refresh_leaf": False},
    Xy_refresh,
    num_boost_round=n_rounds,
    xgb_model=booster,
    evals=[(Xy, "Original"), (Xy_refresh, "Train")],
    evals_result=refresh_result,
)

# Without refreshing the leaf value, resulting trees should be the same with original
# model except for accumulated statistic. The rtol is for floating point error in
# prediction.
np.testing.assert_allclose(
    refresh_result["Original"]["rmse"], evals_result["Train"]["rmse"], rtol=1e-5
)

# But SHAP value is changed as cover in tree nodes are changed.
refreshed_SHAP = refreshed.predict(Xy, pred_contribs=True)
assert not np.allclose(SHAP, refreshed_SHAP, rtol=1e-3)

# Prune the trees with smaller max_depth
X_update = X_train
y_update = y_train
Xy_update = xgb.DMatrix(X_update, y_update)

```

(continues on next page)

(continued from previous page)

```

prune_result: xgb.callback.EvaluationMonitor.EvalsLog = {}
pruned = xgb.train(
    {"process_type": "update", "updater": "prune", "max_depth": 2},
    Xy_update,
    num_boost_round=n_rounds,
    xgb_model=booster,
    evals=[(Xy, "Original"), (Xy_update, "Train")],
    evals_result=prune_result,
)
# Have a smaller model, but similar accuracy.
np.testing.assert_allclose(
    np.array(prune_result["Original"]["rmse"]),
    np.array(prune_result["Train"]["rmse"]),
    atol=1e-5,
)

if __name__ == "__main__":
    main()

```

Train XGBoost with `cat_in_the_dat` dataset

A simple demo for categorical data support using dataset from Kaggle categorical data tutorial.

The excellent tutorial is at: <https://www.kaggle.com/shahules/an-overview-of-encoding-techniques>

And the data can be found at: <https://www.kaggle.com/shahules/an-overview-of-encoding-techniques/data>

Also, see the tutorial for using XGBoost with categorical data: *Categorical Data*.

```

from __future__ import annotations

import os
from tempfile import TemporaryDirectory
from time import time

import pandas as pd
from sklearn.metrics import roc_auc_score
from sklearn.model_selection import train_test_split

import xgboost as xgb

def load_cat_in_the_dat() -> tuple[pd.DataFrame, pd.Series]:
    """Assuming you have already downloaded the data into `input` directory."""

    df_train = pd.read_csv("./input/cat-in-the-dat/train.csv")

    print(
        "train data set has got {} rows and {} columns".format(
            df_train.shape[0], df_train.shape[1]
        )
    )

```

(continues on next page)

(continued from previous page)

```

    )
)
X = df_train.drop(["target"], axis=1)
y = df_train["target"]

for i in range(0, 5):
    X["bin_" + str(i)] = X["bin_" + str(i)].astype("category")

for i in range(0, 5):
    X["nom_" + str(i)] = X["nom_" + str(i)].astype("category")

for i in range(5, 10):
    X["nom_" + str(i)] = X["nom_" + str(i)].apply(int, base=16)

for i in range(0, 6):
    X["ord_" + str(i)] = X["ord_" + str(i)].astype("category")

print(
    "train data set has got {} rows and {} columns".format(X.shape[0], X.shape[1])
)
return X, y

params = {
    "tree_method": "hist",
    "device": "cuda",
    "n_estimators": 32,
    "colsample_bylevel": 0.7,
}

def categorical_model(X: pd.DataFrame, y: pd.Series, output_dir: str) -> None:
    """Train using builtin categorical data support from XGBoost"""
    X_train, X_test, y_train, y_test = train_test_split(
        X, y, random_state=1994, test_size=0.2
    )
    # Specify `enable_categorical` to True.
    clf = xgb.XGBClassifier(
        **params,
        eval_metric="auc",
        enable_categorical=True,
        max_cat_to_onehot=1, # We use optimal partitioning exclusively
    )
    clf.fit(X_train, y_train, eval_set=[(X_test, y_test), (X_train, y_train)])
    clf.save_model(os.path.join(output_dir, "categorical.json"))

    y_score = clf.predict_proba(X_test)[:, 1] # proba of positive samples
    auc = roc_auc_score(y_test, y_score)
    print("AUC of using builtin categorical data support:", auc)

def onehot_encoding_model(X: pd.DataFrame, y: pd.Series, output_dir: str) -> None:

```

(continues on next page)

(continued from previous page)

```

"""Train using one-hot encoded data."""
X_train, X_test, y_train, y_test = train_test_split(
    X, y, random_state=42, test_size=0.2
)
# Specify `enable_categorical` to False as we are using encoded data.
clf = xgb.XGBClassifier(**params, eval_metric="auc", enable_categorical=False)
clf.fit(
    X_train,
    y_train,
    eval_set=[(X_test, y_test), (X_train, y_train)],
)
clf.save_model(os.path.join(output_dir, "one-hot.json"))

y_score = clf.predict_proba(X_test)[: , 1] # proba of positive samples
auc = roc_auc_score(y_test, y_score)
print("AUC of using onehot encoding:", auc)

if __name__ == "__main__":
    X, y = load_cat_in_the_dat()

    with TemporaryDirectory() as tmpdir:
        start = time()
        categorical_model(X, y, tmpdir)
        end = time()
        print("Duration:categorical", end - start)

        X = pd.get_dummies(X)
        start = time()
        onehot_encoding_model(X, y, tmpdir)
        end = time()
        print("Duration:onehot", end - start)

```

Demo for prediction using individual trees and model slices

```

import os

import numpy as np
from scipy.special import logit
from sklearn.datasets import load_svmlight_file

import xgboost as xgb

CURRENT_DIR = os.path.dirname(__file__)
train = os.path.join(CURRENT_DIR, "../data/agaricus.txt.train")
test = os.path.join(CURRENT_DIR, "../data/agaricus.txt.test")

def individual_tree() -> None:
    """Get prediction from each individual tree and combine them together."""

```

(continues on next page)

(continued from previous page)

```

X_train, y_train = load_svmlight_file(train)
X_test, y_test = load_svmlight_file(test)
Xy_train = xgb.QuantileDMatrix(X_train, y_train)

n_rounds = 4
# Specify the base score, otherwise xgboost will estimate one from the training
# data.
base_score = 0.5
params = {
    "max_depth": 2,
    "eta": 1,
    "objective": "reg:logistic",
    "tree_method": "hist",
    "base_score": base_score,
}
booster = xgb.train(params, Xy_train, num_boost_round=n_rounds)

# Use logit to inverse the base score back to raw leaf value (margin)
scores = np.full((X_test.shape[0],), logit(base_score))
for i in range(n_rounds):
    # - Use output_margin to get raw leaf values
    # - Use iteration_range to get prediction for only one tree
    # - Use previous prediction as base margin for the model
    Xy_test = xgb.DMatrix(X_test, base_margin=scores)

    if i == n_rounds - 1:
        # last round, get the transformed prediction
        scores = booster.predict(
            Xy_test, iteration_range=(i, i + 1), output_margin=False
        )
    else:
        # get raw leaf value for accumulation
        scores = booster.predict(
            Xy_test, iteration_range=(i, i + 1), output_margin=True
        )

full = booster.predict(xgb.DMatrix(X_test), output_margin=False)
np.testing.assert_allclose(scores, full)

def model_slices() -> None:
    """Inference with each individual using model slices."""
    X_train, y_train = load_svmlight_file(train)
    X_test, y_test = load_svmlight_file(test)
    Xy_train = xgb.QuantileDMatrix(X_train, y_train)

    n_rounds = 4
    # Specify the base score, otherwise xgboost will estimate one from the training
    # data.
    base_score = 0.5
    params = {
        "max_depth": 2,

```

(continues on next page)

(continued from previous page)

```

    "eta": 1,
    "objective": "reg:logistic",
    "tree_method": "hist",
    "base_score": base_score,
}
booster = xgb.train(params, Xy_train, num_boost_round=n_rounds)
trees = [booster[t] for t in range(n_rounds)]

# Use logit to inverse the base score back to raw leaf value (margin)
scores = np.full((X_test.shape[0],), logit(base_score))
for i, t in enumerate(trees):
    # Feed previous scores into base margin.
    Xy_test = xgb.DMatrix(X_test, base_margin=scores)

    if i == n_rounds - 1:
        # last round, get the transformed prediction
        scores = t.predict(Xy_test, output_margin=False)
    else:
        # get raw leaf value for accumulation
        scores = t.predict(Xy_test, output_margin=True)

full = booster.predict(xgb.DMatrix(X_test), output_margin=False)
np.testing.assert_allclose(scores, full)

if __name__ == "__main__":
    individual_tree()
    model_slices()

```

Collection of examples for using xgboost.spark estimator interface

@author: Weichen Xu

```

import sklearn.datasets
from pyspark.ml.evaluation import MulticlassClassificationEvaluator, RegressionEvaluator
from pyspark.ml.linalg import Vectors
from pyspark.sql import SparkSession
from pyspark.sql.functions import rand
from sklearn.model_selection import train_test_split

from xgboost.spark import SparkXGBClassifier, SparkXGBRegressor

spark = SparkSession.builder.master("local[*]").getOrCreate()

def create_spark_df(X, y):
    return spark.createDataFrame(
        spark.sparkContext.parallelize(
            [(Vectors.dense(features), float(label)) for features, label in zip(X, y)]
        ),
        ["features", "label"],
    )

```

(continues on next page)

(continued from previous page)

```

    )

# load diabetes dataset (regression dataset)
diabetes_X, diabetes_y = sklearn.datasets.load_diabetes(return_X_y=True)
diabetes_X_train, diabetes_X_test, diabetes_y_train, diabetes_y_test = train_test_split(
    diabetes_X, diabetes_y, test_size=0.3, shuffle=True
)

diabetes_train_spark_df = create_spark_df(diabetes_X_train, diabetes_y_train)
diabetes_test_spark_df = create_spark_df(diabetes_X_test, diabetes_y_test)

# train xgboost regressor model
xgb_regressor = SparkXGBRegressor(max_depth=5)
xgb_regressor_model = xgb_regressor.fit(diabetes_train_spark_df)

transformed_diabetes_test_spark_df = xgb_regressor_model.transform(
    diabetes_test_spark_df
)
regressor_evaluator = RegressionEvaluator(metricName="rmse")
print(
    f"regressor rmse={regressor_evaluator.evaluate(transformed_diabetes_test_spark_df)}"
)

diabetes_train_spark_df2 = diabetes_train_spark_df.withColumn(
    "validationIndicatorCol", rand(1) > 0.7
)

# train xgboost regressor model with validation dataset
xgb_regressor2 = SparkXGBRegressor(
    max_depth=5, validation_indicator_col="validationIndicatorCol"
)
xgb_regressor_model2 = xgb_regressor2.fit(diabetes_train_spark_df2)
transformed_diabetes_test_spark_df2 = xgb_regressor_model2.transform(
    diabetes_test_spark_df
)
print(
    f"regressor2 rmse={regressor_evaluator.evaluate(transformed_diabetes_test_spark_df2)}"
    ↪
)

# load iris dataset (classification dataset)
iris_X, iris_y = sklearn.datasets.load_iris(return_X_y=True)
iris_X_train, iris_X_test, iris_y_train, iris_y_test = train_test_split(
    iris_X, iris_y, test_size=0.3, shuffle=True
)

iris_train_spark_df = create_spark_df(iris_X_train, iris_y_train)
iris_test_spark_df = create_spark_df(iris_X_test, iris_y_test)

# train xgboost classifier model

```

(continues on next page)

(continued from previous page)

```

xgb_classifier = SparkXGBClassifier(max_depth=5)
xgb_classifier_model = xgb_classifier.fit(iris_train_spark_df)

transformed_iris_test_spark_df = xgb_classifier_model.transform(iris_test_spark_df)
classifier_evaluator = MulticlassClassificationEvaluator(metricName="f1")
print(f"classifier f1={classifier_evaluator.evaluate(transformed_iris_test_spark_df)}")

iris_train_spark_df2 = iris_train_spark_df.withColumn(
    "validationIndicatorCol", rand(1) > 0.7
)

# train xgboost classifier model with validation dataset
xgb_classifier2 = SparkXGBClassifier(
    max_depth=5, validation_indicator_col="validationIndicatorCol"
)
xgb_classifier_model2 = xgb_classifier2.fit(iris_train_spark_df2)
transformed_iris_test_spark_df2 = xgb_classifier_model2.transform(iris_test_spark_df)
print(
    f"classifier2 f1={classifier_evaluator.evaluate(transformed_iris_test_spark_df2)}"
)

spark.stop()

```

Quantile Regression

New in version 2.0.0.

The script is inspired by this awesome example in sklearn: https://scikit-learn.org/stable/auto_examples/ensemble/plot_gradient_boosting_quantile.html

Note: The feature is only supported using the Python package. In addition, quantile crossing can happen due to limitation in the algorithm.

```

import argparse
from typing import Dict

import numpy as np
from sklearn.model_selection import train_test_split

import xgboost as xgb

def f(x: np.ndarray) -> np.ndarray:
    """The function to predict."""
    return x * np.sin(x)

def quantile_loss(args: argparse.Namespace) -> None:
    """Train a quantile regression model."""
    rng = np.random.RandomState(1994)

```

(continues on next page)

(continued from previous page)

```

# Generate a synthetic dataset for demo, the generate process is from the sklearn
# example.
X = np.atleast_2d(rng.uniform(0, 10.0, size=1000)).T
expected_y = f(X).ravel()

sigma = 0.5 + X.ravel() / 10.0
noise = rng.lognormal(sigma=sigma) - np.exp(sigma**2.0 / 2.0)
y = expected_y + noise

# Train on 0.05 and 0.95 quantiles. The model is similar to multi-class and
# multi-target models.
alpha = np.array([0.05, 0.5, 0.95])
evals_result: Dict[str, Dict] = {}

X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=rng)
# We will be using the `hist` tree method, quantile DMatrix can be used to preserve
# memory.
# Do not use the `exact` tree method for quantile regression, otherwise the
# performance might drop.
Xy = xgb.QuantileDMatrix(X, y)
# use Xy as a reference
Xy_test = xgb.QuantileDMatrix(X_test, y_test, ref=Xy)

booster = xgb.train(
    {
        # Use the quantile objective function.
        "objective": "reg:quantileerror",
        "tree_method": "hist",
        "quantile_alpha": alpha,
        # Let's try not to overfit.
        "learning_rate": 0.04,
        "max_depth": 5,
    },
    Xy,
    num_boost_round=32,
    early_stopping_rounds=2,
    # The evaluation result is a weighted average across multiple quantiles.
    evals=[(Xy, "Train"), (Xy_test, "Test")],
    evals_result=evals_result,
)
xx = np.atleast_2d(np.linspace(0, 10, 1000)).T
scores = booster.inplace_predict(xx)
# dim 1 is the quantiles
assert scores.shape[0] == xx.shape[0]
assert scores.shape[1] == alpha.shape[0]

y_lower = scores[:, 0] # alpha=0.05
y_med = scores[:, 1] # alpha=0.5, median
y_upper = scores[:, 2] # alpha=0.95

# Train a mse model for comparison
booster = xgb.train(

```

(continues on next page)

(continued from previous page)

```

    {
        "objective": "reg:squarederror",
        "tree_method": "hist",
        # Let's try not to overfit.
        "learning_rate": 0.04,
        "max_depth": 5,
    },
    Xy,
    num_boost_round=32,
    early_stopping_rounds=2,
    evals=[(Xy, "Train"), (Xy_test, "Test")],
    evals_result=evals_result,
)
xx = np.atleast_2d(np.linspace(0, 10, 1000)).T
y_pred = booster.inplace_predict(xx)

if args.plot:
    from matplotlib import pyplot as plt

    fig = plt.figure(figsize=(10, 10))
    plt.plot(xx, f(xx), "g:", linewidth=3, label=r"$f(x) = x\backslash,\sin(x)$")
    plt.plot(X_test, y_test, "b.", markersize=10, label="Test observations")
    plt.plot(xx, y_med, "r-", label="Predicted median")
    plt.plot(xx, y_pred, "m-", label="Predicted mean")
    plt.plot(xx, y_upper, "k-")
    plt.plot(xx, y_lower, "k-")
    plt.fill_between(
        xx.ravel(), y_lower, y_upper, alpha=0.4, label="Predicted 90% interval"
    )
    plt.xlabel("$x$")
    plt.ylabel("$f(x)$")
    plt.ylim(-10, 25)
    plt.legend(loc="upper left")
    plt.show()

if __name__ == "__main__":
    parser = argparse.ArgumentParser()
    parser.add_argument(
        "--plot",
        action="store_true",
        help="Specify it to enable plotting the outputs.",
    )
    args = parser.parse_args()
    quantile_loss(args)

```

Demo for training continuation

```

import os
import pickle
import tempfile

from sklearn.datasets import load_breast_cancer

import xgboost

def training_continuation(tmpdir: str, use_pickle: bool) -> None:
    """Basic training continuation."""
    # Train 128 iterations in 1 session
    X, y = load_breast_cancer(return_X_y=True)
    clf = xgboost.XGBClassifier(n_estimators=128)
    clf.fit(X, y, eval_set=[(X, y)], eval_metric="logloss")
    print("Total boosted rounds:", clf.get_booster().num_boosted_rounds())

    # Train 128 iterations in 2 sessions, with the first one runs for 32 iterations and
    # the second one runs for 96 iterations
    clf = xgboost.XGBClassifier(n_estimators=32)
    clf.fit(X, y, eval_set=[(X, y)], eval_metric="logloss")
    assert clf.get_booster().num_boosted_rounds() == 32

    # load back the model, this could be a checkpoint
    if use_pickle:
        path = os.path.join(tmpdir, "model-first-32.pkl")
        with open(path, "wb") as fd:
            pickle.dump(clf, fd)
        with open(path, "rb") as fd:
            loaded = pickle.load(fd)
    else:
        path = os.path.join(tmpdir, "model-first-32.json")
        clf.save_model(path)
        loaded = xgboost.XGBClassifier()
        loaded.load_model(path)

    clf = xgboost.XGBClassifier(n_estimators=128 - 32)
    clf.fit(X, y, eval_set=[(X, y)], eval_metric="logloss", xgb_model=loaded)

    print("Total boosted rounds:", clf.get_booster().num_boosted_rounds())

    assert clf.get_booster().num_boosted_rounds() == 128

def training_continuation_early_stop(tmpdir: str, use_pickle: bool) -> None:
    """Training continuation with early stopping."""
    early_stopping_rounds = 5
    early_stop = xgboost.callback.EarlyStopping(
        rounds=early_stopping_rounds, save_best=True
    )
    n_estimators = 512

```

(continues on next page)

(continued from previous page)

```

X, y = load_breast_cancer(return_X_y=True)
clf = xgboost.XGBClassifier(n_estimators=n_estimators)
clf.fit(X, y, eval_set=[(X, y)], eval_metric="logloss", callbacks=[early_stop])
print("Total boosted rounds:", clf.get_booster().num_boosted_rounds())
best = clf.best_iteration

# Train 512 iterations in 2 sessions, with the first one runs for 128 iterations and
# the second one runs until early stop.
clf = xgboost.XGBClassifier(n_estimators=128)
# Reinitialize the early stop callback
early_stop = xgboost.callback.EarlyStopping(
    rounds=early_stopping_rounds, save_best=True
)
clf.fit(X, y, eval_set=[(X, y)], eval_metric="logloss", callbacks=[early_stop])
assert clf.get_booster().num_boosted_rounds() == 128

# load back the model, this could be a checkpoint
if use_pickle:
    path = os.path.join(tmpdir, "model-first-128.pkl")
    with open(path, "wb") as fd:
        pickle.dump(clf, fd)
    with open(path, "rb") as fd:
        loaded = pickle.load(fd)
else:
    path = os.path.join(tmpdir, "model-first-128.json")
    clf.save_model(path)
    loaded = xgboost.XGBClassifier()
    loaded.load_model(path)

early_stop = xgboost.callback.EarlyStopping(
    rounds=early_stopping_rounds, save_best=True
)
clf = xgboost.XGBClassifier(n_estimators=n_estimators - 128)
clf.fit(
    X,
    y,
    eval_set=[(X, y)],
    eval_metric="logloss",
    callbacks=[early_stop],
    xgb_model=loaded,
)

print("Total boosted rounds:", clf.get_booster().num_boosted_rounds())
assert clf.best_iteration == best

if __name__ == "__main__":
    with tempfile.TemporaryDirectory() as tmpdir:
        training_continuation_early_stop(tmpdir, False)
        training_continuation_early_stop(tmpdir, True)

```

(continues on next page)

(continued from previous page)

```
training_continuation(tmpdir, True)
training_continuation(tmpdir, False)
```

A demo for multi-output regression

The demo is adopted from scikit-learn:

https://scikit-learn.org/stable/auto_examples/ensemble/plot_random_forest_regression_multioutput.html#sphx-glr-auto-examples-ensemble-plot-random-forest-regression-multioutput-py

See *Multiple Outputs* for more information.

Note: The feature is experimental. For the *multi_output_tree* strategy, many features are missing.

```
import argparse
from typing import Dict, List, Tuple

import numpy as np
from matplotlib import pyplot as plt

import xgboost as xgb

def plot_predt(y: np.ndarray, y_predt: np.ndarray, name: str) -> None:
    s = 25
    plt.scatter(y[:, 0], y[:, 1], c="navy", s=s, edgecolor="black", label="data")
    plt.scatter(
        y_predt[:, 0], y_predt[:, 1], c="cornflowerblue", s=s, edgecolor="black"
    )
    plt.xlim([-1, 2])
    plt.ylim([-1, 2])
    plt.show()

def gen_circle() -> Tuple[np.ndarray, np.ndarray]:
    """Generate a sample dataset that y is a 2 dim circle."""
    rng = np.random.RandomState(1994)
    X = np.sort(200 * rng.rand(100, 1) - 100, axis=0)
    y = np.array([np.pi * np.sin(X).ravel(), np.pi * np.cos(X).ravel()]).T
    y[:, :5, :] += 0.5 - rng.rand(20, 2)
    y = y - y.min()
    y = y / y.max()
    return X, y

def rmse_model(plot_result: bool, strategy: str) -> None:
    """Draw a circle with 2-dim coordinate as target variables."""
    X, y = gen_circle()
    # Train a regressor on it
    reg = xgb.XGBRegressor()
```

(continues on next page)

(continued from previous page)

```

        tree_method="hist",
        n_estimators=128,
        n_jobs=16,
        max_depth=8,
        multi_strategy=strategy,
        subsample=0.6,
    )
    reg.fit(X, y, eval_set=[(X, y)])

    y_predt = reg.predict(X)
    if plot_result:
        plot_predt(y, y_predt, "multi")

def custom_rmse_model(plot_result: bool, strategy: str) -> None:
    """Train using Python implementation of Squared Error."""

    # As the experimental support status, custom objective doesn't support matrix as
    # gradient and hessian, which will be changed in future release.
    def gradient(predt: np.ndarray, dtrain: xgb.DMatrix) -> np.ndarray:
        """Compute the gradient squared error."""
        y = dtrain.get_label().reshape(predt.shape)
        return (predt - y).reshape(y.size)

    def hessian(predt: np.ndarray, dtrain: xgb.DMatrix) -> np.ndarray:
        """Compute the hessian for squared error."""
        return np.ones(predt.shape).reshape(predt.size)

    def squared_log(
        predt: np.ndarray, dtrain: xgb.DMatrix
    ) -> Tuple[np.ndarray, np.ndarray]:
        grad = gradient(predt, dtrain)
        hess = hessian(predt, dtrain)
        return grad, hess

    def rmse(predt: np.ndarray, dtrain: xgb.DMatrix) -> Tuple[str, float]:
        y = dtrain.get_label().reshape(predt.shape)
        v = np.sqrt(np.sum(np.power(y - predt, 2)))
        return "PyRMSE", v

X, y = gen_circle()
Xy = xgb.DMatrix(X, y)
results: Dict[str, Dict[str, List[float]]] = {}
# Make sure the `num_target` is passed to XGBoost when custom objective is used.
# When builtin objective is used, XGBoost can figure out the number of targets
# automatically.
booster = xgb.train(
    {
        "tree_method": "hist",
        "num_target": y.shape[1],
        "multi_strategy": strategy,
    },

```

(continues on next page)

(continued from previous page)

```

        dtrain=Xy,
        num_boost_round=128,
        obj=squared_log,
        evals=[(Xy, "Train")],
        evals_result=results,
        custom_metric=rmse,
    )

    y_predt = booster.inplace_predict(X)
    if plot_result:
        plot_predt(y, y_predt, "multi")

if __name__ == "__main__":
    parser = argparse.ArgumentParser()
    parser.add_argument("--plot", choices=[0, 1], type=int, default=1)
    args = parser.parse_args()

    # Train with builtin RMSE objective
    # - One model per output.
    rmse_model(args.plot == 1, "one_output_per_tree")
    # - One model for all outputs, this is still working in progress, many features are
    # missing.
    rmse_model(args.plot == 1, "multi_output_tree")

    # Train with custom objective.
    # - One model per output.
    custom_rmse_model(args.plot == 1, "one_output_per_tree")
    # - One model for all outputs, this is still working in progress, many features are
    # missing.
    custom_rmse_model(args.plot == 1, "multi_output_tree")

```

Demo for using and defining callback functions

New in version 1.3.0.

```

import argparse
import os
import tempfile

import numpy as np
from matplotlib import pyplot as plt
from sklearn.datasets import load_breast_cancer
from sklearn.model_selection import train_test_split

import xgboost as xgb

class Plotting(xgb.callback.TrainingCallback):
    """Plot evaluation result during training. Only for demonstration purpose as it's
    ↪ quite

```

(continues on next page)

(continued from previous page)

```

slow to draw.

"""

def __init__(self, rounds):
    self.fig = plt.figure()
    self.ax = self.fig.add_subplot(111)
    self.rounds = rounds
    self.lines = {}
    self.fig.show()
    self.x = np.linspace(0, self.rounds, self.rounds)
    plt.ion()

def _get_key(self, data, metric):
    return f"{data}-{metric}"

def after_iteration(self, model, epoch, evals_log):
    """Update the plot."""
    if not self.lines:
        for data, metric in evals_log.items():
            for metric_name, log in metric.items():
                key = self._get_key(data, metric_name)
                expanded = log + [0] * (self.rounds - len(log))
                (self.lines[key],) = self.ax.plot(self.x, expanded, label=key)
            self.ax.legend()
    else:
        # https://pythonspot.com/matplotlib-update-plot/
        for data, metric in evals_log.items():
            for metric_name, log in metric.items():
                key = self._get_key(data, metric_name)
                expanded = log + [0] * (self.rounds - len(log))
                self.lines[key].set_ydata(expanded)
        self.fig.canvas.draw()
        # False to indicate training should not stop.
        return False

def custom_callback():
    """Demo for defining a custom callback function that plots evaluation result during
    training."""
    X, y = load_breast_cancer(return_X_y=True)
    X_train, X_valid, y_train, y_valid = train_test_split(X, y, random_state=0)

    D_train = xgb.DMatrix(X_train, y_train)
    D_valid = xgb.DMatrix(X_valid, y_valid)

    num_boost_round = 100
    plotting = Plotting(num_boost_round)

    # Pass it to the `callbacks` parameter as a list.
    xgb.train(
        {

```

(continues on next page)

(continued from previous page)

```

        "objective": "binary:logistic",
        "eval_metric": ["error", "rmse"],
        "tree_method": "hist",
        "device": "cuda",
    },
    D_train,
    evals=[(D_train, "Train"), (D_valid, "Valid")],
    num_boost_round=num_boost_round,
    callbacks=[plotting],
)

def check_point_callback():
    # only for demo, set a larger value (like 100) in practice as checkpointing is quite
    # slow.
    rounds = 2

    def check(as_pickle):
        for i in range(0, 10, rounds):
            if i == 0:
                continue
            if as_pickle:
                path = os.path.join(tmpdir, "model_" + str(i) + ".pkl")
            else:
                path = os.path.join(tmpdir, "model_" + str(i) + ".json")
            assert os.path.exists(path)

    X, y = load_breast_cancer(return_X_y=True)
    m = xgb.DMatrix(X, y)
    # Check point to a temporary directory for demo
    with tempfile.TemporaryDirectory() as tmpdir:
        # Use callback class from xgboost.callback
        # Feel free to subclass/customize it to suit your need.
        check_point = xgb.callback.TrainingCheckPoint(
            directory=tmpdir, iterations=rounds, name="model"
        )
        xgb.train(
            {"objective": "binary:logistic"},
            m,
            num_boost_round=10,
            verbose_eval=False,
            callbacks=[check_point],
        )
        check(False)

    # This version of checkpoint saves everything including parameters and
    # model. See: doc/tutorials/saving_model.rst
    check_point = xgb.callback.TrainingCheckPoint(
        directory=tmpdir, iterations=rounds, as_pickle=True, name="model"
    )
    xgb.train(
        {"objective": "binary:logistic"},

```

(continues on next page)

(continued from previous page)

```

        m,
        num_boost_round=10,
        verbose_eval=False,
        callbacks=[check_point],
    )
    check(True)

if __name__ == "__main__":
    parser = argparse.ArgumentParser()
    parser.add_argument("--plot", default=1, type=int)
    args = parser.parse_args()

    check_point_callback()

    if args.plot:
        custom_callback()

```

Demo for creating customized multi-class objective function

This demo is only applicable after (excluding) XGBoost 1.0.0, as before this version XGBoost returns transformed prediction for multi-class objective function. More details in comments.

See *Custom Objective and Evaluation Metric* for detailed tutorial and notes.

```

import argparse

import numpy as np
from matplotlib import pyplot as plt

import xgboost as xgb

np.random.seed(1994)

kRows = 100
kCols = 10
kClasses = 4                # number of classes

kRounds = 10                # number of boosting rounds.

# Generate some random data for demo.
X = np.random.randn(kRows, kCols)
y = np.random.randint(0, 4, size=kRows)

m = xgb.DMatrix(X, y)

def softmax(x):
    """Softmax function with x as input vector."""
    e = np.exp(x)
    return e / np.sum(e)

```

(continues on next page)

(continued from previous page)

```

def softprob_obj(predt: np.ndarray, data: xgb.DMatrix):
    """Loss function. Computing the gradient and approximated hessian (diagonal).
    Reimplements the `multi:softprob` inside XGBoost.

    """
    labels = data.get_label()
    if data.get_weight().size == 0:
        # Use 1 as weight if we don't have custom weight.
        weights = np.ones((kRows, 1), dtype=float)
    else:
        weights = data.get_weight()

    # The prediction is of shape (rows, classes), each element in a row
    # represents a raw prediction (leaf weight, hasn't gone through softmax
    # yet). In XGBoost 1.0.0, the prediction is transformed by a softmax
    # function, fixed in later versions.
    assert predt.shape == (kRows, kClasses)

    grad = np.zeros((kRows, kClasses), dtype=float)
    hess = np.zeros((kRows, kClasses), dtype=float)

    eps = 1e-6

    # compute the gradient and hessian, slow iterations in Python, only
    # suitable for demo. Also the one in native XGBoost core is more robust to
    # numeric overflow as we don't do anything to mitigate the `exp` in
    # `softmax` here.
    for r in range(predt.shape[0]):
        target = labels[r]
        p = softmax(predt[r, :])
        for c in range(predt.shape[1]):
            assert target >= 0 or target <= kClasses
            g = p[c] - 1.0 if c == target else p[c]
            g = g * weights[r]
            h = max((2.0 * p[c] * (1.0 - p[c]) * weights[r]).item(), eps)
            grad[r, c] = g
            hess[r, c] = h

    # Right now (XGBoost 1.0.0), reshaping is necessary
    grad = grad.reshape((kRows * kClasses, 1))
    hess = hess.reshape((kRows * kClasses, 1))
    return grad, hess

def predict(booster: xgb.Booster, X):
    """A customized prediction function that converts raw prediction to
    target class.

    """
    # Output margin means we want to obtain the raw prediction obtained from

```

(continues on next page)

(continued from previous page)

```

# tree leaf weight.
predt = booster.predict(X, output_margin=True)
out = np.zeros(kRows)
for r in range(predt.shape[0]):
    # the class with maximum prob (not strictly prob as it haven't gone
    # through softmax yet so it doesn't sum to 1, but result is the same
    # for argmax).
    i = np.argmax(predt[r])
    out[r] = i
return out

def merror(predt: np.ndarray, dtrain: xgb.DMatrix):
    y = dtrain.get_label()
    # Like custom objective, the predt is untransformed leaf weight when custom objective
    # is provided.

    # With the use of `custom_metric` parameter in train function, custom metric receives
    # raw input only when custom objective is also being used. Otherwise custom metric
    # will receive transformed prediction.
    assert predt.shape == (kRows, kClasses)
    out = np.zeros(kRows)
    for r in range(predt.shape[0]):
        i = np.argmax(predt[r])
        out[r] = i

    assert y.shape == out.shape

    errors = np.zeros(kRows)
    errors[y != out] = 1.0
    return 'PyMError', np.sum(errors) / kRows

def plot_history(custom_results, native_results):
    fig, axs = plt.subplots(2, 1)
    ax0 = axs[0]
    ax1 = axs[1]

    pymerror = custom_results['train']['PyMError']
    merror = native_results['train']['merror']

    x = np.arange(0, kRounds, 1)
    ax0.plot(x, pymerror, label='Custom objective')
    ax0.legend()
    ax1.plot(x, merror, label='multi:softmax')
    ax1.legend()

    plt.show()

def main(args):
    custom_results = {}

```

(continues on next page)

(continued from previous page)

```

# Use our custom objective function
booster_custom = xgb.train({'num_class': kClasses,
                           'disable_default_eval_metric': True},
                           m,
                           num_boost_round=kRounds,
                           obj=softprob_obj,
                           custom_metric=merror,
                           evals_result=custom_results,
                           evals=[(m, 'train')])

predt_custom = predict(booster_custom, m)

native_results = {}
# Use the same objective function defined in XGBoost.
booster_native = xgb.train({'num_class': kClasses,
                           "objective": "multi:softmax",
                           'eval_metric': 'merror'},
                           m,
                           num_boost_round=kRounds,
                           evals_result=native_results,
                           evals=[(m, 'train')])
predt_native = booster_native.predict(m)

# We are reimplementing the loss function in XGBoost, so it should
# be the same for normal cases.
assert np.all(predt_custom == predt_native)
np.testing.assert_allclose(custom_results['train']['PyMError'],
                           native_results['train']['merror'])

if args.plot != 0:
    plot_history(custom_results, native_results)

if __name__ == '__main__':
    parser = argparse.ArgumentParser(
        description='Arguments for custom softmax objective function demo.')
    parser.add_argument(
        '--plot',
        type=int,
        default=1,
        help='Set to 0 to disable plotting the evaluation history.')
    args = parser.parse_args()
    main(args)

```

Getting started with learning to rank

New in version 2.0.0.

This is a demonstration of using XGBoost for learning to rank tasks using the MSLR_10k_letor dataset. For more information about the dataset, please visit its [description page](#).

This is a two-part demo, the first one contains a basic example of using XGBoost to train on relevance degree, and the second part simulates click data and enable the position debiasing training.

For an overview of learning to rank in XGBoost, please see *Learning to Rank*.

```
from __future__ import annotations

import argparse
import json
import os
import pickle as pkl

import numpy as np
import pandas as pd
from sklearn.datasets import load_svmlight_file

import xgboost as xgb
from xgboost.testing.data import RelDataCV, simulate_clicks, sort_ltr_samples

def load_mslr_10k(data_path: str, cache_path: str) -> RelDataCV:
    """Load the MSLR10k dataset from data_path and cache a pickle object in cache_path.

    Returns
    -----

    A list of tuples [(X, y, qid), ...].

    """
    root_path = os.path.expanduser(args.data)
    cacheroot_path = os.path.expanduser(args.cache)
    cache_path = os.path.join(cacheroot_path, "MSLR_10K_LETOR.pkl")

    # Use only the Fold1 for demo:
    # Train,      Valid, Test
    # {S1,S2,S3}, S4,   S5
    fold = 1

    if not os.path.exists(cache_path):
        fold_path = os.path.join(root_path, f"Fold{fold}")
        train_path = os.path.join(fold_path, "train.txt")
        valid_path = os.path.join(fold_path, "vali.txt")
        test_path = os.path.join(fold_path, "test.txt")
        X_train, y_train, qid_train = load_svmlight_file(
            train_path, query_id=True, dtype=np.float32
        )
        y_train = y_train.astype(np.int32)
        qid_train = qid_train.astype(np.int32)
```

(continues on next page)

(continued from previous page)

```

X_valid, y_valid, qid_valid = load_svmlight_file(
    valid_path, query_id=True, dtype=np.float32
)
y_valid = y_valid.astype(np.int32)
qid_valid = qid_valid.astype(np.int32)

X_test, y_test, qid_test = load_svmlight_file(
    test_path, query_id=True, dtype=np.float32
)
y_test = y_test.astype(np.int32)
qid_test = qid_test.astype(np.int32)

data = RelDataCV(
    train=(X_train, y_train, qid_train),
    test=(X_test, y_test, qid_test),
    max_rel=4,
)

with open(cache_path, "wb") as fd:
    pickle.dump(data, fd)

with open(cache_path, "rb") as fd:
    data = pickle.load(fd)

return data

def ranking_demo(args: argparse.Namespace) -> None:
    """Demonstration for learning to rank with relevance degree."""
    data = load_mlsr_10k(args.data, args.cache)

    # Sort data according to query index
    X_train, y_train, qid_train = data.train
    sorted_idx = np.argsort(qid_train)
    X_train = X_train[sorted_idx]
    y_train = y_train[sorted_idx]
    qid_train = qid_train[sorted_idx]

    X_test, y_test, qid_test = data.test
    sorted_idx = np.argsort(qid_test)
    X_test = X_test[sorted_idx]
    y_test = y_test[sorted_idx]
    qid_test = qid_test[sorted_idx]

    ranker = xgb.XGBRanker(
        tree_method="hist",
        device="cuda",
        lambdarank_pair_method="topk",
        lambdarank_num_pair_per_sample=13,
        eval_metric=["ndcg@1", "ndcg@8"],
    )

```

(continues on next page)

(continued from previous page)

```

ranker.fit(
    X_train,
    y_train,
    qid=qid_train,
    eval_set=[(X_test, y_test)],
    eval_qid=[qid_test],
    verbose=True,
)

def click_data_demo(args: argparse.Namespace) -> None:
    """Demonstration for learning to rank with click data."""
    data = load_mlsr_10k(args.data, args.cache)
    train, test = simulate_clicks(data)
    assert test is not None

    assert train.X.shape[0] == train.click.size
    assert test.X.shape[0] == test.click.size
    assert test.score.dtype == np.float32
    assert test.click.dtype == np.int32

    X_train, clicks_train, y_train, qid_train = sort_ltr_samples(
        train.X,
        train.y,
        train.qid,
        train.click,
        train.pos,
    )
    X_test, clicks_test, y_test, qid_test = sort_ltr_samples(
        test.X,
        test.y,
        test.qid,
        test.click,
        test.pos,
    )

    class ShowPosition(xgb.callback.TrainingCallback):
        def after_iteration(
            self,
            model: xgb.Booster,
            epoch: int,
            evals_log: xgb.callback.TrainingCallback.EvalsLog,
        ) -> bool:
            config = json.loads(model.save_config())
            ti_plus = np.array(config["learner"]["objective"]["ti+"])
            tj_minus = np.array(config["learner"]["objective"]["tj-"])
            df = pd.DataFrame({"ti+": ti_plus, "tj-": tj_minus})
            print(df)
            return False

    ranker = xgb.XGBRanker(
        n_estimators=512,

```

(continues on next page)

(continued from previous page)

```

        tree_method="hist",
        device="cuda",
        learning_rate=0.01,
        reg_lambda=1.5,
        subsample=0.8,
        sampling_method="gradient_based",
        # LTR specific parameters
        objective="rank:ndcg",
        # - Enable bias estimation
        lambdarank_unbiased=True,
        # - normalization (1 / (norm + 1))
        lambdarank_bias_norm=1,
        # - Focus on the top 12 documents
        lambdarank_num_pair_per_sample=12,
        lambdarank_pair_method="topk",
        ndcg_exp_gain=True,
        eval_metric=["ndcg@1", "ndcg@3", "ndcg@5", "ndcg@10"],
        callbacks=[ShowPosition()],
    )
    ranker.fit(
        X_train,
        clicks_train,
        qid=qid_train,
        eval_set=[(X_test, y_test), (X_test, clicks_test)],
        eval_qid=[qid_test, qid_test],
        verbose=True,
    )
    ranker.predict(X_test)

if __name__ == "__main__":
    parser = argparse.ArgumentParser(
        description="Demonstration of learning to rank using XGBoost."
    )
    parser.add_argument(
        "--data",
        type=str,
        help="Root directory of the MSLR-WEB10K data.",
        required=True,
    )
    parser.add_argument(
        "--cache",
        type=str,
        help="Directory for caching processed data.",
        required=True,
    )
    args = parser.parse_args()

    ranking_demo(args)
    click_data_demo(args)

```

Demo for defining a custom regression objective and metric

Demo for defining customized metric and objective. Notice that for simplicity reason weight is not used in following example. In this script, we implement the Squared Log Error (SLE) objective and RMSLE metric as customized functions, then compare it with native implementation in XGBoost.

See *Custom Objective and Evaluation Metric* for a step by step walkthrough, with other details.

The *SLE* objective reduces impact of outliers in training dataset, hence here we also compare its performance with standard squared error.

```
import argparse
from time import time
from typing import Dict, List, Tuple

import matplotlib
import numpy as np
from matplotlib import pyplot as plt

import xgboost as xgb

# shape of generated data.
kRows = 4096
kCols = 16

kOutlier = 10000          # mean of generated outliers
kNumberOfOutliers = 64

kRatio = 0.7
kSeed = 1994

kBoostRound = 20

np.random.seed(seed=kSeed)

def generate_data() -> Tuple[xgb.DMatrix, xgb.DMatrix]:
    """Generate data containing outliers."""
    x = np.random.randn(kRows, kCols)
    y = np.random.randn(kRows)
    y += np.abs(np.min(y))

    # Create outliers
    for i in range(0, kNumberOfOutliers):
        ind = np.random.randint(0, len(y)-1)
        y[ind] += np.random.randint(0, kOutlier)

    train_portion = int(kRows * kRatio)

    # rmsle requires all label be greater than -1.
    assert np.all(y > -1.0)

    train_x: np.ndarray = x[: train_portion]
    train_y: np.ndarray = y[: train_portion]
```

(continues on next page)

(continued from previous page)

```

dtrain = xgb.DMatrix(train_x, label=train_y)

test_x = x[train_portion:]
test_y = y[train_portion:]
dtest = xgb.DMatrix(test_x, label=test_y)
return dtrain, dtest

def native_rmse(dtrain: xgb.DMatrix,
               dtest: xgb.DMatrix) -> Dict[str, Dict[str, List[float]]]:
    """Train using native implementation of Root Mean Squared Loss."""
    print('Squared Error')
    squared_error = {
        'objective': 'reg:squarederror',
        'eval_metric': 'rmse',
        'tree_method': 'hist',
        'seed': kSeed
    }
    start = time()
    results: Dict[str, Dict[str, List[float]]] = {}
    xgb.train(squared_error,
              dtrain=dtrain,
              num_boost_round=kBoostRound,
              evals=[(dtrain, 'dtrain'), (dtest, 'dtest')],
              evals_result=results)
    print('Finished Squared Error in:', time() - start, '\n')
    return results

def native_rmsle(dtrain: xgb.DMatrix,
                dtest: xgb.DMatrix) -> Dict[str, Dict[str, List[float]]]:
    """Train using native implementation of Squared Log Error."""
    print('Squared Log Error')
    results: Dict[str, Dict[str, List[float]]] = {}
    squared_log_error = {
        'objective': 'reg:squaredlogerror',
        'eval_metric': 'rmsle',
        'tree_method': 'hist',
        'seed': kSeed
    }
    start = time()
    xgb.train(squared_log_error,
              dtrain=dtrain,
              num_boost_round=kBoostRound,
              evals=[(dtrain, 'dtrain'), (dtest, 'dtest')],
              evals_result=results)
    print('Finished Squared Log Error in:', time() - start)
    return results

def py_rmsle(dtrain: xgb.DMatrix, dtest: xgb.DMatrix) -> Dict:
    """Train using Python implementation of Squared Log Error."""

```

(continues on next page)

(continued from previous page)

```

def gradient(predt: np.ndarray, dtrain: xgb.DMatrix) -> np.ndarray:
    "Compute the gradient squared log error."
    y = dtrain.get_label()
    return (np.log1p(predt) - np.log1p(y)) / (predt + 1)

def hessian(predt: np.ndarray, dtrain: xgb.DMatrix) -> np.ndarray:
    "Compute the hessian for squared log error."
    y = dtrain.get_label()
    return ((-np.log1p(predt) + np.log1p(y) + 1) /
            np.power(predt + 1, 2))

def squared_log(predt: np.ndarray,
                dtrain: xgb.DMatrix) -> Tuple[np.ndarray, np.ndarray]:
    "Squared Log Error objective. A simplified version for RMSLE used as
    objective function."

    :math:\frac{1}{2}[\log(pred + 1) - \log(label + 1)]^2

    """
    predt[predt < -1] = -1 + 1e-6
    grad = gradient(predt, dtrain)
    hess = hessian(predt, dtrain)
    return grad, hess

def rmsle(predt: np.ndarray, dtrain: xgb.DMatrix) -> Tuple[str, float]:
    "Root mean squared log error metric."

    :math:\sqrt{\frac{1}{N}[\log(pred + 1) - \log(label + 1)]^2}

    """
    y = dtrain.get_label()
    predt[predt < -1] = -1 + 1e-6
    elements = np.power(np.log1p(y) - np.log1p(predt), 2)
    return 'PyRMSLE', float(np.sqrt(np.sum(elements) / len(y)))

results: Dict[str, Dict[str, List[float]]] = {}
xgb.train({'tree_method': 'hist', 'seed': kSeed,
          'disable_default_eval_metric': 1},
          dtrain=dtrain,
          num_boost_round=kBoostRound,
          obj=squared_log,
          custom_metric=rmsle,
          evals=[(dtrain, 'dtrain'), (dtest, 'dtest')],
          evals_result=results)

return results

def plot_history(rmse_evals, rmsle_evals, py_rmsle_evals):
    fig, axs = plt.subplots(3, 1)
    ax0: matplotlib.axes.Axes = axs[0]
    ax1: matplotlib.axes.Axes = axs[1]
    ax2: matplotlib.axes.Axes = axs[2]

```

(continues on next page)

(continued from previous page)

```

x = np.arange(0, kBoostRound, 1)

ax0.plot(x, rmse_evals['dtrain']['rmse'], label='train-RMSE')
ax0.plot(x, rmse_evals['dtest']['rmse'], label='test-RMSE')
ax0.legend()

ax1.plot(x, rmsle_evals['dtrain']['rmsle'], label='train-native-RMSLE')
ax1.plot(x, rmsle_evals['dtest']['rmsle'], label='test-native-RMSLE')
ax1.legend()

ax2.plot(x, py_rmsle_evals['dtrain']['PyRMSLE'], label='train-PyRMSLE')
ax2.plot(x, py_rmsle_evals['dtest']['PyRMSLE'], label='test-PyRMSLE')
ax2.legend()

def main(args):
    dtrain, dtest = generate_data()
    rmse_evals = native_rmse(dtrain, dtest)
    rmsle_evals = native_rmsle(dtrain, dtest)
    py_rmsle_evals = py_rmsle(dtrain, dtest)

    if args.plot != 0:
        plot_history(rmse_evals, rmsle_evals, py_rmsle_evals)
        plt.show()

if __name__ == "__main__":
    parser = argparse.ArgumentParser(
        description='Arguments for custom RMSLE objective function demo.')
    parser.add_argument(
        '--plot',
        type=int,
        default=1,
        help='Set to 0 to disable plotting the evaluation history.')
    args = parser.parse_args()
    main(args)

```

XGBoost Dask Feature Walkthrough

This directory contains some demonstrations for using *dask* with *XGBoost*. For an overview, see *Distributed XGBoost with Dask*

Use scikit-learn regressor interface with CPU histogram tree method

```

from dask import array as da
from dask.distributed import Client, LocalCluster

import xgboost

def main(client):
    # generate some random data for demonstration
    n = 100
    m = 10000
    partition_size = 100
    X = da.random.random((m, n), partition_size)
    y = da.random.random(m, partition_size)

    regressor = xgboost.dask.DaskXGBRegressor(verbosity=1, n_estimators=2)
    regressor.set_params(tree_method="hist")
    # assigning client here is optional
    regressor.client = client

    regressor.fit(X, y, eval_set=[(X, y)])
    prediction = regressor.predict(X)

    bst = regressor.get_booster()
    history = regressor.evals_result()

    print("Evaluation history:", history)
    # returned prediction is always a dask array.
    assert isinstance(prediction, da.Array)
    return bst # returning the trained model

if __name__ == "__main__":
    # or use other clusters for scaling
    with LocalCluster(n_workers=4, threads_per_worker=1) as cluster:
        with Client(cluster) as client:
            main(client)

```

Use scikit-learn regressor interface with GPU histogram tree method

```

from dask import array as da
from dask.distributed import Client

# It's recommended to use dask_cuda for GPU assignment
from dask_cuda import LocalCUDACluster

import xgboost

def main(client):

```

(continues on next page)

(continued from previous page)

```

# generate some random data for demonstration
n = 100
m = 1000000
partition_size = 10000
X = da.random.random((m, n), partition_size)
y = da.random.random(m, partition_size)

regressor = xgboost.dask.DaskXGBRegressor(verbosity=1)
# set the device to CUDA
regressor.set_params(tree_method="hist", device="cuda")
# assigning client here is optional
regressor.client = client

regressor.fit(X, y, eval_set=[(X, y)])
prediction = regressor.predict(X)

bst = regressor.get_booster()
history = regressor.evals_result()

print("Evaluation history:", history)
# returned prediction is always a dask array.
assert isinstance(prediction, da.Array)
return bst # returning the trained model

if __name__ == "__main__":
    # With dask cuda, one can scale up XGBoost to arbitrary GPU clusters.
    # `LocalCUDACluster` used here is only for demonstration purpose.
    with LocalCUDACluster() as cluster:
        with Client(cluster) as client:
            main(client)

```

Example of training with Dask on CPU

```

from dask import array as da
from dask.distributed import Client, LocalCluster

import xgboost as xgb
from xgboost.dask import DaskDMatrix

def main(client):
    # generate some random data for demonstration
    m = 1000000
    n = 100
    X = da.random.random(size=(m, n), chunks=100)
    y = da.random.random(size=(m,), chunks=100)

    # DaskDMatrix acts like normal DMatrix, works as a proxy for local
    # DMatrix scatter around workers.

```

(continues on next page)

(continued from previous page)

```

dtrain = DaskDMatrix(client, X, y)

# Use train method from xgboost.dask instead of xgboost. This
# distributed version of train returns a dictionary containing the
# resulting booster and evaluation history obtained from
# evaluation metrics.
output = xgb.dask.train(
    client,
    {"verbosity": 1, "tree_method": "hist"},
    dtrain,
    num_boost_round=4,
    evals=[(dtrain, "train")],
)
bst = output["booster"]
history = output["history"]

# you can pass output directly into `predict` too.
prediction = xgb.dask.predict(client, bst, dtrain)
print("Evaluation history:", history)
return prediction

if __name__ == "__main__":
    # or use other clusters for scaling
    with LocalCluster(n_workers=7, threads_per_worker=4) as cluster:
        with Client(cluster) as client:
            main(client)

```

Example of training survival model with Dask on CPU

```

import os

import dask.dataframe as dd
from dask.distributed import Client, LocalCluster

import xgboost as xgb
from xgboost.dask import DaskDMatrix

def main(client):
    # Load an example survival data from CSV into a Dask data frame.
    # The Veterans' Administration Lung Cancer Trial
    # The Statistical Analysis of Failure Time Data by Kalbfleisch J. and Prentice R.
    ↪ (1980)
    CURRENT_DIR = os.path.dirname(__file__)
    df = dd.read_csv(
        os.path.join(CURRENT_DIR, os.pardir, "data", "veterans_lung_cancer.csv")
    )

    # DaskDMatrix acts like normal DMatrix, works as a proxy for local

```

(continues on next page)

(continued from previous page)

```

# DMatrix scatter around workers.
# For AFT survival, you'd need to extract the lower and upper bounds for the label
# and pass them as arguments to DaskDMatrix.
y_lower_bound = df["Survival_label_lower_bound"]
y_upper_bound = df["Survival_label_upper_bound"]
X = df.drop(["Survival_label_lower_bound", "Survival_label_upper_bound"], axis=1)
dtrain = DaskDMatrix(
    client, X, label_lower_bound=y_lower_bound, label_upper_bound=y_upper_bound
)

# Use train method from xgboost.dask instead of xgboost. This
# distributed version of train returns a dictionary containing the
# resulting booster and evaluation history obtained from
# evaluation metrics.
params = {
    "verbosity": 1,
    "objective": "survival:aft",
    "eval_metric": "aft-nloglik",
    "learning_rate": 0.05,
    "aft_loss_distribution_scale": 1.20,
    "aft_loss_distribution": "normal",
    "max_depth": 6,
    "lambda": 0.01,
    "alpha": 0.02,
}
output = xgb.dask.train(
    client, params, dtrain, num_boost_round=100, evals=[(dtrain, "train")]
)
bst = output["booster"]
history = output["history"]

# you can pass output directly into `predict` too.
prediction = xgb.dask.predict(client, bst, dtrain)
print("Evaluation history: ", history)

# Uncomment the following line to save the model to the disk
# bst.save_model('survival_model.json')

return prediction

if __name__ == "__main__":
    # or use other clusters for scaling
    with LocalCluster(n_workers=7, threads_per_worker=4) as cluster:
        with Client(cluster) as client:
            main(client)

```

Example of training with Dask on GPU

```
import dask_cudf
from dask import array as da
from dask import dataframe as dd
from dask.distributed import Client
from dask_cuda import LocalCUDACluster

import xgboost as xgb
from xgboost import dask as dxgb
from xgboost.dask import DaskDMatrix

def using_dask_matrix(client: Client, X: da.Array, y: da.Array) -> da.Array:
    # DaskDMatrix acts like normal DMatrix, works as a proxy for local DMatrix scatter
    # around workers.
    dtrain = DaskDMatrix(client, X, y)

    # Use train method from xgboost.dask instead of xgboost. This distributed version
    # of train returns a dictionary containing the resulting booster and evaluation
    # history obtained from evaluation metrics.
    output = xgb.dask.train(
        client,
        {
            "verbosity": 2,
            "tree_method": "hist",
            # Golden line for GPU training
            "device": "cuda",
        },
        dtrain,
        num_boost_round=4,
        evals=[(dtrain, "train")],
    )
    bst = output["booster"]
    history = output["history"]

    # you can pass output directly into `predict` too.
    prediction = xgb.dask.predict(client, bst, dtrain)
    print("Evaluation history:", history)
    return prediction

def using_quantile_device_dmatrix(client: Client, X: da.Array, y: da.Array) -> da.Array:
    """`DaskQuantileDMatrix` is a data type specialized for `hist` tree methods for
    reducing memory usage.

    .. versionadded:: 1.2.0

    """
    X = dask_cudf.from_dask_dataframe(dd.from_dask_array(X))
    y = dask_cudf.from_dask_dataframe(dd.from_dask_array(y))

    # `DaskQuantileDMatrix` is used instead of `DaskDMatrix`, be careful that it can not
```

(continues on next page)

(continued from previous page)

```

# be used for anything else other than training unless a reference is specified. See
# the `ref` argument of `DaskQuantileDMatrix`.
dtrain = dxgb.DaskQuantileDMatrix(client, X, y)
output = xgb.dask.train(
    client,
    {"verbosity": 2, "tree_method": "hist", "device": "cuda"},
    dtrain,
    num_boost_round=4,
)

prediction = xgb.dask.predict(client, output, X)
return prediction

if __name__ == "__main__":
    # `LocalCUDACluster` is used for assigning GPU to XGBoost processes. Here
    # `n_workers` represents the number of GPUs since we use one GPU per worker process.
    with LocalCUDACluster(n_workers=2, threads_per_worker=4) as cluster:
        with Client(cluster) as client:
            # generate some random data for demonstration
            m = 1000000
            n = 100
            X = da.random.random(size=(m, n), chunks=10000)
            y = da.random.random(size=(m,), chunks=10000)

            print("Using DaskQuantileDMatrix")
            from_ddqdm = using_quantile_device_dmatrix(client, X, y)
            print("Using DMatrix")
            from_dmatrix = using_dask_matrix(client, X, y)

```

Example of using callbacks with Dask

```

import numpy as np
from dask.distributed import Client, LocalCluster
from dask_ml.datasets import make_regression
from dask_ml.model_selection import train_test_split

import xgboost as xgb
from xgboost.dask import DaskDMatrix

def probability_for_going_backward(epoch):
    return 0.999 / (1.0 + 0.05 * np.log(1.0 + epoch))

# All callback functions must inherit from TrainingCallback
class CustomEarlyStopping(xgb.callback.TrainingCallback):
    """A custom early stopping class where early stopping is determined stochastically.
    In the beginning, allow the metric to become worse with a probability of 0.999.
    As boosting progresses, the probability should be adjusted downward"""

```

(continues on next page)

(continued from previous page)

```

def __init__(self, *, validation_set, target_metric, maximize, seed):
    self.validation_set = validation_set
    self.target_metric = target_metric
    self.maximize = maximize
    self.seed = seed
    self.rng = np.random.default_rng(seed=seed)
    if maximize:
        self.better = lambda x, y: x > y
    else:
        self.better = lambda x, y: x < y

def after_iteration(self, model, epoch, evals_log):
    metric_history = evals_log[self.validation_set][self.target_metric]
    if len(metric_history) < 2 or self.better(
        metric_history[-1], metric_history[-2]
    ):
        return False # continue training
    p = probability_for_going_backward(epoch)
    go_backward = self.rng.choice(2, size=(1,), replace=True, p=[1 - p, p]).astype(
        np.bool
    )[0]
    print(
        "The validation metric went into the wrong direction. "
        + f"Stopping training with probability {1 - p}..."
    )
    if go_backward:
        return False # continue training
    else:
        return True # stop training

def main(client):
    m = 1000000
    n = 100
    X, y = make_regression(n_samples=m, n_features=n, chunks=200, random_state=0)
    X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=0)

    dtrain = DaskDMatrix(client, X_train, y_train)
    dtest = DaskDMatrix(client, X_test, y_test)

    output = xgb.dask.train(
        client,
        {
            "verbosity": 1,
            "tree_method": "hist",
            "objective": "reg:squarederror",
            "eval_metric": "rmse",
            "max_depth": 6,
            "learning_rate": 1.0,
        },
        dtrain,

```

(continues on next page)

(continued from previous page)

```

num_boost_round=1000,
evals=[(dtrain, "train"), (dtest, "test")],
callbacks=[
    CustomEarlyStopping(
        validation_set="test", target_metric="rmse", maximize=False, seed=0
    )
],
)

if __name__ == "__main__":
    # or use other clusters for scaling
    with LocalCluster(n_workers=4, threads_per_worker=1) as cluster:
        with Client(cluster) as client:
            main(client)

```

Survival Analysis Walkthrough

This is a collection of examples for using the XGBoost Python package for training survival models. For an introduction, see *Survival Analysis with Accelerated Failure Time*

Demo for survival analysis (regression).

Demo for survival analysis (regression). using Accelerated Failure Time (AFT) model.

```

import os

import numpy as np
import pandas as pd
from sklearn.model_selection import ShuffleSplit

import xgboost as xgb

# The Veterans' Administration Lung Cancer Trial
# The Statistical Analysis of Failure Time Data by Kalbfleisch J. and Prentice R (1980)
CURRENT_DIR = os.path.dirname(__file__)
df = pd.read_csv(os.path.join(CURRENT_DIR, '../data/veterans_lung_cancer.csv'))
print('Training data:')
print(df)

# Split features and labels
y_lower_bound = df['Survival_label_lower_bound']
y_upper_bound = df['Survival_label_upper_bound']
X = df.drop(['Survival_label_lower_bound', 'Survival_label_upper_bound'], axis=1)

# Split data into training and validation sets
rs = ShuffleSplit(n_splits=2, test_size=.7, random_state=0)
train_index, valid_index = next(rs.split(X))
dtrain = xgb.DMatrix(X.values[train_index, :])
dtrain.set_float_info('label_lower_bound', y_lower_bound[train_index])

```

(continues on next page)

(continued from previous page)

```

dtrain.set_float_info('label_upper_bound', y_upper_bound[train_index])
dvalid = xgb.DMatrix(X.values[valid_index, :])
dvalid.set_float_info('label_lower_bound', y_lower_bound[valid_index])
dvalid.set_float_info('label_upper_bound', y_upper_bound[valid_index])

# Train gradient boosted trees using AFT loss and metric
params = {'verbosity': 0,
          'objective': 'survival:aft',
          'eval_metric': 'aft-nloglik',
          'tree_method': 'hist',
          'learning_rate': 0.05,
          'aft_loss_distribution': 'normal',
          'aft_loss_distribution_scale': 1.20,
          'max_depth': 6,
          'lambda': 0.01,
          'alpha': 0.02}
bst = xgb.train(params, dtrain, num_boost_round=10000,
               evals=[(dtrain, 'train'), (dvalid, 'valid')],
               early_stopping_rounds=50)

# Run prediction on the validation set
df = pd.DataFrame({'Label (lower bound)': y_lower_bound[valid_index],
                  'Label (upper bound)': y_upper_bound[valid_index],
                  'Predicted label': bst.predict(dvalid)})
print(df)
# Show only data points with right-censored labels
print(df[np.isinf(df['Label (upper bound)'])])

# Save trained model
bst.save_model('aft_model.json')

```

Demo for survival analysis (regression) with Optuna.

Demo for survival analysis (regression) using Accelerated Failure Time (AFT) model, using Optuna to tune hyperparameters

```

import numpy as np
import optuna
import pandas as pd
from sklearn.model_selection import ShuffleSplit

import xgboost as xgb

# The Veterans' Administration Lung Cancer Trial
# The Statistical Analysis of Failure Time Data by Kalbfleisch J. and Prentice R (1980)
df = pd.read_csv('../data/veterans_lung_cancer.csv')
print('Training data:')
print(df)

# Split features and labels
y_lower_bound = df['Survival_label_lower_bound']

```

(continues on next page)

(continued from previous page)

```

y_upper_bound = df['Survival_label_upper_bound']
X = df.drop(['Survival_label_lower_bound', 'Survival_label_upper_bound'], axis=1)

# Split data into training and validation sets
rs = ShuffleSplit(n_splits=2, test_size=.7, random_state=0)
train_index, valid_index = next(rs.split(X))
dtrain = xgb.DMatrix(X.values[train_index, :])
dtrain.set_float_info('label_lower_bound', y_lower_bound[train_index])
dtrain.set_float_info('label_upper_bound', y_upper_bound[train_index])
dvalid = xgb.DMatrix(X.values[valid_index, :])
dvalid.set_float_info('label_lower_bound', y_lower_bound[valid_index])
dvalid.set_float_info('label_upper_bound', y_upper_bound[valid_index])

# Define hyperparameter search space
base_params = {'verbosity': 0,
               'objective': 'survival:aft',
               'eval_metric': 'aft-nloglik',
               'tree_method': 'hist'} # Hyperparameters common to all trials
def objective(trial):
    params = {'learning_rate': trial.suggest_loguniform('learning_rate', 0.01, 1.0),
              'aft_loss_distribution': trial.suggest_categorical('aft_loss_distribution',
                                                                ['normal', 'logistic',
                                                                'extreme']),
              'aft_loss_distribution_scale': trial.suggest_loguniform('aft_loss_
distribution_scale', 0.1, 10.0),
              'max_depth': trial.suggest_int('max_depth', 3, 8),
              'lambda': trial.suggest_loguniform('lambda', 1e-8, 1.0),
              'alpha': trial.suggest_loguniform('alpha', 1e-8, 1.0)} # Search space
    params.update(base_params)
    pruning_callback = optuna.integration.XGBoostPruningCallback(trial, 'valid-aft-
nloglik')
    bst = xgb.train(params, dtrain, num_boost_round=10000,
                    evals=[(dtrain, 'train'), (dvalid, 'valid')],
                    early_stopping_rounds=50, verbose_eval=False, callbacks=[pruning_
callback])
    if bst.best_iteration >= 25:
        return bst.best_score
    else:
        return np.inf # Reject models with < 25 trees

# Run hyperparameter search
study = optuna.create_study(direction='minimize')
study.optimize(objective, n_trials=200)
print('Completed hyperparameter tuning with best aft-nloglik = {}'.format(study.best_
trial.value))
params = {}
params.update(base_params)
params.update(study.best_trial.params)

# Re-run training with the best hyperparameter combination
print('Re-running the best trial... params = {}'.format(params))
bst = xgb.train(params, dtrain, num_boost_round=10000,

```

(continues on next page)

(continued from previous page)

```

        evals=[(dtrain, 'train'), (dvalid, 'valid')],
        early_stopping_rounds=50)

# Run prediction on the validation set
df = pd.DataFrame({'Label (lower bound)': y_lower_bound[valid_index],
                  'Label (upper bound)': y_upper_bound[valid_index],
                  'Predicted label': bst.predict(dvalid)})
print(df)
# Show only data points with right-censored labels
print(df[np.isinf(df['Label (upper bound)'])])

# Save trained model
bst.save_model('aft_best_model.json')

```

Visual demo for survival analysis (regression) with Accelerated Failure Time (AFT) model.

This demo uses 1D toy data and visualizes how XGBoost fits a tree ensemble. The ensemble model starts out as a flat line and evolves into a step function in order to account for all ranged labels.

```

import matplotlib.pyplot as plt
import numpy as np

import xgboost as xgb

plt.rcParams.update({"font.size": 13})

# Function to visualize censored labels
def plot_censored_labels(
    X: np.ndarray, y_lower: np.ndarray, y_upper: np.ndarray
) -> None:
    def replace_inf(x: np.ndarray, target_value: float) -> np.ndarray:
        x[np.isinf(x)] = target_value
        return x

    plt.plot(X, y_lower, "o", label="y_lower", color="blue")
    plt.plot(X, y_upper, "o", label="y_upper", color="fuchsia")
    plt.vlines(
        X,
        ymin=replace_inf(y_lower, 0.01),
        ymax=replace_inf(y_upper, 1000.0),
        label="Range for y",
        color="gray",
    )

# Toy data
X = np.array([1, 2, 3, 4, 5]).reshape((-1, 1))
INF = np.inf
y_lower = np.array([10, 15, -INF, 30, 100])
y_upper = np.array([INF, INF, 20, 50, INF])

```

(continues on next page)

(continued from previous page)

```

# Visualize toy data
plt.figure(figsize=(5, 4))
plot_censored_labels(X, y_lower, y_upper)
plt.ylim((6, 200))
plt.legend(loc="lower right")
plt.title("Toy data")
plt.xlabel("Input feature")
plt.ylabel("Label")
plt.yscale("log")
plt.tight_layout()
plt.show(block=True)

# Will be used to visualize XGBoost model
grid_pts = np.linspace(0.8, 5.2, 1000).reshape((-1, 1))

# Train AFT model using XGBoost
dmat = xgb.DMatrix(X)
dmat.set_float_info("label_lower_bound", y_lower)
dmat.set_float_info("label_upper_bound", y_upper)
params = {"max_depth": 3, "objective": "survival:aft", "min_child_weight": 0}

accuracy_history = []

class PlotIntermediateModel(xgb.callback.TrainingCallback):
    """Custom callback to plot intermediate models."""

    def __init__(self) -> None:
        super().__init__()

    def after_iteration(
        self,
        model: xgb.Booster,
        epoch: int,
        evals_log: xgb.callback.TrainingCallback.EvalsLog,
    ) -> bool:
        """Run after training is finished."""
        # Compute y_pred = prediction using the intermediate model, at current boosting
        # iteration
        y_pred = model.predict(dmat)
        # "Accuracy" = the number of data points whose ranged label (y_lower, y_upper)
        # includes the corresponding predicted label (y_pred)
        acc = np.sum(
            np.logical_and(y_pred >= y_lower, y_pred <= y_upper) / len(X) * 100
        )
        accuracy_history.append(acc)

        # Plot ranged labels as well as predictions by the model
        plt.subplot(5, 3, epoch + 1)
        plot_censored_labels(X, y_lower, y_upper)
        y_pred_grid_pts = model.predict(xgb.DMatrix(grid_pts))

```

(continues on next page)

(continued from previous page)

```

plt.plot(
    grid_pts, y_pred_grid_pts, "r-", label="XGBoost AFT model", linewidth=4
)
plt.title("Iteration {}".format(epoch), x=0.5, y=0.8)
plt.xlim((0.8, 5.2))
plt.ylim((1 if np.min(y_pred) < 6 else 6, 200))
plt.yscale("log")
return False

res: xgb.callback.TrainingCallback.EvalsLog = {}
plt.figure(figsize=(12, 13))
bst = xgb.train(
    params,
    dmat,
    15,
    [(dmat, "train")],
    evals_result=res,
    callbacks=[PlotIntermediateModel()],
)
plt.tight_layout()
plt.legend(
    loc="lower center",
    ncol=4,
    bbox_to_anchor=(0.5, 0),
    bbox_transform=plt.gcf().transFigure,
)
plt.tight_layout()

# Plot negative log likelihood over boosting iterations
plt.figure(figsize=(8, 3))
plt.subplot(1, 2, 1)
plt.plot(res["train"]["aft-nloglik"], "b-o", label="aft-nloglik")
plt.xlabel("# Boosting Iterations")
plt.legend(loc="best")

# Plot "accuracy" over boosting iterations
# "Accuracy" = the number of data points whose ranged label (y_lower, y_upper) includes
#               the corresponding predicted label (y_pred)
plt.subplot(1, 2, 2)
plt.plot(accuracy_history, "r-o", label="Accuracy (%)")
plt.xlabel("# Boosting Iterations")
plt.legend(loc="best")
plt.tight_layout()

plt.show()

```

GPU Acceleration Demo

This is a collection of demonstration scripts to showcase the basic usage of GPU. Please see [XGBoost GPU Support](#) for more info. There are other demonstrations for distributed GPU training using dask or spark.

Using xgboost on GPU devices

Shows how to train a model on the [forest cover type](#) dataset using GPU acceleration. The forest cover type dataset has 581,012 rows and 54 features, making it time consuming to process. We compare the run-time and accuracy of the GPU and CPU histogram algorithms.

In addition, The demo showcases using GPU with other GPU-related libraries including cupy and cuml. These libraries are not strictly required.

```
import time

import cupy as cp
from cuml.model_selection import train_test_split
from sklearn.datasets import fetch_covtype

import xgboost as xgb

# Fetch dataset using sklearn
X, y = fetch_covtype(return_X_y=True)
X = cp.array(X)
y = cp.array(y)
y -= y.min()

# Create 0.75/0.25 train/test split
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.25, train_size=0.75, random_state=42
)

# Specify sufficient boosting iterations to reach a minimum
num_round = 3000

# Leave most parameters as default
clf = xgb.XGBClassifier(device="cuda", n_estimators=num_round)
# Train model
start = time.time()
clf.fit(X_train, y_train, eval_set=[(X_test, y_test)])
gpu_res = clf.evals_result()
print("GPU Training Time: %s seconds" % (str(time.time() - start)))

# Repeat for CPU algorithm
clf = xgb.XGBClassifier(device="cpu", n_estimators=num_round)
start = time.time()
cpu_res = clf.evals_result()
print("CPU Training Time: %s seconds" % (str(time.time() - start)))
```

Use GPU to speedup SHAP value computation

Demonstrates using GPU acceleration to compute SHAP values for feature importance.

```
import shap
from sklearn.datasets import fetch_california_housing

import xgboost as xgb

# Fetch dataset using sklearn
data = fetch_california_housing()
print(data.DESCR)
X = data.data
y = data.target

num_round = 500

param = {
    "eta": 0.05,
    "max_depth": 10,
    "tree_method": "hist",
    "device": "cuda",
}

# GPU accelerated training
dtrain = xgb.DMatrix(X, label=y, feature_names=data.feature_names)
model = xgb.train(param, dtrain, num_round)

# Compute shap values using GPU with xgboost
model.set_param({"device": "cuda"})
shap_values = model.predict(dtrain, pred_contribs=True)

# Compute shap interaction values using GPU
shap_interaction_values = model.predict(dtrain, pred_interactions=True)

# shap will call the GPU accelerated version as long as the device parameter is set to
# "cuda"
explainer = shap.TreeExplainer(model)
shap_values = explainer.shap_values(X)

# visualize the first prediction's explanation
shap.force_plot(
    explainer.expected_value,
    shap_values[0, :],
    X[0, :],
    feature_names=data.feature_names,
    matplotlib=True,
)

# Show a summary of feature importance
shap.summary_plot(shap_values, X, plot_type="bar", feature_names=data.feature_names)
```

Using XGBoost with RAPIDS Memory Manager (RMM) plugin (EXPERIMENTAL)

RAPIDS Memory Manager (RMM) library provides a collection of efficient memory allocators for NVIDIA GPUs. It is now possible to use XGBoost with memory allocators provided by RMM, by enabling the RMM integration plugin.

The demos in this directory highlights one RMM allocator in particular: **the pool sub-allocator**. This allocator addresses the slow speed of `cudaMalloc()` by allocating a large chunk of memory upfront. Subsequent allocations will draw from the pool of already allocated memory and thus avoid the overhead of calling `cudaMalloc()` directly. See [this GTC talk slides](#) for more details.

Before running the demos, ensure that XGBoost is compiled with the RMM plugin enabled. To do this, run CMake with option `-DPLUGIN_RMM=ON` (`-DUSE_CUDA=ON` also required):

```
cmake .. -DUSE_CUDA=ON -DUSE_NCCL=ON -DPLUGIN_RMM=ON
make -j$(nproc)
```

CMake will attempt to locate the RMM library in your build environment. You may choose to build RMM from the source, or install it using the Conda package manager. If CMake cannot find RMM, you should specify the location of RMM with the CMake prefix:

```
# If using Conda:
cmake .. -DUSE_CUDA=ON -DUSE_NCCL=ON -DPLUGIN_RMM=ON -DCMAKE_PREFIX_PATH=$CONDA_PREFIX
# If using RMM installed with a custom location
cmake .. -DUSE_CUDA=ON -DUSE_NCCL=ON -DPLUGIN_RMM=ON -DCMAKE_PREFIX_PATH=/path/to/rmm
```

Informing XGBoost about RMM pool

When XGBoost is compiled with RMM, most of the large size allocation will go through RMM allocators, but some small allocations in performance critical areas are using a different caching allocator so that we can have better control over memory allocation behavior. Users can override this behavior and force the use of rmm for all allocations by setting the global configuration `use_rmm`:

```
with xgb.config_context(use_rmm=True):
    clf = xgb.XGBClassifier(tree_method="hist", device="cuda")
```

Depending on the choice of memory pool size or type of allocator, this may have negative performance impact.

Using rmm on a single node device

```
import rmm
from sklearn.datasets import make_classification

import xgboost as xgb

# Initialize RMM pool allocator
rmm.reinitialize(pool_allocator=True)
# Optionally force XGBoost to use RMM for all GPU memory allocation, see ./README.md
# xgb.set_config(use_rmm=True)

X, y = make_classification(n_samples=10000, n_informative=5, n_classes=3)
dtrain = xgb.DMatrix(X, label=y)
```

(continues on next page)

(continued from previous page)

```

params = {
    "max_depth": 8,
    "eta": 0.01,
    "objective": "multi:softprob",
    "num_class": 3,
    "tree_method": "hist",
    "device": "cuda",
}
# XGBoost will automatically use the RMM pool allocator
bst = xgb.train(params, dtrain, num_boost_round=100, evals=[(dtrain, "train")])

```

Using rmm with Dask

```

import dask
from dask.distributed import Client
from dask_cuda import LocalCUDACluster
from sklearn.datasets import make_classification

import xgboost as xgb

def main(client):
    # Optionally force XGBoost to use RMM for all GPU memory allocation, see ./README.md
    # xgb.set_config(use_rmm=True)

    X, y = make_classification(n_samples=10000, n_informative=5, n_classes=3)
    # In practice one should prefer loading the data with dask collections instead of
    # using `from_array`.
    X = dask.array.from_array(X)
    y = dask.array.from_array(y)
    dtrain = xgb.dask.DaskDMatrix(client, X, label=y)

    params = {
        "max_depth": 8,
        "eta": 0.01,
        "objective": "multi:softprob",
        "num_class": 3,
        "tree_method": "hist",
        "eval_metric": "merror",
        "device": "cuda",
    }
    output = xgb.dask.train(
        client, params, dtrain, num_boost_round=100, evals=[(dtrain, "train")]
    )
    bst = output["booster"]
    history = output["history"]
    for i, e in enumerate(history["train"]["merror"]):
        print(f"[{i}] train-merror: {e}")

```

(continues on next page)

(continued from previous page)

```
if __name__ == "__main__":
    # To use RMM pool allocator with a GPU Dask cluster, just add rmm_pool_size option
    # to LocalCUDACluster constructor.
    with LocalCUDACluster(rmm_pool_size="2GB") as cluster:
        with Client(cluster) as client:
            main(client)
```

1.11 XGBoost R Package

You have found the XGBoost R Package!

1.11.1 Get Started

- Checkout the [Installation Guide](#) contains instructions to install xgboost, and [Tutorials](#) for examples on how to use XGBoost for various tasks.
- Read the [API documentation](#).
- Please visit [Walk-through Examples](#).

1.11.2 Tutorials

XGBoost R Tutorial

Introduction

XGBoost is short for **eXtreme Gradient Boosting** package.

The purpose of this Vignette is to show you how to use **XGBoost** to build a model and make predictions.

It is an efficient and scalable implementation of gradient boosting framework by @friedman2000additive and @friedman2001greedy. Two solvers are included:

- *linear* model ;
- *tree learning* algorithm.

It supports various objective functions, including *regression*, *classification* and *ranking*. The package is made to be extendible, so that users are also allowed to define their own objective functions easily.

It has been [used](#) to win several [Kaggle](#) competitions.

It has several features:

- Speed: it can automatically do parallel computation on *Windows* and *Linux*, with *OpenMP*. It is generally over 10 times faster than the classical *gbm*.
- Input Type: it takes several types of input data:
 - *Dense Matrix*: *R*'s *dense* matrix, i.e. `matrix` ;
 - *Sparse Matrix*: *R*'s *sparse* matrix, i.e. `Matrix::dgCMatrix` ;
 - *Data File*: local data files ;
 - `xgb.DMatrix`: its own class (recommended).

- Sparsity: it accepts *sparse* input for both *tree booster* and *linear booster*, and is optimized for *sparse* input ;
- Customization: it supports customized objective functions and evaluation functions.

Installation

GitHub version

For weekly updated version (highly recommended), install from *GitHub*:

```
install.packages("drat", repos="https://cran.rstudio.com")
drat::addRepo("dmlc")
install.packages("xgboost", repos="http://dmlc.ml/drat/", type = "source")
```

Windows users will need to install *Rtools* first.

CRAN version

The version 0.4-2 is on CRAN, and you can install it by:

```
install.packages("xgboost")
```

Formerly available versions can be obtained from the CRAN [archive](#)

Learning

For the purpose of this tutorial we will load **XGBoost** package.

```
require(xgboost)
```

Dataset presentation

In this example, we are aiming to predict whether a mushroom can be eaten or not (like in many tutorials, example data are the same as you will use on in your every day life :-).

Mushroom data is cited from UCI Machine Learning Repository. @Bache+Lichman:2013.

Dataset loading

We will load the *agaricus* datasets embedded with the package and will link them to variables.

The datasets are already split in:

- **train**: will be used to build the model ;
- **test**: will be used to assess the quality of our model.

Why *split* the dataset in two parts?

In the first part we will build our model. In the second part we will want to test it and assess its quality. Without dividing the dataset we would test the model on the data which the algorithm have already seen.

```
data(agaricus.train, package='xgboost')
data(agaricus.test, package='xgboost')
train <- agaricus.train
test <- agaricus.test
```

In the real world, it would be up to you to make this division between `train` and `test` data. The way to do it is out of scope for this article, however `caret` package may [help](#).

Each variable is a list containing two things, `label` and `data`:

```
str(train)
```

```
## List of 2
## $ data :Formal class 'dgCMatix' [package "Matrix"] with 6 slots
## ..@ i      : int [1:143286] 2 6 8 11 18 20 21 24 28 32 ...
## ..@ p      : int [1:127] 0 369 372 3306 5845 6489 6513 8380 8384 10991 ...
## ..@ Dim    : int [1:2] 6513 126
## ..@ Dimnames:List of 2
## .. ..$ : NULL
## .. ..$ : chr [1:126] "cap-shape=bell" "cap-shape=conical" "cap-shape=convex"
## .. ..$ : chr [1:126] "cap-shape=flat" ...
## ..@ x      : num [1:143286] 1 1 1 1 1 1 1 1 1 1 ...
## ..@ factors : list()
## $ label: num [1:6513] 1 0 0 1 0 0 0 1 0 0 ...
```

`label` is the outcome of our dataset meaning it is the binary *classification* we will try to predict.

Let's discover the dimensionality of our datasets.

```
dim(train$data)
```

```
## [1] 6513 126
```

```
dim(test$data)
```

```
## [1] 1611 126
```

This dataset is very small to not make the **R** package too heavy, however **XGBoost** is built to manage huge datasets very efficiently.

As seen below, the data are stored in a `dgCMatix` which is a *sparse* matrix and `label` vector is a *numeric* vector (`{0,1}`):

```
class(train$data)[1]
```

```
## [1] "dgCMatix"
```

```
class(train$label)
```

```
## [1] "numeric"
```

Basic Training using XGBoost

This step is the most critical part of the process for the quality of our model.

Basic training

We are using the `train` data. As explained above, both `data` and `label` are stored in a `list`.

In a *sparse* matrix, cells containing `0` are not stored in memory. Therefore, in a dataset mainly made of `0`, memory size is reduced. It is very common to have such a dataset.

We will train decision tree model using the following parameters:

- `objective = "binary:logistic"`: we will train a binary classification model ;
- `max.depth = 2`: the trees won't be deep, because our case is very simple ;
- `nthread = 2`: the number of CPU threads we are going to use;
- `nrounds = 2`: there will be two passes on the data, the second one will enhance the model by further reducing the difference between ground truth and prediction.

```
bstSparse <- xgboost(data = train$data, label = train$label, max.depth = 2, eta = 1,
  ↪nthread = 2, nrounds = 2, objective = "binary:logistic")
```

```
## [0]      train-error:0.046522
## [1]      train-error:0.022263
```

The more complex the relationship between your features and your label is, the more passes you need.

Parameter variations

Dense matrix

Alternatively, you can put your dataset in a *dense* matrix, i.e. a basic **R** matrix.

```
bstDense <- xgboost(data = as.matrix(train$data), label = train$label, max.depth = 2,
  ↪eta = 1, nthread = 2, nrounds = 2, objective = "binary:logistic")
```

```
## [0]      train-error:0.046522
## [1]      train-error:0.022263
```

xgb.DMatrix

XGBoost offers a way to group them in a `xgb.DMatrix`. You can even add other meta data in it. This will be useful for the most advanced features we will discover later.

```
dtrain <- xgb.DMatrix(data = train$data, label = train$label)
bstDMatrix <- xgboost(data = dtrain, max.depth = 2, eta = 1, nthread = 2, nrounds = 2,
  ↪objective = "binary:logistic")
```

```
## [0]          train-error:0.046522
## [1]          train-error:0.022263
```

Verbose option

XGBoost has several features to help you view the learning progress internally. The purpose is to help you to set the best parameters, which is the key of your model quality.

One of the simplest way to see the training progress is to set the `verbose` option (see below for more advanced techniques).

```
# verbose = 0, no message
bst <- xgboost(data = dtrain, max.depth = 2, eta = 1, nthread = 2, nrounds = 2,
  ↪objective = "binary:logistic", verbose = 0)
```

```
# verbose = 1, print evaluation metric
bst <- xgboost(data = dtrain, max.depth = 2, eta = 1, nthread = 2, nrounds = 2,
  ↪objective = "binary:logistic", verbose = 1)
```

```
## [0]          train-error:0.046522
## [1]          train-error:0.022263
```

```
# verbose = 2, also print information about tree
bst <- xgboost(data = dtrain, max.depth = 2, eta = 1, nthread = 2, nrounds = 2,
  ↪objective = "binary:logistic", verbose = 2)
```

```
## [11:41:01] amalgamation/./src/tree/updater_prune.cc:74: tree pruning end, 1 roots, 6
  ↪extra nodes, 0 pruned nodes, max_depth=2
## [0]          train-error:0.046522
## [11:41:01] amalgamation/./src/tree/updater_prune.cc:74: tree pruning end, 1 roots, 4
  ↪extra nodes, 0 pruned nodes, max_depth=2
## [1]          train-error:0.022263
```

Basic prediction using XGBoost

Perform the prediction

The purpose of the model we have built is to classify new data. As explained before, we will use the `test` dataset for this step.

```
pred <- predict(bst, test$data)

# size of the prediction vector
print(length(pred))
```

```
## [1] 1611
```

```
# limit display of predictions to the first 10
print(head(pred))
```

```
## [1] 0.28583017 0.92392391 0.28583017 0.28583017 0.05169873 0.92392391
```

These numbers doesn't look like *binary classification* $\{0, 1\}$. We need to perform a simple transformation before being able to use these results.

Transform the regression in a binary classification

The only thing that **XGBoost** does is a *regression*. **XGBoost** is using `label` vector to build its *regression* model.

How can we use a *regression* model to perform a binary classification?

If we think about the meaning of a regression applied to our data, the numbers we get are probabilities that a datum will be classified as 1. Therefore, we will set the rule that if this probability for a specific datum is > 0.5 then the observation is classified as 1 (or 0 otherwise).

```
prediction <- as.numeric(pred > 0.5)
print(head(prediction))
```

```
## [1] 0 1 0 0 0 1
```

Measuring model performance

To measure the model performance, we will compute a simple metric, the *average error*.

```
err <- mean(as.numeric(pred > 0.5) != test$label)
print(paste("test-error=", err))
```

```
## [1] "test-error= 0.0217256362507759"
```

Note that the algorithm has not seen the test data during the model construction.

Steps explanation:

1. `as.numeric(pred > 0.5)` applies our rule that when the probability (\leq regression \leq prediction) is > 0.5 the observation is classified as 1 and 0 otherwise ;
2. `probabilityVectorPreviouslyComputed != test$label` computes the vector of error between true data and computed probabilities ;
3. `mean(vectorOfErrors)` computes the *average error* itself.

The most important thing to remember is that **to do a classification, you just do a regression to the label and then apply a threshold**.

Multiclass classification works in a similar way.

This metric is **0.02** and is pretty low: our yummy mushroom model works well!

Advanced features

Most of the features below have been implemented to help you to improve your model by offering a better understanding of its content.

Dataset preparation

For the following advanced features, we need to put data in `xgb.DMatrix` as explained above.

```
dtrain <- xgb.DMatrix(data = train$data, label=train$label)
dtest  <- xgb.DMatrix(data = test$data, label=test$label)
```

Measure learning progress with `xgb.train`

Both `xgboost` (simple) and `xgb.train` (advanced) functions train models.

One of the special features of `xgb.train` is the capacity to follow the progress of the learning after each round. Because of the way boosting works, there is a time when having too many rounds lead to overfitting. You can see this feature as a cousin of a cross-validation method. The following techniques will help you to avoid overfitting or optimizing the learning time in stopping it as soon as possible.

One way to measure progress in the learning of a model is to provide to **XGBoost** a second dataset already classified. Therefore it can learn on the first dataset and test its model on the second one. Some metrics are measured after each round during the learning.

in some way it is similar to what we have done above with the average error. The main difference is that above it was after building the model, and now it is during the construction that we measure errors.

For the purpose of this example, we use `watchlist` parameter. It is a list of `xgb.DMatrix`, each of them tagged with a name.

```
watchlist <- list(train=dtrain, test=dtest)

bst <- xgb.train(data=dtrain, max.depth=2, eta=1, nthread = 2, nrounds=2,
  ↪watchlist=watchlist, objective = "binary:logistic")
```

```
## [0]      train-error:0.046522      test-error:0.042831
## [1]      train-error:0.022263      test-error:0.021726
```

XGBoost has computed at each round the same average error metric seen above (we set `nrounds` to 2, that is why we have two lines). Obviously, the `train-error` number is related to the training dataset (the one the algorithm learns from) and the `test-error` number to the test dataset.

Both training and test error related metrics are very similar, and in some way, it makes sense: what we have learned from the training dataset matches the observations from the test dataset.

If with your own dataset you do not have such results, you should think about how you divided your dataset in training and test. May be there is something to fix. Again, `caret` package may [help](#).

For a better understanding of the learning progression, you may want to have some specific metric or even use multiple evaluation metrics.

```
bst <- xgb.train(data=dtrain, max.depth=2, eta=1, nthread = 2, nrounds=2,
  ↪watchlist=watchlist, eval.metric = "error", eval.metric = "logloss", objective =
  ↪"binary:logistic")
```

```
## [0]      train-error:0.046522      train-logloss:0.233376      test-error:0.
↪042831      test-logloss:0.226686
## [1]      train-error:0.022263      train-logloss:0.136658      test-error:0.
↪021726      test-logloss:0.137874
```

`eval.metric` allows us to monitor two new metrics for each round, `logloss` and `error`.

Linear boosting

Until now, all the learnings we have performed were based on boosting trees. **XGBoost** implements a second algorithm, based on linear boosting. The only difference with the previous command is `booster = "gblinear"` parameter (and removing `eta` parameter).

```
bst <- xgb.train(data=dtrain, booster = "gblinear", nthread = 2, nrounds=2,
↪watchlist=watchlist, eval.metric = "error", eval.metric = "logloss", objective =
↪"binary:logistic")
```

```
## [0]      train-error:0.024720      train-logloss:0.184616      test-error:0.
↪022967      test-logloss:0.184234
## [1]      train-error:0.004146      train-logloss:0.069885      test-error:0.
↪003724      test-logloss:0.068081
```

In this specific case, *linear boosting* gets slightly better performance metrics than a decision tree based algorithm.

In simple cases, this will happen because there is nothing better than a linear algorithm to catch a linear link. However, decision trees are much better to catch a non linear link between predictors and outcome. Because there is no silver bullet, we advise you to check both algorithms with your own datasets to have an idea of what to use.

Manipulating xgb.DMatrix

Save / Load

Like saving models, `xgb.DMatrix` object (which groups both dataset and outcome) can also be saved using `xgb.DMatrix.save` function.

```
xgb.DMatrix.save(dtrain, "dtrain.buffer")
```

```
## [1] TRUE
```

```
# to load it in, simply call xgb.DMatrix
dtrain2 <- xgb.DMatrix("dtrain.buffer")
```

```
## [11:41:01] 6513x126 matrix with 143286 entries loaded from dtrain.buffer
```

```
bst <- xgb.train(data=dtrain2, max.depth=2, eta=1, nthread = 2, nrounds=2,
↪watchlist=watchlist, objective = "binary:logistic")
```

```
## [0]      train-error:0.046522      test-error:0.042831
## [1]      train-error:0.022263      test-error:0.021726
```

Information extraction

Information can be extracted from an `xgb.DMatrix` using `getinfo` function. Hereafter we will extract label data.

```
label = getinfo(dtest, "label")
pred <- predict(bst, dtest)
err <- as.numeric(sum(as.integer(pred > 0.5) != label))/length(label)
print(paste("test-error=", err))
```

```
## [1] "test-error= 0.0217256362507759"
```

View feature importance/influence from the learnt model

Feature importance is similar to R `gbm` package's relative influence (`rel.inf`).

```
importance_matrix <- xgb.importance(model = bst)
print(importance_matrix)
xgb.plot.importance(importance_matrix = importance_matrix)
```

View the trees from a model

You can dump the tree you learned using `xgb.dump` into a text file.

```
xgb.dump(bst, with_stats = TRUE)
```

```
## [1] "booster[0]"
## [2] "0:[f28<-1.00136e-05] yes=1,no=2,missing=1,gain=4000.53,cover=1628.25"
## [3] "1:[f55<-1.00136e-05] yes=3,no=4,missing=3,gain=1158.21,cover=924.5"
## [4] "3:leaf=1.71218,cover=812"
## [5] "4:leaf=-1.70044,cover=112.5"
## [6] "2:[f108<-1.00136e-05] yes=5,no=6,missing=5,gain=198.174,cover=703.75"
## [7] "5:leaf=-1.94071,cover=690.5"
## [8] "6:leaf=1.85965,cover=13.25"
## [9] "booster[1]"
## [10] "0:[f59<-1.00136e-05] yes=1,no=2,missing=1,gain=832.545,cover=788.852"
## [11] "1:[f28<-1.00136e-05] yes=3,no=4,missing=3,gain=569.725,cover=768.39"
## [12] "3:leaf=0.784718,cover=458.937"
## [13] "4:leaf=-0.96853,cover=309.453"
## [14] "2:leaf=-6.23624,cover=20.4624"
```

You can plot the trees from your model using ```xgb.plot.tree```

```
xgb.plot.tree(model = bst)
```

if you provide a path to `fname` parameter you can save the trees to your hard drive.

Save and load models

Maybe your dataset is big, and it takes time to train a model on it? Maybe you are not a big fan of losing time in redoing the same task again and again? In these very rare cases, you will want to save your model and load it when required.

Helpfully for you, **XGBoost** implements such functions.

```
# save model to binary local file
xgb.save(bst, "xgboost.model")
```

```
## [1] TRUE
```

`xgb.save` function should return TRUE if everything goes well and crashes otherwise.

An interesting test to see how identical our saved model is to the original one would be to compare the two predictions.

```
# load binary model to R
bst2 <- xgb.load("xgboost.model")
pred2 <- predict(bst2, test$data)

# And now the test
print(paste("sum(abs(pred2-pred))=", sum(abs(pred2-pred))))
```

```
## [1] "sum(abs(pred2-pred))= 0"
```

result is 0? We are good!

In some very specific cases, like when you want to pilot **XGBoost** from `caret` package, you will want to save the model as a *R* binary vector. See below how to do it.

```
# save model to R's raw vector
rawVec <- xgb.save.raw(bst)

# print class
print(class(rawVec))
```

```
## [1] "raw"
```

```
# load binary model to R
bst3 <- xgb.load(rawVec)
pred3 <- predict(bst3, test$data)

# pred3 should be identical to pred
print(paste("sum(abs(pred3-pred))=", sum(abs(pred3-pred))))
```

```
## [1] "sum(abs(pred3-pred))= 0"
```

Again 0? It seems that XGBoost works pretty well!

References

Understand your dataset with XGBoost

Introduction

The purpose of this vignette is to show you how to use **XGBoost** to discover and understand your own dataset better.

This vignette is not about predicting anything (see [XGBoost presentation](#)). We will explain how to use **XGBoost** to highlight the *link* between the *features* of your data and the *outcome*.

Package loading:

```
require(xgboost)
require(Matrix)
require(data.table)
if (!require('vcd')) {
  install.packages('vcd')
}
```

VCD package is used for one of its embedded dataset only.

Preparation of the dataset

Numeric v.s. categorical variables

XGBoost manages only **numeric** vectors.

What to do when you have *categorical* data?

A *categorical* variable has a fixed number of different values. For instance, if a variable called *Colour* can have only one of these three values, *red*, *blue* or *green*, then *Colour* is a *categorical* variable.

In **R**, a *categorical* variable is called **factor**.

Type `?factor` in the console for more information.

To answer the question above we will convert *categorical* variables to **numeric** ones.

Conversion from categorical to numeric variables

Looking at the raw data

+In this Vignette we will see how to transform a *dense data.frame* (*dense* = the majority of the matrix is non-zero) with *categorical* variables to a very *sparse* matrix (*sparse* = lots of zero entries in the matrix) of **numeric** features.

The method we are going to see is usually called **one-hot encoding**.

The first step is to load the **Arthritis** dataset in memory and wrap it with the `data.table` package.

```
data(Arthritis)
df <- data.table(Arthritis, keep.rownames = FALSE)
```

`data.table` is 100% compliant with **R data.frame** but its syntax is more consistent and its performance for large dataset is **best in class** (`dplyr` from **R** and `Pandas` from **Python** [included](#)). Some parts of **XGBoost's R** package use `data.table`.

The first thing we want to do is to have a look to the first few lines of the `data.table`:

```
head(df)

##      ID Treatment  Sex Age Improved
## 1:  57   Treated Male  27     Some
## 2:  46   Treated Male  29     None
## 3:  77   Treated Male  30     None
## 4:  17   Treated Male  32   Marked
## 5:  36   Treated Male  46   Marked
## 6:  23   Treated Male  58   Marked
```

Now we will check the format of each column.

```
str(df)

## Classes 'data.table' and 'data.frame':  84 obs. of  5 variables:
## $ ID      : int  57 46 77 17 36 23 75 39 33 55 ...
## $ Treatment: Factor w/ 2 levels "Placebo","Treated": 2 2 2 2 2 2 2 2 2 ...
## $ Sex      : Factor w/ 2 levels "Female","Male": 2 2 2 2 2 2 2 2 2 ...
## $ Age      : int  27 29 30 32 46 58 59 59 63 63 ...
## $ Improved : Ord.factor w/ 3 levels "None"<"Some"<...: 2 1 1 3 3 3 1 3 1 1 ...
## - attr(*, ".internal.selfref")=<externalptr>
```

2 columns have factor type, one has ordinal type.

ordinal variable :

- can take a limited number of values (like factor) ;
- these values are ordered (unlike factor). Here these ordered values are: **Marked > Some > None**

Creation of new features based on old ones

We will add some new *categorical* features to see if it helps.

Grouping per 10 years

For the first features we create groups of age by rounding the real age.

Note that we transform it to `factor` so the algorithm treats these age groups as independent values.

Therefore, 20 is not closer to 30 than 60. In other words, the distance between ages is lost in this transformation.

```
head(df[, AgeDiscret := as.factor(round(Age / 10, 0))])

##      ID Treatment  Sex Age Improved AgeDiscret
## 1:  57   Treated Male  27     Some           3
## 2:  46   Treated Male  29     None           3
## 3:  77   Treated Male  30     None           3
## 4:  17   Treated Male  32   Marked           3
## 5:  36   Treated Male  46   Marked           5
## 6:  23   Treated Male  58   Marked           6
```

Randomly split into two groups

The following is an even stronger simplification of the real age with an arbitrary split at 30 years old. I choose this value **based on nothing**. We will see later if simplifying the information based on arbitrary values is a good strategy (you may already have an idea of how well it will work...).

```
head(df[, AgeCat := as.factor(ifelse(Age > 30, "Old", "Young"))])
```

##	ID	Treatment	Sex	Age	Improved	AgeDiscret	AgeCat
## 1:	57	Treated	Male	27	Some	3	Young
## 2:	46	Treated	Male	29	None	3	Young
## 3:	77	Treated	Male	30	None	3	Young
## 4:	17	Treated	Male	32	Marked	3	Old
## 5:	36	Treated	Male	46	Marked	5	Old
## 6:	23	Treated	Male	58	Marked	6	Old

Risks in adding correlated features

These new features are highly correlated to the **Age** feature because they are simple transformations of this feature.

For many machine learning algorithms, using correlated features is not a good idea. It may sometimes make prediction less accurate, and most of the time make interpretation of the model almost impossible. GLM, for instance, assumes that the features are uncorrelated.

Fortunately, decision tree algorithms (including boosted trees) are very robust to these features. Therefore we don't have to do anything to manage this situation.

Cleaning data

We remove ID as there is nothing to learn from this feature (it would just add some noise).

```
df[, ID := NULL]
```

We will list the different values for the column **Treatment**:

```
levels(df[, Treatment])
```

```
## [1] "Placebo" "Treated"
```

Encoding categorical features

Next step, we will transform the categorical data to dummy variables. Several encoding methods exist, e.g., [one-hot encoding](#) is a common approach. We will use the [dummy contrast coding](#) which is popular because it produces “full rank” encoding (also see [this blog post by Max Kuhn](#)).

The purpose is to transform each value of each *categorical* feature into a *binary* feature {0, 1}.

For example, the column **Treatment** will be replaced by two columns, **TreatmentPlacebo**, and **TreatmentTreated**. Each of them will be *binary*. Therefore, an observation which has the value **Placebo** in column **Treatment** before the transformation will have the value 1 in the new column **TreatmentPlacebo** and the value 0 in the new column **TreatmentTreated** after the transformation. The column **TreatmentPlacebo** will disappear during the contrast encoding, as it would be absorbed into a common constant intercept column.

Column Improved is excluded because it will be our label column, the one we want to predict.

```
sparse_matrix <- sparse.model.matrix(Improved ~ ., data = df)[, -1]
head(sparse_matrix)

## 6 x 9 sparse Matrix of class "dgCMatrix"
##   TreatmentTreated SexMale Age AgeDiscret3 AgeDiscret4 AgeDiscret5 AgeDiscret6
## 1                1      1  27                1          .          .          .
## 2                1      1  29                1          .          .          .
## 3                1      1  30                1          .          .          .
## 4                1      1  32                1          .          .          .
## 5                1      1  46                .          .          1          .
## 6                1      1  58                .          .          .          1
##   AgeDiscret7 AgeCatYoung
## 1            .           1
## 2            .           1
## 3            .           1
## 4            .           .
## 5            .           .
## 6            .           .
```

Formula `Improved ~ .` used above means transform all *categorical* features but column Improved to binary values. The `-1` column selection removes the intercept column which is full of 1 (this column is generated by the conversion). For more information, you can type `?sparse.model.matrix` in the console.

Create the output numeric vector (not as a sparse Matrix):

```
output_vector <- df[, Improved] == "Marked"
```

1. set Y vector to 0;
2. set Y to 1 for rows where Improved == Marked is TRUE ;
3. return Y vector.

Build the model

The code below is very usual. For more information, you can look at the documentation of `xgboost` function (or at the vignette [XGBoost presentation](#)).

```
bst <- xgboost(data = sparse_matrix, label = output_vector, max_depth = 4,
              eta = 1, nthread = 2, nrounds = 10, objective = "binary:logistic")

## [1] train-logloss:0.485466
## [2] train-logloss:0.438534
## [3] train-logloss:0.412250
## [4] train-logloss:0.395828
## [5] train-logloss:0.384264
## [6] train-logloss:0.374028
## [7] train-logloss:0.365005
## [8] train-logloss:0.351233
## [9] train-logloss:0.341678
## [10] train-logloss:0.334465
```

You can see some `train-logloss: 0.XXXXX` lines followed by a number. It decreases. Each line shows how well the model explains the data. Lower is better.

A small value for training error may be a symptom of [overfitting](#), meaning the model will not accurately predict unseen values.

Feature importance

Measure feature importance

Build the feature importance data.table

Remember, each binary column corresponds to a single value of one of *categorical* features.

```
importance <- xgb.importance(feature_names = colnames(sparse_matrix), model = bst)
head(importance)
```

```
##           Feature      Gain      Cover  Frequency
## 1:           Age 0.622031769 0.67251696 0.67241379
## 2: TreatmentTreated 0.285750540 0.11916651 0.10344828
## 3:           SexMale 0.048744022 0.04522028 0.08620690
## 4:    AgeDiscret6 0.016604639 0.04784639 0.05172414
## 5:    AgeDiscret3 0.016373781 0.08028951 0.05172414
## 6:    AgeDiscret4 0.009270557 0.02858801 0.01724138
```

The column `Gain` provides the information we are looking for.

As you can see, features are classified by `Gain`.

`Gain` is the improvement in accuracy brought by a feature to the branches it is on. The idea is that before adding a new split on a feature `X` to the branch there were some wrongly classified elements; after adding the split on this feature, there are two new branches, and each of these branches is more accurate (one branch saying if your observation is on this branch then it should be classified as 1, and the other branch saying the exact opposite).

`Cover` is related to the second order derivative (or Hessian) of the loss function with respect to a particular variable; thus, a large value indicates a variable has a large potential impact on the loss function and so is important.

`Frequency` is a simpler way to measure the `Gain`. It just counts the number of times a feature is used in all generated trees. You should not use it (unless you know why you want to use it).

Plotting the feature importance

All these things are nice, but it would be even better to plot the results.

```
xgb.plot.importance(importance_matrix = importance)
```

Running this line of code, you should get a bar chart showing the importance of the 6 features (containing the same data as the output we saw earlier, but displaying it visually for easier consumption). Note that `xgb.ggplot.importance` is also available for all the `ggplot2` fans!

Depending of the dataset and the learning parameters you may have more than two clusters. Default value is to limit them to 10, but you can increase this limit. Look at the function documentation for more information.

According to the plot above, the most important features in this dataset to predict if the treatment will work are :

- An individual's age;
- Having received a placebo or not;
- Gender;
- Our generated feature AgeDiscret. We can see that its contribution is very low.

Do these results make sense?

Let's check some **Chi2** between each of these features and the label.

Higher **Chi2** means better correlation.

```
c2 <- chisq.test(df$Age, output_vector)
print(c2)

##
## Pearson's Chi-squared test
##
## data: df$Age and output_vector
## X-squared = 35.475, df = 35, p-value = 0.4458
```

The Pearson correlation between Age and illness disappearing is **35.47**.

```
c2 <- chisq.test(df$AgeDiscret, output_vector)
print(c2)

##
## Pearson's Chi-squared test
##
## data: df$AgeDiscret and output_vector
## X-squared = 8.2554, df = 5, p-value = 0.1427
```

Our first simplification of Age gives a Pearson correlation of **8.26**.

```
c2 <- chisq.test(df$AgeCat, output_vector)
print(c2)

##
## Pearson's Chi-squared test with Yates' continuity correction
##
## data: df$AgeCat and output_vector
## X-squared = 2.3571, df = 1, p-value = 0.1247
```

The perfectly random split we did between young and old at 30 years old has a low correlation of **2.36**. This suggests that, for the particular illness we are studying, the age at which someone is vulnerable to this disease is likely very different from 30.

Moral of the story: don't let your *gut* lower the quality of your model.

In *data science*, there is the word *science* :-)

Conclusion

As you can see, in general *destroying information by simplifying it won't improve your model*. **Chi2** just demonstrates that.

But in more complex cases, creating a new feature from an existing one may help the algorithm and improve the model.

+The case studied here is not complex enough to show that. Check [Kaggle website](#) for some challenging datasets.

Moreover, you can see that even if we have added some new features which are not very useful/highly correlated with other features, the boosting tree algorithm was still able to choose the best one (which in this case is the Age).

Linear models may not perform as well.

Special Note: What about Random Forests™?

As you may know, the [Random Forests](#) algorithm is cousin with boosting and both are part of the [ensemble learning](#) family.

Both train several decision trees for one dataset. The *main* difference is that in Random Forests, trees are independent and in boosting, the N+1-st tree focuses its learning on the loss (\Leftrightarrow what has not been well modeled by the tree N).

This difference can have an impact on a edge case in feature importance analysis: *correlated features*.

Imagine two features perfectly correlated, feature A and feature B. For one specific tree, if the algorithm needs one of them, it will choose randomly (true in both boosting and Random Forests).

However, in Random Forests this random choice will be done for each tree, because each tree is independent from the others. Therefore, approximately (and depending on your parameters) 50% of the trees will choose feature A and the other 50% will choose feature B. So the *importance* of the information contained in A and B (which is the same, because they are perfectly correlated) is diluted in A and B. So you won't easily know this information is important to predict what you want to predict! It is even worse when you have 10 correlated features...

In boosting, when a specific link between feature and outcome have been learned by the algorithm, it will try to not refocus on it (in theory it is what happens, reality is not always that simple). Therefore, all the importance will be on feature A or on feature B (but not both). You will know that one feature has an important role in the link between the observations and the label. It is still up to you to search for the correlated features to the one detected as important if you need to know all of them.

If you want to try Random Forests algorithm, you can tweak XGBoost parameters!

For instance, to compute a model with 1000 trees, with a 0.5 factor on sampling rows and columns:

```
data(agaricus.train, package = 'xgboost')
data(agaricus.test, package = 'xgboost')
train <- agaricus.train
test <- agaricus.test

#Random Forest - 1000 trees
bst <- xgboost(
  data = train$data
  , label = train$label
  , max_depth = 4
  , num_parallel_tree = 1000
  , subsample = 0.5
  , colsample_bytree = 0.5
  , nrounds = 1
  , objective = "binary:logistic"
```

(continues on next page)

(continued from previous page)

```

)

## [1]  train-logloss:0.456201

#Boosting - 3 rounds
bst <- xgboost(
  data = train$data
  , label = train$label
  , max_depth = 4
  , nrounds = 3
  , objective = "binary:logistic"
)

## [1]  train-logloss:0.444882
## [2]  train-logloss:0.302428
## [3]  train-logloss:0.212847

```

Note that the parameter `round` is set to 1.

Random Forests is a trademark of Leo Breiman and Adele Cutler and is licensed exclusively to Salford Systems for the commercial release of the software.

1.12 XGBoost JVM Package

You have found the XGBoost JVM Package!

1.12.1 Installation

Checkout the [Installation Guide](#) for how to install the jvm package, or [Building from Source](#) on how to build it from the sources.

1.12.2 Contents

Getting Started with XGBoost4J

This tutorial introduces Java API for XGBoost.

Data Interface

Like the XGBoost python module, XGBoost4J uses `DMatrix` to handle data. LIBSVM txt format file, sparse matrix in CSR/CSC format, and dense matrix are supported.

- The first step is to import `DMatrix`:

```
import ml.dmlc.xgboost4j.java.DMatrix;
```

- Use `DMatrix` constructor to load data from a libsvm text format file:

```
DMatrix dmat = new DMatrix("train.svm.txt");
```

- Pass arrays to DMatrix constructor to load from sparse matrix.

Suppose we have a sparse matrix

```
1 0 2 0
4 0 0 3
3 1 2 0
```

We can express the sparse matrix in Compressed Sparse Row (CSR) format:

```
long[] rowHeaders = new long[] {0,2,4,7};
float[] data = new float[] {1f,2f,4f,3f,3f,1f,2f};
int[] colIndex = new int[] {0,2,0,3,0,1,2};
int numColumn = 4;
DMatrix dmat = new DMatrix(rowHeaders, colIndex, data, DMatrix.SparseType.CSR,
    ↪numColumn);
```

... or in Compressed Sparse Column (CSC) format:

```
long[] colHeaders = new long[] {0,3,4,6,7};
float[] data = new float[] {1f,4f,3f,1f,2f,2f,3f};
int[] rowIndex = new int[] {0,1,2,2,0,2,1};
int numRows = 3;
DMatrix dmat = new DMatrix(colHeaders, rowIndex, data, DMatrix.SparseType.CSC,
    ↪numRows);
```

- You may also load your data from a dense matrix. Let's assume we have a matrix of form

```
1 2
3 4
5 6
```

Using row-major layout, we specify the dense matrix as follows:

```
float[] data = new float[] {1f,2f,3f,4f,5f,6f};
int nrow = 3;
int ncol = 2;
float missing = 0.0f;
DMatrix dmat = new DMatrix(data, nrow, ncol, missing);
```

- To set weight:

```
float[] weights = new float[] {1f,2f,1f};
dmat.setWeight(weights);
```

Setting Parameters

To set parameters, parameters are specified as a Map:

```
Map<String, Object> params = new HashMap<String, Object>() {
    {
        put("eta", 1.0);
        put("max_depth", 2);
        put("objective", "binary:logistic");
    }
}
```

(continues on next page)

(continued from previous page)

```
    put("eval_metric", "logloss");
  }
};
```

Training Model

With parameters and data, you are able to train a booster model.

- Import Booster and XGBoost:

```
import ml.dmlc.xgboost4j.java.Booster;
import ml.dmlc.xgboost4j.java.XGBoost;
```

- Training

```
DMatrix trainMat = new DMatrix("train.svm.txt");
DMatrix validMat = new DMatrix("valid.svm.txt");
// Specify a watch list to see model accuracy on data sets
Map<String, DMatrix> watches = new HashMap<String, DMatrix>() {
    {
        put("train", trainMat);
        put("test", testMat);
    }
};
int nround = 2;
Booster booster = XGBoost.train(trainMat, params, nround, watches, null, null);
```

- Saving model

After training, you can save model and dump it out.

```
booster.saveModel("model.bin");
```

- Generating model dump with feature map

```
// dump without feature map
String[] model_dump = booster.getModelDump(null, false);
// dump with feature map
String[] model_dump_with_feature_map = booster.getModelDump("featureMap.txt",
    ↪ false);
```

- Load a model

```
Booster booster = XGBoost.loadModel("model.bin");
```

Prediction

After training and loading a model, you can use it to make prediction for other data. The result will be a two-dimension float array (nsample, nclass); for `predictLeaf()`, the result would be of shape (nsample, nclass*ntrees).

```
DMatrix dtest = new DMatrix("test.svm.txt");
// predict
float[][] predicts = booster.predict(dtest);
// predict leaf
float[][] leafPredicts = booster.predictLeaf(dtest, 0);
```

XGBoost4J-Spark Tutorial (version 0.9+)

XGBoost4J-Spark is a project aiming to seamlessly integrate XGBoost and Apache Spark by fitting XGBoost to Apache Spark's MLLIB framework. With the integration, user can not only uses the high-performant algorithm implementation of XGBoost, but also leverages the powerful data processing engine of Spark for:

- Feature Engineering: feature extraction, transformation, dimensionality reduction, and selection, etc.
- Pipelines: constructing, evaluating, and tuning ML Pipelines
- Persistence: persist and load machine learning models and even whole Pipelines

This tutorial is to cover the end-to-end process to build a machine learning pipeline with XGBoost4J-Spark. We will discuss

- Using Spark to preprocess data to fit to XGBoost/XGBoost4J-Spark's data interface
- Training a XGBoost model with XGBoost4J-Spark
- Serving XGBoost model (prediction) with Spark
- Building a Machine Learning Pipeline with XGBoost4J-Spark
- Running XGBoost4J-Spark in Production

- *Build an ML Application with XGBoost4J-Spark*
 - *Refer to XGBoost4J-Spark Dependency*
 - *Data Preparation*
 - * *Read Dataset with Spark's Built-In Reader*
 - * *Transform Raw Iris Dataset*
 - *Dealing with missing values*
 - *Training*
 - * *Early Stopping*
 - * *Training with Evaluation Sets*
 - *Prediction*
 - * *Batch Prediction*
 - * *Single instance prediction*
 - *Model Persistence*

- * *Model and pipeline persistence*
- * *Interact with Other Bindings of XGBoost*
- *Building a ML Pipeline with XGBoost4J-Spark*
 - *Basic ML Pipeline*
 - *Pipeline with Hyper-parameter Tunning*
- *Run XGBoost4J-Spark in Production*
 - *Parallel/Distributed Training*
 - *Gang Scheduling*
 - *Checkpoint During Training*

Build an ML Application with XGBoost4J-Spark

Refer to XGBoost4J-Spark Dependency

Before we go into the tour of how to use XGBoost4J-Spark, you should first consult [Installation from Maven repository](#) in order to add XGBoost4J-Spark as a dependency for your project. We provide both stable releases and snapshots.

Note: XGBoost4J-Spark requires Apache Spark 2.4+

XGBoost4J-Spark now requires **Apache Spark 2.4+**. Latest versions of XGBoost4J-Spark uses facilities of *org.apache.spark.ml.param.shared* extensively to provide for a tight integration with Spark MLLIB framework, and these facilities are not fully available on earlier versions of Spark.

Also, make sure to install Spark directly from [Apache website](#). **Upstream XGBoost is not guaranteed to work with third-party distributions of Spark, such as Cloudera Spark.** Consult appropriate third parties to obtain their distribution of XGBoost.

Installation from maven repo

Note: Use of Python in XGBoost4J-Spark

By default, we use the tracker in [Python package](#) to drive the training with XGBoost4J-Spark. It requires Python 3.6+. We also have an experimental Scala version of tracker which can be enabled by passing the parameter `tracker_conf` as `scala`.

Data Preparation

As aforementioned, XGBoost4J-Spark seamlessly integrates Spark and XGBoost. The integration enables users to apply various types of transformation over the training/test datasets with the convenient and powerful data processing framework, Spark.

In this section, we use [Iris](#) dataset as an example to showcase how we use Spark to transform raw dataset and make it fit to the data interface of XGBoost.

Iris dataset is shipped in CSV format. Each instance contains 4 features, “sepal length”, “sepal width”, “petal length” and “petal width”. In addition, it contains the “class” column, which is essentially the label with three possible values: “Iris Setosa”, “Iris Versicolour” and “Iris Virginica”.

Read Dataset with Spark's Built-In Reader

The first thing in data transformation is to load the dataset as Spark's structured data abstraction, `DataFrame`.

```
import org.apache.spark.sql.SparkSession
import org.apache.spark.sql.types.{DoubleType, StringType, StructField, StructType}

val spark = SparkSession.builder().getOrCreate()
val schema = new StructType(Array(
  StructField("sepal length", DoubleType, true),
  StructField("sepal width", DoubleType, true),
  StructField("petal length", DoubleType, true),
  StructField("petal width", DoubleType, true),
  StructField("class", StringType, true)))
val rawInput = spark.read.schema(schema).csv("input_path")
```

At the first line, we create a instance of `SparkSession` which is the entry of any Spark program working with `DataFrame`. The `schema` variable defines the schema of `DataFrame` wrapping Iris data. With this explicitly set schema, we can define the columns' name as well as their types; otherwise the column name would be the default ones derived by Spark, such as `_col0`, etc. Finally, we can use Spark's built-in csv reader to load Iris csv file as a `DataFrame` named `rawInput`.

Spark also contains many built-in readers for other format. The latest version of Spark supports CSV, JSON, Parquet, and LIBSVM.

Transform Raw Iris Dataset

To make Iris dataset be recognizable to XGBoost, we need to

1. Transform String-typed label, i.e. "class", to Double-typed label.
2. Assemble the feature columns as a vector to fit to the data interface of Spark ML framework.

To convert String-typed label to Double, we can use Spark's built-in feature transformer `StringIndexer`.

```
import org.apache.spark.ml.feature.StringIndexer
val stringIndexer = new StringIndexer().
  setInputCol("class").
  setOutputCol("classIndex").
  fit(rawInput)
val labelTransformed = stringIndexer.transform(rawInput).drop("class")
```

With a newly created `StringIndexer` instance:

1. we set input column, i.e. the column containing String-typed label
2. we set output column, i.e. the column to contain the Double-typed label.
3. Then we `fit` `StringIndex` with our input `DataFrame` `rawInput`, so that Spark internals can get information like total number of distinct values, etc.

Now we have a `StringIndexer` which is ready to be applied to our input `DataFrame`. To execute the transformation logic of `StringIndexer`, we `transform` the input `DataFrame` `rawInput` and to keep a concise `DataFrame`, we drop the column "class" and only keeps the feature columns and the transformed Double-typed label column (in the last line of the above code snippet).

The `fit` and `transform` are two key operations in MLLIB. Basically, `fit` produces a "transformer", e.g. `StringIndexer`, and each transformer applies `transform` method on `DataFrame` to add new column(s) containing transformed

features/labels or prediction results, etc. To understand more about `fit` and `transform`, You can find more details in [here](#).

Similarly, we can use another transformer, `VectorAssembler`, to assemble feature columns “sepal length”, “sepal width”, “petal length” and “petal width” as a vector.

```
import org.apache.spark.ml.feature.VectorAssembler
val vectorAssembler = new VectorAssembler().
  setInputCols(Array("sepal length", "sepal width", "petal length", "petal width")).
  setOutputCol("features")
val xgbInput = vectorAssembler.transform(labelTransformed).select("features", "classIndex")
  ↪")
```

Now, we have a `DataFrame` containing only two columns, “features” which contains vector-represented “sepal length”, “sepal width”, “petal length” and “petal width” and “classIndex” which has Double-typed labels. A `DataFrame` like this (containing vector-represented features and numeric labels) can be fed to XGBoost4J-Spark’s training engine directly.

Note: There is no need to assemble feature columns from version 1.6.1+. Instead, users can specify an array of feature column names by `setFeaturesCol(value: Array[String])` and XGBoost4j-Spark will do it.

Dealing with missing values

XGBoost supports missing values by default ([as described here](#)). If given a `SparseVector`, XGBoost will treat any values absent from the `SparseVector` as missing. You are also able to specify to XGBoost to treat a specific value in your Dataset as if it was a missing value. By default XGBoost will treat NaN as the value representing missing.

Example of setting a missing value (e.g. -999) to the “missing” parameter in `XGBoostClassifier`:

```
import ml.dmlc.xgboost4j.scala.spark.XGBoostClassifier
val xgbParam = Map("eta" -> 0.1f,
  "missing" -> -999,
  "objective" -> "multi:softprob",
  "num_class" -> 3,
  "num_round" -> 100,
  "num_workers" -> 2)
val xgbClassifier = new XGBoostClassifier(xgbParam).
  setFeaturesCol("features").
  setLabelCol("classIndex")
```

Note: Missing values with Spark’s `VectorAssembler`

If given a Dataset with enough features having a value of 0 Spark’s `VectorAssembler` transformer class will return a `SparseVector` where the absent values are meant to indicate a value of 0. This conflicts with XGBoost’s default to treat values absent from the `SparseVector` as missing. The model would effectively be treating 0 as missing but not declaring that to be so which can lead to confusion when using the trained model on other platforms. To avoid this, XGBoost will raise an exception if it receives a `SparseVector` and the “missing” parameter has not been explicitly set to 0. To workaround this issue the user has three options:

1. Explicitly convert the Vector returned from `VectorAssembler` to a `DenseVector` to return the zeros to the dataset. If doing this with missing values encoded as NaN, you will want to set `setHandleInvalid = "keep"` on `VectorAssembler` in order to keep the NaN values in the dataset. You would then set the “missing” parameter to whatever you want to be treated as missing. However this may cause a large amount of memory use if your dataset is very sparse. For example:

```
val assembler = new VectorAssembler().setInputCols(feature_names.toArray).setOutputCol("features").setHandleInvalid("keep")
// conversion to dense vector using Array()

val featurePipeline = new Pipeline().setStages(Array(assembler)) val featureModel = featurePipeline.fit(df_training)
val featureDf = featureModel.transform(df_training)

val xgbParam = Map("eta" -> 0.1f,
  "max_depth" -> 2, "objective" -> "multi:softprob", "num_class" -> 3, "num_round" -> 100, "num_workers" ->
  2, "allow_non_zero_for_missing" -> "true", "missing" -> -999)

val xgb = new XGBoostClassifier(xgbParam) val xgbclassifier = xgb.fit(featureDf)
```

2. Before calling VectorAssembler you can transform the values you want to represent missing into an irregular value that is not 0, NaN, or Null and set the "missing" parameter to 0. The irregular value should ideally be chosen to be outside the range of values that your features have.

3. Do not use the VectorAssembler class and instead use a custom way of constructing a SparseVector that allows for specifying sparsity to indicate a non-zero value. You can then set the "missing" parameter to whatever sparsity indicates in your Dataset. If this approach is taken you can pass the parameter "allow_non_zero_for_missing_value" -> true to bypass XGBoost's assertion that "missing" must be zero when given a SparseVector.

Option 1 is recommended if memory constraints are not an issue. Option 3 requires more work to get set up but is guaranteed to give you correct results while option 2 will be quicker to set up but may be difficult to find a good irregular value that does not conflict with your feature values.

Note: Using a non-default missing value when using other bindings of XGBoost.

When XGBoost is saved in native format only the booster itself is saved, the value of the missing parameter is not saved alongside the model. Thus, if a non-default missing parameter is used to train the model in Spark the user should take care to use the same missing parameter when using the saved model in another binding.

Training

XGBoost supports both regression and classification. While we use Iris dataset in this tutorial to show how we use XGBoost/XGBoost4J-Spark to resolve a multi-classes classification problem, the usage in Regression is very similar to classification.

To train a XGBoost model for classification, we need to claim a XGBoostClassifier first:

```
import ml.dmlc.xgboost4j.scala.spark.XGBoostClassifier
val xgbParam = Map("eta" -> 0.1f,
  "max_depth" -> 2,
  "objective" -> "multi:softprob",
  "num_class" -> 3,
  "num_round" -> 100,
  "num_workers" -> 2)
val xgbClassifier = new XGBoostClassifier(xgbParam).
  setFeaturesCol("features").
  setLabelCol("classIndex")
```


The available parameters for training a XGBoost model can be found in [here](#). In XGBoost4J-Spark, we support not only the default set of parameters but also the camel-case variant of these parameters to keep consistent with Spark's MLLIB parameters.

Specifically, each parameter in [this page](#) has its equivalent form in XGBoost4J-Spark with camel case. For example, to set `max_depth` for each tree, you can pass parameter just like what we did in the above code snippet (as `max_depth` wrapped in a Map), or you can do it through setters in `XGBoostClassifier`:

```
val xgbClassifier = new XGBoostClassifier().
  setFeaturesCol("features").
  setLabelCol("classIndex")
xgbClassifier.setMaxDepth(2)
```

After we set `XGBoostClassifier` parameters and feature/label column, we can build a transformer, `XGBoostClassificationModel` by fitting `XGBoostClassifier` with the input `DataFrame`. This `fit` operation is essentially the training process and the generated model can then be used in prediction.

```
val xgbClassificationModel = xgbClassifier.fit(xgbInput)
```

Early Stopping

Early stopping is a feature to prevent the unnecessary training iterations. By specifying `num_early_stopping_rounds` or directly call `setNumEarlyStoppingRounds` over a `XGBoostClassifier` or `XGBoostRegressor`, we can define number of rounds if the evaluation metric going away from the best iteration and early stop training iterations.

When it comes to custom eval metrics, in addition to `num_early_stopping_rounds`, you also need to define `maximize_evaluation_metrics` or call `setMaximizeEvaluationMetrics` to specify whether you want to maximize or minimize the metrics in training. For built-in eval metrics, XGBoost4J-Spark will automatically select the direction.

For example, we need to maximize the evaluation metrics (set `maximize_evaluation_metrics` with `true`), and set `num_early_stopping_rounds` with 5. The evaluation metric of 10th iteration is the maximum one until now. In the following iterations, if there is no evaluation metric greater than the 10th iteration's (best one), the training would be early stopped at 15th iteration.

Training with Evaluation Sets

You can also monitor the performance of the model during training with multiple evaluation datasets. By specifying `eval_sets` or call `setEvalSets` over a `XGBoostClassifier` or `XGBoostRegressor`, you can pass in multiple evaluation datasets typed as a Map from String to `DataFrame`.

Prediction

XGBoost4J-Spark supports two ways for model serving: batch prediction and single instance prediction.

Batch Prediction

When we get a model, either `XGBoostClassificationModel` or `XGBoostRegressionModel`, it takes a `DataFrame`, read the column containing feature vectors, predict for each feature vector, and output a new `DataFrame` with the following columns by default:

- `XGBoostClassificationModel` will output margins (`rawPredictionCol`), probabilities(`probabilityCol`) and the eventual prediction labels (`predictionCol`) for each possible label.
- `XGBoostRegressionModel` will output prediction label(`predictionCol`).

Batch prediction expects the user to pass the testset in the form of a `DataFrame`. `XGBoost4J-Spark` starts a `XGBoost` worker for each partition of `DataFrame` for parallel prediction and generates prediction results for the whole `DataFrame` in a batch.

```
val xgbClassificationModel = xgbClassifier.fit(xgbInput)
val results = xgbClassificationModel.transform(testSet)
```

With the above code snippet, we get a result `DataFrame`, result containing margin, probability for each class and the prediction for each instance

features	classIndex	rawPrediction	probability	prediction
[5.1,3.5,1.4,0.2]	0.0	[3.45569849014282...	[0.99579632282257...	0.0
[4.9,3.0,1.4,0.2]	0.0	[3.45569849014282...	[0.99618089199066...	0.0
[4.7,3.2,1.3,0.2]	0.0	[3.45569849014282...	[0.99643349647521...	0.0
[4.6,3.1,1.5,0.2]	0.0	[3.45569849014282...	[0.99636095762252...	0.0
[5.0,3.6,1.4,0.2]	0.0	[3.45569849014282...	[0.99579632282257...	0.0
[5.4,3.9,1.7,0.4]	0.0	[3.45569849014282...	[0.99428516626358...	0.0
[4.6,3.4,1.4,0.3]	0.0	[3.45569849014282...	[0.99643349647521...	0.0
[5.0,3.4,1.5,0.2]	0.0	[3.45569849014282...	[0.99579632282257...	0.0
[4.4,2.9,1.4,0.2]	0.0	[3.45569849014282...	[0.99618089199066...	0.0
[4.9,3.1,1.5,0.1]	0.0	[3.45569849014282...	[0.99636095762252...	0.0
[5.4,3.7,1.5,0.2]	0.0	[3.45569849014282...	[0.99428516626358...	0.0
[4.8,3.4,1.6,0.2]	0.0	[3.45569849014282...	[0.99643349647521...	0.0
[4.8,3.0,1.4,0.1]	0.0	[3.45569849014282...	[0.99618089199066...	0.0
[4.3,3.0,1.1,0.1]	0.0	[3.45569849014282...	[0.99618089199066...	0.0
[5.8,4.0,1.2,0.2]	0.0	[3.45569849014282...	[0.97809928655624...	0.0
[5.7,4.4,1.5,0.4]	0.0	[3.45569849014282...	[0.97809928655624...	0.0
[5.4,3.9,1.3,0.4]	0.0	[3.45569849014282...	[0.99428516626358...	0.0
[5.1,3.5,1.4,0.3]	0.0	[3.45569849014282...	[0.99579632282257...	0.0
[5.7,3.8,1.7,0.3]	0.0	[3.45569849014282...	[0.97809928655624...	0.0
[5.1,3.8,1.5,0.3]	0.0	[3.45569849014282...	[0.99579632282257...	0.0

Single instance prediction

XGBoostClassificationModel or XGBoostRegressionModel support make prediction on single instance as well. It accepts a single Vector as feature, and output the prediction label.

However, the overhead of single-instance prediction is high due to the internal overhead of XGBoost, use it carefully!

```
val features = xgbInput.head().getAs[Vector]("features")
val result = xgbClassificationModel.predict(features)
```

Model Persistence

Model and pipeline persistence

A data scientist produces an ML model and hands it over to an engineering team for deployment in a production environment. Reversely, a trained model may be used by data scientists, for example as a baseline, across the process of data exploration. So it's important to support model persistence to make the models available across usage scenarios and programming languages.

XGBoost4j-Spark supports saving and loading XGBoostClassifier/XGBoostClassificationModel and XGBoostRegressor/XGBoostRegressionModel. It also supports saving and loading a ML pipeline which includes these estimators and models.

We can save the XGBoostClassificationModel to file system:

```
val xgbClassificationModelPath = "/tmp/xgbClassificationModel"
xgbClassificationModel.write.overwrite().save(xgbClassificationModelPath)
```

and then loading the model in another session:

```
import ml.dmlc.xgboost4j.scala.spark.XGBoostClassificationModel

val xgbClassificationModel2 = XGBoostClassificationModel.load(xgbClassificationModelPath)
xgbClassificationModel2.transform(xgbInput)
```

Note: Besides dumping the model to raw format, users are able to dump the model to be json or ubj format from version 1.7.0+.

```
val xgbClassificationModelPath = "/tmp/xgbClassificationModel"
xgbClassificationModel.write.overwrite().option("format", "json").
  ↪ save(xgbClassificationModelPath)
```

With regards to ML pipeline save and load, please refer the next section.

Interact with Other Bindings of XGBoost

After we train a model with XGBoost4j-Spark on massive dataset, sometimes we want to do model serving in single machine or integrate it with other single node libraries for further processing.

After saving the model, we can load this model with single node Python XGBoost directly from version 1.7.0+.

```
val xgbClassificationModelPath = "/tmp/xgbClassificationModel"
xgbClassificationModel.write.overwrite().save(xgbClassificationModelPath)
```

```
import xgboost as xgb
bst = xgb.Booster({'nthread': 4})
bst.load_model("/tmp/xgbClassificationModel/data/XGBoostClassificationModel")
```

Before version 1.7.0, XGBoost4j-Spark needs to export model to local manually by:

```
val nativeModelPath = "/tmp/nativeModel"
xgbClassificationModel.nativeBooster.saveModel(nativeModelPath)
```

Then we can load this model with single node Python XGBoost:

```
import xgboost as xgb
bst = xgb.Booster({'nthread': 4})
bst.load_model(nativeModelPath)
```

Note: Using HDFS and S3 for exporting the models with `nativeBooster.saveModel()`

When interacting with other language bindings, XGBoost also supports saving-models-to and loading-models-from file systems other than the local one. You can use HDFS and S3 by prefixing the path with `hdfs://` and `s3://` respectively. However, for this capability, you must do **one** of the following:

1. Build XGBoost4J-Spark with the steps described in [here](#), but turning `USE_HDFS` (or `USE_S3`, etc. in the same place) switch on. With this approach, you can reuse the above code example by replacing “`nativeModelPath`” with a HDFS path.
 - However, if you build with `USE_HDFS`, etc. you have to ensure that the involved shared object file, e.g. `libhdfs.so`, is put in the `LIBRARY_PATH` of your cluster. To avoid the complicated cluster environment configuration, choose the other option.
2. Use bindings of HDFS, S3, etc. to pass model files around. Here are the steps (taking HDFS as an example):
 - Create a new file with

```
val outputStream = fs.create("hdfs_path")
```

where “`fs`” is an instance of `org.apache.hadoop.fs.FileSystem` class in Hadoop.

- Pass the returned `OutputStream` in the first step to `nativeBooster.saveModel()`:

```
xgbClassificationModel.nativeBooster.saveModel(outputStream)
```

- Download file in other languages from HDFS and load with the pre-built (without the requirement of `libhdfs.so`) version of XGBoost. (The function “`download_from_hdfs`” is a helper function to be implemented by the user)

```
import xgboost as xgb
bst = xgb.Booster({'nthread': 4})
local_path = download_from_hdfs("hdfs_path")
bst.load_model(local_path)
```

Note: Consistency issue between XGBoost4J-Spark and other bindings

There is a consistency issue between XGBoost4J-Spark and other language bindings of XGBoost.

When users use Spark to load training/test data in LIBSVM format with the following code snippet:

```
spark.read.format("libsvm").load("trainingset_libsvm")
```

Spark assumes that the dataset is using 1-based indexing (feature indices starting with 1). However, when you do prediction with other bindings of XGBoost (e.g. Python API of XGBoost), XGBoost assumes that the dataset is using 0-based indexing (feature indices starting with 0) by default. It creates a pitfall for the users who train model with Spark but predict with the dataset in the same format in other bindings of XGBoost. The solution is to transform the dataset to 0-based indexing before you predict with, for example, Python API, or you append `?indexing_mode=1` to your file path when loading with DMatrix. For example in Python:

```
xgb.DMatrix('test.libsvm?indexing_mode=1')
```

Building a ML Pipeline with XGBoost4J-Spark

Basic ML Pipeline

Spark ML pipeline can combine multiple algorithms or functions into a single pipeline. It covers from feature extraction, transformation, selection to model training and prediction. XGBoost4j-Spark makes it feasible to embed XGBoost into such a pipeline seamlessly. The following example shows how to build such a pipeline consisting of Spark MLlib feature transformer and XGBoostClassifier estimator.

We still use `Iris` dataset and the `rawInput` DataFrame. First we need to split the dataset into training and test dataset.

```
val Array(training, test) = rawInput.randomSplit(Array(0.8, 0.2), 123)
```

The we build the ML pipeline which includes 4 stages:

- Assemble all features into a single vector column.
- From string label to indexed double label.
- Use XGBoostClassifier to train classification model.
- Convert indexed double label back to original string label.

We have shown the first three steps in the earlier sections, and the last step is finished with a new transformer `IndexToString`:

```
val labelConverter = new IndexToString()
  .setInputCol("prediction")
  .setOutputCol("realLabel")
  .setLabels(stringIndexer.labels)
```

We need to organize these steps as a Pipeline in Spark ML framework and evaluate the whole pipeline to get a PipelineModel:

```
import org.apache.spark.ml.feature._
import org.apache.spark.ml.Pipeline

val pipeline = new Pipeline()
    .setStages(Array(assembler, stringIndexer, booster, labelConverter))
val model = pipeline.fit(training)
```

After we get the PipelineModel, we can make prediction on the test dataset and evaluate the model accuracy.

```
import org.apache.spark.ml.evaluation.MulticlassClassificationEvaluator

val prediction = model.transform(test)
val evaluator = new MulticlassClassificationEvaluator()
val accuracy = evaluator.evaluate(prediction)
```

Pipeline with Hyper-parameter Tunning

The most critical operation to maximize the power of XGBoost is to select the optimal parameters for the model. Tuning parameters manually is a tedious and labor-consuming process. With the latest version of XGBoost4J-Spark, we can utilize the Spark model selecting tool to automate this process.

The following example shows the code snippet utilizing CrossValidation and MulticlassClassificationEvaluator to search the optimal combination of two XGBoost parameters, `max_depth` and `eta`. (See *XGBoost Parameters*.) The model producing the maximum accuracy defined by MulticlassClassificationEvaluator is selected and used to generate the prediction for the test set.

```
import org.apache.spark.ml.tuning._
import org.apache.spark.ml.PipelineModel
import ml.dmlc.xgboost4j.scala.spark.XGBoostClassificationModel

val paramGrid = new ParamGridBuilder()
    .addGrid(booster.maxDepth, Array(3, 8))
    .addGrid(booster.eta, Array(0.2, 0.6))
    .build()
val cv = new CrossValidator()
    .setEstimator(pipeline)
    .setEvaluator(evaluator)
    .setEstimatorParamMaps(paramGrid)
    .setNumFolds(3)

val cvModel = cv.fit(training)

val bestModel = cvModel.bestModel.asInstanceOf[PipelineModel].stages(2)
    .asInstanceOf[XGBoostClassificationModel]
bestModel.extractParamMap()
```

Run XGBoost4J-Spark in Production

XGBoost4J-Spark is one of the most important steps to bring XGBoost to production environment easier. In this section, we introduce three key features to run XGBoost4J-Spark in production.

Parallel/Distributed Training

The massive size of training dataset is one of the most significant characteristics in production environment. To ensure that training in XGBoost scales with the data size, XGBoost4J-Spark bridges the distributed/parallel processing framework of Spark and the parallel/distributed training mechanism of XGBoost.

In XGBoost4J-Spark, each XGBoost worker is wrapped by a Spark task and the training dataset in Spark's memory space is fed to XGBoost workers in a transparent approach to the user.

In the code snippet where we build XGBoostClassifier, we set parameter `num_workers` (or `numWorkers`). This parameter controls how many parallel workers we want to have when training a XGBoostClassificationModel.

Note: Regarding OpenMP optimization

By default, we allocate a core per each XGBoost worker. Therefore, the OpenMP optimization within each XGBoost worker does not take effect and the parallelization of training is achieved by running multiple workers (i.e. Spark tasks) at the same time.

If you do want OpenMP optimization, you have to

1. set `nthread` to a value larger than 1 when creating XGBoostClassifier/XGBoostRegressor
 2. set `spark.task.cpus` in Spark to the same value as `nthread`
-

Gang Scheduling

XGBoost uses [AllReduce](#) algorithm to synchronize the stats, e.g. histogram values, of each worker during training. Therefore XGBoost4J-Spark requires that all of `nthread * numWorkers` cores should be available before the training runs.

In the production environment where many users share the same cluster, it's hard to guarantee that your XGBoost4J-Spark application can get all requested resources for every run. By default, the communication layer in XGBoost will block the whole application when it requires more resources to be available. This process usually brings unnecessary resource waste as it keeps the ready resources and try to claim more. Additionally, this usually happens silently and does not bring the attention of users.

XGBoost4J-Spark allows the user to setup a timeout threshold for claiming resources from the cluster. If the application cannot get enough resources within this time period, the application would fail instead of wasting resources for hanging long. To enable this feature, you can set with XGBoostClassifier/XGBoostRegressor:

```
xgbClassifier.setTimeoutRequestWorkers(60000L)
```

or pass in `timeout_request_workers` in `xgbParamMap` when building XGBoostClassifier:

```
val xgbParam = Map("eta" -> 0.1f,
  "max_depth" -> 2,
  "objective" -> "multi:softprob",
  "num_class" -> 3,
  "num_round" -> 100,
```

(continues on next page)

(continued from previous page)

```

    "num_workers" -> 2,
    "timeout_request_workers" -> 60000L)
val xgbClassifier = new XGBoostClassifier(xgbParam).
    setFeaturesCol("features").
    setLabelCol("classIndex")

```

If XGBoost4J-Spark cannot get enough resources for running two XGBoost workers, the application would fail. Users can have external mechanism to monitor the status of application and get notified for such case.

Checkpoint During Training

Transient failures are also commonly seen in production environment. To simplify the design of XGBoost, we stop training if any of the distributed workers fail. However, if the training fails after having been through a long time, it would be a great waste of resources.

We support creating checkpoint during training to facilitate more efficient recovery from failure. To enable this feature, you can set how many iterations we build each checkpoint with `setCheckpointInterval` and the location of checkpoints with `setCheckpointPath`:

```

xgbClassifier.setCheckpointInterval(2)
xgbClassifier.setCheckpointPath("/checkpoint_path")

```

An equivalent way is to pass in parameters in XGBoostClassifier's constructor:

```

val xgbParam = Map("eta" -> 0.1f,
    "max_depth" -> 2,
    "objective" -> "multi:softprob",
    "num_class" -> 3,
    "num_round" -> 100,
    "num_workers" -> 2,
    "checkpoint_path" -> "/checkpoints_path",
    "checkpoint_interval" -> 2)
val xgbClassifier = new XGBoostClassifier(xgbParam).
    setFeaturesCol("features").
    setLabelCol("classIndex")

```

If the training failed during these 100 rounds, the next run of training would start by reading the latest checkpoint file in `/checkpoints_path` and start from the iteration when the checkpoint was built until to next failure or the specified 100 rounds.

XGBoost4J-Spark-GPU Tutorial (version 1.6.1+)

XGBoost4J-Spark-GPU is an open source library aiming to accelerate distributed XGBoost training on Apache Spark cluster from end to end with GPUs by leveraging the [RAPIDS Accelerator for Apache Spark](#) product.

This tutorial will show you how to use **XGBoost4J-Spark-GPU**.

- *Build an ML Application with XGBoost4J-Spark-GPU*
 - *Add XGBoost to Your Project*
 - *Data Preparation*

- * *Read Dataset with Spark's Built-In Reader*
- * *Transform Raw Iris Dataset*
- *Training*
- *Prediction*
- *Submit the application*

Build an ML Application with XGBoost4J-Spark-GPU

Add XGBoost to Your Project

Before we go into the tour of how to use XGBoost4J-Spark-GPU, you should first consult [Installation from Maven repository](#) in order to add XGBoost4J-Spark-GPU as a dependency for your project. We provide both stable releases and snapshots.

Data Preparation

In this section, we use the [Iris](#) dataset as an example to showcase how we use Apache Spark to transform a raw dataset and make it fit the data interface of XGBoost.

The Iris dataset is shipped in CSV format. Each instance contains 4 features, “sepal length”, “sepal width”, “petal length” and “petal width”. In addition, it contains the “class” column, which is essentially the label with three possible values: “Iris Setosa”, “Iris Versicolour” and “Iris Virginica”.

Read Dataset with Spark's Built-In Reader

```
import org.apache.spark.sql.SparkSession
import org.apache.spark.sql.types.{DoubleType, StringType, StructField, StructType}

val spark = SparkSession.builder().getOrCreate()

val labelName = "class"
val schema = new StructType(Array(
  StructField("sepal length", DoubleType, true),
  StructField("sepal width", DoubleType, true),
  StructField("petal length", DoubleType, true),
  StructField("petal width", DoubleType, true),
  StructField(labelName, StringType, true)))

val xgbInput = spark.read.option("header", "false")
  .schema(schema)
  .csv(dataPath)
```

In the first line, we create an instance of a `SparkSession` which is the entry point of any Spark application working with DataFrames. The `schema` variable defines the schema of the DataFrame wrapping Iris data. With this explicitly set schema, we can define the column names as well as their types; otherwise the column names would be the default ones derived by Spark, such as `_col0`, etc. Finally, we can use Spark's built-in CSV reader to load the Iris CSV file as a DataFrame named `xgbInput`.

Apache Spark also contains many built-in readers for other formats such as ORC, Parquet, Avro, JSON.

Transform Raw Iris Dataset

To make the Iris dataset recognizable to XGBoost, we need to encode the String-typed label, i.e. “class”, to the Double-typed label.

One way to convert the String-typed label to Double is to use Spark’s built-in feature transformer [StringIndexer](#). But this feature is not accelerated in RAPIDS Accelerator, which means it will fall back to CPU. Instead, we use an alternative way to achieve the same goal with the following code:

```
import org.apache.spark.sql.expressions.Window
import org.apache.spark.sql.functions._

val spec = Window.orderBy(labelName)
val Array(train, test) = xgbInput
  .withColumn("tmpClassName", dense_rank().over(spec) - 1)
  .drop(labelName)
  .withColumnRenamed("tmpClassName", labelName)
  .randomSplit(Array(0.7, 0.3), seed = 1)

train.show(5)
```

sepal length	sepal width	petal length	petal width	class
4.3	3.0	1.1	0.1	0
4.4	2.9	1.4	0.2	0
4.4	3.0	1.3	0.2	0
4.4	3.2	1.3	0.2	0
4.6	3.2	1.4	0.2	0

With window operations, we have mapped the string column of labels to label indices.

Training

The GPU version of XGBoost-Spark supports both regression and classification models. Although we use the Iris dataset in this tutorial to show how we use XGBoost/XGBoost4J-Spark-GPU to resolve a multi-classes classification problem, the usage in Regression is very similar to classification.

To train a XGBoost model for classification, we need to claim a XGBoostClassifier first:

```
import ml.dmlc.xgboost4j.scala.spark.XGBoostClassifier
val xgbParam = Map(
  "objective" -> "multi:softprob",
  "num_class" -> 3,
  "num_round" -> 100,
  "device" -> "cuda",
  "num_workers" -> 1)

val featuresNames = schema.fieldNames.filter(name => name != labelName)
```

(continues on next page)

(continued from previous page)

```
val xgbClassifier = new XGBoostClassifier(xgbParam)
    .setFeaturesCol(featuresNames)
    .setLabelCol(labelName)
```

The device parameter is for informing XGBoost that CUDA devices should be used instead of CPU. Unlike the single-node mode, GPUs are managed by spark instead of by XGBoost. Therefore, explicitly specified device ordinal like `cuda:1` is not support.

The available parameters for training a XGBoost model can be found in [here](#). Similar to the XGBoost4J-Spark package, in addition to the default set of parameters, XGBoost4J-Spark-GPU also supports the camel-case variant of these parameters to be consistent with Spark's MLlib naming convention.

Specifically, each parameter in [this page](#) has its equivalent form in XGBoost4J-Spark-GPU with camel case. For example, to set `max_depth` for each tree, you can pass parameter just like what we did in the above code snippet (as `max_depth` wrapped in a Map), or you can do it through setters in XGBoostClassifier:

```
val xgbClassifier = new XGBoostClassifier(xgbParam)
    .setFeaturesCol(featuresNames)
    .setLabelCol(labelName)
xgbClassifier.setMaxDepth(2)
```

Note: In contrast with XGBoost4j-Spark which accepts both a feature column with VectorUDT type and an array of feature column names, XGBoost4j-Spark-GPU only accepts an array of feature column names by `setFeaturesCol(value: Array[String])`.

After setting XGBoostClassifier parameters and feature/label columns, we can build a transformer, XGBoostClassificationModel by fitting XGBoostClassifier with the input DataFrame. This `fit` operation is essentially the training process and the generated model can then be used in other tasks like prediction.

```
val xgbClassificationModel = xgbClassifier.fit(train)
```

Prediction

When we get a model, either a XGBoostClassificationModel or a XGBoostRegressionModel, it takes a DataFrame as an input, reads the column containing feature vectors, predicts for each feature vector, and outputs a new DataFrame with the following columns by default:

- XGBoostClassificationModel will output margins (`rawPredictionCol`), probabilities(`probabilityCol`) and the eventual prediction labels (`predictionCol`) for each possible label.
- XGBoostRegressionModel will output prediction a label(`predictionCol`).

```
val xgbClassificationModel = xgbClassifier.fit(train)
val results = xgbClassificationModel.transform(test)
results.show()
```

With the above code snippet, we get a DataFrame as result, which contains the margin, probability for each class, and the prediction for each instance.

```
+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+
```

(continues on next page)

Chapter 1. Contents

Submit the application

Here's an example to submit an end-to-end XGBoost-4j-Spark-GPU Spark application to an Apache Spark Standalone cluster, assuming the application main class is Iris and the application jar is iris-1.0.0.jar

```
cudf_version=22.02.0
rapids_version=22.02.0
xgboost_version=1.6.1
main_class=Iris
app_jar=iris-1.0.0.jar

spark-submit \
  --master $master \
  --packages ai.rapids:cudf:${cudf_version},com.nvidia:rapids-4-spark_2.12:${rapids_
↪version},ml.dmlc:xgboost4j-gpu_2.12:${xgboost_version},ml.dmlc:xgboost4j-spark-gpu_2.
↪12:${xgboost_version} \
  --conf spark.executor.cores=12 \
  --conf spark.task.cpus=1 \
  --conf spark.executor.resource.gpu.amount=1 \
  --conf spark.task.resource.gpu.amount=0.08 \
  --conf spark.rapids.sql.csv.read.double.enabled=true \
  --conf spark.rapids.sql.hasNans=false \
  --conf spark.plugins=com.nvidia.spark.SQLPlugin \
  --class ${main_class} \
  ${app_jar}
```

- First, we need to specify the RAPIDS Accelerator, cudf, xgboost4j-gpu, xgboost4j-spark-gpu packages by --packages
- Second, RAPIDS Accelerator is a Spark plugin, so we need to configure it by specifying spark.plugins=com.nvidia.spark.SQLPlugin

For details about other RAPIDS Accelerator other configurations, please refer to the [configuration](#).

For RAPIDS Accelerator Frequently Asked Questions, please refer to the [frequently-asked-questions](#).

XGBoost4J Java API

XGBoost4J Scala API

XGBoost4J-Spark Scala API

XGBoost4J-Flink Scala API

Note: Please note that the flink interface is still under construction.

1.13 XGBoost.jl

See [XGBoost.jl Project page](#).

1.14 XGBoost C Package

XGBoost implements a set of C API designed for various bindings, we maintain its stability and the CMake/make build interface. See [C API Tutorial](#) for an introduction and `demo/c-api/` for related examples. Also one can generate doxygen document by providing `-DBUILD_C_DOC=ON` as parameter to CMake during build, or simply look at function comments in `include/xgboost/c_api.h`. The reference is exported to sphinx with the help of breathe, which doesn't contain links to examples but might be easier to read. For the original doxygen pages please visit:

- [C API documentation \(latest master branch\)](#)
- [C API documentation \(last stable release\)](#)

1.14.1 C API Reference

- *Library*
- *DMatrix*
 - *Streaming*
- *Booster*
 - *Prediction*
 - *Serialization*
- *Collective*

Library

group **Library**

These functions are used to obtain general information about XGBoost including version, build info and current global configuration.

Typedefs

typedef void ***DMatrixHandle**
handle to DMatrix

typedef void ***BoosterHandle**
handle to Booster

Functions

void **XGBoostVersion**(int *major, int *minor, int *patch)

Return the version of the XGBoost library being currently used.

The output variable is only written if it's not NULL.

Parameters

- **major** – Store the major version number
- **minor** – Store the minor version number
- **patch** – Store the patch (revision) number

int **XGBuildInfo**(char const **out)

Get compile information of shared library.

Parameters

out – string encoded JSON object containing build flags and dependency version.

Returns

0 for success, -1 for failure

const char ***XGBGetLastError**()

get string message of the last error

all function in this file will return 0 when success and -1 when an error occurred, XGBGetLastError can be called to retrieve the error

this function is thread safe and can be called by different thread

Returns

const char* error information

int **XGBRegisterLogCallback**(void (*callback)(const char*))

register callback function for LOG(INFO) messages — helpful messages that are not errors. Note: this function can be called by multiple threads. The callback function will run on the thread that registered it

Returns

0 for success, -1 for failure

int **XGBSetGlobalConfig**(char const *config)

Set global configuration (collection of parameters that apply globally). This function accepts the list of key-value pairs representing the global-scope parameters to be configured. The list of key-value pairs are passed in as a JSON string.

Parameters

config – a JSON string representing the list of key-value pairs. The JSON object shall be flat: no value can be a JSON object or an array.

Returns

0 for success, -1 for failure

int **XGBGetGlobalConfig**(char const **out_config)

Get current global configuration (collection of parameters that apply globally).

Parameters

out_config – pointer to received returned global configuration, represented as a JSON string.

Returns

0 for success, -1 for failure

DMatrix*group* **DMatrix**

DMatrix is the basic data storage for XGBoost used by all XGBoost algorithms including both training, prediction and explanation. There are a few variants of DMatrix including normal DMatrix, which is a CSR matrix, QuantileDMatrix, which is used by histogram-based tree methods for saving memory, and lastly the experimental external-memory-based DMatrix, which reads data in batches during training. For the last two variants, see the *Streaming* group.

Functions

int **XGDMatrixCreateFromFile**(const char *fname, int silent, *DMatrixHandle* *out)

load a data matrix

Deprecated:

since 2.0.0

See also:

XGDMatrixCreateFromURI()

Parameters

- **fname** – the name of the file
- **silent** – whether print messages during loading
- **out** – a loaded data matrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromURI**(char const *config, *DMatrixHandle* *out)

load a data matrix

- uri: The URI of the input file. The URI parameter format is required when loading text data. See *Text Input Format of DMatrix* for more info.
- silent (optional): Whether to print message during loading. Default to true.
- data_split_mode (optional): Whether to split by row or column. In distributed mode, the file is split accordingly; otherwise this is only an indicator on how the file was split beforehand. Default to row.

Parameters

- **out** – a loaded data matrix
- **config** – JSON encoded parameters for DMatrix construction. Accepted fields are:

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromCSREx**(const size_t *indptr, const unsigned *indices, const float *data, size_t nindptr, size_t nelelem, size_t num_col, *DMatrixHandle* *out)

create a matrix content from CSR format

Deprecated:

since 2.0.0

See also:

XGDMatrixCreateFromCSR()

int **XGDMatrixCreateFromCSR**(char const *indptr, char const *indices, char const *data, bst_ulong ncol, char const *config, *DMatrixHandle* *out)

Create a matrix from CSR matrix.

Parameters

- **indptr** – JSON encoded **array_interface** to row pointers in CSR.
- **indices** – JSON encoded **array_interface** to column indices in CSR.
- **data** – JSON encoded **array_interface** to values in CSR.
- **ncol** – Number of columns.
- **config** – JSON encoded configuration. Required values are:
 - missing: Which value to represent missing value.
 - nthread (optional): Number of threads used for initializing DMatrix.
- **out** – created dmatrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromDense**(char const *data, char const *config, *DMatrixHandle* *out)

Create a matrix from dense array.

Parameters

- **data** – JSON encoded **array_interface** to array values.
- **config** – JSON encoded configuration. Required values are:
 - missing: Which value to represent missing value.
 - nthread (optional): Number of threads used for initializing DMatrix.
- **out** – created dmatrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromCSC**(char const *indptr, char const *indices, char const *data, bst_ulong nrow, char const *config, *DMatrixHandle* *out)

Create a matrix from a CSC matrix.

Parameters

- **indptr** – JSON encoded **array_interface** to column pointers in CSC.
- **indices** – JSON encoded **array_interface** to row indices in CSC.

- **data** – JSON encoded **array_interface** to values in CSC.
- **nrow** – number of rows in the matrix.
- **config** – JSON encoded configuration. Supported values are:
 - **missing**: Which value to represent missing value.
 - **nthread** (optional): Number of threads used for initializing DMatrix.
- **out** – created dmatrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromCSCEx**(const size_t *col_ptr, const unsigned *indices, const float *data, size_t nindptr, size_t nelelem, size_t num_row, *DMatrixHandle* *out)

create a matrix content from CSC format

Deprecated:

since 2.0.0

See also:

XGDMatrixCreateFromCSC()

int **XGDMatrixCreateFromMat**(const float *data, bst_ulong nrow, bst_ulong ncol, float missing, *DMatrixHandle* *out)

create matrix content from dense matrix

Parameters

- **data** – pointer to the data space
- **nrow** – number of rows
- **ncol** – number columns
- **missing** – which value to represent missing value
- **out** – created dmatrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromMat_omp**(const float *data, bst_ulong nrow, bst_ulong ncol, float missing, *DMatrixHandle* *out, int nthread)

create matrix content from dense matrix

Parameters

- **data** – pointer to the data space
- **nrow** – number of rows
- **ncol** – number columns
- **missing** – which value to represent missing value
- **out** – created dmatrix
- **nthread** – number of threads (up to maximum cores available, if <=0 use all cores)

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromDT**(void **data, const char **feature_types, bst_ulong nrow, bst_ulong ncol, *DMatrixHandle* *out, int nthread)

create matrix content from python data table

Parameters

- **data** – pointer to pointer to column data
- **feature_types** – pointer to strings
- **nrow** – number of rows
- **ncol** – number columns
- **out** – created dmatrix
- **nthread** – number of threads (up to maximum cores available, if <=0 use all cores)

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromCudaColumnar**(char const *data, char const *config, *DMatrixHandle* *out)

Create DMatrix from CUDA columnar format. (cuDF)

Parameters

- **data** – Array of JSON encoded **cuda_array_interface** for each column.
- **config** – JSON encoded configuration. Required values are:
 - missing: Which value to represent missing value.
 - nthread (optional): Number of threads used for initializing DMatrix.
- **out** – created dmatrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromCudaArrayInterface**(char const *data, char const *config, *DMatrixHandle* *out)

Create DMatrix from CUDA array.

Parameters

- **data** – JSON encoded **cuda_array_interface** for array data.
- **config** – JSON encoded configuration. Required values are:
 - missing: Which value to represent missing value.
 - nthread (optional): Number of threads used for initializing DMatrix.
- **out** – created dmatrix

Returns

0 when success, -1 when failure happens

int **XGImportArrowRecordBatch**(*DataIterHandle* data_handle, void *ptr_array, void *ptr_schema)

int **XGDMatrixCreateFromArrowCallback**(*XGDMatrixCallbackNext* *next, char const *config, *DMatrixHandle* *out)

Construct DMatrix from arrow using callbacks. Arrow related C API is not stable and subject to change in the future.

Parameters

- **next** – Callback function for fetching arrow records.
- **config** – JSON encoded configuration. Required values are:
 - missing: Which value to represent missing value.
 - nbatch: Number of batches in arrow table.
 - nthread (optional): Number of threads used for initializing DMatrix.
- **out** – The created DMatrix.

Returns

0 when success, -1 when failure happens

int **XGDMatrixSliceDMatrix**(*DMatrixHandle* handle, const int *idxset, bst_ulong len, *DMatrixHandle* *out)

create a new dmatrix from sliced content of existing matrix

Parameters

- **handle** – instance of data matrix to be sliced
- **idxset** – index set
- **len** – length of index set
- **out** – a sliced new matrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixSliceDMatrixEx**(*DMatrixHandle* handle, const int *idxset, bst_ulong len, *DMatrixHandle* *out, int allow_groups)

create a new dmatrix from sliced content of existing matrix

Parameters

- **handle** – instance of data matrix to be sliced
- **idxset** – index set
- **len** – length of index set
- **out** – a sliced new matrix
- **allow_groups** – allow slicing of an array with groups

Returns

0 when success, -1 when failure happens

int **XGDMatrixFree**(*DMatrixHandle* handle)

free space in data matrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixSaveBinary**(*DMatrixHandle* handle, const char *fname, int silent)

load a data matrix into binary file

Parameters

- **handle** – a instance of data matrix
- **fname** – file name
- **silent** – print statistics when saving

Returns

0 when success, -1 when failure happens

int **XGDMatrixSetInfoFromInterface**(*DMatrixHandle* handle, char const *field, char const *c_interface_str)

Set content in array interface to a content in info.

Parameters

- **handle** – a instance of data matrix
- **field** – field name.
- **c_interface_str** – JSON string representation of array interface.

Returns

0 when success, -1 when failure happens

int **XGDMatrixSetFloatInfo**(*DMatrixHandle* handle, const char *field, const float *array, bst_ulong len)
 set float vector to a content in info

Parameters

- **handle** – a instance of data matrix
- **field** – field name, can be label, weight
- **array** – pointer to float vector
- **len** – length of array

Returns

0 when success, -1 when failure happens

int **XGDMatrixSetUIntInfo**(*DMatrixHandle* handle, const char *field, const unsigned *array, bst_ulong len)
 set uint32 vector to a content in info

Parameters

- **handle** – a instance of data matrix
- **field** – field name
- **array** – pointer to unsigned int vector
- **len** – length of array

Returns

0 when success, -1 when failure happens

int **XGDMatrixSetStrFeatureInfo**(*DMatrixHandle* handle, const char *field, const char **features, const bst_ulong size)

Set string encoded information of all features.

Accepted fields are:

- feature_name
- feature_type

```
char const* feat_names [] {"feat_0", "feat_1"};
XGDMatrixSetStrFeatureInfo(handle, "feature_name", feat_names, 2);

// i for integer, q for quantitative, c for categorical. Similarly "int" and
// "float"
// are also recognized.
char const* feat_types [] {"i", "q"};
XGDMatrixSetStrFeatureInfo(handle, "feature_type", feat_types, 2);
```

Parameters

- **handle** – An instance of data matrix
- **field** – Field name
- **features** – Pointer to array of strings.
- **size** – Size of features pointer (number of strings passed in).

Returns

0 when success, -1 when failure happens

int **XGDMatrixGetStrFeatureInfo**(*DMatrixHandle* handle, const char *field, bst_ulong *size, const char ***out_features)

Get string encoded information of all features.

Accepted fields are:

- feature_name
- feature_type

Caller is responsible for copying out the data, before next call to any API function of XGBoost.

```
char const **c_out_features = NULL;
bst_ulong out_size = 0;

// Assuming the feature names are already set by `XGDMatrixSetStrFeatureInfo`.
XGDMatrixGetStrFeatureInfo(handle, "feature_name", &out_size,
                           &c_out_features)

for (bst_ulong i = 0; i < out_size; ++i) {
    // Here we are simply printing the string. Copy it out if the feature name is
    // useful after printing.
    printf("feature %lu: %s\n", i, c_out_features[i]);
}
```

Parameters

- **handle** – An instance of data matrix
- **field** – Field name
- **size** – Size of output pointer features (number of strings returned).
- **out_features** – Address of a pointer to array of strings. Result is stored in thread local memory.

Returns

0 when success, -1 when failure happens

int **XGDMatrixSetDenseInfo**(*DMatrixHandle* handle, const char *field, void const *data, bst_ulong size, int type)

Set meta info from dense matrix. Valid field names are:

- label
- weight
- base_margin
- group
- label_lower_bound
- label_upper_bound
- feature_weights

Parameters

- **handle** – An instance of data matrix
- **field** – Field name
- **data** – Pointer to consecutive memory storing data.
- **size** – Size of the data, this is relative to size of type. (Meaning NOT number of bytes.)
- **type** – Indicator of data type. This is defined in `xgboost::DataType` enum class.
 - float = 1
 - double = 2
 - uint32_t = 3
 - uint64_t = 4

Returns

0 when success, -1 when failure happens

int **XGDMatrixSetGroup**(*DMatrixHandle* handle, const unsigned *group, bst_ulong len)
(deprecated) Use `XGDMatrixSetUIntInfo` instead. Set group of the training matrix

Parameters

- **handle** – a instance of data matrix
- **group** – pointer to group size
- **len** – length of array

Returns

0 when success, -1 when failure happens

int **XGDMatrixGetFloatInfo**(const *DMatrixHandle* handle, const char *field, bst_ulong *out_len, const float **out_dptr)

get float info vector from matrix.

Parameters

- **handle** – a instance of data matrix
- **field** – field name
- **out_len** – used to set result length
- **out_dptr** – pointer to the result

Returns

0 when success, -1 when failure happens

int **XGDMatrixGetUIntInfo**(const *DMatrixHandle* handle, const char *field, bst_ulong *out_len, const unsigned **out_dptr)

get uint32 info vector from matrix

Parameters

- **handle** – a instance of data matrix
- **field** – field name
- **out_len** – The length of the field.
- **out_dptr** – pointer to the result

Returns

0 when success, -1 when failure happens

int **XGDMatrixNumRow**(*DMatrixHandle* handle, bst_ulong *out)

get number of rows.

Parameters

- **handle** – the handle to the DMatrix
- **out** – The address to hold number of rows.

Returns

0 when success, -1 when failure happens

int **XGDMatrixNumCol**(*DMatrixHandle* handle, bst_ulong *out)

get number of columns

Parameters

- **handle** – the handle to the DMatrix
- **out** – The output of number of columns

Returns

0 when success, -1 when failure happens

int **XGDMatrixNumNonMissing**(*DMatrixHandle* handle, bst_ulong *out)

Get number of valid values from DMatrix.

Parameters

- **handle** – the handle to the DMatrix
- **out** – The output of number of non-missing values

Returns

0 when success, -1 when failure happens


```
int XGDMatrixGetDataAsCSR(DMatrixHandle const handle, char const *config, bst_ulong *out_indptr,
                        unsigned *out_indices, float *out_data)
```

Get the predictors from DMatrix as CSR matrix for testing. If this is a quantized DMatrix, quantized values are returned instead.

Unlike most of XGBoost C functions, caller of `XGDMatrixGetDataAsCSR` is required to allocate the memory for return buffer instead of using thread local memory from XGBoost. This is to avoid allocating a huge memory buffer that can not be freed until exiting the thread.

Since

1.7.0

Parameters

- **handle** – the handle to the DMatrix
- **config** – JSON configuration string. At the moment it should be an empty document, preserved for future use.
- **out_indptr** – indptr of output CSR matrix.
- **out_indices** – Column index of output CSR matrix.
- **out_data** – Data value of CSR matrix.

Returns

0 when success, -1 when failure happens

```
int XGDMatrixGetQuantileCut(DMatrixHandle const handle, char const *config, char const **out_indptr,
                          char const **out_data)
```

Export the quantile cuts used for training histogram-based models like `hist` and `approx`. Useful for model compression.

Since

2.0.0

Parameters

- **handle** – the handle to the DMatrix
- **config** – JSON configuration string. At the moment it should be an empty document, preserved for future use.
- **out_indptr** – indptr of output CSC matrix represented by a JSON encoded `__(cuda_)array_interface__`.
- **out_data** – Data value of CSC matrix represented by a JSON encoded `__(cuda_)array_interface__`.

Streaming

group Streaming

Quantile DMatrix and external memory DMatrix can be created from batches of data.

There are 2 sets of data callbacks for DMatrix. The first one is currently exclusively used by JVM packages. It uses *XGBoostBatchCSR* to accept batches for CSR formatted input, and concatenate them into 1 final big CSR. The related functions are:

- *XGBCallbackSetData*
- *XGBCallbackDataAlterNext*
- *XGDMatrixCreateFromDataIter*

Another set is used by external data iterator. It accept foreign data iterators as callbacks. There are 2 different scenarios where users might want to pass in callbacks instead of raw data. First it's the Quantile DMatrix used by hist and GPU Hist. For this case, the data is first compressed by quantile sketching then merged. This is particular useful for distributed setting as it eliminates 2 copies of data. 1 by a concat from external library to make the data into a blob for normal DMatrix initialization, another by the internal CSR copy of DMatrix. The second use case is external memory support where users can pass a custom data iterator into XGBoost for loading data in batches. There are short notes on each of the use cases in respected DMatrix factory function.

Related functions are:

Factory functions

- *XGDMatrixCreateFromCallback* for external memory
- *XGQuantileDMatrixCreateFromCallback* for quantile DMatrix

Proxy that callers can use to pass data to XGBoost

- *XGProxyDMatrixCreate*
- *XGDMatrixCallbackNext*
- *DataIterResetCallback*
- *XGProxyDMatrixSetDataCudaArrayInterface*
- *XGProxyDMatrixSetDataCudaColumnar*
- *XGProxyDMatrixSetDataDense*
- *XGProxyDMatrixSetDataCSR*
- ... (data setters)

Typedefs

typedef void ***DataIterHandle**

handle to a external data iterator

typedef void ***DataHolderHandle**

handle to a internal data holder.

typedef int **XGBCallbackSetData**(*DataHolderHandle* handle, *XGBoostBatchCSR* batch)

Callback to set the data to handle,.

Param handle

The handle to the callback.

Param batch

The data content to be set.

typedef int **XGBCallbackDataIterNext**(*DataIterHandle* data_handle, *XGBCallbackSetData* *set_function, *DataHolderHandle* set_function_handle)

The data reading callback function. The iterator will be able to give subset of batch in the data.

If there is data, the function will call set_function to set the data.

Param data_handle

The handle to the callback.

Param set_function

The batch returned by the iterator

Param set_function_handle

The handle to be passed to set function.

Return

0 if we are reaching the end and batch is not returned.

typedef int **XGDMatrixCallbackNext**(*DataIterHandle* iter)

Callback function prototype for getting next batch of data.

Param iter

A handler to the user defined iterator.

Return

0 when success, -1 when failure happens

typedef void **DataIterResetCallback**(*DataIterHandle* handle)

Callback function prototype for resetting external iterator.

Functions

int **XGDMatrixCreateFromDataIter**(*DataIterHandle* data_handle, *XGBCallbackDataIterNext* *callback, const char *cache_info, *DMatrixHandle* *out)

Create a DMatrix from a data iterator.

Parameters

- **data_handle** – The handle to the data.
- **callback** – The callback to get the data.

- **cache_info** – Additional information about cache file, can be null.
- **out** – The created DMatrix

Returns

0 when success, -1 when failure happens.

int **XGProxyDMatrixCreate**(*DMatrixHandle* *out)

Create a DMatrix proxy for setting data, can be free by XGDMatrixFree.

Second set of callback functions, used by constructing Quantile DMatrix or external memory DMatrix using custom iterator.

Parameters

out – The created Device Quantile DMatrix

Returns

0 when success, -1 when failure happens

int **XGDMatrixCreateFromCallback**(*DataIterHandle* iter, *DMatrixHandle* proxy, *DataIterResetCallback* *reset, *XGDMatrixCallbackNext* *next, char const *config, *DMatrixHandle* *out)

Create an external memory DMatrix with data iterator.

Short note for how to use second set of callback for external memory data support:

- Step 0: Define a data iterator with 2 methods **reset**, and **next**.
- Step 1: Create a DMatrix proxy by *XGProxyDMatrixCreate* and hold the handle.
- Step 2: Pass the iterator handle, proxy handle and 2 methods into *XGDMatrixCreateFromCallback*, along with other parameters encoded as a JSON object.
- Step 3: Call appropriate data setters in **next** functions.

Parameters

- **iter** – A handle to external data iterator.
- **proxy** – A DMatrix proxy handle created by *XGProxyDMatrixCreate*.
- **reset** – Callback function resetting the iterator state.
- **next** – Callback function yielding the next batch of data.
- **config** – JSON encoded parameters for DMatrix construction. Accepted fields are:
 - **missing**: Which value to represent missing value
 - **cache_prefix**: The path of cache file, caller must initialize all the directories in this path.
 - **nthread** (optional): Number of threads used for initializing DMatrix.
- **out** – [**out**] The created external memory DMatrix

Returns

0 when success, -1 when failure happens

int **XGQuantileDMatrixCreateFromCallback**(*DataIterHandle* iter, *DMatrixHandle* proxy, *DataIterHandle* ref, *DataIterResetCallback* *reset, *XGDMatrixCallbackNext* *next, char const *config, *DMatrixHandle* *out)

Create a Quantile DMatrix with data iterator.

Short note for how to use the second set of callback for (GPU)Hist tree method:

- Step 0: Define a data iterator with 2 methods `reset`, and `next`.
- Step 1: Create a DMatrix proxy by *XGProxyDMatrixCreate* and hold the handle.
- Step 2: Pass the iterator handle, proxy handle and 2 methods into `XGQuantileDMatrixCreateFromCallback`.
- Step 3: Call appropriate data setters in `next` functions.

See `test_iterative_dmatrix.cu` or Python interface for examples.

Parameters

- **iter** – A handle to external data iterator.
- **proxy** – A DMatrix proxy handle created by *XGProxyDMatrixCreate*.
- **ref** – Reference DMatrix for providing quantile information.
- **reset** – Callback function resetting the iterator state.
- **next** – Callback function yielding the next batch of data.
- **config** – JSON encoded parameters for DMatrix construction. Accepted fields are:
 - `missing`: Which value to represent missing value
 - `nthread` (optional): Number of threads used for initializing DMatrix.
 - `max_bin` (optional): Maximum number of bins for building histogram.
- **out** – The created Device Quantile DMatrix

Returns

0 when success, -1 when failure happens

```
int XGDeviceQuantileDMatrixCreateFromCallback(DMatrixHandle iter, DMatrixHandle proxy,
                                             DMatrixResetCallback *reset,
                                             XGDMatrixCallbackNext *next, float missing, int
                                             nthread, int max_bin, DMatrixHandle *out)
```

Create a Device Quantile DMatrix with data iterator.

Deprecated:

since 1.7.0

See also:

XGQuantileDMatrixCreateFromCallback()

```
int XGProxyDMatrixSetDataCudaArrayInterface(DMatrixHandle handle, const char *c_interface_str)
```

Set data on a DMatrix proxy.

Parameters

- **handle** – A DMatrix proxy created by *XGProxyDMatrixCreate*
- **c_interface_str** – Null terminated JSON document string representation of CUDA array interface.

Returns

0 when success, -1 when failure happens

int **XGProxyDMatrixSetDataCudaColumnar**(*DMatrixHandle* handle, const char *c_interface_str)

Set data on a DMatrix proxy.

Parameters

- **handle** – A DMatrix proxy created by *XGProxyDMatrixCreate*
- **c_interface_str** – Null terminated JSON document string representation of CUDA array interface, with an array of columns.

Returns

0 when success, -1 when failure happens

int **XGProxyDMatrixSetDataDense**(*DMatrixHandle* handle, char const *c_interface_str)

Set data on a DMatrix proxy.

Parameters

- **handle** – A DMatrix proxy created by *XGProxyDMatrixCreate*
- **c_interface_str** – Null terminated JSON document string representation of array interface.

Returns

0 when success, -1 when failure happens

int **XGProxyDMatrixSetDataCSR**(*DMatrixHandle* handle, char const *indptr, char const *indices, char const *data, bst_ulong ncol)

Set data on a DMatrix proxy.

Parameters

- **handle** – A DMatrix proxy created by *XGProxyDMatrixCreate*
- **indptr** – JSON encoded **array_interface** to row pointer in CSR.
- **indices** – JSON encoded **array_interface** to column indices in CSR.
- **data** – JSON encoded **array_interface** to values in CSR..
- **ncol** – The number of columns of input CSR matrix.

Returns

0 when success, -1 when failure happens

struct **XGBoostBatchCSR**

#include <c_api.h> Mini batch used in XGBoost Data Iteration.

Booster

group **Booster**

The **Booster** class is the gradient-boosted model for XGBoost.

Functions

int **XGBoosterCreate**(const *DMatrixHandle* dmats[], bst_ulong len, *BoosterHandle* *out)

create xgboost learner

Parameters

- **dmats** – matrices that are set to be cached
- **len** – length of dmats
- **out** – handle to the result booster

Returns

0 when success, -1 when failure happens

int **XGBoosterFree**(*BoosterHandle* handle)

free obj in handle

Parameters

handle – handle to be freed

Returns

0 when success, -1 when failure happens

int **XGBoosterSlice**(*BoosterHandle* handle, int begin_layer, int end_layer, int step, *BoosterHandle* *out)

Slice a model using boosting index. The slice m:n indicates taking all trees that were fit during the boosting rounds m, (m+1), (m+2), ..., (n-1).

Parameters

- **handle** – Booster to be sliced.
- **begin_layer** – start of the slice
- **end_layer** – end of the slice; end_layer=0 is equivalent to end_layer=num_boost_round
- **step** – step size of the slice
- **out** – Sliced booster.

Returns

0 when success, -1 when failure happens, -2 when index is out of bound.

int **XGBoosterBoostedRounds**(*BoosterHandle* handle, int *out)

Get number of boosted rounds from gradient booster. When process_type is update, this number might drop due to removed tree.

Parameters

- **handle** – Handle to booster.
- **out** – Pointer to output integer.

Returns

0 when success, -1 when failure happens

int **XGBoosterSetParam**(*BoosterHandle* handle, const char *name, const char *value)

set parameters

Parameters

- **handle** – handle
- **name** – parameter name

- **value** – value of parameter

Returns

0 when success, -1 when failure happens

int **XGBoosterGetNumFeature**(*BoosterHandle* handle, bst_ulong *out)

get number of features

Parameters

- **handle** – Handle to booster.
- **out** – number of features

Returns

0 when success, -1 when failure happens

int **XGBoosterUpdateOneIter**(*BoosterHandle* handle, int iter, *DMatrixHandle* dtrain)

update the model in one round using dtrain

Parameters

- **handle** – handle
- **iter** – current iteration rounds
- **dtrain** – training data

Returns

0 when success, -1 when failure happens

int **XGBoosterBoostOneIter**(*BoosterHandle* handle, *DMatrixHandle* dtrain, float *grad, float *hess, bst_ulong len)

update the model, by directly specify gradient and second order gradient, this can be used to replace UpdateOneIter, to support customized loss function

Parameters

- **handle** – handle
- **dtrain** – training data
- **grad** – gradient statistics
- **hess** – second order gradient statistics
- **len** – length of grad/hess array

Returns

0 when success, -1 when failure happens

int **XGBoosterEvalOneIter**(*BoosterHandle* handle, int iter, *DMatrixHandle* dmats[], const char *evnames[], bst_ulong len, const char **out_result)

get evaluation statistics for xgboost

Parameters

- **handle** – handle
- **iter** – current iteration rounds
- **dmats** – pointers to data to be evaluated
- **evnames** – pointers to names of each data
- **len** – length of dmats

- **out_result** – the string containing evaluation statistics

Returns

0 when success, -1 when failure happens

int **XGBoosterDumpModel**(*BoosterHandle* handle, const char *fmap, int with_stats, bst_ulong *out_len, const char ***out_dump_array)

dump model, return array of strings representing model dump

Parameters

- **handle** – handle
- **fmap** – name to fmap can be empty string
- **with_stats** – whether to dump with statistics
- **out_len** – length of output array
- **out_dump_array** – pointer to hold representing dump of each model

Returns

0 when success, -1 when failure happens

int **XGBoosterDumpModelEx**(*BoosterHandle* handle, const char *fmap, int with_stats, const char *format, bst_ulong *out_len, const char ***out_dump_array)

dump model, return array of strings representing model dump

Parameters

- **handle** – handle
- **fmap** – name to fmap can be empty string
- **with_stats** – whether to dump with statistics
- **format** – the format to dump the model in
- **out_len** – length of output array
- **out_dump_array** – pointer to hold representing dump of each model

Returns

0 when success, -1 when failure happens

int **XGBoosterDumpModelWithFeatures**(*BoosterHandle* handle, int fnum, const char **fname, const char **ftype, int with_stats, bst_ulong *out_len, const char ***out_models)

dump model, return array of strings representing model dump

Parameters

- **handle** – handle
- **fnum** – number of features
- **fname** – names of features
- **ftype** – types of features
- **with_stats** – whether to dump with statistics
- **out_len** – length of output array
- **out_models** – pointer to hold representing dump of each model

Returns

0 when success, -1 when failure happens

int **XGBoosterDumpModelExWithFeatures**(*BoosterHandle* handle, int fnum, const char **fname, const char **ftype, int with_stats, const char *format, bst_ulong *out_len, const char ***out_models)

dump model, return array of strings representing model dump

Parameters

- **handle** – handle
- **fnum** – number of features
- **fname** – names of features
- **ftype** – types of features
- **with_stats** – whether to dump with statistics
- **format** – the format to dump the model in
- **out_len** – length of output array
- **out_models** – pointer to hold representing dump of each model

Returns

0 when success, -1 when failure happens

int **XGBoosterGetAttr**(*BoosterHandle* handle, const char *key, const char **out, int *success)

Get string attribute from Booster.

Parameters

- **handle** – handle
- **key** – The key of the attribute.
- **out** – The result attribute, can be NULL if the attribute do not exist.
- **success** – Whether the result is contained in out.

Returns

0 when success, -1 when failure happens

int **XGBoosterSetAttr**(*BoosterHandle* handle, const char *key, const char *value)

Set or delete string attribute.

Parameters

- **handle** – handle
- **key** – The key of the attribute.
- **value** – The value to be saved. If nullptr, the attribute would be deleted.

Returns

0 when success, -1 when failure happens

int **XGBoosterGetAttrNames**(*BoosterHandle* handle, bst_ulong *out_len, const char ***out)

Get the names of all attribute from Booster.

Parameters

- **handle** – handle
- **out_len** – the argument to hold the output length

- **out** – pointer to hold the output attribute stings

Returns

0 when success, -1 when failure happens

int **XGBoosterSetStrFeatureInfo**(*BoosterHandle* handle, const char *field, const char **features, const bst_ulong size)

Set string encoded feature info in Booster, similar to the feature info in DMatrix.

Accepted fields are:

- feature_name
- feature_type

Parameters

- **handle** – An instance of Booster
- **field** – Field name
- **features** – Pointer to array of strings.
- **size** – Size of features pointer (number of strings passed in).

Returns

0 when success, -1 when failure happens

int **XGBoosterGetStrFeatureInfo**(*BoosterHandle* handle, const char *field, bst_ulong *len, const char ***out_features)

Get string encoded feature info from Booster, similar to feature info in DMatrix.

Accepted fields are:

- feature_name
- feature_type

Caller is responsible for copying out the data, before next call to any API function of XGBoost.

Parameters

- **handle** – An instance of Booster
- **field** – Field name
- **len** – Size of output pointer features (number of strings returned).
- **out_features** – Address of a pointer to array of strings. Result is stored in thread local memory.

Returns

0 when success, -1 when failure happens

int **XGBoosterFeatureScore**(*BoosterHandle* handle, const char *config, bst_ulong *out_n_features, char const ***out_features, bst_ulong *out_dim, bst_ulong const **out_shape, float const **out_scores)

Calculate feature scores for tree models. When used on linear model, only the **weight** importance type is defined, and output scores is a row major matrix with shape [n_features, n_classes] for multi-class model. For tree model, out_n_feature is always equal to out_n_scores and has multiple definitions of importance type.

Parameters

- **handle** – An instance of Booster
- **config** – Parameters for computing scores encoded as JSON. Accepted JSON keys are:
 - **importance_type**: A JSON string with following possible values:
 - * **'weight'**: the number of times a feature is used to split the data across all trees.
 - * **'gain'**: the average gain across all splits the feature is used in.
 - * **'cover'**: the average coverage across all splits the feature is used in.
 - * **'total_gain'**: the total gain across all splits the feature is used in.
 - * **'total_cover'**: the total coverage across all splits the feature is used in.
 - **feature_map**: An optional JSON string with URI or path to the feature map file.
 - **feature_names**: An optional JSON array with string names for each feature.
- **out_n_features** – Length of output feature names.
- **out_features** – An array of string as feature names, ordered the same as output scores.
- **out_dim** – Dimension of output feature scores.
- **out_shape** – Shape of output feature scores with length of **out_dim**.
- **out_scores** – An array of floating point as feature scores with shape of **out_shape**.

Returns

0 when success, -1 when failure happens

Prediction

group Prediction

These functions are used for running prediction and explanation algorithms.

Functions

int **XGBoosterPredict**(*BoosterHandle* handle, *DMatrixHandle* dmat, int option_mask, unsigned ntree_limit, int training, bst_ulong *out_len, const float **out_result)

make prediction based on dmat (deprecated, use *XGBoosterPredictFromDMatrix* instead)

Deprecated:

See also:

XGBoosterPredictFromDMatrix()

Parameters

- **handle** – handle
- **dmat** – data matrix
- **option_mask** – bit-mask of options taken in prediction, possible values 0:normal prediction 1:output margin instead of transformed value 2:output leaf index of trees instead of leaf value, note leaf index is unique per tree 4:output feature contributions to individual predictions

- **ntree_limit** – limit number of trees used for prediction, this is only valid for boosted trees when the parameter is set to 0, we will use all the trees
- **training** – Whether the prediction function is used as part of a training loop. Prediction can be run in 2 scenarios:
 - a. Given data matrix X, obtain prediction y_pred from the model.
 - b. Obtain the prediction for computing gradients. For example, DART booster performs dropout during training, and the prediction result will be different from the one obtained by normal inference step due to dropped trees. Set training=false for the first scenario. Set training=true for the second scenario. The second scenario applies when you are defining a custom objective function.
- **out_len** – used to store length of returning result
- **out_result** – used to set a pointer to array

Returns

0 when success, -1 when failure happens

```
int XGBoosterPredictFromDMatrix(BoosterHandle handle, DMatrixHandle dmat, char const *config,
                               bst_ulong const **out_shape, bst_ulong *out_dim, float const
                               **out_result)
```

Make prediction from DMatrix, replacing *XGBoosterPredict*.

“type”: [0, 6]

- 0: normal prediction
 - 1: output margin
 - 2: predict contribution
 - 3: predict approximated contribution
 - 4: predict feature interaction
 - 5: predict approximated feature interaction
 - 6: predict leaf “training”: bool Whether the prediction function is used as part of a training loop.
- Not used for inplace prediction.**

Prediction can be run in 2 scenarios:

- a. Given data matrix X, obtain prediction y_pred from the model.
- b. Obtain the prediction for computing gradients. For example, DART booster performs dropout during training, and the prediction result will be different from the one obtained by normal inference step due to dropped trees. Set training=false for the first scenario. Set training=true for the second scenario. The second scenario applies when you are defining a custom objective function. “iteration_begin”: int Beginning iteration of prediction. “iteration_end”: int End iteration of prediction. Set to 0 this will become the size of tree model (all the trees). “strict_shape”: bool Whether should we reshape the output with stricter rules. If set to true, normal/margin/contrib/interaction predict will output consistent shape disregarding the use of multi-class model, and leaf prediction will output 4-dim array representing: (n_samples, n_iterations, n_classes, n_trees_in_forest)

Example JSON input for running a normal prediction with strict output shape, 2 dim for softmax , 1 dim for others.

```
{
  "type": 0,
  "training": false,
  "iteration_begin": 0,
  "iteration_end": 0,
  "strict_shape": true
}
```

See also:

XGBoosterPredictFromDense *XGBoosterPredictFromCSR* *XGBoosterPredictFromCudaArray* *XGBoosterPredictFromCudaColumnar*

Parameters

- **handle** – Booster handle
- **dmat** – DMatrix handle
- **config** – String encoded predict configuration in JSON format, with following available fields in the JSON object:
- **out_shape** – Shape of output prediction (copy before use).
- **out_dim** – Dimension of output prediction.
- **out_result** – Buffer storing prediction value (copy before use).

Returns

0 when success, -1 when failure happens

```
int XGBoosterPredictFromDense(BoosterHandle handle, char const *values, char const *config,
                             DMatrixHandle m, bst_ulong const **out_shape, bst_ulong *out_dim,
                             const float **out_result)
```

Inplace prediction from CPU dense matrix.

Note: If the booster is configured to run on a CUDA device, XGBoost falls back to run prediction with DMatrix with a performance warning.

Parameters

- **handle** – Booster handle.
- **values** – JSON encoded **array_interface** to values.
- **config** – See *XGBoosterPredictFromDMatrix* for more info. Additional fields for inplace prediction are:
 - "missing": float
- **m** – An optional (NULL if not available) proxy DMatrix instance storing meta info.
- **out_shape** – See *XGBoosterPredictFromDMatrix* for more info.
- **out_dim** – See *XGBoosterPredictFromDMatrix* for more info.
- **out_result** – See *XGBoosterPredictFromDMatrix* for more info.

Returns

0 when success, -1 when failure happens

```
int XGBoosterPredictFromCSR(BoosterHandle handle, char const *indptr, char const *indices, char const
                           *values, bst_ulong ncol, char const *config, DMatrixHandle m, bst_ulong
                           const **out_shape, bst_ulong *out_dim, const float **out_result)
```

Inplace prediction from CPU CSR matrix.

Note: If the booster is configured to run on a CUDA device, XGBoost falls back to run prediction with DMatrix with a performance warning.

Parameters

- **handle** – Booster handle.
- **indptr** – JSON encoded **array_interface** to row pointer in CSR.
- **indices** – JSON encoded **array_interface** to column indices in CSR.
- **values** – JSON encoded **array_interface** to values in CSR..
- **ncol** – Number of features in data.
- **config** – See *XGBoosterPredictFromDMatrix* for more info. Additional fields for inplace prediction are:
 - "missing": float
- **m** – An optional (NULL if not available) proxy DMatrix instance storing meta info.
- **out_shape** – See *XGBoosterPredictFromDMatrix* for more info.
- **out_dim** – See *XGBoosterPredictFromDMatrix* for more info.
- **out_result** – See *XGBoosterPredictFromDMatrix* for more info.

Returns

0 when success, -1 when failure happens

```
int XGBoosterPredictFromCudaArray(BoosterHandle handle, char const *values, char const *config,
                                  DMatrixHandle m, bst_ulong const **out_shape, bst_ulong
                                  *out_dim, const float **out_result)
```

Inplace prediction from CUDA Dense matrix (cupy in Python).

Note: If the booster is configured to run on a CPU, XGBoost falls back to run prediction with DMatrix with a performance warning.

Parameters

- **handle** – Booster handle
- **values** – JSON encoded **cuda_array_interface** to values.
- **config** – See *XGBoosterPredictFromDMatrix* for more info. Additional fields for inplace prediction are:
 - "missing": float
- **m** – An optional (NULL if not available) proxy DMatrix instance storing meta info.

- **out_shape** – See *XGBoosterPredictFromDMatrix* for more info.
- **out_dim** – See *XGBoosterPredictFromDMatrix* for more info.
- **out_result** – See *XGBoosterPredictFromDMatrix* for more info.

Returns

0 when success, -1 when failure happens

```
int XGBoosterPredictFromCudaColumnar(BoosterHandle handle, char const *values, char const *config,
                                     DMatrixHandle m, bst_ulong const **out_shape, bst_ulong
                                     *out_dim, const float **out_result)
```

Inplace prediction from CUDA dense dataframe (cuDF in Python).

Note: If the booster is configured to run on a CPU, XGBoost falls back to run prediction with DMatrix with a performance warning.

Parameters

- **handle** – Booster handle
- **values** – List of **cuda_array_interface** for all columns encoded in JSON list.
- **config** – See *XGBoosterPredictFromDMatrix* for more info. Additional fields for inplace prediction are:
 - "missing": float
- **m** – An optional (NULL if not available) proxy DMatrix instance storing meta info.
- **out_shape** – See *XGBoosterPredictFromDMatrix* for more info.
- **out_dim** – See *XGBoosterPredictFromDMatrix* for more info.
- **out_result** – See *XGBoosterPredictFromDMatrix* for more info.

Returns

0 when success, -1 when failure happens

Serialization

group **Serialization**

There are multiple ways to serialize a Booster object depending on the use case.

Short note for serialization APIs. There are 3 different sets of serialization API.

- Functions with the term “Model” handles saving/loading XGBoost model like trees or linear weights. Striping out parameters configuration like training algorithms or CUDA device ID. These functions are designed to let users reuse the trained model for different tasks, examples are prediction, training continuation or model interpretation.
- Functions with the term “Config” handles save/loading configuration. It helps user to study the internal of XGBoost. Also user can use the load method for specifying parameters in a structured way. These functions are introduced in 1.0.0, and are not yet stable.

- Functions with the term “Serialization” are combined of above two. They are used in situations like check-pointing, or continuing training task in distributed environment. In these cases the task must be carried out without any user intervention.

Functions

int **XGBoosterLoadModel**(*BoosterHandle* handle, const char *fname)

Load model from existing file.

Parameters

- **handle** – handle
- **fname** – File URI or file name. The string must be UTF-8 encoded.

Returns

0 when success, -1 when failure happens

int **XGBoosterSaveModel**(*BoosterHandle* handle, const char *fname)

Save model into existing file.

Parameters

- **handle** – handle
- **fname** – File URI or file name. The string must be UTF-8 encoded.

Returns

0 when success, -1 when failure happens

int **XGBoosterLoadModelFromBuffer**(*BoosterHandle* handle, const void *buf, bst_ulong len)

load model from in memory buffer

Parameters

- **handle** – handle
- **buf** – pointer to the buffer
- **len** – the length of the buffer

Returns

0 when success, -1 when failure happens

int **XGBoosterSaveModelToBuffer**(*BoosterHandle* handle, char const *config, bst_ulong *out_len, char const **out_dptr)

Save model into raw bytes, return header of the array. User must copy the result out, before next xgboost call.

“format”: str

- json: Output booster will be encoded as JSON.
- ubj: Output booster will be encoded as Universal binary JSON.
- deprecated: Output booster will be encoded as old custom binary format. Do not use this format except for compatibility reasons.

Parameters

- **handle** – handle

- **config** – JSON encoded string storing parameters for the function. Following keys are expected in the JSON document:
- **out_len** – The argument to hold the output length
- **out_dptr** – The argument to hold the output data pointer

Returns

0 when success, -1 when failure happens

int **XGBoosterGetModelRaw**(*BoosterHandle* handle, bst_ulong *out_len, const char **out_dptr)

Save booster to a buffer with in binary format.

Deprecated:

since 1.6.0

See also:

XGBoosterSaveModelToBuffer()

int **XGBoosterSerializeToBuffer**(*BoosterHandle* handle, bst_ulong *out_len, const char **out_dptr)

Memory snapshot based serialization method. Saves everything states into buffer.

Parameters

- **handle** – handle
- **out_len** – the argument to hold the output length
- **out_dptr** – the argument to hold the output data pointer

Returns

0 when success, -1 when failure happens

int **XGBoosterUnserializeFromBuffer**(*BoosterHandle* handle, const void *buf, bst_ulong len)

Memory snapshot based serialization method. Loads the buffer returned from *XGBoosterSerializeToBuffer*.

Parameters

- **handle** – handle
- **buf** – pointer to the buffer
- **len** – the length of the buffer

Returns

0 when success, -1 when failure happens

int **XGBoosterLoadRabitCheckpoint**(*BoosterHandle* handle, int *version)

Initialize the booster from rabbit checkpoint. This is used in distributed training API.

Parameters

- **handle** – handle
- **version** – The output version of the model.

Returns

0 when success, -1 when failure happens

int **XGBoosterSaveRabitCheckpoint**(*BoosterHandle* handle)

Save the current checkpoint to rabbit.

Parameters

handle – handle

Returns

0 when success, -1 when failure happens

int **XGBoosterSaveJsonConfig**(*BoosterHandle* handle, bst_ulong *out_len, char const **out_str)

Save XGBoost's internal configuration into a JSON document. Currently the support is experimental, function signature may change in the future without notice.

Parameters

- **handle** – handle to Booster object.
- **out_len** – length of output string
- **out_str** – A valid pointer to array of characters. The characters array is allocated and managed by XGBoost, while pointer to that array needs to be managed by caller.

Returns

0 when success, -1 when failure happens

int **XGBoosterLoadJsonConfig**(*BoosterHandle* handle, char const *config)

Load XGBoost's internal configuration from a JSON document. Currently the support is experimental, function signature may change in the future without notice.

Parameters

- **handle** – handle to Booster object.
- **config** – string representation of a JSON document.

Returns

0 when success, -1 when failure happens

Collective

group Collective

Experimental support for exposing internal communicator in XGBoost.

Functions

int **XGCommunicatorInit**(char const *config)

Initialize the collective communicator.

Currently the communicator API is experimental, function signatures may change in the future without notice.

Call this once before using anything.

The additional configuration is not required. Usually the communicator will detect settings from environment variables.

Parameters

config – JSON encoded configuration. Accepted JSON keys are:

- `xgboost_communicator`: The type of the communicator. Can be set as an environment variable.
 - `rabit`: Use Rabit. This is the default if the type is unspecified.
 - `mpi`: Use MPI.
 - `federated`: Use the gRPC interface for Federated Learning. Only applicable to the Rabit communicator (these are case-sensitive):
- `rabit_tracker_uri`: Hostname of the tracker.
- `rabit_tracker_port`: Port number of the tracker.
- `rabit_task_id`: ID of the current task, can be used to obtain deterministic rank assignment.
- `rabit_world_size`: Total number of workers.
- `rabit_hadoop_mode`: Enable Hadoop support.
- `rabit_tree_reduce_minsize`: Minimal size for tree reduce.
- `rabit_reduce_ring_mincount`: Minimal count to perform ring reduce.
- `rabit_reduce_buffer`: Size of the reduce buffer.
- `rabit_bootstrap_cache`: Size of the bootstrap cache.
- `rabit_debug`: Enable debugging.
- `rabit_timeout`: Enable timeout.
- `rabit_timeout_sec`: Timeout in seconds.
- `rabit_enable_tcp_no_delay`: Enable TCP no delay on Unix platforms. Only applicable to the Rabit communicator (these are case-sensitive, and can be set as environment variables):
- `DMLC_TRACKER_URI`: Hostname of the tracker.
- `DMLC_TRACKER_PORT`: Port number of the tracker.
- `DMLC_TASK_ID`: ID of the current task, can be used to obtain deterministic rank assignment.
- `DMLC_ROLE`: Role of the current task, “worker” or “server”.
- `DMLC_NUM_ATTEMPT`: Number of attempts after task failure.
- `DMLC_WORKER_CONNECT_RETRY`: Number of retries to connect to the tracker. Only applicable to the Federated communicator (use upper case for environment variables, use lower case for runtime configuration):
- `federated_server_address`: Address of the federated server.
- `federated_world_size`: Number of federated workers.
- `federated_rank`: Rank of the current worker.
- `federated_server_cert`: Server certificate file path. Only needed for the SSL mode.
- `federated_client_key`: Client key file path. Only needed for the SSL mode.
- `federated_client_cert`: Client certificate file path. Only needed for the SSL mode.

Returns

0 for success, -1 for failure.

int **XGCommunicatorFinalize**(void)

Finalize the collective communicator.

Call this function after you finished all jobs.

Returns

0 for success, -1 for failure.

int **XGCommunicatorGetRank**(void)

Get rank of current process.

Returns

Rank of the worker.

int **XGCommunicatorGetWorldSize**(void)

Get total number of processes.

Returns

Total world size.

int **XGCommunicatorIsDistributed**(void)

Get if the communicator is distributed.

Returns

True if the communicator is distributed.

int **XGCommunicatorPrint**(char const *message)

Print the message to the communicator.

This function can be used to communicate the information of the progress to the user who monitors the communicator.

Parameters

message – The message to be printed.

Returns

0 for success, -1 for failure.

int **XGCommunicatorGetProcessorName**(const char **name_str)

Get the name of the processor.

Parameters

name_str – Pointer to received returned processor name.

Returns

0 for success, -1 for failure.

int **XGCommunicatorBroadcast**(void *send_receive_buffer, size_t size, int root)

Broadcast a memory region to all others from root. This function is NOT thread-safe.

Example:

```
int a = 1;
Broadcast(&a, sizeof(a), root);
```

Parameters

- **send_receive_buffer** – Pointer to the send or receive buffer.
- **size** – Size of the data.
- **root** – The process rank to broadcast from.

Returns

0 for success, -1 for failure.

int **XGCommunicatorAllreduce**(void *send_receive_buffer, size_t count, int data_type, int op)

Perform in-place allreduce. This function is NOT thread-safe.

Example Usage: the following code gives sum of the result

```
vector<int> data(10);  
...  
Allreduce(&data[0], data.size(), DataType:kInt32, Op::kSum);  
...
```

Parameters

- **send_receive_buffer** – Buffer for both sending and receiving data.
- **count** – Number of elements to be reduced.
- **data_type** – Enumeration of data type, see `xgboost::collective::DataType` in `communicator.h`.
- **op** – Enumeration of operation type, see `xgboost::collective::Operation` in `communicator.h`.

Returns

0 for success, -1 for failure.

1.15 XGBoost C++ API

Starting from 1.0 release, CMake will generate installation rules to export all C++ headers. But the c++ interface is much closer to the internal of XGBoost than other language bindings. As a result it's changing quite often and we don't maintain its stability. Along with the plugin system (see `plugin/example` in XGBoost's source tree), users can utilize some existing c++ headers for gaining more access to the internal of XGBoost.

- [C++ interface documentation \(latest master branch\)](#)
- [C++ interface documentation \(last stable release\)](#)

1.16 XGBoost Command Line version

See [XGBoost Command Line walkthrough](#).

1.17 Contribute to XGBoost

XGBoost has been developed by community members. Everyone is welcome to contribute. We value all forms of contributions, including, but not limited to:

- Code reviews for pull requests
- Documentation and usage examples
- Community participation in forums and issues

- Code readability and developer guide
 - We welcome contributions that add code comments to improve readability.
 - We also welcome contributions to docs to explain the design choices of the XGBoost internals.
- Test cases to make the codebase more robust.
- Tutorials, blog posts, talks that promote the project.

Here are guidelines for contributing to various aspect of the XGBoost project:

1.17.1 XGBoost Community Guideline

XGBoost adopts the Apache style model and governs by merit. We believe that it is important to create an inclusive community where everyone can use, contribute to, and influence the direction of the project. See [CONTRIBUTORS.md](#) for the current list of contributors.

General Development Process

Everyone in the community is welcomed to send patches, documents, and propose new directions to the project. The key guideline here is to enable everyone in the community to get involved and participate the decision and development. When major changes are proposed, an RFC should be sent to allow discussion by the community. We encourage public discussion, archivable channels such as issues and discuss forum, so that everyone in the community can participate and review the process later.

Code reviews are one of the key ways to ensure the quality of the code. High-quality code reviews prevent technical debt for long-term and are crucial to the success of the project. A pull request needs to be reviewed before it gets merged. A committer who has the expertise of the corresponding area would moderate the pull request and then merge the code when it is ready. The corresponding committer could request multiple reviewers who are familiar with the area of the code. We encourage contributors to request code reviews themselves and help review each other's code – remember everyone is volunteering their time to the community, high-quality code review itself costs as much as the actual code contribution, you could get your code quickly reviewed if you do others the same favor.

The community should strive to reach a consensus on technical decisions through discussion. We expect committers and PMCs to moderate technical discussions in a diplomatic way, and provide suggestions with clear technical reasoning when necessary.

Committers

Committers are individuals who are granted the write access to the project. A committer is usually responsible for a certain area or several areas of the code where they oversee the code review process. The area of contribution can take all forms, including code contributions and code reviews, documents, education, and outreach. Committers are essential for a high quality and healthy project. The community actively look for new committers from contributors. Here is a list of useful traits that help the community to recognize potential committers:

- Sustained contribution to the project, demonstrated by discussion over RFCs, code reviews and proposals of new features, and other development activities. Being familiar with, and being able to take ownership on one or several areas of the project.
- Quality of contributions: High-quality, readable code contributions indicated by pull requests that can be merged without a substantial code review. History of creating clean, maintainable code and including good test cases. Informative code reviews to help other contributors that adhere to a good standard.
- Community involvement: active participation in the discussion forum, promote the projects via tutorials, talks and outreach. We encourage committers to collaborate broadly, e.g. do code reviews and discuss designs with community members that they do not interact physically.

The Project Management Committee(PMC) consists of a group of active committers that moderate the discussion, manage the project release, and proposes new committer/PMC members. Potential candidates are usually proposed via an internal discussion among PMCs, followed by a consensus approval, i.e. least 3 +1 votes, and no vetoes. Any veto must be accompanied by reasoning. PMCs should serve the community by upholding the community practices and guidelines in order to make XGBoost a better community for everyone. PMCs should strive to only nominate new candidates outside of their own organization.

The PMC is in charge of the project's **continuous integration (CI)** and testing infrastructure. Currently, we host our own Jenkins server at <https://xgboost-ci.net>. The PMC shall appoint committer(s) to manage the CI infrastructure. The PMC may accept 3rd-party donations and sponsorships that would defray the cost of the CI infrastructure. See [Donations](#).

Reviewers

Reviewers are individuals who actively contributed to the project and are willing to participate in the code review of new contributions. We identify reviewers from active contributors. The committers should explicitly solicit reviews from reviewers. High-quality code reviews prevent technical debt for the long-term and are crucial to the success of the project. A pull request to the project has to be reviewed by at least one reviewer in order to be merged.

1.17.2 Donations

Motivation

DMLC/XGBoost has grown from a research project incubated in academia to one of the most widely used gradient boosting framework in production environment. On one side, with the growth of volume and variety of data in the production environment, users are putting accordingly growing expectation to XGBoost in terms of more functions, scalability and robustness. On the other side, as an open source project which develops in a fast pace, XGBoost has been receiving contributions from many individuals and organizations around the world. Given the high expectation from the users and the increasing channels of contribution to the project, delivering the high quality software presents a challenge to the project maintainers.

A robust and efficient **continuous integration (CI)** infrastructure is one of the most critical solutions to address the above challenge. A CI service will monitor an open-source repository and run a suite of integration tests for every incoming contribution. This way, the CI ensures that every proposed change in the codebase is compatible with existing functionalities. Furthermore, XGBoost can enable more thorough tests with a powerful CI infrastructure to cover cases which are closer to the production environment.

There are several CI services available free to open source projects, such as Travis CI and AppVeyor. The XGBoost project already utilizes GitHub Actions. However, the XGBoost project has needs that these free services do not adequately address. In particular, the limited usage quota of resources such as CPU and memory leaves XGBoost developers unable to bring “too-intensive” tests. In addition, they do not offer test machines with GPUs for testing XGBoost-GPU code base which has been attracting more and more interest across many organizations. Consequently, the XGBoost project uses a cloud-hosted test farm. We use **BuildKite** to organize CI pipelines.

The cloud-hosted test farm has recurring operating expenses. It utilizes a leading cloud provider (AWS) to accommodate variable workload. BuildKite launches worker machines on AWS on demand, to run the test suite on incoming contributions. To save cost, the worker machines are terminated when they are no longer needed.

To help defray the hosting cost, the XGBoost project seeks donations from third parties.

Donations and Sponsorships

Donors may choose to make one-time donations or recurring donations on monthly or yearly basis. Donors who commit to the Sponsor tier will have their logo displayed on the front page of the XGBoost project.

Fiscal host: Open Source Collective 501(c)(6)

The Project Management Committee (PMC) of the XGBoost project appointed [Open Source Collective](#) as their **fiscal host**. The platform is a 501(c)(6) registered entity and will manage the funds on the behalf of the PMC so that PMC members will not have to manage the funds directly. The platform currently hosts several well-known JavaScript frameworks such as Babel, Vue, and Webpack.

All expenses incurred for hosting CI will be submitted to the fiscal host with receipts. Only the expenses in the following categories will be approved for reimbursement:

- Cloud expenses for the cloud test farm (<https://buildkite.com/xgboost>)
- Cost of domain <https://xgboost-ci.net>
- Monthly cost of using BuildKite
- Hosting cost of the User Forum (<https://discuss.xgboost.ai>)

Administration of cloud CI infrastructure

The PMC shall appoint committer(s) to administer the cloud CI infrastructure on their behalf. The current administrators are as follows:

- Primary administrator: [Hyunsu Cho](#)
- Secondary administrator: [Jiaming Yuan](#)

The administrators shall make good-faith effort to keep the CI expenses under control. The expenses shall not exceed the available funds. The administrators should post regular updates on CI expenses.

1.17.3 Coding Guideline

Contents

- *C++ Coding Guideline*
- *Python Coding Guideline*
- *R Coding Guideline*
 - *Code Style*
 - *Rmarkdown Vignettes*
 - *R package versioning*
 - *Registering native routines in R*
 - *Generating the Package and Running Tests*
- *Running Formatting Checks Locally*
 - *Lint*

- *Clang-tidy*
- *Guide for handling user input data*

C++ Coding Guideline

- Follow [Google style for C++](#), with two exceptions:
 - Each line of text may contain up to 100 characters.
 - The use of C++ exceptions is allowed.
- Use C++17 features such as smart pointers, braced initializers, lambda functions, and `std::thread`.
- Use Doxygen to document all the interface code.
- We have some comments around symbols imported by headers, some of those are hinted by [include-what-you-use](#). It's not required.
- We use clang-tidy and clang-format. You can check their configuration in the root directory of the XGBoost source tree.
- We have a series of automatic checks to ensure that all of our codebase complies with the Google style. Before submitting your pull request, you are encouraged to run the style checks on your machine. See [R Coding Guideline](#).

Python Coding Guideline

- Follow [PEP 8: Style Guide for Python Code](#). We use Pylint to automatically enforce PEP 8 style across our Python codebase. Before submitting your pull request, you are encouraged to run Pylint on your machine. See [R Coding Guideline](#).
- Docstrings should be in [NumPy docstring format](#).

R Coding Guideline

Code Style

- We follow Google's C++ Style guide for C++ code.
 - This is mainly to be consistent with the rest of the project.
 - Another reason is we will be able to check style automatically with a linter.
- When needed, you can disable the linter warning of certain line with `// NOLINT(*)` comments.
- We use [roxygen](#) for documenting the R package.

Rmarkdown Vignettes

Rmarkdown vignettes are placed in `R-package/vignettes`. These Rmarkdown files are not compiled. We host the compiled version on `doc/R-package`.

The following steps are followed to add a new Rmarkdown vignettes:

- Add the original rmarkdown to `R-package/vignettes`.
- Modify `doc/R-package/Makefile` to add the markdown files to be build.
- Clone the `dmlc/web-data` repo to folder `doc`.
- Now type the following command on `doc/R-package`:

```
make the-markdown-to-make.md
```

- This will generate the markdown, as well as the figures in `doc/web-data/xgboost/knitr`.
- Modify the `doc/R-package/index.md` to point to the generated markdown.
- Add the generated figure to the `dmlc/web-data` repo.
 - If you already cloned the repo to `doc`, this means `git add`
- Create PR for both the markdown and `dmlc/web-data`.
- You can also build the document locally by typing the following command at the `doc` directory:

```
make html
```

The reason we do this is to avoid exploded repo size due to generated images.

R package versioning

See *XGBoost Release Policy*.

Registering native routines in R

According to [R extension manual](#), it is good practice to register native routines and to disable symbol search. When any changes or additions are made to the C++ interface of the R package, please make corresponding changes in `src/init.c` as well.

Generating the Package and Running Tests

The source layout of XGBoost is a bit unusual to normal R packages as XGBoost is primarily written in C++ with multiple language bindings in mind. As a result, some special cares need to be taken to generate a standard R tarball. Most of the tests are being run on CI, and as a result, the best way to see how things work is by looking at the CI configuration files (GitHub action, at the time of writing). There are helper scripts in `tests/ci_build` and `R-package/tests/helper_scripts` for running various checks including linter and making the standard tarball.

Running Formatting Checks Locally

Once you submit a pull request to [dmlc/xgboost](#), we perform two automatic checks to enforce coding style conventions. To expedite the code review process, you are encouraged to run the checks locally on your machine prior to submitting your pull request.

Linters

We use [pylint](#) and [cpplint](#) to enforce style convention and find potential errors. Linting is especially useful for Python, as we can catch many errors that would have otherwise occurred at run-time.

To run this check locally, run the following command from the top level source tree:

```
cd /path/to/xgboost/  
make lint
```

This command requires the Python packages `pylint` and `cpplint`.

Clang-tidy

[Clang-tidy](#) is an advance linter for C++ code, made by the LLVM team. We use it to conform our C++ codebase to modern C++ practices and conventions.

To run this check locally, run the following command from the top level source tree:

```
cd /path/to/xgboost/  
python3 tests/ci_build/tidy.py
```

Also, the script accepts two optional integer arguments, namely `--cpp` and `--cuda`. By default they are both set to 1, meaning that both C++ and CUDA code will be checked. If the CUDA toolkit is not installed on your machine, you'll encounter an error. To exclude CUDA source from linting, use:

```
cd /path/to/xgboost/  
python3 tests/ci_build/tidy.py --cuda=0
```

Similarly, if you want to exclude C++ source from linting:

```
cd /path/to/xgboost/  
python3 tests/ci_build/tidy.py --cpp=0
```

Guide for handling user input data

This is an in-comprehensive guide for handling user input data. XGBoost has wide verity of native supported data structures, mostly come from higher level language bindings. The inputs ranges from basic contiguous 1 dimension memory buffer to more sophisticated data structures like columnar data with validity mask. Raw input data can be used in 2 places, firstly it's the construction of various `DMatrix`, secondly it's the in-place prediction. For plain memory buffer, there's not much to discuss since it's just a pointer with a size. But for general n-dimension array and columnar data, there are many subtleties. XGBoost has 3 different data structures for handling optionally masked arrays (tensors), for consuming user inputs `ArrayInterface` should be chosen. There are many existing functions that accept only plain pointer due to legacy reasons (XGBoost started as a much simpler library and didn't care about memory usage that much back then). The `ArrayInterface` is a in memory representation of `__array_interface__` protocol defined by numpy or the `__cuda_array_interface__` defined by numba. Following is a check list of things to have in mind when accepting related user inputs:

- [] Is it strided? (identified by the `strides` field)
- [] If it's a vector, is it row vector or column vector? (Identified by both `shape` and `strides`).
- [] Is the data type supported? Half type and 128 integer types should be converted before going into XGBoost.
- [] Does it have higher than 1 dimension? (identified by `shape` field)
- [] Are some of dimensions trivial? (`shape[dim] <= 1`)
- [] Does it have mask? (identified by `mask` field)
- [] Can the mask be broadcasted? (unsupported at the moment)
- [] Is it on CUDA memory? (identified by `data` field, and optionally `stream`)

Most of the checks are handled by the `ArrayInterface` during construction, except for the data type issue since it doesn't know how to cast such pointers with C builtin types. But for safety reason one should still try to write related tests for the all items. The data type issue should be taken care of in language binding for each of the specific data input. For single-chunk columnar format, it's just a masked array for each column so it should be treated uniformly as normal array. For input predictor `X`, we have adapters for each type of input. Some are composition of the others. For instance, CSR matrix has 3 potentially strided arrays for `indptr`, `indices` and `values`. No assumption should be made to these components (all the check boxes should be considered). Slicing row of CSR matrix should calculate the offset of each field based on respective strides.

For meta info like labels, which is growing both in size and complexity, we accept only masked array at the moment (no specialized adapter). One should be careful about the input data shape. For base margin it can be 2 dim or higher if we have multiple targets in the future. The getters in `DMatrix` returns only 1 dimension flatten vectors at the moment, which can be improved in the future when it's needed.

1.17.4 Notes on packaging XGBoost's Python package

Contents

- *How to build binary wheels and source distributions*
 - *Building sdist*
 - *Building binary wheels*

How to build binary wheels and source distributions

Wheels and source distributions (sdist for short) are the two main mechanisms for packaging and distributing Python packages.

- A **source distribution** (sdist) is a tarball (`.tar.gz` extension) that contains the source code.
- A **wheel** is a ZIP-compressed archive (with `.whl` extension) representing a *built* distribution. Unlike an sdist, a wheel can contain compiled components. The compiled components are compiled prior to distribution, making it more convenient for end-users to install a wheel. Wheels containing compiled components are referred to as **binary wheels**.

See [Python Packaging User Guide](#) to learn more about how Python packages in general are packaged and distributed.

For the remainder of this document, we will focus on packaging and distributing XGBoost.

Building sdists

In the case of XGBoost, an sdist contains both the Python code as well as the C++ code, so that the core part of XGBoost can be compiled into the shared library `libxgboost.so`¹.

You can obtain an sdist as follows:

```
$ python -m build --sdist .
```

(You'll need to install the build package first: `pip install build` or `conda install python-build`.)

Running `pip install` with an sdist will launch CMake and a C++ compiler to compile the bundled C++ code into `libxgboost.so`:

```
$ pip install -v xgboost-2.0.0.tar.gz # Add -v to show build progress
```

Building binary wheels

You can also build a wheel as follows:

```
$ pip wheel --no-deps -v .
```

Notably, the resulting wheel contains a copy of the shared library `libxgboost.so`¹. The wheel is a **binary wheel**, since it contains a compiled binary.

Running `pip install` with the binary wheel will extract the content of the wheel into the current Python environment. Since the wheel already contains a pre-built copy of `libxgboost.so`, it does not have to be built at the time of install. So `pip install` with the binary wheel completes quickly:

```
$ pip install xgboost-2.0.0-py3-none-linux_x86_64.whl # Completes quickly
```

1.17.5 Adding and running tests

A high-quality suite of tests is crucial in ensuring correctness and robustness of the codebase. Here, we provide instructions how to run unit tests, and also how to add a new one.

Contents

- *Adding a new unit test*
 - *Python package: `pytest`*
 - *C++: `Google Test`*
 - *JVM packages: `JUnit` / `scalatest`*
 - *R package: `testthat`*
- *Running Unit Tests Locally*
 - *R package*
 - *JVM packages*
 - *Python package: `pytest`*

¹ The name of the shared library file will differ depending on the operating system in use. See *Building the Shared Library*.

- *C++: Google Test*
- *Sanitizers: Detect memory errors and data races*
 - *How to build XGBoost with sanitizers*
 - *How to use sanitizers with CUDA support*
 - *Other sanitizer runtime options*

Adding a new unit test

Python package: pytest

Add your test under the directory `tests/python/` or `tests/python-gpu/` (if you are testing GPU code). Refer to the [PyTest tutorial](#) to learn how to write tests for Python code.

You may try running your test by following instructions in [this section](#).

C++: Google Test

Add your test under the directory `tests/cpp/`. Refer to [this excellent tutorial](#) on using Google Test.

You may try running your test by following instructions in [this section](#). Note. Google Test version 1.8.1 or later is required.

JVM packages: JUnit / scalatest

The JVM packages for XGBoost (XGBoost4J / XGBoost4J-Spark) use the [Maven Standard Directory Layout](#). Specifically, the tests for the JVM packages are located in the following locations:

- `jvm-packages/xgboost4j/src/test/`
- `jvm-packages/xgboost4j-spark/src/test/`

To write a test for Java code, see [JUnit 5 tutorial](#). To write a test for Scala, see [Scalatest tutorial](#).

You may try running your test by following instructions in [this section](#).

R package: testthat

Add your test under the directory `R-package/tests/testthat`. Refer to [this excellent tutorial](#) on testthat.

You may try running your test by following instructions in [this section](#).

Running Unit Tests Locally

R package

Run

```
make Rcheck
```

at the root of the project directory.

JVM packages

As part of the building process, tests are run:

```
mvn package
```

Python package: pytest

To run Python unit tests, first install `pytest` package:

```
pip3 install pytest
```

Then compile XGBoost according to instructions in *Building the Shared Library*. Finally, invoke `pytest` at the project root directory:

```
# Tell Python where to find XGBoost module
export PYTHONPATH=./python-package
pytest -v -s --fulltrace tests/python
```

In addition, to test CUDA code, run:

```
# Tell Python where to find XGBoost module
export PYTHONPATH=./python-package
pytest -v -s --fulltrace tests/python-gpu
```

(For this step, you should have compiled XGBoost with CUDA enabled.)

C++: Google Test

To build and run C++ unit tests enable tests while running CMake:

```
mkdir build
cd build
cmake -DGOOGLE_TEST=ON -DUSE_DMLC_GTEST=ON ..
make
make test
```

To enable tests for CUDA code, add `-DUSE_CUDA=ON` and `-DUSE_NCCL=ON` (CUDA toolkit required):


```
mkdir build
cd build
cmake -DGOOGLE_TEST=ON -DUSE_DMLC_GTEST=ON -DUSE_CUDA=ON -DUSE_NCCL=ON ..
make
make test
```

One can also run all unit test using ctest tool which provides higher flexibility. For example:

```
ctest --verbose
```

Sanitizers: Detect memory errors and data races

By default, sanitizers are bundled in GCC and Clang/LLVM. One can enable sanitizers with GCC ≥ 4.8 or LLVM ≥ 3.1 . But some distributions might package sanitizers separately. Here is a list of supported sanitizers with corresponding library names:

- Address sanitizer: libasan
- Undefined sanitizer: libubsan
- Leak sanitizer: liblsan
- Thread sanitizer: libtsan

Memory sanitizer is exclusive to LLVM, hence not supported in XGBoost. With latest compilers like gcc-9, when sanitizer flags are specified, the compiler driver should be able to link the runtime libraries automatically.

How to build XGBoost with sanitizers

One can build XGBoost with sanitizer support by specifying `-DUSE_SANITIZER=ON`. By default, address sanitizer and leak sanitizer are used when you turn the `USE_SANITIZER` flag on. You can always change the default by providing a semicolon separated list of sanitizers to `ENABLED_SANITIZERS`. Note that thread sanitizer is not compatible with the other two sanitizers.

```
cmake -DUSE_SANITIZER=ON -DENABLED_SANITIZERS="address;leak" /path/to/xgboost
```

By default, CMake will search regular system paths for sanitizers, you can also supply a specified `SANITIZER_PATH`.

```
cmake -DUSE_SANITIZER=ON -DENABLED_SANITIZERS="address;leak" \
-DSANITIZER_PATH=/path/to/sanitizers /path/to/xgboost
```

How to use sanitizers with CUDA support

Running XGBoost on CUDA with address sanitizer (asan) will raise memory error. To use asan with CUDA correctly, you need to configure asan via `ASAN_OPTIONS` environment variable:

```
ASAN_OPTIONS=protect_shadow_gap=0 ${BUILD_DIR}/testxgboost
```

Other sanitizer runtime options

By default undefined sanitizer doesn't print out the backtrace. You can enable it by exporting environment variable:

```
UBSAN_OPTIONS=print_stacktrace=1 ${BUILD_DIR}/testxgboost
```

For details, please consult [official documentation](#) for sanitizers.

1.17.6 Documentation and Examples

Contents

- *Documentation*
 - *Build the Python Docs using pip and Conda*
- *Examples*

Documentation

- Python and C documentation is built using [Sphinx](#).
- Each document is written in [reStructuredText](#).
- The documentation is the `doc/` directory.
- You can build it locally using `make html` command.

```
make html
```

Run `make help` to learn about the other commands.

The online document is hosted by [Read the Docs](#) where the imported project is managed by [Hyunsu Cho](#) and [Jiaming Yuan](#).

Build the Python Docs using pip and Conda

1. Create a conda environment.

```
conda create -n xgboost-docs --yes python=3.10
```

Note: Python 3.10 is required by [xgboost_ray](#) package.

2. Activate the environment

```
conda activate xgboost-docs
```

3. Install required packages (in the current environment) using `pip` command.

```
pip install -r requirements.txt
```

Note: It is currently not possible to install the required packages using conda due to xgboost_ray being unavailable in conda channels.

```
conda install --file requirements.txt --yes -c conda-forge
```

4. (optional) Install `graphviz`

```
conda install graphviz --yes
```

5. Eventually, build the docs.

```
make html
```

You should see the following messages in the console:

```
$ make html
sphinx-build -b html -d _build/doctrees . _build/html
Running Sphinx v6.2.1
...
The HTML pages are in _build/html.

Build finished. The HTML pages are in _build/html.
```

Examples

- Use cases and examples are in `demo` directory.
- We are super excited to hear about your story. If you have blog posts, tutorials, or code solutions using XGBoost, please tell us, and we will add a link in the example pages.

1.17.7 Git Workflow Howtos

Contents

- *How to resolve conflict with master*
- *How to combine multiple commits into one*
- *What is the consequence of force push*

How to resolve conflict with master

- First rebase to most recent master

```
# The first two steps can be skipped after you do it once.
git remote add upstream https://github.com/dmlc/xgboost
git fetch upstream
git rebase upstream/master
```

- The git may show some conflicts it cannot merge, say `conflicted.py`.

- Manually modify the file to resolve the conflict.
- After you resolved the conflict, mark it as resolved by

```
git add conflicted.py
```

- Then you can continue rebase by

```
git rebase --continue
```

- Finally push to your fork, you may need to force push here.

```
git push --force
```

How to combine multiple commits into one

Sometimes we want to combine multiple commits, especially when later commits are only fixes to previous ones, to create a PR with set of meaningful commits. You can do it by following steps.

- Before doing so, configure the default editor of git if you haven't done so before.

```
git config core.editor the-editor-you-like
```

- Assume we want to merge last 3 commits, type the following commands

```
git rebase -i HEAD~3
```

- It will pop up an text editor. Set the first commit as `pick`, and change later ones to `squash`.
- After you saved the file, it will pop up another text editor to ask you modify the combined commit message.
- Push the changes to your fork, you need to force push.

```
git push --force
```

What is the consequence of force push

The previous two tips requires force push, this is because we altered the path of the commits. It is fine to force push to your own fork, as long as the commits changed are only yours.

1.17.8 XGBoost Release Policy

Versioning Policy

Starting from XGBoost 1.0.0, each XGBoost release will be versioned as [MAJOR].[FEATURE].[MAINTENANCE]

- **MAJOR:** We guarantee the API compatibility across releases with the same major version number. We expect to have a 1+ years development period for a new MAJOR release version.
- **FEATURE:** We ship new features, improvements and bug fixes through feature releases. The cycle length of a feature is decided by the size of feature roadmap. The roadmap is decided right after the previous release.
- **MAINTENANCE:** Maintenance version only contains bug fixes. This type of release only occurs when we found significant correctness and/or performance bugs and barrier for users to upgrade to a new version of XGBoost smoothly.

Making a Release

1. Create an issue for the release, noting the estimated date and expected features or major fixes, pin that issue.
2. Create a release branch if this is a major release. Bump release version. There's a helper script `tests/ci_build/change_version.py`.
3. Commit the change, create a PR on GitHub on release branch. Port the bumped version to default branch, optionally with the postfix `SNAPSHOT`.
4. Create a tag on release branch, either on GitHub or locally.
5. Make a release on GitHub tag page, which might be done with previous step if the tag is created on GitHub.
6. Submit pip, CRAN, and Maven packages.

There are helper scripts for automating the process in `xgboost/dev/`.

- The pip package is maintained by [Hyunsu Cho](#) and [Jiaming Yuan](#).
- The CRAN package is maintained by [Tong He](#) and [Jiaming Yuan](#).
- The Maven package is maintained by [Nan Zhu](#) and [Hyunsu Cho](#).

R CRAN Package

Before submitting a release, one should test the package on [R-hub](#) and [win-builder](#) first. Please note that the R-hub Windows instance doesn't have the exact same environment as the one hosted on win-builder.

According to the [CRAN policy](#):

If running a package uses multiple threads/cores it must never use more than two simultaneously: the check farm is a shared resource and will typically be running many checks simultaneously.

We need to check the number of CPUs used in examples. Export `_R_CHECK_EXAMPLE_TIMING_CPU_TO_ELAPSED_THRESHOLD_=2`. 5 before running R CMD check `--as-cran [1]` and make sure the machine you are using has enough CPU cores to reveal any potential policy violation.

References

[1] <https://stat.ethz.ch/pipermail/r-package-devel/2022q4/008610.html>

1.17.9 Automated testing in XGBoost project

This document collects tips for using the Continuous Integration (CI) service of the XGBoost project.

Contents

- *GitHub Actions*
- *Reproduce CI testing environments using Docker containers*
 - *Prerequisites*
 - *Building and Running Docker containers locally*
- *Update pipeline definitions for BuildKite CI*
- *Managing Elastic CI Stack with BuildKite*

- *Worker Image Pipeline*
- *EC2 Autoscaling Groups*

GitHub Actions

The configuration files are located under the directory `.github/workflows`.

Most of the tests listed in the configuration files run automatically for every incoming pull requests and every update to branches. A few tests however require manual activation:

- R tests with noLD option: Run R tests using a custom-built R with compilation flag `--disable-long-double`. See [this page](#) for more details about noLD. This is a requirement for keeping XGBoost on CRAN (the R package index). To invoke this test suite for a particular pull request, simply add a review comment `/gha run r-nold-test`. (Ordinary comment won't work. It needs to be a review comment.)

GitHub Actions is also used to build Python wheels targeting MacOS Intel and Apple Silicon. See [.github/workflows/python_wheels.yml](#). The `python_wheels` pipeline sets up environment variables prefixed `CIBW_*` to indicate the target OS and processor. The pipeline then invokes the script `build_python_wheels.sh`, which in turns calls `cibuildwheel` to build the wheel. The `cibuildwheel` is a library that sets up a suitable Python environment for each OS and processor target. Since we don't have Apple Silicon machine in GitHub Actions, cross-compilation is needed; `cibuildwheel` takes care of the complex task of cross-compiling a Python wheel. (Note that `cibuildwheel` will call `pip wheel`. Since XGBoost has a native library component, we created a customized build backend that hooks into `pip`. The customized backend contains the glue code to compile the native library on the fly.)

Reproduce CI testing environments using Docker containers

In our CI pipelines, we use Docker containers extensively to package many software packages together. You can reproduce the same testing environment as the CI pipelines by running Docker locally.

Prerequisites

1. Install Docker: <https://docs.docker.com/engine/install/ubuntu/>
2. Install NVIDIA Docker runtime: <https://docs.nvidia.com/datacenter/cloud-native/container-toolkit/install-guide.html#installing-on-ubuntu-and-debian> The runtime lets you access NVIDIA GPUs inside a Docker container.

Building and Running Docker containers locally

For your convenience, we provide the wrapper script `tests/ci_build/ci_build.sh`. You can use it as follows:

```
tests/ci_build/ci_build.sh <CONTAINER_TYPE> <DOCKER_BINARY> --build-arg <BUILD_ARG> \
<COMMAND> ...
```

where:

- `<CONTAINER_TYPE>` is the identifier for the container. The wrapper script will use the container definition (Dockerfile) located at `tests/ci_build/Dockerfile.<CONTAINER_TYPE>`. For example, setting the container type to `gpu` will cause the script to load the Dockerfile `tests/ci_build/Dockerfile.gpu`.
- `<DOCKER_BINARY>` must be either `docker` or `nvidia-docker`. Choose `nvidia-docker` as long as you need to run any GPU code.

- `<BUILD_ARG>` is a build argument to be passed to Docker. Must be of form `VAR=VALUE`. Example: `--build-arg CUDA_VERSION_ARG=11.0`. You can pass multiple `--build-arg`.
- `<COMMAND>` is the command to run inside the Docker container. This can be more than one argument. Example: `tests/ci_build/build_via_cmake.sh -DUSE_CUDA=ON -DUSE_NCCL=ON`.

Optionally, you can set the environment variable `CI_DOCKER_EXTRA_PARAMS_INIT` to pass extra arguments to Docker. For example:

```
# Allocate extra space in /dev/shm to enable NCCL
export CI_DOCKER_EXTRA_PARAMS_INIT='--shm-size=4g'
# Run multi-GPU test suite
tests/ci_build/ci_build.sh gpu nvidia-docker --build-arg CUDA_VERSION_ARG=11.0 \
  tests/ci_build/test_python.sh mgpu
```

To pass multiple extra arguments:

```
export CI_DOCKER_EXTRA_PARAMS_INIT='-e VAR1=VAL1 -e VAR2=VAL2 -e VAR3=VAL3'
```

Update pipeline definitions for BuildKite CI

BuildKite is a SaaS (Software as a Service) platform that orchestrates cloud machines to host CI pipelines. The BuildKite platform allows us to define CI pipelines as a declarative YAML file.

The pipeline definitions are found in `tests/buildkite/`:

- `tests/buildkite/pipeline-win64.yml`: This pipeline builds and tests XGBoost for the Windows platform.
- `tests/buildkite/pipeline-mgpu.yml`: This pipeline builds and tests XGBoost with access to multiple NVIDIA GPUs.
- `tests/buildkite/pipeline.yml`: This pipeline builds and tests XGBoost with access to a single NVIDIA GPU. Most tests are located here.

Managing Elastic CI Stack with BuildKite

BuildKite allows us to define cloud resources in a declarative fashion. Every configuration step is now documented explicitly as code.

Prerequisite: You should have some knowledge of [CloudFormation](#). CloudFormation lets us define a stack of cloud resources (EC2 machines, Lambda functions, S3 etc) using a single YAML file.

Prerequisite: Gain access to the XGBoost project's AWS account (`admin@xgboost-ci.net`), and then set up a credential pair in order to provision resources on AWS. See [Creating an IAM user in your AWS account](#).

- Option 1. Give full admin privileges to your IAM user. This is the simplest option.
- Option 2. Give limited set of permissions to your IAM user, to reduce the possibility of messing up other resources. For this, use the script `tests/buildkite/infrastructure/service-user/create_service_user.py`.

Worker Image Pipeline

Building images for worker machines used to be a chore: you'd provision an EC2 machine, SSH into it, and manually install the necessary packages. This process is not only laborious but also error-prone. You may forget to install a package or change a system configuration.

No more. Now we have an automated pipeline for building images for worker machines.

- Run `tests/buildkite/infrastructure/worker-image-pipeline/create_worker_image_pipelines.py` in order to provision CloudFormation stacks named `buildkite-linux-amd64-gpu-worker` and `buildkite-windows-gpu-worker`. They are pipelines that create AMIs (Amazon Machine Images) for Linux and Windows workers, respectively.
- Navigate to the CloudFormation web console to verify that the image builder pipelines have been provisioned. It may take some time.
- Once they pipelines have been fully provisioned, run the script `tests/buildkite/infrastructure/worker-image-pipeline/run_pipelines.py` to execute the pipelines. New AMIs will be uploaded to the EC2 service. You can locate them in the EC2 console.
- Make sure to modify `tests/buildkite/infrastructure/aws-stack-creator/metadata.py` to use the correct AMI IDs. (For `linux-amd64-cpu` and `linux-arm64-cpu`, use the AMIs provided by BuildKite. Consult the `AWSRegion2AMI` section of <https://s3.amazonaws.com/buildkite-aws-stack/latest/aws-stack.yml>.)

EC2 Autoscaling Groups

In EC2, you can create auto-scaling groups, where you can dynamically adjust the number of worker instances according to workload. When a pull request is submitted, the following steps take place:

1. GitHub sends a signal to the registered webhook, which connects to the BuildKite server.
2. BuildKite sends a signal to a [Lambda](#) function named `Autoscaling`.
3. The Lambda function sends a signal to the auto-scaling group. The group scales up and adds additional worker instances.
4. New worker instances run the test jobs. Test results are reported back to BuildKite.
5. When the test jobs complete, BuildKite sends a signal to `Autoscaling`, which in turn requests the autoscaling group to scale down. Idle worker instances are shut down.

To set up the auto-scaling group, run the script `tests/buildkite/infrastructure/aws-stack-creator/create_stack.py`. Check the CloudFormation web console to verify successful provision of auto-scaling groups.

PYTHON MODULE INDEX

X

- `xgboost.callback`, 218
- `xgboost.core`, 134
- `xgboost.dask`, 223
- `xgboost.plotting`, 216
- `xgboost.sklearn`, 152
- `xgboost.spark`, 291
- `xgboost.training`, 149

A

`after_iteration()` (*xgboost.callback.EarlyStopping* method), 220
`after_iteration()` (*xgboost.callback.EvaluationMonitor* method), 219
`after_iteration()` (*xgboost.callback.LearningRateScheduler* method), 221
`after_iteration()` (*xgboost.callback.TrainingCallback* method), 218
`after_iteration()` (*xgboost.callback.TrainingCheckPoint* method), 222
`after_training()` (*xgboost.callback.EarlyStopping* method), 220
`after_training()` (*xgboost.callback.EvaluationMonitor* method), 219
`after_training()` (*xgboost.callback.LearningRateScheduler* method), 221
`after_training()` (*xgboost.callback.TrainingCallback* method), 218
`after_training()` (*xgboost.callback.TrainingCheckPoint* method), 222
`apply()` (*xgboost.dask.DaskXGBClassifier* method), 231
`apply()` (*xgboost.dask.DaskXGBRanker* method), 257
`apply()` (*xgboost.dask.DaskXGBRegressor* method), 245
`apply()` (*xgboost.dask.DaskXGBRFClassifier* method), 282
`apply()` (*xgboost.dask.DaskXGBRFRegressor* method), 269
`apply()` (*xgboost.XGBClassifier* method), 168
`apply()` (*xgboost.XGBRanker* method), 182
`apply()` (*xgboost.XGBRegressor* method), 156
`apply()` (*xgboost.XGBRFClassifier* method), 206
`apply()` (*xgboost.XGBRFRegressor* method), 194
`attr()` (*xgboost.Booster* method), 140

`attributes()` (*xgboost.Booster* method), 141

B

`before_iteration()` (*xgboost.callback.EarlyStopping* method), 220
`before_iteration()` (*xgboost.callback.EvaluationMonitor* method), 219
`before_iteration()` (*xgboost.callback.LearningRateScheduler* method), 221
`before_iteration()` (*xgboost.callback.TrainingCallback* method), 218
`before_iteration()` (*xgboost.callback.TrainingCheckPoint* method), 222
`before_training()` (*xgboost.callback.EarlyStopping* method), 221
`before_training()` (*xgboost.callback.EvaluationMonitor* method), 219
`before_training()` (*xgboost.callback.LearningRateScheduler* method), 222
`before_training()` (*xgboost.callback.TrainingCallback* method), 218
`before_training()` (*xgboost.callback.TrainingCheckPoint* method), 223
`best_iteration` (*xgboost.Booster* property), 141
`best_iteration` (*xgboost.dask.DaskXGBClassifier* property), 231
`best_iteration` (*xgboost.dask.DaskXGBRanker* property), 257
`best_iteration` (*xgboost.dask.DaskXGBRegressor* property), 245
`best_iteration` (*xgboost.dask.DaskXGBRFClassifier* property), 282
`best_iteration` (*xgboost.dask.DaskXGBRFRegressor* property), 270

best_iteration (xgboost.XGBClassifier property), 168
 best_iteration (xgboost.XGBRanker property), 182
 best_iteration (xgboost.XGBRegressor property), 156
 best_iteration (xgboost.XGBRFClassifier property), 207
 best_iteration (xgboost.XGBRFRegressor property), 194
 best_score (xgboost.Booster property), 141
 best_score (xgboost.dask.DaskXGBClassifier property), 232
 best_score (xgboost.dask.DaskXGBRanker property), 257
 best_score (xgboost.dask.DaskXGBRegressor property), 245
 best_score (xgboost.dask.DaskXGBRFClassifier property), 282
 best_score (xgboost.dask.DaskXGBRFRegressor property), 270
 best_score (xgboost.XGBClassifier property), 168
 best_score (xgboost.XGBRanker property), 182
 best_score (xgboost.XGBRegressor property), 156
 best_score (xgboost.XGBRFClassifier property), 207
 best_score (xgboost.XGBRFRegressor property), 194
 boost() (xgboost.Booster method), 141
 Booster (class in xgboost), 140
 BoosterHandle (C++ type), 426

C

clear() (xgboost.spark.SparkXGBClassifier method), 293
 clear() (xgboost.spark.SparkXGBClassifierModel method), 297
 clear() (xgboost.spark.SparkXGBRanker method), 313
 clear() (xgboost.spark.SparkXGBRankerModel method), 317
 clear() (xgboost.spark.SparkXGBRegressor method), 303
 clear() (xgboost.spark.SparkXGBRegressorModel method), 307
 client (xgboost.dask.DaskXGBClassifier property), 232
 client (xgboost.dask.DaskXGBRanker property), 258
 client (xgboost.dask.DaskXGBRegressor property), 245
 client (xgboost.dask.DaskXGBRFClassifier property), 282
 client (xgboost.dask.DaskXGBRFRegressor property), 270
 coef_ (xgboost.dask.DaskXGBClassifier property), 232
 coef_ (xgboost.dask.DaskXGBRanker property), 258
 coef_ (xgboost.dask.DaskXGBRegressor property), 245
 coef_ (xgboost.dask.DaskXGBRFClassifier property), 282
 coef_ (xgboost.dask.DaskXGBRFRegressor property), 270

coef_ (xgboost.XGBClassifier property), 168
 coef_ (xgboost.XGBRanker property), 182
 coef_ (xgboost.XGBRegressor property), 156
 coef_ (xgboost.XGBRFClassifier property), 207
 coef_ (xgboost.XGBRFRegressor property), 194
 config_context() (in module xgboost), 131
 copy() (xgboost.Booster method), 141
 copy() (xgboost.spark.SparkXGBClassifier method), 293
 copy() (xgboost.spark.SparkXGBClassifierModel method), 298
 copy() (xgboost.spark.SparkXGBRanker method), 313
 copy() (xgboost.spark.SparkXGBRankerModel method), 318
 copy() (xgboost.spark.SparkXGBRegressor method), 303
 copy() (xgboost.spark.SparkXGBRegressorModel method), 308
 cv() (in module xgboost), 150

D

DaskDMatrix (class in xgboost.dask), 223
 DaskQuantileDMatrix (class in xgboost.dask), 224
 DaskXGBClassifier (class in xgboost.dask), 227
 DaskXGBRanker (class in xgboost.dask), 253
 DaskXGBRegressor (class in xgboost.dask), 241
 DaskXGBRFClassifier (class in xgboost.dask), 278
 DaskXGBRFRegressor (class in xgboost.dask), 265
 DataHolderHandle (C++ type), 439
 DataIter (class in xgboost), 148
 DataIterHandle (C++ type), 439
 DataIterResetCallback (C++ type), 439
 DMatrix (class in xgboost), 134
 DMatrixHandle (C++ type), 426
 dump_model() (xgboost.Booster method), 141

E

EarlyStopping (class in xgboost.callback), 219
 eval() (xgboost.Booster method), 141
 eval_set() (xgboost.Booster method), 142
 evals_result() (xgboost.dask.DaskXGBClassifier method), 232
 evals_result() (xgboost.dask.DaskXGBRanker method), 258
 evals_result() (xgboost.dask.DaskXGBRegressor method), 246
 evals_result() (xgboost.dask.DaskXGBRFClassifier method), 283
 evals_result() (xgboost.dask.DaskXGBRFRegressor method), 270
 evals_result() (xgboost.XGBClassifier method), 169
 evals_result() (xgboost.XGBRanker method), 182
 evals_result() (xgboost.XGBRegressor method), 156
 evals_result() (xgboost.XGBRFClassifier method), 207

<code>evals_result()</code> (<i>xgboost.XGBRFRegressor</i> method), 195	<code>feature_importances_</code> (<i>xgboost.dask.DaskXGBRegressor</i> property), 246
<code>EvaluationMonitor</code> (class in <i>xgboost.callback</i>), 218	
<code>explainParam()</code> (<i>xgboost.spark.SparkXGBClassifier</i> method), 294	<code>feature_importances_</code> (<i>xgboost.dask.DaskXGBRFClassifier</i> property), 283
<code>explainParam()</code> (<i>xgboost.spark.SparkXGBClassifierModel</i> method), 298	<code>feature_importances_</code> (<i>xgboost.dask.DaskXGBRFRegressor</i> property), 270
<code>explainParam()</code> (<i>xgboost.spark.SparkXGBRanker</i> method), 314	<code>feature_importances_</code> (<i>xgboost.XGBClassifier</i> property), 169
<code>explainParam()</code> (<i>xgboost.spark.SparkXGBRankerModel</i> method), 318	<code>feature_importances_</code> (<i>xgboost.XGBRanker</i> property), 183
<code>explainParam()</code> (<i>xgboost.spark.SparkXGBRegressor</i> method), 304	<code>feature_importances_</code> (<i>xgboost.XGBRegressor</i> property), 157
<code>explainParam()</code> (<i>xgboost.spark.SparkXGBRegressorModel</i> method), 308	<code>feature_importances_</code> (<i>xgboost.XGBRFClassifier</i> property), 207
<code>explainParams()</code> (<i>xgboost.spark.SparkXGBClassifier</i> method), 294	<code>feature_importances_</code> (<i>xgboost.XGBRFRegressor</i> property), 195
<code>explainParams()</code> (<i>xgboost.spark.SparkXGBClassifierModel</i> method), 298	<code>feature_names</code> (<i>xgboost.Booster</i> property), 142
<code>explainParams()</code> (<i>xgboost.spark.SparkXGBRanker</i> method), 314	<code>feature_names</code> (<i>xgboost.DMatrix</i> property), 135
<code>explainParams()</code> (<i>xgboost.spark.SparkXGBRankerModel</i> method), 318	<code>feature_names_in_</code> (<i>xgboost.dask.DaskXGBClassifier</i> property), 232
<code>explainParams()</code> (<i>xgboost.spark.SparkXGBRegressor</i> method), 304	<code>feature_names_in_</code> (<i>xgboost.dask.DaskXGBRanker</i> property), 258
<code>explainParams()</code> (<i>xgboost.spark.SparkXGBRegressorModel</i> method), 308	<code>feature_names_in_</code> (<i>xgboost.dask.DaskXGBRegressor</i> property), 246
<code>extractParamMap()</code> (<i>xgboost.spark.SparkXGBClassifier</i> method), 294	<code>feature_names_in_</code> (<i>xgboost.dask.DaskXGBRFClassifier</i> property), 283
<code>extractParamMap()</code> (<i>xgboost.spark.SparkXGBClassifierModel</i> method), 298	<code>feature_names_in_</code> (<i>xgboost.dask.DaskXGBRFRegressor</i> property), 271
<code>extractParamMap()</code> (<i>xgboost.spark.SparkXGBRanker</i> method), 314	<code>feature_names_in_</code> (<i>xgboost.XGBClassifier</i> property), 169
<code>extractParamMap()</code> (<i>xgboost.spark.SparkXGBRankerModel</i> method), 318	<code>feature_names_in_</code> (<i>xgboost.XGBRanker</i> property), 183
<code>extractParamMap()</code> (<i>xgboost.spark.SparkXGBRegressor</i> method), 304	<code>feature_names_in_</code> (<i>xgboost.XGBRegressor</i> property), 157
<code>extractParamMap()</code> (<i>xgboost.spark.SparkXGBRegressorModel</i> method), 308	<code>feature_names_in_</code> (<i>xgboost.XGBRFClassifier</i> property), 207
	<code>feature_names_in_</code> (<i>xgboost.XGBRFRegressor</i> property), 195
	<code>feature_types</code> (<i>xgboost.Booster</i> property), 142
	<code>feature_types</code> (<i>xgboost.DMatrix</i> property), 135
F	<code>fit()</code> (<i>xgboost.dask.DaskXGBClassifier</i> method), 232
<code>feature_importances_</code> (<i>xgboost.dask.DaskXGBClassifier</i> property), 232	<code>fit()</code> (<i>xgboost.dask.DaskXGBRanker</i> method), 258
<code>feature_importances_</code> (<i>xgboost.dask.DaskXGBRanker</i> property), 258	<code>fit()</code> (<i>xgboost.dask.DaskXGBRegressor</i> method), 246
	<code>fit()</code> (<i>xgboost.dask.DaskXGBRFClassifier</i> method), 283
	<code>fit()</code> (<i>xgboost.dask.DaskXGBRFRegressor</i> method), 271
	<code>fit()</code> (<i>xgboost.spark.SparkXGBClassifier</i> method), 294
	<code>fit()</code> (<i>xgboost.spark.SparkXGBRanker</i> method), 314

- [fit\(\)](#) (*xgboost.spark.SparkXGBRegressor method*), 304
[fit\(\)](#) (*xgboost.XGBClassifier method*), 169
[fit\(\)](#) (*xgboost.XGBRanker method*), 183
[fit\(\)](#) (*xgboost.XGBRegressor method*), 157
[fit\(\)](#) (*xgboost.XGBRFClassifier method*), 207
[fit\(\)](#) (*xgboost.XGBRFRegressor method*), 195
[fitMultiple\(\)](#) (*xgboost.spark.SparkXGBClassifier method*), 294
[fitMultiple\(\)](#) (*xgboost.spark.SparkXGBRanker method*), 314
[fitMultiple\(\)](#) (*xgboost.spark.SparkXGBRegressor method*), 305
- ## G
- [get_base_margin\(\)](#) (*xgboost.DMatrix method*), 135
[get_booster\(\)](#) (*xgboost.dask.DaskXGBClassifier method*), 234
[get_booster\(\)](#) (*xgboost.dask.DaskXGBRanker method*), 260
[get_booster\(\)](#) (*xgboost.dask.DaskXGBRegressor method*), 247
[get_booster\(\)](#) (*xgboost.dask.DaskXGBRFClassifier method*), 284
[get_booster\(\)](#) (*xgboost.dask.DaskXGBRFRegressor method*), 272
[get_booster\(\)](#) (*xgboost.spark.SparkXGBClassifierModel method*), 299
[get_booster\(\)](#) (*xgboost.spark.SparkXGBRankerModel method*), 319
[get_booster\(\)](#) (*xgboost.spark.SparkXGBRegressorModel method*), 309
[get_booster\(\)](#) (*xgboost.XGBClassifier method*), 170
[get_booster\(\)](#) (*xgboost.XGBRanker method*), 185
[get_booster\(\)](#) (*xgboost.XGBRegressor method*), 158
[get_booster\(\)](#) (*xgboost.XGBRFClassifier method*), 209
[get_booster\(\)](#) (*xgboost.XGBRFRegressor method*), 196
[get_callbacks\(\)](#) (*xgboost.DataIter method*), 148
[get_config\(\)](#) (in module *xgboost*), 133
[get_data\(\)](#) (*xgboost.DMatrix method*), 135
[get_dump\(\)](#) (*xgboost.Booster method*), 142
[get_feature_importances\(\)](#) (*xgboost.spark.SparkXGBClassifierModel method*), 299
[get_feature_importances\(\)](#) (*xgboost.spark.SparkXGBRankerModel method*), 319
[get_feature_importances\(\)](#) (*xgboost.spark.SparkXGBRegressorModel method*), 309
[get_float_info\(\)](#) (*xgboost.DMatrix method*), 135
[get_fscore\(\)](#) (*xgboost.Booster method*), 142
[get_group\(\)](#) (*xgboost.DMatrix method*), 135
[get_label\(\)](#) (*xgboost.DMatrix method*), 136
[get_metadata_routing\(\)](#) (*xgboost.dask.DaskXGBClassifier method*), 234
[get_metadata_routing\(\)](#) (*xgboost.dask.DaskXGBRanker method*), 260
[get_metadata_routing\(\)](#) (*xgboost.dask.DaskXGBRegressor method*), 247
[get_metadata_routing\(\)](#) (*xgboost.dask.DaskXGBRFClassifier method*), 284
[get_metadata_routing\(\)](#) (*xgboost.dask.DaskXGBRFRegressor method*), 272
[get_metadata_routing\(\)](#) (*xgboost.XGBClassifier method*), 170
[get_metadata_routing\(\)](#) (*xgboost.XGBRanker method*), 185
[get_metadata_routing\(\)](#) (*xgboost.XGBRegressor method*), 158
[get_metadata_routing\(\)](#) (*xgboost.XGBRFClassifier method*), 209
[get_metadata_routing\(\)](#) (*xgboost.XGBRFRegressor method*), 196
[get_num_boosting_rounds\(\)](#) (*xgboost.dask.DaskXGBClassifier method*), 234
[get_num_boosting_rounds\(\)](#) (*xgboost.dask.DaskXGBRanker method*), 261
[get_num_boosting_rounds\(\)](#) (*xgboost.dask.DaskXGBRegressor method*), 247
[get_num_boosting_rounds\(\)](#) (*xgboost.dask.DaskXGBRFClassifier method*), 285
[get_num_boosting_rounds\(\)](#) (*xgboost.dask.DaskXGBRFRegressor method*), 272
[get_num_boosting_rounds\(\)](#) (*xgboost.XGBClassifier method*), 171
[get_num_boosting_rounds\(\)](#) (*xgboost.XGBRanker method*), 185
[get_num_boosting_rounds\(\)](#) (*xgboost.XGBRegressor method*), 158
[get_num_boosting_rounds\(\)](#) (*xgboost.XGBRFClassifier method*), 209
[get_num_boosting_rounds\(\)](#) (*xgboost.XGBRFRegressor method*), 196
[get_params\(\)](#) (*xgboost.dask.DaskXGBClassifier method*), 234
[get_params\(\)](#) (*xgboost.dask.DaskXGBRanker method*), 261
[get_params\(\)](#) (*xgboost.dask.DaskXGBRegressor method*), 247

method), 248

get_params() (xgboost.dask.DaskXGBRFClassifier method), 285

get_params() (xgboost.dask.DaskXGBRFRegressor method), 272

get_params() (xgboost.XGBClassifier method), 171

get_params() (xgboost.XGBRanker method), 185

get_params() (xgboost.XGBRegressor method), 158

get_params() (xgboost.XGBRFClassifier method), 209

get_params() (xgboost.XGBRFRegressor method), 197

get_quantile_cut() (xgboost.DMatrix method), 136

get_score() (xgboost.Booster method), 143

get_split_value_histogram() (xgboost.Booster method), 143

get_uint_info() (xgboost.DMatrix method), 136

get_weight() (xgboost.DMatrix method), 136

get_xgb_params() (xgboost.dask.DaskXGBClassifier method), 234

get_xgb_params() (xgboost.dask.DaskXGBRanker method), 261

get_xgb_params() (xgboost.dask.DaskXGBRegressor method), 248

get_xgb_params() (xgboost.dask.DaskXGBRFClassifier method), 285

get_xgb_params() (xgboost.dask.DaskXGBRFRegressor method), 272

get_xgb_params() (xgboost.XGBClassifier method), 171

get_xgb_params() (xgboost.XGBRanker method), 185

get_xgb_params() (xgboost.XGBRegressor method), 159

get_xgb_params() (xgboost.XGBRFClassifier method), 209

get_xgb_params() (xgboost.XGBRFRegressor method), 197

getFeaturesCol() (xgboost.spark.SparkXGBClassifier method), 295

getFeaturesCol() (xgboost.spark.SparkXGBClassifierModel method), 298

getFeaturesCol() (xgboost.spark.SparkXGBRanker method), 315

getFeaturesCol() (xgboost.spark.SparkXGBRankerModel method), 318

getFeaturesCol() (xgboost.spark.SparkXGBRegressor method), 305

getFeaturesCol() (xgboost.spark.SparkXGBRegressorModel method), 308

getLabelCol() (xgboost.spark.SparkXGBClassifier method), 295

getLabelCol() (xgboost.spark.SparkXGBClassifierModel method), 298

getLabelCol() (xgboost.spark.SparkXGBRanker method), 315

getLabelCol() (xgboost.spark.SparkXGBRankerModel method), 318

getLabelCol() (xgboost.spark.SparkXGBRegressor method), 305

getLabelCol() (xgboost.spark.SparkXGBRegressorModel method), 308

getOrDefault() (xgboost.spark.SparkXGBClassifier method), 295

getOrDefault() (xgboost.spark.SparkXGBClassifierModel method), 299

getOrDefault() (xgboost.spark.SparkXGBRanker method), 315

getOrDefault() (xgboost.spark.SparkXGBRankerModel method), 318

getOrDefault() (xgboost.spark.SparkXGBRegressor method), 305

getOrDefault() (xgboost.spark.SparkXGBRegressorModel method), 309

getParam() (xgboost.spark.SparkXGBClassifier method), 295

getParam() (xgboost.spark.SparkXGBClassifierModel method), 299

getParam() (xgboost.spark.SparkXGBRanker method), 315

getParam() (xgboost.spark.SparkXGBRankerModel method), 319

getParam() (xgboost.spark.SparkXGBRegressor method), 305

getParam() (xgboost.spark.SparkXGBRegressorModel method), 309

getPredictionCol() (xgboost.spark.SparkXGBClassifier method), 295

getPredictionCol() (xgboost.spark.SparkXGBClassifierModel method), 299

getPredictionCol() (xgboost.spark.SparkXGBRanker method), 315

getPredictionCol() (xgboost.spark.SparkXGBRankerModel method), 319

getPredictionCol() (xgboost.spark.SparkXGBRegressor method), 305

getPredictionCol() (xgboost.spark.SparkXGBRegressorModel method), 309

getProbabilityCol() (xgboost.spark.SparkXGBClassifier method), 295

<code>getProbabilityCol()</code> <i>(xgboost.spark.SparkXGBClassifierModel method), 299</i>	<code>hasParam()</code> <i>(xgboost.spark.SparkXGBClassifierModel method), 300</i>
<code>getRawPredictionCol()</code> <i>(xgboost.spark.SparkXGBClassifier method), 295</i>	<code>hasParam()</code> <i>(xgboost.spark.SparkXGBRanker method), 316</i>
<code>getRawPredictionCol()</code> <i>(xgboost.spark.SparkXGBClassifierModel method), 299</i>	<code>hasParam()</code> <i>(xgboost.spark.SparkXGBRankerModel method), 320</i>
<code>getValidationIndicatorCol()</code> <i>(xgboost.spark.SparkXGBClassifier method), 295</i>	<code>hasParam()</code> <i>(xgboost.spark.SparkXGBRegressor method), 306</i>
<code>getValidationIndicatorCol()</code> <i>(xgboost.spark.SparkXGBClassifierModel method), 299</i>	<code>hasParam()</code> <i>(xgboost.spark.SparkXGBRegressorModel method), 310</i>
<code>getValidationIndicatorCol()</code> <i>(xgboost.spark.SparkXGBRanker method), 315</i>	<code>inplace_predict()</code> <i>(in module xgboost.dask), 226</i>
<code>getValidationIndicatorCol()</code> <i>(xgboost.spark.SparkXGBRankerModel method), 319</i>	<code>inplace_predict()</code> <i>(xgboost.Booster method), 144</i>
<code>getValidationIndicatorCol()</code> <i>(xgboost.spark.SparkXGBRegressor method), 305</i>	<code>intercept_</code> <i>(xgboost.dask.DaskXGBClassifier property), 234</i>
<code>getValidationIndicatorCol()</code> <i>(xgboost.spark.SparkXGBRegressorModel method), 309</i>	<code>intercept_</code> <i>(xgboost.dask.DaskXGBRanker property), 261</i>
<code>getWeightCol()</code> <i>(xgboost.spark.SparkXGBClassifier method), 296</i>	<code>intercept_</code> <i>(xgboost.dask.DaskXGBRegressor property), 248</i>
<code>getWeightCol()</code> <i>(xgboost.spark.SparkXGBClassifierModel method), 299</i>	<code>intercept_</code> <i>(xgboost.dask.DaskXGBRFClassifier property), 285</i>
<code>getWeightCol()</code> <i>(xgboost.spark.SparkXGBRanker method), 315</i>	<code>intercept_</code> <i>(xgboost.dask.DaskXGBRFRegressor property), 272</i>
<code>getWeightCol()</code> <i>(xgboost.spark.SparkXGBRankerModel method), 319</i>	<code>intercept_</code> <i>(xgboost.XGBClassifier property), 171</i>
<code>getWeightCol()</code> <i>(xgboost.spark.SparkXGBRegressor method), 306</i>	<code>intercept_</code> <i>(xgboost.XGBRanker property), 185</i>
<code>getWeightCol()</code> <i>(xgboost.spark.SparkXGBRegressorModel method), 309</i>	<code>intercept_</code> <i>(xgboost.XGBRegressor property), 159</i>
	<code>intercept_</code> <i>(xgboost.XGBRFClassifier property), 209</i>
	<code>intercept_</code> <i>(xgboost.XGBRFRegressor property), 197</i>
	<code>isDefined()</code> <i>(xgboost.spark.SparkXGBClassifier method), 296</i>
	<code>isDefined()</code> <i>(xgboost.spark.SparkXGBClassifierModel method), 300</i>
	<code>isDefined()</code> <i>(xgboost.spark.SparkXGBRanker method), 316</i>
	<code>isDefined()</code> <i>(xgboost.spark.SparkXGBRankerModel method), 320</i>
	<code>isDefined()</code> <i>(xgboost.spark.SparkXGBRegressor method), 306</i>
	<code>isDefined()</code> <i>(xgboost.spark.SparkXGBRegressorModel method), 310</i>
	<code>isSet()</code> <i>(xgboost.spark.SparkXGBClassifier method), 296</i>
	<code>isSet()</code> <i>(xgboost.spark.SparkXGBClassifierModel method), 300</i>
	<code>isSet()</code> <i>(xgboost.spark.SparkXGBRanker method), 316</i>
	<code>isSet()</code> <i>(xgboost.spark.SparkXGBRankerModel method), 320</i>
	<code>isSet()</code> <i>(xgboost.spark.SparkXGBRegressor method), 306</i>
	<code>isSet()</code> <i>(xgboost.spark.SparkXGBRegressorModel method), 310</i>
H	
<code>hasDefault()</code> <i>(xgboost.spark.SparkXGBClassifier method), 296</i>	
<code>hasDefault()</code> <i>(xgboost.spark.SparkXGBClassifierModel method), 300</i>	
<code>hasDefault()</code> <i>(xgboost.spark.SparkXGBRanker method), 316</i>	
<code>hasDefault()</code> <i>(xgboost.spark.SparkXGBRankerModel method), 319</i>	
<code>hasDefault()</code> <i>(xgboost.spark.SparkXGBRegressor method), 306</i>	
<code>hasDefault()</code> <i>(xgboost.spark.SparkXGBRegressorModel method), 310</i>	
<code>hasParam()</code> <i>(xgboost.spark.SparkXGBClassifier method), 296</i>	

L

[LearningRateScheduler \(class in xgboost.callback\), 221](#)
[load\(\) \(xgboost.spark.SparkXGBClassifier class method\), 296](#)
[load\(\) \(xgboost.spark.SparkXGBClassifierModel class method\), 300](#)
[load\(\) \(xgboost.spark.SparkXGBRanker class method\), 316](#)
[load\(\) \(xgboost.spark.SparkXGBRankerModel class method\), 320](#)
[load\(\) \(xgboost.spark.SparkXGBRegressor class method\), 306](#)
[load\(\) \(xgboost.spark.SparkXGBRegressorModel class method\), 310](#)
[load_config\(\) \(xgboost.Booster method\), 145](#)
[load_model\(\) \(xgboost.Booster method\), 145](#)
[load_model\(\) \(xgboost.dask.DaskXGBClassifier method\), 235](#)
[load_model\(\) \(xgboost.dask.DaskXGBRanker method\), 261](#)
[load_model\(\) \(xgboost.dask.DaskXGBRegressor method\), 248](#)
[load_model\(\) \(xgboost.dask.DaskXGBRFClassifier method\), 285](#)
[load_model\(\) \(xgboost.dask.DaskXGBRFRegressor method\), 273](#)
[load_model\(\) \(xgboost.XGBClassifier method\), 171](#)
[load_model\(\) \(xgboost.XGBRanker method\), 186](#)
[load_model\(\) \(xgboost.XGBRegressor method\), 159](#)
[load_model\(\) \(xgboost.XGBRFClassifier method\), 209](#)
[load_model\(\) \(xgboost.XGBRFRegressor method\), 197](#)

M

[module

- \[xgboost.callback, 218\]\(#\)
- \[xgboost.core, 134\]\(#\)
- \[xgboost.dask, 223\]\(#\)
- \[xgboost.plotting, 216\]\(#\)
- \[xgboost.sklearn, 152\]\(#\)
- \[xgboost.spark, 291\]\(#\)
- \[xgboost.training, 149\]\(#\)](#)

N

[n_features_in_ \(xgboost.dask.DaskXGBClassifier property\), 235](#)
[n_features_in_ \(xgboost.dask.DaskXGBRanker property\), 261](#)
[n_features_in_ \(xgboost.dask.DaskXGBRegressor property\), 248](#)
[n_features_in_ \(xgboost.dask.DaskXGBRFClassifier property\), 286](#)
[n_features_in_ \(xgboost.dask.DaskXGBRFRegressor property\), 273](#)

[n_features_in_ \(xgboost.XGBClassifier property\), 172](#)
[n_features_in_ \(xgboost.XGBRanker property\), 186](#)
[n_features_in_ \(xgboost.XGBRegressor property\), 159](#)
[n_features_in_ \(xgboost.XGBRFClassifier property\), 210](#)
[n_features_in_ \(xgboost.XGBRFRegressor property\), 197](#)
[next\(\) \(xgboost.DataIter method\), 148](#)
[num_boosted_rounds\(\) \(xgboost.Booster method\), 145](#)
[num_col\(\) \(xgboost.dask.DaskDMatrix method\), 224](#)
[num_col\(\) \(xgboost.dask.DaskQuantileDMatrix method\), 225](#)
[num_col\(\) \(xgboost.DMatrix method\), 136](#)
[num_features\(\) \(xgboost.Booster method\), 145](#)
[num_nonmissing\(\) \(xgboost.DMatrix method\), 136](#)
[num_row\(\) \(xgboost.DMatrix method\), 136](#)

P

[params \(xgboost.spark.SparkXGBClassifier property\), 296](#)
[params \(xgboost.spark.SparkXGBClassifierModel property\), 301](#)
[params \(xgboost.spark.SparkXGBRanker property\), 316](#)
[params \(xgboost.spark.SparkXGBRankerModel property\), 320](#)
[params \(xgboost.spark.SparkXGBRegressor property\), 306](#)
[params \(xgboost.spark.SparkXGBRegressorModel property\), 310](#)
[plot_importance\(\) \(in module xgboost\), 216](#)
[plot_tree\(\) \(in module xgboost\), 216](#)
[predict\(\) \(in module xgboost.dask\), 226](#)
[predict\(\) \(xgboost.Booster method\), 145](#)
[predict\(\) \(xgboost.dask.DaskXGBClassifier method\), 235](#)
[predict\(\) \(xgboost.dask.DaskXGBRanker method\), 262](#)
[predict\(\) \(xgboost.dask.DaskXGBRegressor method\), 248](#)
[predict\(\) \(xgboost.dask.DaskXGBRFClassifier method\), 286](#)
[predict\(\) \(xgboost.dask.DaskXGBRFRegressor method\), 273](#)
[predict\(\) \(xgboost.XGBClassifier method\), 172](#)
[predict\(\) \(xgboost.XGBRanker method\), 186](#)
[predict\(\) \(xgboost.XGBRegressor method\), 159](#)
[predict\(\) \(xgboost.XGBRFClassifier method\), 210](#)
[predict\(\) \(xgboost.XGBRFRegressor method\), 197](#)
[predict_proba\(\) \(xgboost.dask.DaskXGBClassifier method\), 235](#)
[predict_proba\(\) \(xgboost.dask.DaskXGBRFClassifier method\), 286](#)
[predict_proba\(\) \(xgboost.XGBClassifier method\), 172](#)

predict_proba() (*xgboost.XGBRFClassifier* method), 210
 proxy (*xgboost.DataIter* property), 148

Q

QuantileDMatrix (*class* in *xgboost*), 139

R

read() (*xgboost.spark.SparkXGBClassifier* class method), 296
 read() (*xgboost.spark.SparkXGBClassifierModel* class method), 301
 read() (*xgboost.spark.SparkXGBRanker* class method), 316
 read() (*xgboost.spark.SparkXGBRankerModel* class method), 320
 read() (*xgboost.spark.SparkXGBRegressor* class method), 306
 read() (*xgboost.spark.SparkXGBRegressorModel* class method), 310
 reraise() (*xgboost.DataIter* method), 148
 reset() (*xgboost.DataIter* method), 149

S

save() (*xgboost.spark.SparkXGBClassifier* method), 297
 save() (*xgboost.spark.SparkXGBClassifierModel* method), 301
 save() (*xgboost.spark.SparkXGBRanker* method), 316
 save() (*xgboost.spark.SparkXGBRankerModel* method), 320
 save() (*xgboost.spark.SparkXGBRegressor* method), 307
 save() (*xgboost.spark.SparkXGBRegressorModel* method), 310
 save_binary() (*xgboost.DMatrix* method), 136
 save_config() (*xgboost.Booster* method), 146
 save_model() (*xgboost.Booster* method), 146
 save_model() (*xgboost.dask.DaskXGBClassifier* method), 236
 save_model() (*xgboost.dask.DaskXGBRanker* method), 262
 save_model() (*xgboost.dask.DaskXGBRegressor* method), 249
 save_model() (*xgboost.dask.DaskXGBRFClassifier* method), 287
 save_model() (*xgboost.dask.DaskXGBRFRegressor* method), 274
 save_model() (*xgboost.XGBClassifier* method), 173
 save_model() (*xgboost.XGBRanker* method), 187
 save_model() (*xgboost.XGBRegressor* method), 160
 save_model() (*xgboost.XGBRFClassifier* method), 211
 save_model() (*xgboost.XGBRFRegressor* method), 198
 save_raw() (*xgboost.Booster* method), 147

score() (*xgboost.dask.DaskXGBClassifier* method), 236
 score() (*xgboost.dask.DaskXGBRegressor* method), 249
 score() (*xgboost.dask.DaskXGBRFClassifier* method), 287
 score() (*xgboost.dask.DaskXGBRFRegressor* method), 274
 score() (*xgboost.XGBClassifier* method), 173
 score() (*xgboost.XGBRanker* method), 187
 score() (*xgboost.XGBRegressor* method), 160
 score() (*xgboost.XGBRFClassifier* method), 211
 score() (*xgboost.XGBRFRegressor* method), 198
 set() (*xgboost.spark.SparkXGBClassifier* method), 297
 set() (*xgboost.spark.SparkXGBClassifierModel* method), 301
 set() (*xgboost.spark.SparkXGBRanker* method), 317
 set() (*xgboost.spark.SparkXGBRankerModel* method), 321
 set() (*xgboost.spark.SparkXGBRegressor* method), 307
 set() (*xgboost.spark.SparkXGBRegressorModel* method), 311
 set_attr() (*xgboost.Booster* method), 147
 set_base_margin() (*xgboost.DMatrix* method), 137
 set_config() (*in module xgboost*), 132
 set_device() (*xgboost.spark.SparkXGBClassifier* method), 297
 set_device() (*xgboost.spark.SparkXGBClassifierModel* method), 301
 set_device() (*xgboost.spark.SparkXGBRanker* method), 317
 set_device() (*xgboost.spark.SparkXGBRankerModel* method), 321
 set_device() (*xgboost.spark.SparkXGBRegressor* method), 307
 set_device() (*xgboost.spark.SparkXGBRegressorModel* method), 311
 set_fit_request() (*xgboost.dask.DaskXGBClassifier* method), 237
 set_fit_request() (*xgboost.dask.DaskXGBRanker* method), 262
 set_fit_request() (*xgboost.dask.DaskXGBRegressor* method), 250
 set_fit_request() (*xgboost.dask.DaskXGBRFClassifier* method), 287
 set_fit_request() (*xgboost.dask.DaskXGBRFRegressor* method), 275
 set_fit_request() (*xgboost.XGBClassifier* method), 173
 set_fit_request() (*xgboost.XGBRanker* method), 187
 set_fit_request() (*xgboost.XGBRegressor* method), 161

- [set_fit_request\(\)](#) (*xgboost.XGBRFClassifier method*), 211
[set_fit_request\(\)](#) (*xgboost.XGBRFRegressor method*), 199
[set_float_info\(\)](#) (*xgboost.DMatrix method*), 137
[set_float_info_np2d\(\)](#) (*xgboost.DMatrix method*), 137
[set_group\(\)](#) (*xgboost.DMatrix method*), 137
[set_info\(\)](#) (*xgboost.DMatrix method*), 137
[set_label\(\)](#) (*xgboost.DMatrix method*), 138
[set_param\(\)](#) (*xgboost.Booster method*), 147
[set_params\(\)](#) (*xgboost.dask.DaskXGBClassifier method*), 238
[set_params\(\)](#) (*xgboost.dask.DaskXGBRanker method*), 264
[set_params\(\)](#) (*xgboost.dask.DaskXGBRegressor method*), 251
[set_params\(\)](#) (*xgboost.dask.DaskXGBRFClassifier method*), 289
[set_params\(\)](#) (*xgboost.dask.DaskXGBRFRegressor method*), 276
[set_params\(\)](#) (*xgboost.XGBClassifier method*), 175
[set_params\(\)](#) (*xgboost.XGBRanker method*), 189
[set_params\(\)](#) (*xgboost.XGBRegressor method*), 162
[set_params\(\)](#) (*xgboost.XGBRFClassifier method*), 213
[set_params\(\)](#) (*xgboost.XGBRFRegressor method*), 200
[set_predict_proba_request\(\)](#) (*xgboost.dask.DaskXGBClassifier method*), 238
[set_predict_proba_request\(\)](#) (*xgboost.dask.DaskXGBRFClassifier method*), 289
[set_predict_proba_request\(\)](#) (*xgboost.XGBClassifier method*), 175
[set_predict_proba_request\(\)](#) (*xgboost.XGBRFClassifier method*), 213
[set_predict_request\(\)](#) (*xgboost.dask.DaskXGBClassifier method*), 239
[set_predict_request\(\)](#) (*xgboost.dask.DaskXGBRanker method*), 264
[set_predict_request\(\)](#) (*xgboost.dask.DaskXGBRegressor method*), 252
[set_predict_request\(\)](#) (*xgboost.dask.DaskXGBRFClassifier method*), 290
[set_predict_request\(\)](#) (*xgboost.dask.DaskXGBRFRegressor method*), 276
[set_predict_request\(\)](#) (*xgboost.XGBClassifier method*), 176
[set_predict_request\(\)](#) (*xgboost.XGBRanker method*), 189
[set_predict_request\(\)](#) (*xgboost.XGBRegressor method*), 162
[set_predict_request\(\)](#) (*xgboost.XGBRFClassifier method*), 214
[set_predict_request\(\)](#) (*xgboost.XGBRFRegressor method*), 201
[set_score_request\(\)](#) (*xgboost.dask.DaskXGBClassifier method*), 240
[set_score_request\(\)](#) (*xgboost.dask.DaskXGBRegressor method*), 252
[set_score_request\(\)](#) (*xgboost.dask.DaskXGBRFClassifier method*), 291
[set_score_request\(\)](#) (*xgboost.dask.DaskXGBRFRegressor method*), 277
[set_score_request\(\)](#) (*xgboost.XGBClassifier method*), 177
[set_score_request\(\)](#) (*xgboost.XGBRegressor method*), 163
[set_score_request\(\)](#) (*xgboost.XGBRFClassifier method*), 215
[set_score_request\(\)](#) (*xgboost.XGBRFRegressor method*), 201
[set_uint_info\(\)](#) (*xgboost.DMatrix method*), 138
[set_weight\(\)](#) (*xgboost.DMatrix method*), 138
[setParams\(\)](#) (*xgboost.spark.SparkXGBClassifier method*), 297
[setParams\(\)](#) (*xgboost.spark.SparkXGBRanker method*), 317
[setParams\(\)](#) (*xgboost.spark.SparkXGBRegressor method*), 307
[slice\(\)](#) (*xgboost.DMatrix method*), 139
[SparkXGBClassifier](#) (class in *xgboost.spark*), 291
[SparkXGBClassifierModel](#) (class in *xgboost.spark*), 297
[SparkXGBRanker](#) (class in *xgboost.spark*), 311
[SparkXGBRankerModel](#) (class in *xgboost.spark*), 317
[SparkXGBRegressor](#) (class in *xgboost.spark*), 302
[SparkXGBRegressorModel](#) (class in *xgboost.spark*), 307
- ## T
- [to_graphviz\(\)](#) (in module *xgboost*), 217
[train\(\)](#) (in module *xgboost*), 149
[train\(\)](#) (in module *xgboost.dask*), 225
[TrainingCallback](#) (class in *xgboost.callback*), 218
[TrainingCheckPoint](#) (class in *xgboost.callback*), 222
[transform\(\)](#) (*xgboost.spark.SparkXGBClassifierModel method*), 301
[transform\(\)](#) (*xgboost.spark.SparkXGBRankerModel method*), 321

transform() (*xgboost.spark.SparkXGBRegressorModel* method), 311
 trees_to_dataframe() (*xgboost.Booster* method), 147

U

uid (*xgboost.spark.SparkXGBClassifier* attribute), 297
 uid (*xgboost.spark.SparkXGBClassifierModel* attribute), 301
 uid (*xgboost.spark.SparkXGBRanker* attribute), 317
 uid (*xgboost.spark.SparkXGBRankerModel* attribute), 321
 uid (*xgboost.spark.SparkXGBRegressor* attribute), 307
 uid (*xgboost.spark.SparkXGBRegressorModel* attribute), 311
 update() (*xgboost.Booster* method), 147

W

write() (*xgboost.spark.SparkXGBClassifier* method), 297
 write() (*xgboost.spark.SparkXGBClassifierModel* method), 301
 write() (*xgboost.spark.SparkXGBRanker* method), 317
 write() (*xgboost.spark.SparkXGBRankerModel* method), 321
 write() (*xgboost.spark.SparkXGBRegressor* method), 307
 write() (*xgboost.spark.SparkXGBRegressorModel* method), 311

X

XGBCallbackDataIterNext (C++ type), 439
 XGBCallbackSetData (C++ type), 439
 XGBClassifier (class in *xgboost*), 164
 XGBGetGlobalConfig (C++ function), 427
 XGBGetLastError (C++ function), 427
 xgboost.callback
 module, 218
 xgboost.core
 module, 134
 xgboost.dask
 module, 223
 xgboost.plotting
 module, 216
 xgboost.sklearn
 module, 152
 xgboost.spark
 module, 291
 xgboost.training
 module, 149
 XGBoostBatchCSR (C++ struct), 442
 XGBoosterBoostedRounds (C++ function), 443
 XGBoosterBoostOneIter (C++ function), 444
 XGBoosterCreate (C++ function), 443
 XGBoosterDumpModel (C++ function), 445

XGBoosterDumpModelEx (C++ function), 445
 XGBoosterDumpModelExWithFeatures (C++ function), 446
 XGBoosterDumpModelWithFeatures (C++ function), 445
 XGBoosterEvalOneIter (C++ function), 444
 XGBoosterFeatureScore (C++ function), 447
 XGBoosterFree (C++ function), 443
 XGBoosterGetAttr (C++ function), 446
 XGBoosterGetAttrNames (C++ function), 446
 XGBoosterGetModelRaw (C++ function), 454
 XGBoosterGetNumFeature (C++ function), 444
 XGBoosterGetStrFeatureInfo (C++ function), 447
 XGBoosterLoadJsonConfig (C++ function), 455
 XGBoosterLoadModel (C++ function), 453
 XGBoosterLoadModelFromBuffer (C++ function), 453
 XGBoosterLoadRabitCheckpoint (C++ function), 454
 XGBoosterPredict (C++ function), 448
 XGBoosterPredictFromCSR (C++ function), 451
 XGBoosterPredictFromCudaArray (C++ function), 451
 XGBoosterPredictFromCudaColumnar (C++ function), 452
 XGBoosterPredictFromDense (C++ function), 450
 XGBoosterPredictFromDMatrix (C++ function), 449
 XGBoosterSaveJsonConfig (C++ function), 455
 XGBoosterSaveModel (C++ function), 453
 XGBoosterSaveModelToBuffer (C++ function), 453
 XGBoosterSaveRabitCheckpoint (C++ function), 454
 XGBoosterSerializeToBuffer (C++ function), 454
 XGBoosterSetAttr (C++ function), 446
 XGBoosterSetParam (C++ function), 443
 XGBoosterSetStrFeatureInfo (C++ function), 447
 XGBoosterSlice (C++ function), 443
 XGBoosterUnserializeFromBuffer (C++ function), 454
 XGBoosterUpdateOneIter (C++ function), 444
 XGBoostVersion (C++ function), 427
 XGBRanker (class in *xgboost*), 177
 XGBRegisterLogCallback (C++ function), 427
 XGBRegressor (class in *xgboost*), 152
 XGBRFClassifier (class in *xgboost*), 202
 XGBRFRegressor (class in *xgboost*), 190
 XGBSetGlobalConfig (C++ function), 427
 XGBuildInfo (C++ function), 427
 XGCommunicatorAllreduce (C++ function), 458
 XGCommunicatorBroadcast (C++ function), 457
 XGCommunicatorFinalize (C++ function), 456
 XGCommunicatorGetProcessorName (C++ function), 457
 XGCommunicatorGetRank (C++ function), 457
 XGCommunicatorGetWorldSize (C++ function), 457
 XGCommunicatorInit (C++ function), 455
 XGCommunicatorIsDistributed (C++ function), 457

XGCommunicatorPrint (C++ *function*), 457
 XGDeviceQuantileDMatrixCreateFromCallback
 (C++ *function*), 441
 XGDMatrixCallbackNext (C++ *type*), 439
 XGDMatrixCreateFromArrowCallback (C++ *function*), 431
 XGDMatrixCreateFromCallback (C++ *function*), 440
 XGDMatrixCreateFromCSC (C++ *function*), 429
 XGDMatrixCreateFromCSCEX (C++ *function*), 430
 XGDMatrixCreateFromCSR (C++ *function*), 429
 XGDMatrixCreateFromCSREX (C++ *function*), 428
 XGDMatrixCreateFromCudaArrayInterface (C++
 function), 431
 XGDMatrixCreateFromCudaColumnar (C++ *function*),
 431
 XGDMatrixCreateFromDataIter (C++ *function*), 439
 XGDMatrixCreateFromDense (C++ *function*), 429
 XGDMatrixCreateFromDT (C++ *function*), 431
 XGDMatrixCreateFromFile (C++ *function*), 428
 XGDMatrixCreateFromMat (C++ *function*), 430
 XGDMatrixCreateFromMat_omp (C++ *function*), 430
 XGDMatrixCreateFromURI (C++ *function*), 428
 XGDMatrixFree (C++ *function*), 432
 XGDMatrixGetDataAsCSR (C++ *function*), 436
 XGDMatrixGetFloatInfo (C++ *function*), 435
 XGDMatrixGetQuantileCut (C++ *function*), 437
 XGDMatrixGetStrFeatureInfo (C++ *function*), 434
 XGDMatrixGetUIntInfo (C++ *function*), 436
 XGDMatrixNumCol (C++ *function*), 436
 XGDMatrixNumNonMissing (C++ *function*), 436
 XGDMatrixNumRow (C++ *function*), 436
 XGDMatrixSaveBinary (C++ *function*), 432
 XGDMatrixSetDenseInfo (C++ *function*), 435
 XGDMatrixSetFloatInfo (C++ *function*), 433
 XGDMatrixSetGroup (C++ *function*), 435
 XGDMatrixSetInfoFromInterface (C++ *function*),
 433
 XGDMatrixSetStrFeatureInfo (C++ *function*), 433
 XGDMatrixSetUIntInfo (C++ *function*), 433
 XGDMatrixSlicedMatrix (C++ *function*), 432
 XGDMatrixSlicedMatrixEX (C++ *function*), 432
 XGImportArrowRecordBatch (C++ *function*), 431
 XGProxyDMatrixCreate (C++ *function*), 440
 XGProxyDMatrixSetDataCSR (C++ *function*), 442
 XGProxyDMatrixSetDataCudaArrayInterface
 (C++ *function*), 441
 XGProxyDMatrixSetDataCudaColumnar (C++ *function*), 442
 XGProxyDMatrixSetDataDense (C++ *function*), 442
 XGQuantileDMatrixCreateFromCallback (C++
 function), 440